

Maestro Cloud Control Infrastructure Setup on VMware

Admin Guide

M3AG-4

February 2026

Version 2.0

CONTENTS

Preface 3

 About This Guide..... 3

 Audience..... 3

1 Instance Configuration**Error! Bookmark not defined.**

2 Instance Setup Flow.....**Error! Bookmark not defined.**

Version History.....**Error! Bookmark not defined.**

PREFACE

ABOUT THIS GUIDE

This document provides the information on the configuration of an instance in VMware for on premise installation of Maestro.

The infrastructure setup includes several steps:

- Maestro Instance Setup
- Certificate Configuration
- Maestro Pre-Configuration
- Maestro Initial Configuration

AUDIENCE

The guide is designed for administrative users who are authorized to perform infrastructure setup for further Maestro configuration.

MAESTRO INSTANCE SETUP

Maestro Instance setup is performed according to the following steps:

1. Deploy the instance with following configuration from Maestro OVA template:

Minimum instance type:	2 vCPU, 4 RAM
Disk size:	100 GB
Operating System:	Ubuntu 22.04
2. Open the ports necessary for Maestro on premise setup (22, 80, 443, 3000, 8080, 8200, 9000, 9001, 9090, 15672, 27017).
3. Make sure Maestro can access its own public IP address by port 9000, 9090
4. Setup a DNS name for the demo stand (use either own DNS server or Maestro can provide an A record for the demo stand). To obtain the DNS from Maestro, its IP address should be accessible from internet.

CERTIFICATE CONFIGURATION

To configure a certificate for Maestro, follow the steps below:

1. Create an A record pointing to the Maestro VM. You can see an example below:

Record name
 demo-vmware.maestro3.community
Record type
A
Value
 212.98.181.144

2. Request an SSL certificate using the cert-self-nginx.sh shell script.
 - a. Login to VM and set variable required for script execution:

```
M3_WORKING_DIR=

ONPREM_DNS=

sed -i "s/ONPREM_DNS=.* /ONPREM_DNS=$ONPREM_DNS/"
$M3_WORKING_DIR/components/pre-configuration.sh

sed -i "s/M3_WORKING_DIR=.* /M3_WORKING_DIR=$M3_WORKING_DIR/"
$M3_WORKING_DIR/components/pre-configuration.sh
```

For M3_WORKING_DIR set user home directory (e.g. M3_WORKING_DIR="/home/ubuntu")
 For ONPREM_DNS set DNS designated for Maestro setup (e.g. ONPREM_DNS="demo-vmware.maestro3.community")

- b. Execute the script using the root user:

```
bash $M3_WORKING_DIR/components/cert-self-nginx.sh
```

Note: Script executing may take up to 5 minutes.

MAESTRO PRE-CONFIGURATION

Maestro pre-configuration can be completed with pre-configuration.sh shell script. Do it following the steps below:

1. Set the required variables into the script:

```
M3_WORKING_DIR=
ONPREM_DNS=

sed -i "s/ONPREM_DNS=.* /ONPREM_DNS=$ONPREM_DNS/"
$M3_WORKING_DIR/components/pre-configuration.sh

sed -i "s/M3_WORKING_DIR=.* /M3_WORKING_DIR=$M3_WORKING_DIR/"
$M3_WORKING_DIR/components/pre-configuration.sh
```

2. Set M3_WORKING_DIR and ONPREM_DNS variables as in previous examples.
3. Execute the script using the root user:

```
bash $M3_WORKING_DIR/components/pre-configuration.sh
```

Note: Pre-configuration, configuration, and application startup may take up to 10-15 minutes.

MAESTRO INITIAL CONFIGURATION

After the pre-configuration is completed, it is necessary to setup an admin user for Maestro. It can be done with `customer-setup.sh` shell script, according to the following steps:

1. Set the following variables required for the initial setup:

```
CUSTOMER_ID=

USER_EMAIL=

PASSWORD=

SECURITY_GROUPS_FILE=

sed -i "s/CUSTOMER_ID=.* /CUSTOMER_ID=$CUSTOMER_ID/"
$M3_WORKING_DIR/components/customer-setup.sh

sed -i "s/USER_EMAIL=.* /USER_EMAIL=$USER_EMAIL/"
$M3_WORKING_DIR/components/customer-setup.sh

sed -i "s/PASSWORD=.* /PASSWORD=$PASSWORD/"
$M3_WORKING_DIR/components/customer-setup.sh

sed -i
"s/SECURITY_GROUPS_FILE=.* /SECURITY_GROUPS_FILE=$SECURITY_GROUPS_FIL
E/" $M3_WORKING_DIR/components/customer-setup.sh
```

Where:

- `CUSTOMER_ID` – represents a customer/organization (e.g. `CUSTOMER_ID="Maestro"`)
- `USER_EMAIL` – admin user (e.g. `USER_EMAIL="username@mail.com"`)
- `PASSWORD` – will be used for admin user credentials creation. Use uppercase, lowercase and digits.
- `SECURITY_GROUPS_FILE` – path to file with IP address list configuration for Maestro (e.g. `SECURITY_GROUPS_FILE="/home/ubuntu/components/security_groups.json"`). All resources launched by Maestro will be accessible from these addresses. Below you can find an example for file structure:

```
[
  {
    "n": "my_security_group",
    "d": "My security group",
    "ii": [
      {
```

```
    "ip": "1.1.1.0/24",  
    "d": "security group A"  
  },  
  {  
    "ip": "2.2.2.0/24",  
    "d": "security group B"  
  }  
]  
}
```

2. Execute the script using the root user:

```
bash $M3_WORKING_DIR/components/customer-setup.sh
```

It may take up to 5 minutes.

When the initial configuration is completed, the admin user should be able to login to Maestro.

To check it, open the following link in your browser: [https://\\$ONPREM_DNS](https://$ONPREM_DNS) (replace with actual DNS) and use the credentials created before (\$USER_EMAIL and \$PASSOWRD)

VERSION HISTORY

Version	Date	Summary
2.0	February 23, 2026	Structure updated
1.0	March 25, 2024	Initial version created