

Case 2: We want to find the rows where specific column don't have Null values.

IS NOT NULL

```
SELECT *  
FROM table_name  
WHERE column_name IS NOT NULL;
```

```
SELECT Product,  
amount  
FROM Fruit_sales  
WHERE amount IS NOT NULL
```

Product	amount
Banana	100
Orange	20
Grapes	40

Case 3: Replacing a Null value in a specific column with a default value.

IF NULL (column_name, replacement_value)

Placed within a SELECT statement

used with AS to give it a descriptive name.

Sale_id	Product	amount
1	Banana	100
2	Apple	Null
3	Orange	20
4	Grapes	40
5	Lemon	Null

```
SELECT sale_id,  
product  
IFNULL (amount, 0) AS amount  
FROM Fruit_sales
```

Output

Sale_id	Product	amount
1	Banana	100
2	Apple	0
3	Orange	20
4	Grapes	40
5	Lemon	0

~~~~~

## Brightlearn

### Null functions

What is a Null?

- No value
- Missing value
- No data
- Empty space
- Blank
- No record
- Empty
- Missing information

→ Null functions are functions that help us to deal with Null values in our dataset.  
→ help us to handle Null values.

### Fruit\_sales

| Sale id | Product | amount |
|---------|---------|--------|
| 1       | Banana  | 100    |
| 2       | Apple   | Null   |
| 3       | Orange  | 20     |
| 4       | Grapes  | 40     |
| 5       | Lemons  | Null   |

SELECT SUM(amount) AS total\_revenue  
FROM Fruit\_sales

Output = Error

Case 1: How to check for Null values in a specific table on a specific column.

We use IS NULL

```
SELECT column(s)  
FROM table_name  
WHERE column_name IS NULL;
```

This code is used to check if you have a Null value in a specific column

```
SELECT product,  
amount  
FROM Fruit_sales  
WHERE amount IS NULL
```

| Product | amount |
|---------|--------|
| Apple   | Null   |
| Lemon   | Null   |

IS NOT NULL → is used to check the rows with no Null

4) Min() AND Max functions

```
SELECT Min(salary) AS lowest_salary,  
       Max(salary) AS highest_salary  
FROM Employees;
```

5. ~~SE~~ GROUP BY Statement

```
SELECT department,  
       sum(salary) AS total_salary  
FROM employees  
GROUP BY department;
```

14/04/2026

SELECT DATEADD(DAY, 2, '2025-06-02') AS subtracting\_days;  
TO\_DATE (DATEADD(DAY, 2, DATE)) AS adding\_days

is used to change string  
to a date format

TO\_CHAR (DATE, 'yyyymm') AS month\_id --- TO\_CHAR converts a date  
into a string

--- DATEDIFF - it looks for the difference between two dates  
(unit, date1, date2)  
date2 - date1 = Value

SELECT DATEDIFF (YEAR, 2, '2025-06-02', '2027-06-02');