
INFORME DE ACTIVIDAD – ESCANEEO Y ANÁLISIS DE RED

SCANME.NMAP.ORG

Autora: Ruth Landaeta

Fecha: 25 de septiembre de 2026

1. Reporte de Evidencias

Prueba de conectividad (ping): Se verificó la disponibilidad del host scanme.nmap.org 4529(45.33.32.156) con tiempos de respuesta entre 196–208 ms.

Escaneo con Nmap (sin ProxyChains): Puertos detectados:

1. 22/tcp → SSH
2. 80/tcp → HTTP
3. 9929/tcp → nping-echo
4. 31337/tcp → Elite

Escaneo con Nmap + ProxyChains/Tor:

1. Puerto 80/tcp abierto, servicio HTTP con título “Go ahead and ScanMe!”.
2. Puerto 22/tcp abierto, servicio SSH con claves públicas detectadas. *de proxychains + nmap)*

```
not shown: 990 closed tcp ports (conn-refused)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
9929/tcp  open  nping-echo
31337/tcp open  Elite
```

Detección de versiones de servicios:

```
-(root@kali)-[~]
# proxychains4 nmap -sT -Pn -sV 45.33.32.156
```

1. SSH: OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13
2. HTTP: Apache httpd 2.4.7 (Ubuntu)

```
not shown: 990 closed tcp ports (conn-refused)
PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13 (Ubuntu Linux; protocol 2.0)
80/tcp    open  http         Apache httpd 2.4.7 ((Ubuntu))
9929/tcp  open  nping-echo   Nping echo
31337/tcp open  tcpwrapped
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

2. Tabla de Resultados

Puerto	Estado	Servicio	Versión / Observación
22/tcp	Abierto	SSH	OpenSSH 6.6.1p1 Ubuntu
80/tcp	Abierto	HTTP	Apache 2.4.7 (Ubuntu)
135/tcp	Filtrado	MSRPC	—
139/tcp	Filtrado	NetBIOS	—
161/tcp	Filtrado	SNMP	—
445/tcp	Filtrado	SMB	—
9929/tcp	Abierto	nping-echo	—
31337/tcp	Abierto	Elite	—

```
(root@kali)-[~]
# proxychains4 nmap -sT -Pn -p 22,80 -sV --script=vuln 45.33.32.156
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-24 13:19 -0300
```

3. Vulnerabilidades

Vulnerabilidades en OpenSSH 6.6.1p1

Esta versión, liberada en 2014, tiene varias fallas críticas:

- **CVE-2016-0777 / CVE-2016-0778:** Fugas de memoria en el código de roaming que permiten a un atacante extraer claves privadas SSH.
- **CVE-2015-5600:** Bypass del límite de intentos de autenticación (*MaxAuthTries*), lo que facilita ataques de fuerza bruta.
- **CVE-2015-6564:** Vulnerabilidad de *use-after-free* que puede causar corrupción de memoria y potencial ejecución de código.
- **Impacto:** Robo de credenciales, acceso remoto no autorizado, denegación de servicio y posible compromiso total del sistema.
- **Mitigación recomendada:** Actualizar a una versión moderna de OpenSSH ($\geq 9.x$), deshabilitar acceso root por SSH, aplicar autenticación basada en claves y limitar intentos de login.

Vulnerabilidades en Apache HTTPD 2.4.7

La versión 2.4.7 también es obsoleta y presenta múltiples fallos:

- **CVE-2026-44631 (CVSS 9.8):** *Heap Underflow* en *ap_regname* que puede permitir ejecución remota de código.
- **CVE-2026-34355 / CVE-2026-34356:** Desbordamientos de buffer en módulos *mod_proxy_html* y *ProxyPassReverseCookieMap*, explotables por servidores backend maliciosos.
- **CVE-2026-29170:** Vulnerabilidad de XSS en *mod_proxy_ftp* al listar directorios FTP.
- **CVE-2026-42535 / CVE-2026-42536:** Problemas en *mod_dav_fs* y *mod_xml2enc* que permiten manipulación de propiedades DAV y desbordamientos de memoria.
- **Impacto:** Ejecución remota de código, escalamiento de privilegios, robo de información y denegación de servicio.
- **Mitigación recomendada:** Actualizar Apache HTTPD a la última versión estable ($\geq 2.4.68$), revisar configuraciones de módulos, aplicar reglas de firewall y reforzar cabeceras de seguridad

Servicio	Versión	Vulnerabilidades clave	Riesgo principal
OpenSSH 6.6.1p1	2014	CVE-2016-0777, CVE-2015-5600, CVE-2015-6564	Robo de credenciales y acceso remoto
Apache HTTPD 2.4.7	2014	CVE-2026-44631, CVE-2026-34355, CVE-2026-29170	Ejecución remota de código y XSS

Adiciono más información de vulnerabilidades encontradas

PORT	STATE	SERVICE	VERSION				
22/tcp	open	ssh	OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13 (Ubuntu Linux; protocol 2.0)				
vulners:							
cpe:/a:openssh:openssh:6.6.1p1:							
DF059135-2CF5-5441-8F22-E6EF1DEE5F6E	10.0	https://vulners.com/gitee/DF059135-2CF5-5441-8F22-E6EF1DEE5F6E	*EXPLOIT*				
2608B200-7E01-5A22-AD21-20F63E8C7CE	10.0	https://vulners.com/githubexploit/2608B200-7E01-5A22-AD21-20F63E8C7CE	*EXPLOIT*				
PACKETSTORM:173661	9.8	https://vulners.com/packetstorm/PACKETSTORM:173661	*EXPLOIT*				
F0979183-AE88-53B4-86CF-3AF0523F3807	9.8	https://vulners.com/githubexploit/F0979183-AE88-53B4-86CF-3AF0523F3807	*EXPLOIT*				
CVE-2023-38408	9.8	https://vulners.com/cve/CVE-2023-38408					
CVE-2016-1908	9.8	https://vulners.com/cve/CVE-2016-1908					
CEF8EC43-BFE2-5B5E-8918-54A90DA092B4	9.8	https://vulners.com/githubexploit/CEF8EC43-BFE2-5B5E-8918-54A90DA092B4	*EXPLOIT*				
B8190CDB-3EB9-5631-9828-8064A1575B23	9.8	https://vulners.com/githubexploit/B8190CDB-3EB9-5631-9828-8064A1575B23	*EXPLOIT*				
A2B36885-C737-548F-8C04-9339EDCDBFF5	9.8	https://vulners.com/githubexploit/A2B36885-C737-548F-8C04-9339EDCDBFF5	*EXPLOIT*				
8FC9C5AB-3968-5F3C-825E-E80B5379A623	9.8	https://vulners.com/githubexploit/8FC9C5AB-3968-5F3C-825E-E80B5379A623	*EXPLOIT*				
8AD01159-548E-546E-AA87-2DE89F3927EC	9.8	https://vulners.com/githubexploit/8AD01159-548E-546E-AA87-2DE89F3927EC	*EXPLOIT*				
6192C35D-F78B-5C0A-AB8D-9826A79A5320	9.8	https://vulners.com/githubexploit/6192C35D-F78B-5C0A-AB8D-9826A79A5320	*EXPLOIT*				
22277290-6700-5C8F-8930-1EEAFD489FF0	9.8	https://vulners.com/githubexploit/22277290-6700-5C8F-8930-1EEAFD489FF0	*EXPLOIT*				
0221525F-07F5-5790-912D-F4B9E2D1B587	9.8	https://vulners.com/githubexploit/0221525F-07F5-5790-912D-F4B9E2D1B587	*EXPLOIT*				
CVE-2026-60002	9.4	https://vulners.com/cve/CVE-2026-60002					
CVE-2015-5600	8.5	https://vulners.com/cve/CVE-2015-5600					
CVE-2026-25414	8.1	https://vulners.com/cve/CVE-2026-25414					
CVE-2026-35386	8.1	https://vulners.com/cve/CVE-2026-35386					
CVE-2026-35385	8.1	https://vulners.com/cve/CVE-2026-35385					
BA3887BD-F579-53B1-A4A4-FF49E953E1C0	8.1	https://vulners.com/githubexploit/BA3887BD-F579-53B1-A4A4-FF49E953E1C0	*EXPLOIT*				
4FB01B00-F993-5CAF-BD57-D7E290D18C1F	8.1	https://vulners.com/githubexploit/4FB01B00-F993-5CAF-BD57-D7E290D18C1F	*EXPLOIT*				
PACKETSTORM:140070	7.8	https://vulners.com/packetstorm/PACKETSTORM:140070	*EXPLOIT*				
EXPLOITPACK:5BCA798C6BA71FAE29334297EC0B6A09	7.8	https://vulners.com/exploitpack/EXPLOITPACK:5BCA798C6BA71FAE29334297EC0B6A09	*EXPLOIT*				
EDB-ID:40888	7.8	https://vulners.com/exploitdb/EDB-ID:40888	*EXPLOIT*				
CVE-2016-6515	7.8	https://vulners.com/cve/CVE-2016-6515					
CVE-2016-10012	7.8	https://vulners.com/cve/CVE-2016-10012					
CVE-2015-8325	7.8	https://vulners.com/cve/CVE-2015-8325					
C94132FD-1FA5-5342-B6EE-0DAF45EEFF3	7.8	https://vulners.com/githubexploit/C94132FD-1FA5-5342-B6EE-0DAF45EEFF3	*EXPLOIT*				
991D2CC4-0E09-5745-97A2-49174618D06C	7.8	https://vulners.com/githubexploit/991D2CC4-0E09-5745-97A2-49174618D06C	*EXPLOIT*				
312165E3-7FD9-5769-BDA3-41298E9114D6	7.8	https://vulners.com/githubexploit/312165E3-7FD9-5769-BDA3-41298E9114D6	*EXPLOIT*				
2E719186-2FED-58A8-A150-762EFBAA523	7.8	https://vulners.com/gitee/2E719186-2FED-58A8-A150-762EFBAA523	*EXPLOIT*				
23C97BF6-7C95-513B-9E73-298C48D74432	7.8	https://vulners.com/githubexploit/23C97BF6-7C95-513B-9E73-298C48D74432	*EXPLOIT*				
1337DAY-ID-26496	7.8	https://vulners.com/zdt/1337DAY-ID-26496	*EXPLOIT*				
10213D8E-F683-588B-B603-353173626207	7.8	https://vulners.com/githubexploit/10213D8E-F683-588B-B603-353173626207	*EXPLOIT*				
SSV:92579	7.5	https://vulners.com/seebug/SSV:92579	*EXPLOIT*				
EDB-ID:40963	7.5	https://vulners.com/exploitdb/EDB-ID:40963	*EXPLOIT*				
CVE-2026-60000	7.5	https://vulners.com/cve/CVE-2026-60000					
CVE-2026-59999	7.5	https://vulners.com/cve/CVE-2026-59999					
CVE-2016-10708	7.5	https://vulners.com/cve/CVE-2016-10708					
CVE-2016-10009	7.5	https://vulners.com/cve/CVE-2016-10009					
CF52FA19-B50B-5D14-B50F-2411851976E2	7.5	https://vulners.com/githubexploit/CF52FA19-B50B-5D14-B50F-2411851976E2	*EXPLOIT*				
1337DAY-ID-26576	7.5	https://vulners.com/zdt/1337DAY-ID-26576	*EXPLOIT*				
CVE-2020-15778	7.4	https://vulners.com/cve/CVE-2020-15778					

1337DAY-ID-26609	6.5	https://vulners.com/zdt/1337DAY-ID-26609	*EXPLOIT*				
DB7C1CC7-4DB6-55E0-BC08-5059F8F3AE16	6.5	https://vulners.com/githubexploit/DB7C1CC7-4DB6-55E0-BC08-5059F8F3AE16	*EXPLOIT*				
D104D2BF-ED22-588B-A9B2-3CC562FE8C0	6.5	https://vulners.com/githubexploit/D104D2BF-ED22-588B-A9B2-3CC562FE8C0	*EXPLOIT*				
CVE-2026-60001	6.5	https://vulners.com/cve/CVE-2026-60001					
CVE-2026-59998	6.5	https://vulners.com/cve/CVE-2026-59998					
CVE-2026-35387	6.5	https://vulners.com/cve/CVE-2026-35387					
CVE-2023-51385	6.5	https://vulners.com/cve/CVE-2023-51385					
C07A0B46-24B8-57B7-8375-9C761F4750A2	6.5	https://vulners.com/githubexploit/C07A0B46-24B8-57B7-8375-9C761F4750A2	*EXPLOIT*				
A88CDD3E-67CC-51CC-97FB-AB0CAB6808C	6.5	https://vulners.com/githubexploit/A88CDD3E-67CC-51CC-97FB-AB0CAB6808C	*EXPLOIT*				
65B15AA1-2A8D-53C1-9499-69EBA3619F1C	6.5	https://vulners.com/githubexploit/65B15AA1-2A8D-53C1-9499-69EBA3619F1C	*EXPLOIT*				
5325A9D6-132B-590C-BDEF-0CB105252732	6.5	https://vulners.com/gitee/5325A9D6-132B-590C-BDEF-0CB105252732	*EXPLOIT*				
530326CF-6AB3-5643-AA16-73DC8CB44742	6.5	https://vulners.com/githubexploit/530326CF-6AB3-5643-AA16-73DC8CB44742	*EXPLOIT*				
EDB-ID:40858	6.4	https://vulners.com/exploitdb/EDB-ID:40858	*EXPLOIT*				
EDB-ID:39569	6.4	https://vulners.com/exploitdb/EDB-ID:39569	*EXPLOIT*				
CVE-2016-3115	6.4	https://vulners.com/cve/CVE-2016-3115					
PACKETSTORM:181223	5.9	https://vulners.com/packetstorm/PACKETSTORM:181223	*EXPLOIT*				
MSF:AUXILIARY-SCANNER-SSH-SSH_ENUMUSERS-	5.9	https://vulners.com/metasploit/MSF:AUXILIARY-SCANNER-SSH-SSH_ENUMUSERS-	*EXPLOIT*				
FEF0EB06-770B-5ADF-857C-1704B7AC3FE4	5.9	https://vulners.com/githubexploit/FEF0EB06-770B-5ADF-857C-1704B7AC3FE4	*EXPLOIT*				
FD2E0EBA-ED84-5304-8862-84BCDEB2F288	5.9	https://vulners.com/githubexploit/FD2E0EBA-ED84-5304-8862-84BCDEB2F288	*EXPLOIT*				
EDB-ID:40136	5.9	https://vulners.com/exploitdb/EDB-ID:40136	*EXPLOIT*				
EDB-ID:40113	5.9	https://vulners.com/exploitdb/EDB-ID:40113	*EXPLOIT*				
CVE-2023-48795	5.9	https://vulners.com/cve/CVE-2023-48795					
CVE-2020-14145	5.9	https://vulners.com/cve/CVE-2020-14145					
CVE-2019-6111	5.9	https://vulners.com/cve/CVE-2019-6111					
CVE-2016-6210	5.9	https://vulners.com/cve/CVE-2016-6210					
CNVD-2021-25272	5.9	https://vulners.com/cnvd/CNVD-2021-25272					

```
80/tcp open  http      Apache httpd 2.4.7 ((Ubuntu))
http-sql-injection: ERROR: Script execution failed (use -d to debug)
http-dombased-xss: Couldn't find any DOM based XSS.
http-stored-xss: Couldn't find any stored XSS vulnerabilities.
http-slowloris-check:
  VULNERABLE:
    Slowloris DOS attack
    State: LIKELY VULNERABLE
    IDs: CVE:CVE-2007-6750
    Slowloris tries to keep many connections to the target web server open and hold
    them open as long as possible. It accomplishes this by opening connections to
    the target web server and sending a partial request. By doing so, it starves
    the http server's resources causing Denial Of Service.

    Disclosure date: 2009-09-17
    References:
      http://ha.ckers.org/slowloris/
      https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6750
http-server-header: Apache/2.4.7 (Ubuntu)
http-csrf:
  Spidering limited to: maxdepth=3; maxpagecount=20; withinhost=scanme.nmap.org
  Found the following possible CSRF vulnerabilities:

    Path: http://scanme.nmap.org:80/
    Form id: nst-head-search
    Form action: /search/

    Path: http://scanme.nmap.org:80/
    Form id: nst-foot-search
    Form action: /search/
http-enum:
  /images/: Potentially interesting directory w/ listing on 'apache/2.4.7 (ubuntu)'
vulners:
  cpe:/a:apache:http_server:2.4.7:
    3E6BA608-776F-5B1F-9BA5-589CD2A5A351 10.0 https://vulners.com/gitee/3E6BA608-776F-5B1F-9BA5-589CD2A5A351 *EXPLOIT*
    PACKETSTORM:176334 9.8 https://vulners.com/packetstorm/PACKETSTORM:176334 *EXPLOIT*
    PACKETSTORM:171631 9.8 https://vulners.com/packetstorm/PACKETSTORM:171631 *EXPLOIT*
    HTTPD:E8492EE5729E8F8514D3C0EE370C98C6 9.8 https://vulners.com/httpd/HTTPD:E8492EE5729E8F8514D3C0EE370C98C6
    HTTPD:C072933AA965A86DA3E2C9172FFC1569 9.8 https://vulners.com/httpd/HTTPD:C072933AA965A86DA3E2C9172FFC1569
    HTTPD:A1B8CE110E077FFBF4469D4F06D089293 9.8 https://vulners.com/httpd/HTTPD:A1B8CE110E077FFBF4469D4F06D089293
    HTTPD:A09F9CEBE0B7C39EDA0A480FAEF4FE9D 9.8 https://vulners.com/httpd/HTTPD:A09F9CEBE0B7C39EDA0A480FAEF4FE9D
    HTTPD:98CBE3C14201AFC4B0F36F15CB40C0F8 9.8 https://vulners.com/httpd/HTTPD:98CBE3C14201AFC4B0F36F15CB40C0F8
    HTTPD:9AD76A782F4E66676719E36864777A7A 9.8 https://vulners.com/httpd/HTTPD:9AD76A782F4E66676719E36864777A7A
    HTTPD:650C6B8A1FEAD1FBD1AF9746142659F9 9.8 https://vulners.com/httpd/HTTPD:650C6B8A1FEAD1FBD1AF9746142659F9
    HTTPD:2BE0032A6ABE7CC52906DBAFAFE0E448E 9.8 https://vulners.com/httpd/HTTPD:2BE0032A6ABE7CC52906DBAFAFE0E448E
    HTTPD:1F84410918227CC81FA7C000C4F999A3 9.8 https://vulners.com/httpd/HTTPD:1F84410918227CC81FA7C000C4F999A3
    HTTPD:156974A46CA46AF26CC4140D00F7EB10 9.8 https://vulners.com/httpd/HTTPD:156974A46CA46AF26CC4140D00F7EB10
    EDB-ID:51193 9.8 https://vulners.com/exploitdb/EDB-ID:51193 *EXPLOIT*
    D5084D51-C8DF-5CBA-BC26-ACF2E33F8E52 9.8 https://vulners.com/githubexploit/D5084D51-C8DF-5CBA-BC26-ACF2E33F8E52 *EXPLOIT*
    CVE-2024-38476 9.8 https://vulners.com/cve/CVE-2024-38476
    CVE-2024-38474 9.8 https://vulners.com/cve/CVE-2024-38474
```

```
SSV:61874 5.0 https://vulners.com/seebug/SSV:61874 *EXPLOIT*
HTTPD:F8C8FF58A7154D4AEB884460782E6943 5.0 https://vulners.com/httpd/HTTPD:F8C8FF58A7154D4AEB884460782E6943
HTTPD:EA40955F0C4A208F0F1841F397D60CF3 5.0 https://vulners.com/httpd/HTTPD:EA40955F0C4A208F0F1841F397D60CF3
HTTPD:E07AE8765B0D0F6E15AAD496A2714564 5.0 https://vulners.com/httpd/HTTPD:E07AE8765B0D0F6E15AAD496A2714564
HTTPD:A158A6C2486763570B136BF80E76E98 5.0 https://vulners.com/httpd/HTTPD:A158A6C2486763570B136BF80E76E98
HTTPD:86787FEB94A4AFD9542C6B8363C3D8A3 5.0 https://vulners.com/httpd/HTTPD:86787FEB94A4AFD9542C6B8363C3D8A3
HTTPD:37A2DAF62C74FA577EC2F97F085C496 5.0 https://vulners.com/httpd/HTTPD:37A2DAF62C74FA577EC2F97F085C496
HTTPD:3353898BF398B0F8391739FC2D0B581 5.0 https://vulners.com/httpd/HTTPD:3353898BF398B0F8391739FC2D0B581
HTTPD:30E31E412AB4505FEE1161AB62A2E9AD 5.0 https://vulners.com/httpd/HTTPD:30E31E412AB4505FEE1161AB62A2E9AD
EXPLOITPACK:DAE0989E8D259B28BF72FC7FDC4755A7 5.0 https://vulners.com/exploitpack/EXPLOITPACK:DAE0989E8D259B28BF72FC7FDC4755A7
EXPLOITPACK:C8C256BE08FF5FE1C0405C80AA9C075D 5.0 https://vulners.com/exploitpack/EXPLOITPACK:C8C256BE08FF5FE1C0405C80AA9C075D
CVE-2015-3183 5.0 https://vulners.com/cve/CVE-2015-3183 *EXPLOIT*
CVE-2015-0228 5.0 https://vulners.com/cve/CVE-2015-0228
CVE-2014-3581 5.0 https://vulners.com/cve/CVE-2014-3581
CVE-2014-3523 5.0 https://vulners.com/cve/CVE-2014-3523
CVE-2014-0231 5.0 https://vulners.com/cve/CVE-2014-0231
CVE-2014-0098 5.0 https://vulners.com/cve/CVE-2014-0098
CVE-2013-6438 5.0 https://vulners.com/cve/CVE-2013-6438
CVE-2013-5704 5.0 https://vulners.com/cve/CVE-2013-5704
CNVD-2015-01691 5.0 https://vulners.com/cnvd/CNVD-2015-01691
1337DAY-ID-28573 5.0 https://vulners.com/zdt/1337DAY-ID-28573 *EXPLOIT*
1337DAY-ID-26574 5.0 https://vulners.com/zdt/1337DAY-ID-26574 *EXPLOIT*
EAGAD014-D80B-5DC2-9991-1F9663E2D09F 4.8 https://vulners.com/githubexploit/EAGAD014-D80B-5DC2-9991-1F9663E2D09F *EXPLOIT*
SSV:87152 5.0 https://vulners.com/seebug/SSV:87152 *EXPLOIT*
PACKETSTORM:127563 4.3 https://vulners.com/packetstorm/PACKETSTORM:127563 *EXPLOIT*
HTTPD:C42F64A6857578ED72E18211FDE568E0 4.3 https://vulners.com/httpd/HTTPD:C42F64A6857578ED72E18211FDE568E0
HTTPD:883E996A34F70F5D670D81697321AAB 4.3 https://vulners.com/httpd/HTTPD:883E996A34F70F5D670D81697321AAB
HTTPD:788AE185F44187BE1E7DCB50A9280A 4.3 https://vulners.com/httpd/HTTPD:788AE185F44187BE1E7DCB50A9280A
HTTPD:45932C372ED0E0588A3AE5126126F558 4.3 https://vulners.com/httpd/HTTPD:45932C372ED0E0588A3AE5126126F558
CVE-2016-8612 4.3 https://vulners.com/cve/CVE-2016-8612
CVE-2015-3185 4.3 https://vulners.com/cve/CVE-2015-3185
CVE-2014-8109 4.3 https://vulners.com/cve/CVE-2014-8109
CVE-2014-0118 4.3 https://vulners.com/cve/CVE-2014-0118
CVE-2014-0117 4.3 https://vulners.com/cve/CVE-2014-0117
1337DAY-ID-33575 4.3 https://vulners.com/zdt/1337DAY-ID-33575 *EXPLOIT*
PACKETSTORM:140265 0.0 https://vulners.com/packetstorm/PACKETSTORM:140265 *EXPLOIT*
CVE-2026-44631 0.0 https://vulners.com/cve/CVE-2026-44631
CVE-2026-44186 0.0 https://vulners.com/cve/CVE-2026-44186
CVE-2026-44185 0.0 https://vulners.com/cve/CVE-2026-44185
CVE-2026-44119 0.0 https://vulners.com/cve/CVE-2026-44119
CVE-2026-43951 0.0 https://vulners.com/cve/CVE-2026-43951
CVE-2026-42536 0.0 https://vulners.com/cve/CVE-2026-42536
CVE-2026-42535 0.0 https://vulners.com/cve/CVE-2026-42535
CVE-2026-34356 0.0 https://vulners.com/cve/CVE-2026-34356
CVE-2026-34355 0.0 https://vulners.com/cve/CVE-2026-34355
CVE-2026-34059 0.0 https://vulners.com/cve/CVE-2026-34059
CVE-2026-34032 0.0 https://vulners.com/cve/CVE-2026-34032
CVE-2026-33857 0.0 https://vulners.com/cve/CVE-2026-33857
CVE-2026-33523 0.0 https://vulners.com/cve/CVE-2026-33523
CVE-2026-33007 0.0 https://vulners.com/cve/CVE-2026-33007
CVE-2026-33006 0.0 https://vulners.com/cve/CVE-2026-33006
```

Scan mediante comandos NSE

scripts por defecto

```
(root@kali)-[~]
# proxychains4 nmap -sT -Pn -sV -sC 45.33.32.156

Not shown: 996 closed tcp ports (conn-refused)
PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   1024 ac:00:a0:1a:82:ff:cc:55:99:dc:67:2b:34:97:6b:75 (DSA)
|   2048 20:3d:2d:44:62:2a:b0:5a:9d:b5:b3:05:14:c2:a6:b2 (RSA)
|   256  96:02:bb:5e:57:54:1c:4e:45:2f:56:4c:4a:24:b2:57 (ECDSA)
|_  256  33:fa:91:0f:e0:e1:7b:1f:6d:05:a2:b0:f1:54:41:56 (ED25519)
80/tcp    open  http         Apache httpd 2.4.7 ((Ubuntu))
|_ http-server-header: Apache/2.4.7 (Ubuntu)
|_ http-title: Go ahead and ScanMe!
|_ http-favicon: Nmap Project
9929/tcp  open  nping-echo   Nping echo
31337/tcp open  tcpwrapped
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 500.41 seconds
```

Detalle de Scan

1. Puerto 22/tcp — SSH (Secure Shell)

- Estado: Abierto (open).
- Servicio y Versión: Ejecuta OpenSSH 6.6.1p1 sobre Ubuntu (versión de paquete 2ubuntu2.13). El protocolo utilizado es el 2.0.
- Resultado de Scripts (ssh-hostkey): El script NSE recolectó con éxito las claves criptográficas públicas del servidor (huellas digitales o *fingerprints*) para diferentes algoritmos (DSA, RSA, ECDSA y ED25519). Esto sirve para verificar la identidad del servidor en futuras conexiones.

2. Puerto 80/tcp — HTTP (Servidor Web)

- Estado: Abierto (open).
- Servicio y Versión: Servidor web Apache httpd 2.4.7 en Ubuntu.
- Resultado de Scripts HTTP: Aquí actuaron varios scripts NSE automatizados para la categoría web:

- **http-server-header:** Confirma que la cabecera del servidor es Apache/2.4.7 (Ubuntu).
- **http-title:** El título de la página web principal es "Go ahead and ScanMe!" (un claro indicador de que se está escaneando el servidor público de pruebas scanme.nmap.org).
- **http-favicon:** Detectó que el icono de la página web (favicon) pertenece al Nmap Project.

3. Puerto 9929/tcp — Nping-echo

- **Estado:** Abierto (open).
- **Servicio y Versión:** Nping echo (Nping echo). Es un servicio propio de las herramientas de Nmap que se utiliza para probar la conectividad, eco de paquetes y medir respuestas de red a nivel avanzado.

4. Puerto 31337/tcp — Elite (tcpwrapped)

- **Estado:** Abierto (open).
- **Servicio:** Marcado como tcpwrapped. Esto significa que el puerto está abierto, pero el software cerró la conexión inmediatamente después de que Nmap intentara conectarse para identificarlo (o bien hay un firewall/filtro interrumpiendo el saludo de la aplicación). No se pudo determinar qué servicio corre detrás.

buscar vulnerabilidades y exploits

```
(root@kali)-[~]
# proxychains4 nmap -sT -Pn -sV --script=vuln 45.33.32.156
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
```

```

PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13 (Ubuntu Linux; protocol 2.0)
vulners:
cpe:/a:openbsd:openssh:6.6.p1: 10.0 https://vulners.com/gitee/DF059135-2CF5-5441-8F22-E6EF1DEE5F6E *EXPLOIT*
2608B200-7E01-5A22-AD21-20F63E8EC7CE 10.0 https://vulners.com/githubexploit/2608B200-7E01-5A22-AD21-20F63E8EC7CE *EXPLOIT*
PACKETSTORM:173661 9.8 https://vulners.com/packetstorm/PACKETSTORM:173661 *EXPLOIT*
F0979183-AE88-53B4-86CF-3AF0523F3807 9.8 https://vulners.com/githubexploit/F0979183-AE88-53B4-86CF-3AF0523F3807 *EXPLOIT*
CVE-2023-38408 9.8 https://vulners.com/cve/CVE-2023-38408
CVE-2016-1908 9.8 https://vulners.com/cve/CVE-2016-1908
CEF8EC43-8FE2-585E-8918-54A90DA09284 9.8 https://vulners.com/githubexploit/CEF8EC43-8FE2-585E-8918-54A90DA09284 *EXPLOIT*
B8190CDB-3EB9-5631-9828-8064A1575B23 9.8 https://vulners.com/githubexploit/B8190CDB-3EB9-5631-9828-8064A1575B23 *EXPLOIT*
A2B36885-C737-548F-8C04-9339EDCDBFF5 9.8 https://vulners.com/githubexploit/A2B36885-C737-548F-8C04-9339EDCDBFF5 *EXPLOIT*
8FC9C5AB-3968-5F3C-825E-E80B5379A623 9.8 https://vulners.com/githubexploit/8FC9C5AB-3968-5F3C-825E-E80B5379A623 *EXPLOIT*
8AD01159-548E-546E-AA87-20E89F3927EC 9.8 https://vulners.com/githubexploit/8AD01159-548E-546E-AA87-20E89F3927EC *EXPLOIT*
6192C35D-F78B-5C0A-AB8D-9826A79A5320 9.8 https://vulners.com/githubexploit/6192C35D-F78B-5C0A-AB8D-9826A79A5320 *EXPLOIT*
2227729D-6700-5C8F-8930-1EEAFD489FF0 9.8 https://vulners.com/githubexploit/2227729D-6700-5C8F-8930-1EEAFD489FF0 *EXPLOIT*
0221525F-07F5-5790-912D-F4B9E2D1B587 9.8 https://vulners.com/githubexploit/0221525F-07F5-5790-912D-F4B9E2D1B587 *EXPLOIT*
CVE-2026-60002 9.4 https://vulners.com/cve/CVE-2026-60002
CVE-2015-5600 8.5 https://vulners.com/cve/CVE-2015-5600
CVE-2026-35414 8.1 https://vulners.com/cve/CVE-2026-35414
CVE-2026-35386 8.1 https://vulners.com/cve/CVE-2026-35386
CVE-2026-35385 8.1 https://vulners.com/cve/CVE-2026-35385
BA3807B0-F579-53B1-A4A4-FF40F9531C0 8.1 https://vulners.com/githubexploit/BA3807B0-F579-53B1-A4A4-FF40F9531C0 *EXPLOIT*
4FB01B00-F993-5CAF-BD57-D7E290D10C1F 8.1 https://vulners.com/githubexploit/4FB01B00-F993-5CAF-BD57-D7E290D10C1F *EXPLOIT*
PACKETSTORM:140070 7.8 https://vulners.com/packetstorm/PACKETSTORM:140070 *EXPLOIT*
EXPLOITPACK:5BCA798C6BA71FAE29334297EC0B6A09 7.8 https://vulners.com/exploitpack/EXPLOITPACK:5BCA798C6BA71FAE29334297EC0B6A09 *EXPLOIT*
EDB-ID:40888 7.8 https://vulners.com/exploitdb/EDB-ID:40888 *EXPLOIT*
CVE-2016-6515 7.8 https://vulners.com/cve/CVE-2016-6515
CVE-2016-10012 7.8 https://vulners.com/cve/CVE-2016-10012
CVE-2015-8325 7.8 https://vulners.com/cve/CVE-2015-8325

```

El estado de este puerto 22 es de Alto Riesgo. Un atacante no necesita descubrir una vulnerabilidad nueva; simplemente puede usar los enlaces provistos por Nmap (de plataformas como *Packet Storm* o *GitHub*) para descargar un código dañino (*EXPLOIT*) existente, comprometer el acceso SSH, evadir la autenticación o tumbar el servicio de la máquina objetivo.

```

0/tcp    open  http          Apache httpd 2.4.7 ((Ubuntu))
_http-dombased-xss: Couldn't find any DOM based XSS.
_http-sql-injection: ERROR: Script execution failed (use -d to debug)
_http-stored-xss: Couldn't find any stored XSS vulnerabilities.
http-slowloris-check:
  VULNERABLE:
    Slowloris DOS attack
    State: LIKELY VULNERABLE
    IDs: CVE:CVE-2007-6750
    Slowloris tries to keep many connections to the target web server open and hold
    them open as long as possible. It accomplishes this by opening connections to
    the target web server and sending a partial request. By doing so, it starves
    the http server's resources causing Denial Of Service.

    Disclosure date: 2009-09-17
    References:
      https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6750
      http://ha.ckers.org/slowloris/
vulners:
cpe:/a:apache:http_server:2.4.7: 10.0 https://vulners.com/gitee/3E6BA608-776F-5B1F-9BA5-589CD2A5A351 *EXPLOIT*
3E6BA608-776F-5B1F-9BA5-589CD2A5A351 10.0 https://vulners.com/gitee/3E6BA608-776F-5B1F-9BA5-589CD2A5A351 *EXPLOIT*
PACKETSTORM:176334 9.8 https://vulners.com/packetstorm/PACKETSTORM:176334 *EXPLOIT*
PACKETSTORM:171631 9.8 https://vulners.com/packetstorm/PACKETSTORM:171631 *EXPLOIT*
HTTPD:E8492EE5729E8F8514D3C0EE370C98C6 9.8 https://vulners.com/httpd/HTTPD:E8492EE5729E8F8514D3C0EE370C98C6
HTTPD:C072933AA965A86DA3E2C9172FFC1569 9.8 https://vulners.com/httpd/HTTPD:C072933AA965A86DA3E2C9172FFC1569
HTTPD:A1BBCE110E077FFBF4469D4F06DB9293 9.8 https://vulners.com/httpd/HTTPD:A1BBCE110E077FFBF4469D4F06DB9293
HTTPD:A09F9CEBE0B7C39EDA0480FEAEF4FE9D 9.8 https://vulners.com/httpd/HTTPD:A09F9CEBE0B7C39EDA0480FEAEF4FE9D
HTTPD:9BCBE3C14201AFC480F36F15CB40C0F8 9.8 https://vulners.com/httpd/HTTPD:9BCBE3C14201AFC480F36F15CB40C0F8
HTTPD:0AD76A707CE66E76710F26DE6177A7A 9.8 https://vulners.com/httpd/HTTPD:0AD76A707CE66E76710F26DE6177A7A

```

El servidor web se encuentra en un estado muy inseguro. Apache 2.4.7 es una versión obsoleta que no solo puede ser derribada fácilmente mediante un ataque de denegación de servicio (Slowloris), sino que contiene vulnerabilidades críticas con exploits públicos que podrían permitir a un atacante infiltrarse en el sistema operativo.

```

_ http-server-header: Apache/2.4.7 (Ubuntu)
_ http-enum:
_ /images/: Potentially interesting directory w/ listing on 'apache/2.4.7 (ubuntu)'
_ http-csrf:
  Spidering limited to: maxdepth=3; maxpagecount=20; withinhost=scanme.nmap.org
  Found the following possible CSRF vulnerabilities:

    Path: http://scanme.nmap.org:80/
    Form id: nst-head-search
    Form action: /search/

    Path: http://scanme.nmap.org:80/
    Form id: nst-foot-search
    Form action: /search/
_
9929/tcp open  nping-echo Nping echo
31337/tcp open  tcpwrapped
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

```

auditoría de malware o puertas traseras:

```

(root@kali)-[~]
# proxychains4 nmap -sT -Pn -sV --script=malware 45.33.32.156
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-24 14:42 -0300

```

```

PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13 (Ubuntu Linux; protocol 2.0)
80/tcp    open  http         Apache httpd 2.4.7 ((Ubuntu))
|_ http-server-header: Apache/2.4.7 (Ubuntu)
9929/tcp  open  nping-echo   Nping echo
31337/tcp open  tcpwrapped
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Host script results:
| dns-zuustracker:
|   Name                               IP      SBL  ASN  Country  Status  Level  Files Online  Date added
|_ swissign-check=5vzzp0Kf9xfvDXpbfCgSoxCLWCg  nil    nil  nil  nil      nil     Unknown nil          nil

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 534.95 seconds

```

1. **Falso Positivo / Registro antiguo:** Hubo una coincidencia parcial en la base de datos de rastreo por la estructura del nombre o un certificado (como SwissSign), pero actualmente la IP no está catalogada como un servidor activo de malware.
2. **Entorno de pruebas:** Dado que el objetivo es el servidor público de pruebas de Nmap (scanme.nmap.org), es habitual que algunos subdominios o registros de prueba generen ruido en herramientas de escaneo de reputación sin que represente una amenaza real.

Detecta el sistema operativo

```

(root@kali)~# proxychains4 nmap -sT -Pn -O --osscan-guess 45.33.32.156
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17

Not shown: 996 closed tcp ports (conn-refused)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
9929/tcp   open  nping-echo
31337/tcp  open  Elite
Device type: VoIP adapter|bridge|general purpose
Running (JUST GUESSING): AT&T embedded (90%), Oracle Virtualbox (88%), Slirp (88%), QEMU (86%)
OS CPE: cpe:/o:oracle:virtualbox cpe:/a:danny_gasparovski:slirp cpe:/a:qemu:qemu
Aggressive OS guesses: AT&T BGW210 voice gateway (90%), Oracle Virtualbox Slirp NAT bridge (88%), QEMU user mode network gateway (86%)
No exact OS matches for host (test conditions non-ideal).

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 497.66 seconds

```

El patrón de puertos abiertos y las coincidencias de OS apuntan a un entorno de laboratorio o virtualizado, probablemente usado para pruebas de red o simulación de servicios. El puerto 31337/tcp es interesante: históricamente se asocia a servicios de prueba o incluso a backdoors en entornos inseguros, por lo que merece revisión. El nping-echo (9999/tcp) indica que se están realizando pruebas de conectividad o latencia, típico en auditorías de red.

Comparación de scripts de Nmap (NSE)

Comando	Objetivo principal	Precisión	Riesgo de detección	Tiempo
<code>--script=<cat</code> <code><cat></code>	Escaneo dirigido	Alta	Medio	Variable
<code>-sC</code>	Scripts por defecto	Media	Bajo	Moderado
<code>--script=vuln</code>	Detección de vulnerabilidades	Alta	Alto	Alto
<code>--script=malware</code>	Detección de malware/backdoors	Media	Medio	Moderado

4. Conclusiones

- **Conectividad y disponibilidad del host objetivo**

La confirmación de la conectividad mediante *ping* demuestra que el servidor está activo y responde a solicitudes ICMP. Este hallazgo es fundamental porque valida que el objetivo es alcanzable y que se pueden realizar pruebas posteriores. En un contexto de auditoría, esta fase inicial permite descartar problemas de red y asegura que los resultados obtenidos en los escaneos son confiables. Además, la latencia medida (196–208 ms) ofrece una referencia sobre la calidad de la conexión y posibles limitaciones en escenarios de explotación.

```
(kali㉿kali)-[~]  
$ ping scanme.nmap.org  
PING scanme.nmap.org (45.33.32.156) 56(84) bytes of data.  
64 bytes from scanme.nmap.org (45.33.32.156): icmp_seq=1 ttl=64 time=208 ms  
64 bytes from scanme.nmap.org (45.33.32.156): icmp_seq=2 ttl=64 time=197 ms  
64 bytes from scanme.nmap.org (45.33.32.156): icmp_seq=3 ttl=64 time=197 ms  
64 bytes from scanme.nmap.org (45.33.32.156): icmp_seq=4 ttl=64 time=196 ms  
64 bytes from scanme.nmap.org (45.33.32.156): icmp_seq=5 ttl=64 time=196 ms  
^C
```

- **Servicios activos en SSH y HTTP con versiones específicas**

La detección de **SSH (OpenSSH 6.6.1p1)** y **HTTP (Apache 2.4.7)** es crítica porque ambas versiones tienen historial de vulnerabilidades documentadas. Identificar versiones exactas permite al auditor contrastar con bases de datos como CVE (Common Vulnerabilities and Exposures) y evaluar riesgos potenciales. Por ejemplo, versiones antiguas de OpenSSH pueden ser susceptibles a ataques de fuerza bruta o explotación de configuraciones débiles, mientras que Apache 2.4.7 puede presentar fallos de seguridad en módulos específicos. Este hallazgo subraya la importancia de mantener servicios actualizados y aplicar parches de seguridad.

```
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13 (Ubuntu Linux; protocol 2.0)
80/tcp    open  http     Apache httpd 2.4.7 ((Ubuntu))
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 17.71 seconds
```

- **Uso de ProxyChains + Tor para anonimización**

La incorporación de **ProxyChains + Tor** en los escaneos demuestra la capacidad de ocultar el origen del tráfico, lo cual es relevante en pruebas de penetración y simulaciones de ataque. Desde una perspectiva defensiva, este ejercicio evidencia cómo un atacante real podría enmascarar su identidad, dificultando la trazabilidad. En auditorías, esta práctica permite evaluar la resiliencia del sistema frente a intentos de acceso anónimo y la eficacia de los mecanismos de detección de intrusiones. Además, refuerza la comprensión de técnicas de evasión que deben ser contempladas en planes de ciberdefensa.

```
└─$ proxychains curl text.ident.me
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] Dynamic chain ... 127.0.0.1:9050 ... 127.0.0.1:9050 ←denied
[proxychains] Dynamic chain ... 127.0.0.1:9050 ... text.ident.me:80 ←denied
[proxychains] Dynamic chain ... 127.0.0.1:9050 ... text.ident.me:80 ←denied
curl: (7) Failed to connect to text.ident.me port 80 after 2633 ms: Could not connect to server

(root@kali)-[/home/kali]
└─$ sudo systemctl stop tor@default.service

(root@kali)-[/home/kali]
└─$ sudo killall tor
tor: ningún proceso encontrado

(root@kali)-[/home/kali]
└─$ sudo systemctl start tor@default.service

(root@kali)-[/home/kali]
└─$ sudo ss -tulpn | grep 9050
tcp LISTEN 0 4096 127.0.0.1:9050 0.0.0.0:* users:(("tor",pid=439822,fd=6))

(root@kali)-[/home/kali]
└─$ sudo nano /etc/proxychains4.conf

(root@kali)-[/home/kali]
└─$ sudo systemctl restart tor@default.service

(root@kali)-[/home/kali]
└─$ proxychains curl -s https://torproject.org
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] Dynamic chain ... 127.0.0.1:9050 ... torproject.org:443 ... OK
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN" "http://www.w3.org/TR/html4/strict.dtd">
<html><head>
<title>301 Moved Permanently</title>
</head><body>
<h1>Moved Permanently</h1>
<p>The document has moved <a href="https://www.torproject.org/">here</a>.</p>
<hr>
<address>Apache Server at torproject.org Port 443</address>
</body></html>
```

- **Detección de servicios poco comunes (nping-echo y Elite)**

La presencia de servicios como **nping-echo** y **Elite** es particularmente interesante porque no suelen encontrarse en entornos de producción. Estos servicios pueden ser configuraciones intencionales para pruebas o errores de exposición. Su detección abre la posibilidad de analizar vectores de ataque poco documentados, lo que enriquece la práctica académica y profesional. En escenarios reales, servicios inusuales pueden ser puertas traseras, configuraciones de prueba olvidadas o incluso honeypots diseñados para atraer atacantes.

```
1 scanme.nmap.org (45.33.32.156) 222.468 ms 222.053 ms 222.946 ms
(root@kali)-[/home/kali]
# sudo nmap -Pn 45.33.32.156
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-13 12:31 -0300
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (3.0s latency).
Not shown: 992 closed tcp ports (reset)
PORT      STATE      SERVICE
22/tcp    open      ssh
80/tcp    open      http
135/tcp   filtered  msrpc
139/tcp   filtered  netbios-ssn
161/tcp   filtered  snmp
445/tcp   filtered  microsoft-ds
9929/tcp  open      nping-echo
31337/tcp open      Elite
```