


<b>Name: Villasenor, Hans Rainier A.</b>	<b>Date Performed: 08/28/25</b>
<b>Course/Section: CPE 212 - CPE31S2</b>	<b>Date Submitted: 08/28/25</b>
<b>Instructor: Engr. Robin Valenzuela</b>	<b>Semester and SY:</b>
<b>Activity 4: Running Elevated Ad hoc Commands</b>	
<b>1. Objectives:</b> 1.1 Use commands that makes changes to remote machines 1.2 Use playbook in automating ansible commands	
<b>2. Discussion:</b>  <i>Provide screenshots for each task.</i>  <b>Elevated Ad hoc commands</b> So far, we have not performed ansible commands that makes changes to the remote servers. We manage to gather facts and connect to the remote machines, but we still did not make changes on those machines. In this activity, we will learn to use commands that would install, update, and upgrade packages in the remote machines. We will also create a playbook that will be used for automations.  <b>Playbooks</b> record and execute <b>Ansible's</b> configuration, deployment, and orchestration functions. They can describe a policy you want your remote systems to enforce, or a set of steps in a general IT process. If Ansible modules are the tools in your workshop, playbooks are your instruction manuals, and your inventory of hosts are your raw material. At a basic level, playbooks can be used to manage configurations of and deployments to remote machines. At a more advanced level, they can sequence multi-tier rollouts involving rolling updates, and can delegate actions to other hosts, interacting with monitoring servers and load balancers along the way. You can check this documentation if you want to learn more about playbooks. <a href="#">Working with playbooks — Ansible Documentation</a>	
<b>Task 1: Run elevated ad hoc commands</b>  1. Locally, we use the command <i>sudo apt update</i> when we want to download package information from all configured resources. The sources often defined in <i>/etc/apt/sources.list</i> file and other files located in <i>/etc/apt/sources.list.d/</i> directory. So, when you run update command, it downloads the package information from the Internet. It is useful to get info on an updated version of packages or their dependencies. We can only run	

an apt update command in a remote machine. Issue the following command:

*ansible all -m apt -a update\_cache=true*



```
Villaseñor_ControlNode [Running] - Oracle VirtualBox
File Machine View Input Devices Help

Aug 28 09:59

HANS@LocalMachine: ~
HANS@LocalMachine:~$ ansible all -m apt update_cache=true
usage: ansible [-h] [--version] [-v] [-b] [--become-method BECOME_METHOD]
               [--become-user BECOME_USER]
               [-K | --become-password-file BECOME_PASSWORD_FILE]
               [-i INVENTORY] [--list-hosts] [-l SUBSET] [-P POLL_INTERVAL]
               [-B SECONDS] [-o] [-t TREE] [--private-key PRIVATE_KEY_FILE]
               [-u REMOTE_USER] [-c CONNECTION] [-T TIMEOUT]
               [--ssh-common-args SSH_COMMON_ARGS]
               [--sftp-extra-args SFTP_EXTRA_ARGS]
               [--scp-extra-args SCP_EXTRA_ARGS]
               [--ssh-extra-args SSH_EXTRA_ARGS]
               [-k | --connection-password-file CONNECTION_PASSWORD_FILE] [-C]
               [-D] [-e EXTRA_VARS] [--vault-id VAULT_IDS]
               [-J | --vault-password-file VAULT_PASSWORD_FILES] [-f FORKS]
               [-M MODULE_PATH] [--playbook-dir BASEDIR]
               [--task-timeout TASK_TIMEOUT] [-a MODULE_ARGS] [-m MODULE_NAME]
               pattern
ansible: error: unrecognized arguments: update_cache=true

usage: ansible [-h] [--version] [-v] [-b] [--become-method BECOME_METHOD]
               [--become-user BECOME_USER]
               [-K | --become-password-file BECOME_PASSWORD_FILE]
               [-i INVENTORY] [--list-hosts] [-l SUBSET] [-P POLL_INTERVAL]
               [-B SECONDS] [-o] [-t TREE] [--private-key PRIVATE_KEY_FILE]
```


What is the result of the command? Is it successful?

**Its not successful it just show the other commands.**

Try editing the command and add something that would elevate the privilege. Issue the command *ansible all -m apt -a update\_cache=true*


**--become --ask-become-pass.** Enter the sudo password when prompted. You will notice now that the output of this command is a success. The **update\_cache=true** is the same thing as running **sudo apt update**. The **--become** command elevate the privileges and the **--ask-become-pass** asks for the password. For now, even if we only have changed the packaged index, we were able to change something on the remote server.

You may notice after the second command was executed, the status is CHANGED compared to the first command, which is FAILED.



```
HANS@LocalMachine: ~/CPE212
HANS@LocalMachine:~/CPE212$ ansible all -m apt -a update_cache=true --become --ask-become-pass
BECOME password:
192.168.56.105 | UNREACHABLE! ==> {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.105 port 22: No route to host",
  "unreachable": true
}
192.168.56.107 | UNREACHABLE! ==> {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.107 port 22: No route to host",
  "unreachable": true
}
192.168.56.103 | UNREACHABLE! ==> {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.103 port 22: No route to host",
  "unreachable": true
}
192.168.56.102 | CHANGED ==> {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/bin/python3"
  },
  "cache_update_time": 1756375542,
  "cache_updated": true,
  "changed": true
}
HANS@LocalMachine:~/CPE212$
```

2. Let's try to install VIM, which is an almost compatible version of the UNIX editor Vi. To do this, we will just changed the module part in 1.1 instruction. Here is the command: **ansible all -m apt -a name=vim-nox --become --ask-become-pass**. The command would take some time after typing the password because the local machine instructed the remote servers to actually install the package.




The screenshot shows a terminal window titled 'HANS@LocalMachine: ~/CPE212' within an Oracle VM VirtualBox environment. The terminal displays the output of an Ansible command: `ansible all -m apt -a name=vim-nox --become --ask-become-pass`. The output indicates that the command failed for three hosts (192.168.56.103, 192.168.56.107, and 192.168.56.105) due to 'UNREACHABLE!' status, with the message 'Failed to connect to the host via ssh: ssh: connect to host 192.168.56.103 port 22: No route to host'. For the host 192.168.56.102, the command was successful, showing 'CHANGED' status and the installation of the 'vim-nox' package. The terminal output for 192.168.56.102 includes details about the package installation, such as the package name, version, and the path to the python3 interpreter.

```
HANS@LocalMachine:~/CPE212$ ansible all -m apt -a name=vim-nox --become --ask-become-pass
BECOME password:
192.168.56.103 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.103 port
22: No route to host",
  "unreachable": true
}
192.168.56.107 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.107 port
22: No route to host",
  "unreachable": true
}
192.168.56.105 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.105 port
22: No route to host",
  "unreachable": true
}
192.168.56.102 | CHANGED => {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/bin/python3"
  },
  "cache_update_time": 1756303869,
  "cache_updated": false,
  "changed": true,
  "stderr": "",
  "stderr_lines": [],
  "stdout": "Reading package lists...\nBuilding dependency tree...\nReading state informat
```

2.1 Verify that you have installed the package in the remote servers. Issue the command *which vim* and the command *apt search vim-nox* respectively. Was the command successful?

**Yes the command is successful because the vim is downloaded in the server**



The screenshot shows a terminal window titled "Villaseñor\_ManageNode1 [Running] - Oracle VirtualBox". The terminal has a menu bar with "File", "Machine", "View", "Input", "Devices", and "Help". On the left side, there are icons for a terminal, a trash can, and a refresh button. The terminal output shows the following commands and results:

```
Processing triggers for man-db (2.12.0-4build2) ...
Processing triggers for libc-bin (2.39-0ubuntu8.5) ...
HANS@Server1:~$ which vim
/usr/bin/vim
HANS@Server1:~$ apt search vim-nox
Sorting... Done
Full Text Search... Done
vim-nox/noble-updates,noble-security,now 2:9.1.0016-1ubuntu7.8 amd64 [inst
  Vi IMproved - enhanced vi editor - with scripting languages support

vim-tiny/noble-updates,noble-security,now 2:9.1.0016-1ubuntu7.8 amd64 [ins
  ,automatic]
  Vi IMproved - enhanced vi editor - compact version

HANS@Server1:~$
```

2.2 Check the logs in the servers using the following commands: `cd /var/log`. After this, issue the command `ls`, go to the folder `apt` and open `history.log`. Describe what you see in the `history.log`.

**It shows the history po downloading the packages**

The screenshot shows a terminal window titled 'Villaseñor\_ManageNode1 [Running] - Oracle VM VirtualBox'. The terminal is running on a system named 'HANS@Server1'. The user navigates to the /var/log directory and lists its contents, which include various log files and compressed archives. The user then navigates to the /var/log/apt directory and lists its contents, which include a history.log file. The user then navigates to the history.log file and displays its contents, which shows the output of the command 'apt-get -y --fix-policy install'.

```
HANS@Server1:~$ cd /var/log
HANS@Server1:/var/log$ ls
alternatives.log  dmesg.0      lastlog
apache2           dmesg.1.gz   openvpn
apport.log        dmesg.2.gz   private
apt              dmesg.3.gz   README
auth.log          dmesg.4.gz   speech-dispatcher
boot.log          dpkg.log     sssd
bootstrap.log     faillog      syslog
btm               fontconfig.log sysstat
cloud-init.log    gdm3         ubuntu-advantage-apt-hook.log
cloud-init-output.log gpu-manager.log ufw.log
cups              hp           unattended-upgrades
cups-browsed      installer    vboxpostinstall.log
dist-upgrade      journal      wtmp
dmesg             kern.log

HANS@Server1:/var/log$ cd apt
HANS@Server1:/var/log/apt$ ls
eipp.log.xz  history.log  term.log
HANS@Server1:/var/log/apt$ cd history.log
bash: cd: history.log: Not a directory
HANS@Server1:/var/log/apt$ cat history.log

Start-Date: 2025-08-05 16:48:47
Commandline: apt-get -y --fix-policy install
Install: libgpg-error-l10n:amd64 (1.47-3build2, automatic), e2fsprogs-l10n:amd64 (1.47.0-2.4-exp1ut
4, automatic), libgpm2:amd64 (1.20.7-11, automatic), psmisc:amd64 (23.7-1build1, automatic), uuid-
me:amd64 (2.39.3-9ubuntu6, automatic), bash-completion:amd64 (1:2.11-8, automatic), bsdxtrutils::
```

3. This time, we will install a package called snapd. Snap is pre-installed in Ubuntu system. However, our goal is to create a command that checks for the latest installation package.

3.1 Issue the command: *ansible all -m apt -a name=snapd --become --ask-become-pass*


```
Some actions do not make sense in Ad-Hoc (include, meta, etc)
HANS@LocalMachine:~/CPE212$ ansible all -m apt -a name=snapt --become --ask-become-p
BECOME password:
192.168.56.105 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.105:
22: No route to host",
  "unreachable": true
}
192.168.56.103 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.103:
22: No route to host",
  "unreachable": true
}
192.168.56.107 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.107:
22: No route to host",
  "unreachable": true
}
192.168.56.102 | SUCCESS => {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/bin/python3"
  },
  "cache_update_time": 1756375542,
  "cache_updated": false,
  "changed": false
}
HANS@LocalMachine:~/CPE212$
```

Can you describe the result of this command? Is it a success? Did it change anything in the remote servers?

**I think its successful because it reach the dbserver but it didnt not change in remote server**

3.2 Now, try to issue this command: *ansible all -m apt -a "name=snapt state=latest" --become --ask-become-pass*

Describe the output of this command. Notice how we added the command *state=latest* and placed them in double quotations.



```
HANS@LocalMachine: ~/CPE212
HANS@LocalMachine:~/CPE212$ ansible all -m apt -a "name=snapd state=latest" --become --ask-become-pass
BECOME password:
192.168.56.102 | SUCCESS => {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/bin/python3"
  },
  "cache_update_time": 1756375542,
  "cache_updated": false,
  "changed": false
}
192.168.56.103 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.103 port 22: No route to host",
  "unreachable": true
}
192.168.56.107 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.107 port 22: No route to host",
  "unreachable": true
}
192.168.56.105 | UNREACHABLE! => {
  "changed": false,
  "msg": "Failed to connect to the host via ssh: ssh: connect to host 192.168.56.105 port 22: No route to host",
  "unreachable": true
}
HANS@LocalMachine:~/CPE212$
```

4. At this point, make sure to commit all changes to GitHub.

## Task 2: Writing our First Playbook

1. With ad hoc commands, we can simplify the administration of remote servers. For example, we can install updates, packages, and applications, etc. However, the real strength of ansible comes from its playbooks. When we write a playbook, we can define the state that we want our servers to be in and the place or commands that ansible will carry out to bring to that state. You can use an editor to create a playbook. Before we proceed, make sure that you are in the directory of the repository that we use in the previous activities (*CPE232\_yourname*). Issue the command *nano install\_apache.yml*. This will create a playbook file called *install\_apache.yml*. The .yml is the basic standard extension for playbook files.




When the editor appears, type the following:

```
GNU nano 4.8          install_apache.yml
--
- hosts: all
  become: true
  tasks:

  - name: install apache2 package
    apt:
      name: apache2
```

Make sure to save the file. Take note also of the alignments of the texts.




```
Villasenor_ControlNode [Running] - Oracle VirtualBox
File  Machine  View  Input  Devices  Help
Aug 28 10:16
HANS@LocalMachine: ~/CPE212
GNU nano 7.2          install_apache.yml
--
- hosts: dbserver
  become: true
  tasks:

  - name: installing Apache2
    apt:
      name: apache2
  - name: Ping
    ansible.builtin.ping:
```


2. Run the yml file using the command: *ansible-playbook --ask-become-pass install\_apache.yml*. Describe the result of this command.


```
Villaseñor_ControlNode [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Aug 28 10:18
HANS@LocalMachine: ~/CPE212
connect as this user (default=None)
Privilege Escalation Options:
  control how and which user you become as on target hosts
--become-method BECOME_METHOD
  privilege escalation method to use (default=sudo), use `ansible-
  doc -t become -l` to list valid choices.
--become-user BECOME_USER
  run operations as this user (default=root)
-b, --become
  run operations with become (does not imply password prompting)
HANS@LocalMachine:~/CPE212$ ansible-playbook --ask-become-pass install_apache.yaml
BECOME password:
PLAY [dbserver] *****
TASK [Gathering Facts] *****
ok: [192.168.56.102]
TASK [installing Apache2] *****
ok: [192.168.56.102]
TASK [Ping] *****
ok: [192.168.56.102]
PLAY RECAP *****
192.168.56.102 : ok=3  changed=0  unreachable=0  failed=0  skipped=0
rescued=0  ignored=0
HANS@LocalMachine:~/CPE212$
```

3. To verify that apache2 was installed automatically in the remote servers, go to the web browsers on each server and type its IP address. You should see something like this.



4. Try to edit the *install\_apache.yml* and change the name of the package to any name that will not be recognized. What is the output?






```
Villaseñor_ControlNode [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Aug 28 10:26
HANS@LocalMachine: ~/CPE212
ok: [192.168.56.102]
TASK [installing HANS] *****
ok: [192.168.56.102]
TASK [Ping] *****
ok: [192.168.56.102]
PLAY RECAP *****
192.168.56.102 : ok=3 changed=0 unreachable=0 failed=0 skipped=0
rescued=0 ignored=0
HANS@LocalMachine:~/CPE212$ sudo nano install_apache.yaml
HANS@LocalMachine:~/CPE212$ ansible-playbook --ask-become-pass install_apache.yaml
BECOME password:
PLAY [dbserver] *****
TASK [Gathering Facts] *****
ok: [192.168.56.102]
TASK [installing Apache2] *****
fatal: [192.168.56.102]: FAILED! => {"changed": false, "msg": "No package matching 'HANS' is
available"}
PLAY RECAP *****
192.168.56.102 : ok=1 changed=0 unreachable=0 failed=1 skipped=0
rescued=0 ignored=0
HANS@LocalMachine:~/CPE212$
```

5. This time, we are going to put additional task to our playbook. Edit the *install\_apache.yml*. As you can see, we are now adding an additional command, which is the *update\_cache*. This command updates existing package-indexes on a supporting distro but not upgrading installed-packages (utilities) that were being installed.

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes

    - name: install apache2 package
      apt:
        name: apache2
```



The screenshot shows a VirtualBox window titled "Villasenor\_ControlNode [Running] - Oracle VirtualBox". The terminal window displays the nano 7.2 editor editing the file "install\_apache.yaml". The content of the file is as follows:

```
--  
- hosts: dbserver  
  become: true  
  tasks:  
    - name: installing Apache2  
      apt:  
        name: apache2  
    - name: Ping  
      ansible.builtin.ping:  
    - name: update repository index  
      apt:  
        update_cache: yes
```

At the bottom of the terminal, there is a status bar with various keyboard shortcuts: ^G Help, ^O Write Out, ^W Where Is, ^K Cut, ^T Execute, ^C Location, ^X Exit, ^R Read File, ^\_ Replace, ^U Paste, ^J Justify, and ^\_/ Go To Li. A message "[ Read 14 lines ]" is also visible.

Save the changes to this file and exit.

6. Run the playbook and describe the output. Did the new command change anything on the remote servers? **Yes, it change in the task repository index**

The screenshot shows a terminal window titled "Villaseñor\_ControlNode [Running] - Oracle VirtualBox". The terminal is running on a host named "HANS@LocalMachine" in the directory "~/CPE212". The user has just edited a file and is prompted to save. The text "be elsewhere in the file depending on the exact syntax problem." and "The offending line appears to be:" is shown in red. The user then runs `sudo nano install_apache.yaml` and `ansible-playbook --ask-become-pass install_apache.yaml`. The terminal output shows the Ansible playbook execution for the host 192.168.56.102. The tasks performed are: Gathering Facts, installing Apache2, Ping, and update repository index. The final output shows that 4 packages were installed, 1 repository was updated, and no packages were failed or skipped.

```
HANS@LocalMachine:~/CPE212$ sudo nano install_apache.yaml
HANS@LocalMachine:~/CPE212$ ansible-playbook --ask-become-pass install_apache.yaml
BECOME password:

PLAY [dbserver] *****

TASK [Gathering Facts] *****
ok: [192.168.56.102]

TASK [installing Apache2] *****
ok: [192.168.56.102]

TASK [Ping] *****
ok: [192.168.56.102]

TASK [update repository index] *****
changed: [192.168.56.102]

PLAY RECAP *****
192.168.56.102 : ok=4    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0

HANS@LocalMachine:~/CPE212$
```

7. Edit again the *install\_apache.yaml*. This time, we are going to add a PHP support for the apache package we installed earlier.

```
---
- hosts: all
  become: true
  tasks:


    - name: update repository index
      apt:
        update_cache: yes

    - name: install apache2 package
      apt:
        name: apache2

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
```

Save the changes to this file and exit.

8. Run the playbook and describe the output. Did the new command change anything on the remote servers?



```
Villasenor_ControlNode [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Aug 28 10:35
HANS@LocalMachine: ~/CPE212
PLAY RECAP *****
192.168.56.102 : ok=4 changed=1 unreachable=0 failed=0 skippe
rescued=0 ignored=0
HANS@LocalMachine:~/CPE212$ sudo nano install_apache.yaml
HANS@LocalMachine:~/CPE212$ ansible-playbook --ask-become-pass install_apache.yaml
BECOME password:
PLAY [dbserver] *****
TASK [Gathering Facts] *****
ok: [192.168.56.102]
TASK [installing Apache2] *****
ok: [192.168.56.102]
TASK [Ping] *****
ok: [192.168.56.102]
TASK [update repository index] *****
changed: [192.168.56.102]
TASK [add PHP support for apache] *****
changed: [192.168.56.102]
PLAY RECAP *****
192.168.56.102 : ok=5 changed=2 unreachable=0 failed=0 skippe
rescued=0 ignored=0
HANS@LocalMachine:~/CPE212$
```

9. Finally, make sure that we are in sync with GitHub. Provide the link of your GitHub repository.

[https://github.com/hrvillasenor-ux/CPE31S2\\_VILLASENOR](https://github.com/hrvillasenor-ux/CPE31S2_VILLASENOR)

### Reflections:

Answer the following:

1. What is the importance of using a playbook?

A playbook is important because it helps automate Ansible tasks. It makes it easier to manage updates, installations, and other changes on many machines at once, while keeping everything consistent.

2. Summarize what we have done on this activity.



In this activity, I used ad hoc commands in Ansible to install, update, and upgrade packages on remote machines. I also created a playbook to automate these tasks, which made the work faster and easier to repeat.