



Advanced Brain Tumor Mapping with U-Net

**PROJECT
USING DESIGN
THINKING
July 2024**

PROJECT USING DESIGN THINKING REPORT SUBMITTED
IN PARTIAL FULFILLMENT OF THE REQUIREMENTS
FOR THE AWARD OF THE
DEGREE OF **BACHELOR OF TECHNOLOGY IN**
ARTIFICIAL INTELLIGENCE AND DATA SCIENCE
OF THE ANNA UNIVERSITY

**PROJECT
WORK**

Submitted by

DHARSHINI MV – 722822243014

DHINAKARAN R – 722822243015

MAGESHWARAN P – 722822243044

MAHIMA TEJESHWINI R – 722822243046

**BATCH
2022 – 2026**

Under the Guidance of

Mrs M. SOWMIYA

Assistant Professor

Department of Artificial Intelligence and Data Science

Sri Eshwar College of Engineering

(An Autonomous Institution – Affiliated to Anna University)

COIMBATORE – 641 202

Sri Eshwar College of Engineering
(An Autonomous Institution – Affiliated to Anna University)
COIMBATORE – 641 202

BONAFIDE CERTIFICATE

Certified that this project report titled “**Advanced Brain Tumor Mapping using U-Net**” done using Design Thinking is the bonafide work of

DHARSHINI MV	722822243014
DHINAKARAN R	722822243015
MAGESHWARAN P	722822243044
MAHIMA TEJESHWINI R	722822243046

who carried out the project work under my supervision

.....
SIGNATURE
Dr. S.Vimal,
M.E., Ph.D.,
HEAD OF THE DEPARTMENT
Professor & Head,
Department of AI&DS,
Sri Eshwar College of Engineering,
Coimbatore-641202.

.....
SIGNATURE
Mrs. M. Sowmiya,
B.E., M.E.,
SUPERVISOR
Assistant Professor,
Department of AI&DS,
Sri Eshwar College of Engineering,
Coimbatore-641202.

Submitted for the End Semester practical examination – Project using
Design Thinking viva-voce held on _ _ _ _ _

.....
(Internal Examiner)

.....
(External Examiner)

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	iii
	LIST OF FIGURES	viii
1	INTRODUCTION	1
2	LITERATURE SURVEY	4
	2.1 EXISTING PRODUCT	8
	2.2 PROBLEM STATEMENT	9
3	PROPOSED SOLUTION	10
	3.1 OVERVIEW	10
	3.2 FLOW DIAGRAM	10
4	HARDWARE / SOFTWARE DESCRIPTION	
	4.1 HARDWARE DESCRIPTION	17
	4.2 SOFTWARE DESCRIPTION	18
	4.3 DATASET	19
5	RESULT & IMPLEMENTATIONS	20
6	CONCLUSION & FUTURE SCOPE	22
	REFERENCE	23

Abstract

Accurate segmentation of brain tumors in MRI scans is essential for diagnosis and treatment planning, yet it remains a challenging task due to the variability in tumor appearance and size.

Our project addresses the challenge of accurately segmenting brain tumors in MRI scans using the 'Brain MRI Segmentation' dataset by Mateusz Buda, which includes MRIs and FLAIR abnormality segmentation masks. We employed the U-Net architecture, known for its effectiveness in biomedical imaging, with a contracting path (encoder) and an expansive path (decoder).

The model was trained using a combination of Dice Loss and Categorical Focal Loss, optimizing with the Adam-W optimizer at a learning rate of 0.0001. Evaluation metrics included accuracy, precision, recall, Dice score, and Intersection over Union (IoU). The model achieved a high Dice score, indicating robust segmentation performance. This demonstrates the potential of U-Net in automating brain tumor segmentation, which can significantly enhance clinical workflows in medical imaging.

Keywords: Brain Tumor Segmentation, MRI Scans, CNN, U-Net Architecture, TCGA Lower-Grade Glioma Collection

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
1	Block Diagram	
2	Train Data	
3	U-Net Architecture	
4	Model Architecture	
5	Diagnosis Classification Metrics	
6	Overall Performance	
7	Dice Score Formula	
8	Jaccard Index Formula	

CHAPTER - 1

INTRODUCTION

Brain tumors pose a significant threat to global health, accounting for approximately 7% of new cancer cases worldwide. Early and precise detection through Magnetic Resonance Imaging (MRI) scans is crucial for effective treatment. However, manually segmenting tumors in MRI scans, a critical step for accurate diagnosis, is a laborious and time-consuming process for medical professionals. The advent of deep learning offers a promising solution to automate this task, potentially leading to improved efficiency and accuracy in medical imaging.

This project focuses on brain tumor segmentation using the U-Net architecture. U-Net is renowned for its effectiveness in biomedical image analysis, featuring a symmetric encoder-decoder structure that excels in learning both global and local features from imaging data. While U-Net is a popular and powerful tool for this purpose, other architectures like V-Net and 3D U-Net have also shown promise in brain tumor segmentation tasks.

Our project leverages the "Brain MRI Segmentation" dataset by Mateusz Buda, which includes both MRI scans and corresponding tumor segmentation masks. By utilizing this dataset, we aim to train and validate a U-Net model that can accurately segment brain tumors, thereby automating a critical step in the diagnostic process.

Automating segmentation not only enhances accuracy but also frees up valuable time for medical professionals, allowing them to focus more on patient diagnosis and treatment planning. By demonstrating the effectiveness of U-Net in brain tumor segmentation, this project paves the way for significant advancements in medical imaging analysis, ultimately contributing to better patient outcomes and more efficient clinical workflows.

CHAPTER - 2

SYSTEM ANALYSIS AND DESIGN

2.1 LITERATURE SURVEY

2.1.1 Brain Tumor Segmentation and Survival Prediction Using 3D Attention U-Net

Published Year: 19 May 2020

Authors: Mobarakol Islam, V. S. Vibashan, V. Jeya Maria Jose, Navodini Wijethilake, Uppal Utkarsh & Hongliang Ren.

Successful training of deep networks often requires a vast number of annotated training samples. However, this study introduces a network and training strategy that utilizes strong data augmentation to maximize the efficiency of available annotated samples. The architecture, characterized by a contracting path to capture context and a symmetric expanding path for precise localization, can be trained end-to-end from a limited number of images. This approach outperforms the previous leading method, a sliding-window convolutional network, in the ISBI challenge for segmenting neuronal structures in electron microscopic stacks. The same network, when applied to transmitted light microscopy images, achieved top performance in the ISBI cell tracking challenge 2015.

The network's implementation, based on Caffe, is capable of segmenting a 512x512 image in less than a second on a modern GPU, demonstrating its efficiency. The method demonstrated superior results, achieving low warping, Rand, and pixel errors on the EM segmentation challenge, and high Intersection over Union (IoU) scores in the ISBI cell tracking challenge 2015. These findings highlight the potential of data augmentation in training deep networks with limited samples and underscore the network's effectiveness and speed in biomedical image segmentation. The study was supported by the Excellence Initiative of the German Federal and State governments and the BMBF [1].

2.1.2 A Multi Brain Tumor Region Segmentation Based on 3D U-Net

Published Year: 16 August 2023

Authors: Zhenwei Li, Xiaoqin Wu, Xiaoli Yang.

This paper presents an enhanced 3D U-Net model designed for the accurate segmentation of brain tumor regions from MRI images, addressing the limitations of traditional 2D U-Net models. The model retains the U-shaped structure of the original U-Net while incorporating improved encoding and decoding modules to enhance feature extraction and utilization. Additionally, a hybrid loss function combining binary cross-entropy and dice similarity coefficient is used to accelerate convergence and improve segmentation accuracy. The model's performance was evaluated on the BraTS2018 and BraTS2019 datasets, showing significant improvements in segmenting whole tumor (WT), tumor core (TC), and enhanced tumor (ET) regions compared to existing 2D segmentation networks.

The results demonstrate that the proposed 3D U-Net model achieves higher accuracy, particularly in the TC and ET regions. The dice similarity coefficient for WT, TC, and ET regions improved significantly, with values of 0.778, 0.875, and 0.903, respectively. Sensitivity also increased to 0.906 for WT, 0.926 for TC, and 0.946 for ET. These findings highlight the model's effectiveness in handling the detailed segmentation of brain tumors, offering a promising tool for clinical diagnosis and treatment. The study underscores the importance of using 3D convolutional networks to fully capture the spatial features of brain tumors and optimize the segmentation process [2].

2.1.3 Using U-Net network for efficient brain tumor segmentation in MRI images

Published Year: August 2022

Authors: Jason Walsh, Alice Othmani, Mayank Jain, Soumyabrata Dev

The paper explores various techniques for brain tumor segmentation in MRI scans, focusing on a lightweight U-Net architecture that allows real-time segmentation without requiring large datasets or additional data augmentation. The proposed U-Net achieves a mean intersection-over-union (IoU) of 89% on the BITE dataset, outperforming standard benchmark algorithms. Additionally, the architecture simplifies the segmentation process by using three perspective planes instead of the original three-dimensional volumetric images, making it more efficient and accessible.

Traditional segmentation methods such as thresholding, including Otsu's method and global thresholding, are highlighted for their effectiveness in extracting the region of interest (ROI) from images. Recent advances have combined binary thresholding with the watershed algorithm to improve brain

tumor segmentation, incorporating median filtering for noise reduction and morphological operations for refined results. Classification-based techniques like the k-nearest neighbor classifier and advanced models such as Hidden Markov Models (HMM) are discussed for their roles in learning features from annotated datasets and segmenting cancerous portions of MRI scans.

The paper also covers unsupervised learning algorithms like clustering, which identify underlying patterns in the data without labeled datasets. Common algorithms such as k-means and fuzzy c-means are used to partition features into clusters based on similarity. The implementation of the U-Net using TensorFlow is detailed, with convolutional blocks featuring varying filter sizes and batch normalization. Results show high accuracy and effectiveness of the lightweight U-Net, achieving a pixel accuracy of 99% and a mean IoU of up to 89% across different datasets, demonstrating its potential as a promising tool for medical image segmentation [3].

2.1.4 Improved Brain Tumor Segmentation Using UNet-LSTM Architecture

Published Year: April 2024

Authors: Saran Raj Sowrirajan, Logeshwaran K S, Anisha Devi Kalluri, Ravi Kumar Subburam

The paper “Improved Brain Tumor Segmentation Using UNet-LSTM Architecture” focuses on addressing the complexities of brain tumors, a challenging medical condition with significant implications for patient survival. Brain tumors are categorized into benign and malignant types, with the latter requiring early detection for effective treatment. Utilizing MRI images from the BraTs2020 dataset, we developed a segmentation model using a combination of Long Short Term Memory (LSTM) and U-Net architecture. The U-Net, a convolutional neural network model, was enhanced with both contraction and expansive pathways to accurately segment tumor regions into classes including Edema, Background, Enhancing, and Non-enhancing. Our approach achieved impressive metrics with an accuracy of 99.16%, a loss of 0.0240, and a precision of 99.30%, demonstrating its efficacy in precise tumor localization and classification [4].

2.1.5 Brain tumor segmentation using neuro-technology enabled intelligence-cascaded U-Net model

Published Year: April 2024

Authors: Haewon Byeon, Mohannad Al-Kubaisi, Ashit Kumar Dutta, Faisal Alghayadh, Mukesh Soni, Manisha Bhende, Venkata Chundur, K. Suresh Babu,

Brain tumor segmentation in medical imaging plays a pivotal role in neurology, aiding in precise diagnosis and treatment planning. Traditional methods face challenges due to the heterogeneous nature of brain tumors, necessitating advanced computational approaches. Recent studies have highlighted the effectiveness of deep learning architectures like U-Net for automated segmentation tasks. However, issues such as limited receptive fields and spatial information loss remain prevalent. To address these, novel techniques integrating dynamic convolution and non-local attention mechanisms have emerged. For instance, a recent study proposed the Intelligence Cascade U-Net (ICU-Net), a two-stage cascade architecture based on 3DU-Net. ICU-Net incorporates dynamic convolutions to adaptively adjust receptive fields and an Expectation-Maximization Attention (EMA) module for capturing long-range dependencies, thereby enhancing the segmentation accuracy of brain tumors. Evaluation on BraTS 2019/2020 datasets demonstrated significant improvements over conventional models, achieving Dice similarity coefficient (DSC) scores of 0.786 for enhancing tumor (ET), 0.903 for whole tumor (WT), and 0.828 for tumor core (TC), underscoring its effectiveness in robust and precise segmentation.

In addition to architectural advancements, recent literature emphasizes the importance of dataset quality and model generalizability in enhancing segmentation performance. The BraTS datasets, consisting of multi-modal MRI scans with manually annotated tumor regions, serve as benchmark datasets for evaluating segmentation algorithms. These datasets facilitate rigorous testing and comparison of different methodologies, allowing researchers to benchmark novel approaches like ICU-Net against established techniques. Furthermore, studies have explored various enhancements such as the integration of dynamic convolutions to improve feature representation without significantly increasing model complexity. Such innovations aim to overcome the challenges posed by irregular tumor boundaries and variability in tumor sizes, paving the way for more accurate and clinically relevant brain tumor segmentation techniques. The continuous evolution and refinement of these methods promise further advancements in medical image analysis, offering potential benefits for accurate diagnosis and personalized treatment strategies in neuro-oncology.

2.3 Existing Solution

Brain tumor segmentation is a critical task in medical imaging, essential for accurate diagnosis and treatment planning. Numerous methods have been developed to address this challenge, leveraging the capabilities of deep learning and advanced computational techniques. One notable approach is the 3D Attention U-Net, introduced by Mobarakol Islam et al. in 2020. This method

uses a contracting path to capture context and a symmetric expanding path for precise localization, making it highly efficient even with a limited number of annotated samples. The network's strong data augmentation strategy and efficient training allow it to outperform previous leading methods, demonstrating superior performance in both electron microscopy and light microscopy segmentation challenges. Additionally, the model's implementation based on Caffe enables fast segmentation of 512x512 images, proving its efficiency and effectiveness in biomedical image segmentation.

Another significant contribution is the enhanced 3D U-Net model by Zhenwei Li et al., designed to overcome the limitations of traditional 2D U-Net models. This model retains the U-shaped structure while incorporating improved encoding and decoding modules, as well as a hybrid loss function combining binary cross-entropy and dice similarity coefficient. These enhancements accelerate convergence and improve segmentation accuracy. Evaluated on the BraTS2018 and BraTS2019 datasets, the model showed substantial improvements in segmenting whole tumors, tumor cores, and enhancing tumor regions, with dice similarity coefficients reaching up to 0.903 for enhancing tumor regions. Similarly, Jason Walsh et al. proposed a lightweight U-Net architecture in 2022, optimized for real-time segmentation without the need for large datasets or extensive data augmentation. This approach simplifies the segmentation process and achieves high accuracy and efficiency, with a mean intersection-over-union (IoU) of 89% on the BITE dataset.

Furthermore, recent advancements have introduced innovative architectures like the Intelligence Cascade U-Net (ICU-Net) by Haewon Byeon et al. in 2024. This model integrates dynamic convolutions and an Expectation-Maximization Attention (EMA) module within a two-stage 3DU-Net cascade architecture. The ICU-Net significantly enhances segmentation accuracy by capturing both local and long-range features, achieving Dice similarity coefficients of 0.786 for enhancing tumors, 0.903 for whole tumors, and 0.828 for tumor cores on the BraTS 2019/2020 datasets. Additionally, Saran Raj Sowrirajan et al. proposed an improved brain tumor segmentation method using a UNet-LSTM architecture. This approach combines the strengths of U-Net and Long Short Term Memory (LSTM) networks to precisely segment tumor regions into classes such as Edema, Background, Enhancing, and Non-enhancing, achieving high accuracy and precision. These existing solutions highlight the continuous evolution of brain tumor segmentation techniques, showcasing the potential of advanced deep learning models in improving segmentation accuracy and efficiency.

2.4 Problem Statement

The accurate segmentation of brain tumors in MRI scans is a crucial yet formidable task due to the heterogeneous nature of tumor appearance, size, and location, which complicates the diagnosis and treatment planning processes. Traditional segmentation methods and even some advanced deep learning models struggle with issues such as limited receptive fields, loss of spatial information, and inadequate contextual understanding, leading to suboptimal results. These challenges necessitate the development of more sophisticated models capable of handling the intricate details and variability inherent in brain tumor images. Our project aims to address these issues by leveraging the U-Net architecture with enhancements to improve segmentation accuracy, ultimately contributing to more precise and reliable brain tumor detection and aiding in the advancement of clinical workflows in medical imaging.

CHAPTER - 3

PROPOSED SOLUTION

3.1 Overview:

This project focuses on improving the accuracy of brain tumor segmentation in MRI scans using the 'Brain MRI Segmentation' dataset by Mateusz buda, which includes MRI images and FLAIR abnormality segmentation masks. We utilized the U-Net architecture, renowned for its effectiveness in biomedical imaging, featuring a contracting path (encoder) and an expansive path (decoder). The model was trained with a combination of Dice Loss and Categorical Focal Loss, optimized using the Adam-W optimizer at a learning rate of 0.0001. Evaluation metrics included accuracy, precision, recall, Dice score, and Intersection over Union (IoU), with the model achieving a high Dice score, indicating robust segmentation performance. This demonstrates the potential of U-Net in automating brain tumor segmentation, significantly enhancing clinical workflows and aiding in the accurate diagnosis and treatment planning in medical imaging.

3.2 Block Diagram:




Fig-1 Block Diagram

CHAPTER - 4

SYSTEM SPECIFICATION

4.1 Hardware Specification:

Each T4 GPU features:

- 2,560 CUDA Cores
- 320 Tensor Cores
- 16 GB GDDR6 memory
- 320 GB/s memory bandwidth
- 8.1 TFLOPS FP32 performance
- 65 TFLOPS tensor performance (mixed precision)
-

The hardware that are needed for the system functioning are:

- CPU: Intel Core i7 or AMD Ryzen 7
- RAM: 16 or 32 GB
- GPU: NVIDIA RTX 2070 or higher
- Storage: SSD with at least 500 GB of space
- Operating System: Windows, Linux, or macOS.

4.2 Software Requirements:

The software prerequisites for the Brain Tumor Segmentation using U-NET system are basic. It should run on a Windows or Linux operating system with Python (3.10.5) installed. The required Python libraries and their versions are as follows:

- Torch: 2.0.0
- Torchvision: 0.15.1
- Albumentations: 1.3.1
- PIL (Python Imaging Library): 9.5.0
- tqdm: 4.66.1
- scikit-learn (sklearn): 1.2.2
- torchinfo: 1.8.0
- torchview: 0.2.6

Additionally, TensorFlow and Keras libraries will be utilized for the software's Brain Tumor Segmentation using U-NET.

4.3 Dataset:

The dataset utilized in this project is the 'Brain MRI Segmentation' dataset, specifically focusing on lower-grade gliomas (LGG). This dataset was employed in research studies by Mateusz Buda et al. (2019) and Maciej A. Mazurowski et al. (2017), exploring the association of genomic subtypes of lower-grade gliomas with shape features extracted through deep learning algorithms. The dataset includes brain MRI images and manual segmentation masks for FLAIR abnormalities, which are critical for identifying regions affected by the tumor. These images were sourced from The Cancer Imaging Archive (TCIA), ensuring high-quality and standardized imaging data suitable for rigorous analysis.

The dataset comprises MRI scans from 110 patients, all part of The Cancer Genome Atlas (TCGA) lower-grade glioma collection. Each patient's dataset includes at least one fluid-attenuated inversion recovery (FLAIR) sequence and corresponding genomic cluster data, making it a rich resource for radiogenomic studies. Additionally, tumor genomic clusters and patient data are provided in a comprehensive data.csv file, enabling researchers to correlate imaging features with genomic subtypes and clinical outcomes. This extensive dataset supports the development and validation of advanced deep learning models for brain tumor segmentation, enhancing the potential for automated, accurate, and clinically relevant tumor detection and characterization.




Fig-2 Train Data

CHAPTER - 5

PROJECT DESCRIPTION

5.1 Methodology:

5.1.1 Model Architecture:

The U-Net architecture is an advanced technique used in segmentation tasks, particularly beneficial in the field of biotechnology. The architecture of U-Net consists of three main parts: the contraction path, the bottleneck, and the expansion path. The below architecture clearly depicts the different parts of it and layers used in them.




Fig-3 u-net architecture

Contraction Path:

In the contraction path, the input undergoes two convolutional layers, each followed by a ReLU activation function, and one max-pooling operation with a 2x2 window. As we proceed through the contraction phase, the number of channels increases, capturing more complex features. During max pooling, the height and width of the image are reduced, which helps in downsampling the spatial dimensions while increasing the depth.

Bottleneck:

The bottleneck is the part of the network that connects the contraction and expansion paths. It consists of two convolutional layers with ReLU activations. This part of the network captures the most abstract features of the input image.

Expansion Path:

In the expansion path, the features are upsampled to the original image size. At each level, the upsampled feature map is concatenated with the corresponding feature map from the contraction path. This concatenation helps in retaining high-resolution features and ensures that the spatial information is preserved. The upsampling is typically done using transposed convolution layers.

5.1.2 Model Implementation

The U-Net architecture used in brain tumor segmentation has main parts:

- Contraction Path (Encoder)
- Bottleneck
- Expansion Path (Decoder)

Contraction Path (Encoder)

The contraction path captures the context of the input image through a series of convolutional and max-pooling layers. Each step in the contraction path consists of two 3x3 convolutional layers followed by a 2x2 max-pooling layer. As we move deeper into the network, the spatial dimensions of the feature maps reduce, while the number of channels increases, allowing the network to learn complex features.

Input Image:

The input to the network is a 2D image tile of size 572x572 pixels with a single channel.

Convolutional Layers:

Each convolutional layer is followed by a ReLU activation function. The number of filters increases at each step, starting from 64 filters and doubling at each subsequent step.

Max-Pooling Layers:

After each pair of convolutional layers, a max-pooling operation with a 2x2 window is applied, reducing the spatial dimensions by half.

Bottleneck:

The bottleneck connects the contraction path to the expansion path. It consists of two 3x3 convolutional layers followed by ReLU activations. This part of the network captures the most abstract features of the input image.

Convolutional Layers:

The bottleneck consists of 1024 filters, and it operates on feature maps of reduced spatial dimensions.

Expansion Path (Decoder):

The expansion path reconstructs the image from the abstract features learned in the bottleneck. It uses transposed convolutional layers (also known as up-convolutional layers) to upsample the feature maps, increasing the spatial dimensions. At each step, the upsampled feature map is concatenated with the corresponding feature map from the contraction path, ensuring that high-resolution features are preserved.

Transposed Convolutional Layers:

These layers upsample the feature maps by a factor of 2.

Concatenation: The upsampled feature maps are concatenated with the corresponding feature maps from the contraction path.

Convolutional Layers: Each concatenated feature map passes through two 3x3 convolutional layers followed by ReLU activations. The number of filters decreases at each step, halving at each subsequent step.

Output Layer:

The final layer of the U-Net is a 1x1 convolutional layer that maps each feature vector to the desired number of output channels. In this case, we have two output channels corresponding to the binary segmentation map (tumor and background).

Output Segmentation Map:

The final output is a segmentation map of size 388x388 pixels.




Fig-4 Model architecture

5.1.3 Model Evaluation

The evaluation involves analyzing the training and validation loss, as well as the Dice score over 100 epochs. The loss and Dice score trends are plotted to visualize the performance improvement throughout the training process.

Loss Analysis

The loss curve shows a consistent decline over the epochs for both training and evaluation datasets. Initially, the training loss starts at 0.378506 and decreases sharply during the first few epochs. By the end of the training (epoch 100), the training loss reaches a low of 0.006100. Similarly, the evaluation loss starts at 0.320369 and reduces steadily, concluding at 0.007239. This consistent reduction in loss for both training and evaluation indicates that the model is learning effectively without overfitting, as the evaluation loss remains close to the training loss.

Dice Score Analysis

The Dice score, which is a measure of the model's accuracy in segmenting the tumor regions, shows significant improvement over the training epochs. Initially, the training Dice score starts at 0.317758 and sees a rapid increase, stabilizing at around epoch 20. By the end of the training, the Dice score reaches 0.919853. The evaluation Dice score follows a similar trend, starting at 0.071576 and improving steadily to 0.903832. The close alignment between the training and evaluation Dice scores suggests that the model maintains good generalization performance on unseen data.

The evaluation metrics demonstrates the model's robustness in segmenting brain tumors. The continuous decline in loss values and the substantial increase in Dice scores across epochs highlight the model's effectiveness. The minimal gap between training and evaluation metrics confirms that the model is not overfitting and performs consistently well on both training and validation datasets. These results validate the model's capability to accurately segment brain tumors, making it a reliable tool for medical image analysis

CHAPTER – 6

RESULT & IMPLEMENTATIONS

6.1 Results:

Diagnosis Classification Metrics:

The model's performance on the classification of MRI samples into 'NORMAL' and 'TUMOR' categories is summarized below:

	precision	recall	f1-score	support
NORMAL	0.96	0.98	0.97	499
TUMOR	0.97	0.93	0.95	268
accuracy			0.97	767
macro avg	0.97	0.96	0.96	767
weighted avg	0.97	0.97	0.97	767

Fig-5: Diagnosis Classification Metrics

Performance Metrics:

- Accuracy: 0.9661
- Precision: 0.9662
- Recall: 0.9661
- F1-Score: 0.9659
- Matthew's Correlation Coefficient (MCC): 0.9252

The model achieved an F1-score of approximately 96% for tumor detection, indicating quality differentiation between normal and tumor MRI cases. The high MCC of around 93% further supports the model's strong diagnostic capabilities. The error rate for diagnosing tumor presence is approximately 3%. Given the test set consists of 767 samples, this amounts to about 23 incorrectly assessed samples. For every 1000 MRI samples, we can expect around 30 incorrectly diagnosed samples.

Semantic Segmentation Metrics

The performance of the brain tumor segmentation model was evaluated using various metrics, including accuracy, precision, recall, Dice score, and Intersection over Union (IoU). The metrics are presented in the table below for overall performance, as well as for non-diagnosed and diagnosed cases separately.

	accuracy	precision	recall	dice_score	IoU
overall_metrics	0.997745	0.795368	0.852853	0.280552	0.251145
non_diagnosed_metrics	0.999907	0.000000	NaN	0.000000	0.000000
diagnosed_metrics	0.993720	0.839381	0.852853	0.802923	0.718761

Fig-6: Overall Performance

Accuracy: Measures the number of correctly classified pixels in the generated mask. While straightforward, this metric is not always the most appropriate for segmentation due to class imbalance. It often reports an accuracy greater than 90%, but actual segmentation performance may be lower.

Dice Score/Coefficient: A popular segmentation metric that measures the overlap between the predicted and actual masks. It ranges from 0 to 1, with 1 indicating perfect overlap. The Dice score is computed as:

$$DiceScore = 2 \frac{|y_{target} \cap y_{pred}|}{|y_{target}| + |y_{pred}|}$$

Fig-7: Dice Score Formula

Jaccard Index (IoU): Evaluates the overlap between the predicted and actual segmentation masks, divided by their union area. It ranges from 0 to 1, with 1 indicating perfect overlap. The IoU is calculated as:

$$IoU = \frac{|y_{target} \cap y_{pred}|}{|y_{target} \cup y_{pred}|}$$

Fig-8: Jaccard Index Formula

The model achieved a validation average Dice score of approximately 90%, compared to the test average Dice score of around 82%. This discrepancy indicates that while the model produces good segmentation masks, there is still room for improvement. Overall, the model demonstrated the ability to converge to a lower loss for both training and validation sets and reached a plateau on the training and validation Dice scores, suggesting stable training and validation performance.

CHAPTER – 7

CONCLUSION & FUTURE SCOPE

7.1 Conclusion:

The project is successfully implemented with U-Net architecture to train a model for segmenting brain tumors in MRI scans. The model achieved a Jaccard Index of approximately 0.73 and a Dice score of around 0.82 on the test set. These metrics indicate that the model can produce decent quality segmentations, though there is room for further improvement.

Moreover, the model demonstrated its capability to accurately diagnose normal and tumor cases, achieving an error rate of about 3%. This means that for every 1000 MRI samples, approximately 30 may be incorrectly diagnosed.

Additionally, the model achieved a high Matthew's Correlation Coefficient (MCC) of approximately 93%, indicating a strong understanding of how to diagnose MRI samples effectively.

These results underscore the potential of the U-Net model in clinical applications, offering a robust foundation for automated brain tumor segmentation and diagnosis. With further enhancements, such as using pre-trained backbones, training for more epochs, and employing ensemble techniques, the model's performance can be significantly improved. This project thus lays the groundwork for developing more reliable and efficient clinical workflows in medical imaging, ultimately benefiting patient diagnosis and treatment planning.

7.2 Future Scope:

The future scope of this project depends on several key enhancements to improve the current results achieved by the U-Net model for brain tumor segmentation.

Training for more epochs: Training for more epochs allows the model to learn more from the data, capturing more complex patterns and relationships, which can potentially lead to better performance. Increasing the number of training epochs can help, but it is crucial to monitor for overfitting by evaluating the model's performance on the validation set at each epoch. Implementing learning rate schedulers to adjust the learning rate dynamically during training can help the model converge better over longer training periods. However, more epochs will increase training time, so adequate computational resources and early stopping criteria should be in place to manage this.

Using ensembles: Ensembling involves combining the predictions of multiple models to produce a more robust and accurate final prediction. This technique can mitigate the weaknesses of individual models and leverage their strengths. Training several instances of the U-Net model, possibly with different initializations, hyperparameters, or even different architectures, and aggregating the predictions from these models using techniques like averaging, majority voting, or more sophisticated methods like stacking can significantly improve segmentation performance by reducing variance and bias.

However, training multiple models will require substantial computational resources and time, and inference time may also increase as predictions need to be aggregated from multiple models. Ensuring adequate computational resources and optimizing the ensembling process will balance performance improvements with resource constraints.

Implementing these strategies can substantially improve the performance of the brain tumor segmentation model. By leveraging pre-trained models, extending training duration, and employing ensemble techniques, the model's accuracy, precision, recall, Dice score, and IoU can be enhanced. These improvements will contribute to more reliable and efficient clinical workflows in medical imaging, ultimately benefiting patient diagnosis and treatment planning.

REFERENCES:

1. Islam, M., Vibashan, V.S., Jose, V.J.M., Wijethilake, N., Utkarsh, U., Ren, H. (2020). Brain Tumor Segmentation and Survival Prediction Using 3D Attention UNet. In: Crimi, A., Bakas, S. (eds) Brainlesion: Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries. BrainLes 2019. Lecture Notes in Computer Science(), vol 11992. Springer, Cham. https://doi.org/10.1007/978-3-030-46640-4_25
2. Li Z, Wu X, Yang X. A Multi Brain Tumor Region Segmentation Model Based on 3D U-Net. Applied Sciences. 2023; 13(16):9282. <https://doi.org/10.3390/app13169282>
3. Jason Walsh, Alice Othmani, Mayank Jain, Soumyabrata Dev, Using U-Net network for efficient brain tumor segmentation in MRI images, Healthcare Analytics, Volume 2, 2022, 100098, ISSN 2772-4425. <https://doi.org/10.1016/j.health.2022.100098>.

4. Sowrirajan, Saran & K S, Logeshwaran & Kalluri, Anisha & Subburam, Ravi. (2024). Improved Brain Tumor Segmentation Using UNet-LSTM Architecture. SN Computer Science. 5. 10.1007/s42979-024-02799-0.
5. Byeon H, Al-Kubaisi M, Dutta AK, Alghayadh F, Soni M, Bhende M, Chunduri V, Suresh Babu K and Jeet R (2024) Brain tumor segmentation using neuro-technology enabled intelligence-cascaded U-Net model. Front. Comput. Neurosci. 18:1391025. doi: 10.3389/fncom.2024.1391025
6. 1.Wang G., Li W., Ourselin S. and Vercauteren T. Automatic Brain Tumor Segmentation Based on Cascaded Convolutional Neural Networks With Uncertainty Estimation. Frontiers in Computational Neuroscience vol.13 pages 56 <https://doi.org/10.3389/fncom.2019.00056>, 2019
7. 2.McKinley R., Meier R., Wiest R. (2019) Ensembles of Densely-Connected CNNs with Label-Uncertainty for Brain Tumor Segmentation. In: Crimi A., Bakas S., Kuijf H., Keyvan F., Reyes M., van Walsum T. (eds) Brainlesion: Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries. BrainLes 2018. Lecture Notes in Computer Science, vol 11384. Springer.
8. 3.Dmitry Ulyanov and Andrea Vedaldi and Victor Lempitsky. Instance Normalization: The Missing Ingredient for Fast Stylization. arXiv preprint arXiv:1607.08022, 2016
9. 4.Kamnitsas, K., Ledig, C., Newcombe, V.F., Simpson, J.P., Kane, A.D., Menon, D.K., Rueckert, D., Glocker, B.: Efficient multi-scale 3D CNN with fully connected CRF for accurate brain lesion segmentation. Med. Image Anal. 36 (2017) 61–78
10. 5.Yarin Gal and Zoubin Ghahraman.Dropout as a Bayesian Approximation: Representing Model Uncertainty in Deep Learning. arXiv preprint arXiv:1506.02142, 2015
11. 6.Paszke, Adam and Gross, Sam and Chintala, Soumith and Chanan, Gregory and Yang, Edward and DeVito, Zachary and Lin, Zeming and Desmaison, Alban and Antiga, Luca and Lerer, Adam. Automatic differentiation in PyTorch, NIPS-W 2017
12. 7.Ronneberger, Olaf, Philipp Fischer, and Thomas Brox. "U-net: Convolutional net- works for biomedical image segmentation." MICCAI. Springer, 2015. https://doi.org/10.1007/978-3-319-24574-4_28
13. 8.Ozgün C, i,cek and Ahmed Abdulkadir and Soeren S. Lienkamp and Thomas Brox "and Olaf Ronneberger, "3D U-Net: Learning Dense Volumetric Segmentation from Sparse Annotation", arXiv preprint arXiv:1606.06650, 2016.

14. 9.W. R. Crum and O. Camara and D. L. G. Hill, "Generalized Overlap Measures for Evaluation and Validation in Medical Image Analysis", IEEE Transactions on Medical Imaging vol. 25, no. 11, pp. 1451–1461, 2006
15. Casamitjana, A., Puch, S., Aduriz, A., Vilaplana, V., "3D Convolutional Neural Networks for Brain Tumor Segmentation: a comparison of multi-resolution architectures". In: Brainlesion: Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries. BrainLes 2016. Lecture Notes in Computer Science, vol 10154. Springer,2017