

## Request Mocking

Intercept, mock, modify, and block network requests.

### CLI Route Commands

*# Mock with custom status*

```
playwright-cli route "**/*.jpg" --status=404
```

*# Mock with JSON body*

```
playwright-cli route "**/api/users" --body='[{"id":1,"name":"Alice"}]' --content
```

*# Mock with custom headers*

```
playwright-cli route "**/api/data" --body='{ "ok":true }' --header="X-Custom: valu
```

*# Remove headers from requests*

```
playwright-cli route "**/*" --remove-header=cookie,authorization
```

*# List active routes*

```
playwright-cli route-list
```

*# Remove a route or all routes*

```
playwright-cli unroute "**/*.jpg"
```

```
playwright-cli unroute
```

### URL Patterns

|                     |                          |
|---------------------|--------------------------|
| **/api/users        | - Exact path match       |
| **/api/*/details    | - Wildcard in path       |
| **/*.{png,jpg,jpeg} | - Match file extensions  |
| **/search?q=*       | - Match query parameters |

### Advanced Mocking with run-code

For conditional responses, request body inspection, response modification, or delays:

#### Conditional Response Based on Request

```
playwright-cli run-code "async page => {  
  await page.route('**/api/login', route => {  
    const body = route.request().postDataJSON();  
    if (body.username === 'admin') {  
      route.fulfill({ body: JSON.stringify({ token: 'mock-token' }) });  
    }  
  });  
}
```

```

    } else {
      route.fulfill({ status: 401, body: JSON.stringify({ error: 'Invalid' }) });
    }
  });
}

```

### Modify Real Response

```

playwright-cli run-code "async page => {
  await page.route('**/api/user', async route => {
    const response = await route.fetch();
    const json = await response.json();
    json.isPremium = true;
    await route.fulfill({ response, json });
  });
}"

```

### Simulate Network Failures

```

playwright-cli run-code "async page => {
  await page.route('**/api/offline', route => route.abort('internetdisconnected'
}"
# Options: connectionrefused, timedout, connectionreset, internetdisconnected

```

### Delayed Response

```

playwright-cli run-code "async page => {
  await page.route('**/api/slow', async route => {
    await new Promise(r => setTimeout(r, 3000));
    route.fulfill({ body: JSON.stringify({ data: 'loaded' }) });
  });
}"

```