

Storage Management

Manage cookies, localStorage, sessionStorage, and browser storage state.

Storage State

Save and restore complete browser state including cookies and storage.

Save Storage State

Save to auto-generated filename (storage-state-{timestamp}.json)
playwright-cli state-save

Save to specific filename
playwright-cli state-save my-auth-state.json

Restore Storage State

Load storage state from file
playwright-cli state-load my-auth-state.json

Reload page to apply cookies
playwright-cli open https://example.com

Storage State File Format

The saved file contains:

```
{
  "cookies": [
    {
      "name": "session_id",
      "value": "abc123",
      "domain": "example.com",
      "path": "/",
      "expires": 1735689600,
      "httpOnly": true,
      "secure": true,
      "sameSite": "Lax"
    }
  ],
  "origins": [
    {
```

```

    "origin": "https://example.com",
    "localStorage": [
      { "name": "theme", "value": "dark" },
      { "name": "user_id", "value": "12345" }
    ]
  }
]
}

```

Cookies

List All Cookies

```
playwright-cli cookie-list
```

Filter Cookies by Domain

```
playwright-cli cookie-list --domain=example.com
```

Filter Cookies by Path

```
playwright-cli cookie-list --path=/api
```

Get Specific Cookie

```
playwright-cli cookie-get session_id
```

Set a Cookie

Basic cookie

```
playwright-cli cookie-set session abc123
```

Cookie with options

```
playwright-cli cookie-set session abc123 --domain=example.com --path=/ --httpOnly
```

Cookie with expiration (Unix timestamp)

```
playwright-cli cookie-set remember_me token123 --expires=1735689600
```

Delete a Cookie

```
playwright-cli cookie-delete session_id
```

Clear All Cookies

```
playwright-cli cookie-clear
```

Advanced: Multiple Cookies or Custom Options

For complex scenarios like adding multiple cookies at once, use run-code:

```
playwright-cli run-code "async page => {  
  await page.context().addCookies([  
    { name: 'session_id', value: 'sess_abc123', domain: 'example.com', path: '/' },  
    { name: 'preferences', value: JSON.stringify({ theme: 'dark' }), domain: 'example.com' },  
  ]);  
}"
```

Local Storage

List All localStorage Items

```
playwright-cli localStorage-list
```

Get Single Value

```
playwright-cli localStorage-get token
```

Set Value

```
playwright-cli localStorage-set theme dark
```

Set JSON Value

```
playwright-cli localStorage-set user_settings '{"theme":"dark","language":"en"}'
```

Delete Single Item

```
playwright-cli localStorage-delete token
```

Clear All localStorage

```
playwright-cli localStorage-clear
```

Advanced: Multiple Operations

For complex scenarios like setting multiple values at once, use run-code:

```
playwright-cli run-code "async page => {  
  await page.evaluate(() => {  
    localStorage.setItem('token', 'jwt_abc123');  
  });  
}"
```

```

        localStorage.setItem('user_id', '12345');
        localStorage.setItem('expires_at', Date.now() + 3600000);
    });
}"

```

Session Storage

List All sessionStorage Items

```
playwright-cli sessionstorage-list
```

Get Single Value

```
playwright-cli sessionstorage-get form_data
```

Set Value

```
playwright-cli sessionstorage-set step 3
```

Delete Single Item

```
playwright-cli sessionstorage-delete step
```

Clear sessionStorage

```
playwright-cli sessionstorage-clear
```

IndexedDB

List Databases

```

playwright-cli run-code "async page => {
  return await page.evaluate(async () => {
    const databases = await indexedDB.databases();
    return databases;
  });
}"

```

Delete Database

```

playwright-cli run-code "async page => {
  await page.evaluate(() => {
    indexedDB.deleteDatabase('myDatabase');
  });
}"

```

Common Patterns

Authentication State Reuse

```
# Step 1: Login and save state
playwright-cli open https://app.example.com/login
playwright-cli snapshot
playwright-cli fill e1 "user@example.com"
playwright-cli fill e2 "password123"
playwright-cli click e3

# Save the authenticated state
playwright-cli state-save auth.json

# Step 2: Later, restore state and skip login
playwright-cli state-load auth.json
playwright-cli open https://app.example.com/dashboard
# Already logged in!
```

Save and Restore Roundtrip

```
# Set up authentication state
playwright-cli open https://example.com
playwright-cli eval "() => { document.cookie = 'session=abc123'; localStorage.se

# Save state to file
playwright-cli state-save my-session.json

# ... later, in a new session ...

# Restore state
playwright-cli state-load my-session.json
playwright-cli open https://example.com
# Cookies and localStorage are restored!
```

Security Notes

- Never commit storage state files containing auth tokens
- Add *.auth-state.json to .gitignore
- Delete state files after automation completes
- Use environment variables for sensitive data
- By default, sessions run in-memory mode which is safer for sensitive operations