

Running Playwright Tests

To run Playwright tests, use the `npx playwright test` command, or a package manager script. To avoid opening the interactive html report, use `PLAYWRIGHT_HTML_OPEN=never` environment variable.

```
# Run all tests
```

```
PLAYWRIGHT_HTML_OPEN=never npx playwright test
```

```
# Run all tests through a custom npm script
```

```
PLAYWRIGHT_HTML_OPEN=never npm run special-test-command
```

Debugging Playwright Tests

To debug a failing Playwright test, run it with `--debug=cli` option. This command will pause the test at the start and print the debugging instructions.

IMPORTANT: run the command in the background and check the output until “Debugging Instructions” is printed. Make sure to stop the command after you have finished.

Once instructions containing a session name are printed, use `playwright-cli` to attach the session and explore the page.

```
# Run the test
```

```
PLAYWRIGHT_HTML_OPEN=never npx playwright test --debug=cli
```

```
# ...
```

```
# ... debugging instructions for "tw-abcdef" session ...
```

```
# ...
```

```
# Attach to the test
```

```
playwright-cli attach tw-abcdef
```

Keep the test running in the background while you explore and look for a fix. The test is paused at the start, so you should step over or pause at a particular location where the problem is most likely to be.

Every action you perform with `playwright-cli` generates corresponding Playwright TypeScript code. This code appears in the output and can be copied directly into the test. Most of the time, a specific locator or an expectation should be updated, but it could also be a bug in the app. Use your judgement.

After fixing the test, stop the background test run. Rerun to check that test passes.