



Ollscoil
Teicneolaíochta
an Oirdheiscirt

South East
Technological
University

Physics 2 Reports

SETU - South East Technological University

Imbriani Paolo - W20114452

Professor Joe Murphy

April 1, 2025

Contents

1	Lab 1 - Specific Heat Capacity by Electrical Heating, 28/01/2025	3
1.1	Theory	3
1.1.1	Aim(s)	3
1.1.2	Procedure	3
1.2	Experiment	4
1.3	Questions	5
1.4	Conclusion	5
2	Exp 3 - Calibration of a Thermocouple, 11/02/2025	6
2.1	Theory	6
2.1.1	Aim(s)	6
2.1.2	Procedure	6
2.2	Diagrams/Apparatus	6
2.3	Questions	8
3	Exp 5 - RC Circuitry	8
3.1	Theory	8
3.1.1	Aim(s)	9
3.2	Experiment	9
3.2.1	Charging	9
3.2.2	Discharging	11
4	Exp 5 - Experiments on Half-wave and Full-wave Rectifiers	12
4.1	Aim	12

1 Lab 1 - Specific Heat Capacity by Electrical Heating, 28/01/2025

1.1 Theory


By electrically heating a lagged metal block and carefully noting the rate of heating and the temperature changes caused, the specific heat capacity of a metal can be evaluated by plotting a suitable graph.

1.1.1 Aim(s)

The aim of this experiment is to find the specific heat of the material we are heating electrically.

1.1.2 Procedure

As in Lab manual.



1.2 Experiment

V (volt)	I (Ampere)	t (s)	Temp (°C)	ΔT	Q (mc ΔT)
0	0	0	17	0	0
8.34	2.7	120	20.5	3.5	2702.16
8.34	2.7	240	27	10	5404.32
8.34	2.7	360	35	18	8106
8.4	2.7	480	43	26	10808
8.3	2.7	600	51	34	13510.8

Figure 1: Table of measurements




Figure 2: Graph of ΔT against t




Figure 3: Graph of Q against ΔT

1.3 Questions

1. In your opinion, is it important that the block is well insulated during the experiment? Why? It is important since proper insulation ensures that most of the electrical energy supplied to the block is used to increase its temperature rather than being lost to the surroundings.
2. If you were to increase the current (A) used in this experiment, to a value higher than you used, would it change the experiment in any way? Give reasons as to your answer. Uncreasing the current beyond 2.7 Ampere, would definitely change the experiment. The rate of heating would increase, and the temperature of the block would increase more rapidly. This would make it more difficult to measure the temperature accurately and to record the data in a timely manner.
3. What is the function of the big variable resistor (rheostat) in this experiment? Give reasons as to you answer. The big variable resistor (rheostat) is used to control the current flowing through the circuit. By adjusting the resistance of the rheostat, the current can be adjusted to the desired value. This allows the rate of heating of the block to be controlled and the temperature changes to be measured accurately.

1.4 Conclusion

We found the slope coefficient which 379,9975. We just divide the slope by the mass of the material to get the specific heat capacity of the material. The specific heat capacity of the material is 385 J/kg°C. Which exactly matches the specific heat capacity of the material we were testing.

2 Exp 3 - Calibration of a Thermocouple, 11/02/2025

2.1 Theory

A Thermocouple is formed by joining two metals. When two different metals are joined and connected through a sensitive voltmeter, it is found that whenever a temperature difference exists between the junctions a reading is recorded on the voltmeter. The greater the temperature difference between the junctions the larger the reading. This property of the Thermocouple can be used to measure temperature. In practice the cold junction is maintained at a fix temperature i.e 0° C.

2.1.1 Aim(s)

The aim of the experiment is to calibrate a Thermocouple.

2.1.2 Procedure


As in lab manual.

2.2 Diagrams/Apparatus

Voltmeter, 2 Becker, Thermocouple, thermometer.

Temperature (°C)	Voltage (mV) Hot	Voltage (mV) Cold	Average Voltage (mV)
0	0	0	0
10	0.1	0.35	0.05
20	0.4	0.3	0.35
30	1.1	0.9	1
40	1.5	1.3	1.4
50	2.1	1.6	1.7
60	2.3	2.1	2.2
70	2.7	2.4	2.55
80	3	2.8	2.9
90	3.5	3.2	3.35
100	3.8	3.7	3.75

Figure 4: Table of measurements






Figure 5: Graph of Average Voltage against Temperature

So we found that the equation for this graph is:

$$y = 0.04x - 0.2114$$

2.3 Questions

Use the thermocouple and the calibration graph to estimate:

- a. Room Temperature $\rightarrow 19^\circ\text{C}$ so using the graph equation: $y = 0.04x - 0.2114 \rightarrow 0.5486$
- b. Body Temperature $\rightarrow 37^\circ\text{C} \rightarrow (37 * 0.04) - 0.2114 = 1.2686$
- c. The temperature of water from the tap in the lab $\rightarrow 17.5^\circ\text{C}$ $(17.5 * 0.04) - 0.2114 = 0.4886$

3 Exp 5 - RC Circuitry

3.1 Theory

It can be shown that the voltage and the current in the circuit as follow:

$$V_c(t) = V_0(1 - e^{-\frac{t}{\tau}})$$

$$I(t) = \frac{V_0}{R}e^{-\frac{t}{\tau}}$$

where $\tau = CR$. In this experiment we are going to show these relationships.

3.1.1 Aim(s)

To build and test an RC circuit under (a) charge and (b) discharge conditions

3.2 Experiment

3.2.1 Charging

Time (s)	Voltage (V)
0	0
5	0.20
10	0.45
15	0.69
20	1.1
:	:
60	2.65
120	4.20
180	5.45
240	6.40
300	7.12
360	7.70
420	8.14
480	8.50
540	8.83
600	9.17
:	:
1380	9.99

Figure 6: Table of measurements while charging the circuits




Figure 7: Graph of Voltage against Time

The RC time constant (τ) is estimated to be approximately 240 seconds, as indicated by the red dashed line at the time where the voltage reaches 63% of its final value

3.2.2 Discharging

Time (s)	Voltage (V)
0	10
5	9.95
10	9.92
15	9.90
20	9.87
:	:
60	9.65
120	9.35
180	9.10
240	8.90
300	8.70
360	8.50
420	8.30
:	:
A long time	0.1

Figure 8: Table of measurements while discharging the circuits




Figure 9: Graph of Voltage against Time while discharging

The plot of Voltage (V) versus Time (s) for the discharging circuit shows an exponential decay. However, based on the extracted data, the estimated RC time constant (τ) appears to be around 5000 seconds, which seems too large and might be due to the lack of a closer data point near 37% of the initial voltage.

Questions:

- **Does the graph follow the expected shape for an RC circuit?** Yes, the graph follows the expected shape for an RC circuit which is an exponential decay for the discharging circuit and an exponential growth for the charging circuit.
- **What is the value of τ , the time constant for your circuit?** We have that $R = 0.230 \times 10^6 \Omega$ and $C = 1000 \times 10^{-6} F$. The theoretical RC time constant τ is 230 seconds. This is close to our earlier estimated value of 240 seconds from the charging experiment, which suggests that our experimental data is reasonably accurate.
- **How does this compare to your experimental value? (67.3% of voltage in charge, 32.7% of voltage in discharge).** The experimental value of the time constant for the charging circuit is close to the theoretical value, as the voltage reaches 63% of its final value at 240 seconds. However, the time constant for the discharging circuit is significantly larger than the theoretical value, which might be due to the lack of a closer data point near 37% of the initial voltage.

4 Exp 5 - Experiments on Half-wave and Full-wave Rectifiers

4.1 Aim

The objectives of this experiment are:

1. To display a sinusoidal electrical signal on an oscilloscope and measure its amplitude and frequency
2. To set up a half-wave rectifier circuit and investigate its operation using the oscilloscope
3. To set up a full-wave rectifier circuit and investigate its operation using the oscilloscope