

MagicCode Super-Resolution Software API Reference

Document Version: v1.2.0. Header: mc_interface.h

1. Overview

The MagicCode Super-Resolution native API is a C-compatible interface for initialization, image processing, parameter control, status query, resource release, and version query. C++ projects should include the header normally; symbols are exported with extern "C".

2. Core Workflow

- 1 Create and fill input_param_t.
- 2 Call MC_Init and keep the returned opaque handle.
- 3 Call MC_Process for processing.
 - 4 Optionally call MC_Control with SET_PARAM or QUERY_STATUS.
- 5 Call MC_Uninit exactly once for each successfully initialized handle.

3. Enumerations

Enum Values	Description
-------------	-------------

cmd_params_e	
SET_PARAM, QUERY_STATUS	
Control command type.	
input_type_e	
INPUT_BUFFER, INPUT_BUFFER_R8, INPUT_BUFFER_RGB, INPUT_TEXTURE_RGB8Unorm, INPUT_TEXTURE_R8Unorm	
Input memory or texture type.	
alg_mode_e	
SPEED_MODE, BALANCED_MODE	
Public algorithm mode.	
magic_backend_e	
MAGIC_BACKEND_DEFAULT, MAGIC_BACKEND_X86, MAGIC_BACKEND_NEON, MAGIC_BACKEND_METAL, MAGIC_BACKEND_OPENGL, MAGIC_BACKEND_OPENGL_ES, MAGIC_BACKEND_VULKAN, MAGIC_BACKEND_D3D11	
Runtime backend selector.	
log_level_e	
NONE, ERROR, WARNING, INFO, DEBUG	
Runtime log verbosity.	

4. Structures

4.1 input_param_t

Field	Description
-------	-------------

input_type	Input type. CPU backends use buffer input (R8 or planar RGB); GPU backends use texture input.
model_path[256]	Path to model file. Maximum effective path length is 255 characters plus null terminator.
width, height	Input width and height. Valid range: 64 to 4096.
scalar_factor	Requested scale. Valid range: 1.0 to 8.0; actual support depends on backend/model.
alg_mode	SPEED_MODE or BALANCED_MODE. sharpen_level is 0 to 5 (0 = off).
num_threads	CPU thread count, valid range 1 to 8. Multi-threading takes effect when height is at least 256.
log_level	Log verbosity.

backend
Runtime backend selector.

4.2 control_param_t

Used with MC_Control(..., SET_PARAM, ...) to update width, height, scale, mode, and model path. Reinitialization may occur internally when parameters require it.

4.3 output_status_params_t

Used with MC_Control(..., QUERY_STATUS, ...). It returns input dimensions, output dimensions, scale, algorithm mode, input type, backend, thread count, GPU time, and latest error code.

5. Functions

	Function Purpose Return
--	-------------------------------

void* MC_Init(input_param_t* param)	Initializes the SR engine and creates a handle. Opaque handle on success; NULL on failure.
int MC_Process(void* handle, void* image_in, void* image_out)	Runs super-resolution on one input buffer or texture. 0 on success; non-zero on failure.
int MC_Control(void* handle, cmd_params_e cmd, control_param_t* ctrl, output_status_params_t* output)	Sets parameters or queries status. 0 on success; non-zero on failure.
int MC_Uninit(void* handle)	Releases resources for a handle. 0 on success; non-zero on failure.
char* MC_GetVersion(void)	Returns static version string. Non-null version string pointer. Do not free.

6. Minimal Native C Example

The following example shows the basic lifecycle for CPU buffer input. It is intended as a compact reference for API usage. Production code should add project-specific memory management, image format conversion, logging, and error handling.

```
#include "mc_interface.h"
#include <stdio.h>
#include <string.h>

int run_magic_sr_y8(const char *model_path,
                   unsigned char *input_y,
                   unsigned char *output_y,
                   unsigned int width,
                   unsigned int height)
{
    input_param_t param;
    memset(&param, 0, sizeof(param));

    param.input_type = INPUT_BUFFER;
    strncpy(param.model_path, model_path, sizeof(param.model_path) - 1);
    param.width = width;
    param.height = height;
    param.scaler_factor = 2.0f;
    param.alg_mode = SPEED_MODE;
    param.sharpen_level = 0;
    param.num_threads = 4;
    param.log_level = MAGIC_LOG_INFO;
    param.backend = MAGIC_BACKEND_NEON; /* Use MAGIC_BACKEND_X86 on x86_64 CPU
    builds. */
```

```

printf("MagicSR version: %s\n", MC_GetVersion());

void *handle = MC_Init(&param);
if (handle == NULL) {
    printf("MC_Init failed\n");
    return -1;
}

int process_ret = MC_Process(handle, input_y, output_y);
if (process_ret != 0) {
    printf("MC_Process failed: %d\n", process_ret);
    MC_Uninit(handle);
    return process_ret;
}

output_status_params_t status;
memset(&status, 0, sizeof(status));
int query_ret = MC_Control(handle, QUERY_STATUS, NULL, &status);
if (query_ret == 0) {
    printf("output=%ux%u backend=%d error=0x%08x\n",
        status.output_width,
        status.output_height,
        status.backend,
        status.error_code);
}

int uninit_ret = MC_Uninit(handle);
return uninit_ret;
}

```

6.1 Example Notes

- Use MAGIC_BACKEND_NEON on ARM64 CPU builds and MAGIC_BACKEND_X86 on supported x86_64 CPU builds.
- For GPU backends such as Metal, OpenGL, OpenGLES, Vulkan, or Direct3D 11, set a texture input type and pass valid backend-specific texture handles to MC_Process.
- The model file must match the selected backend, algorithm mode, sharpen level, and scale configuration. Combined bins magic_sr_gpu_params.bin and magic_sr_cpu_params.bin are preferred.
- Always call MC_Uninit for a successfully created handle, including error paths after initialization.

7. Error Handling

Most API failures are represented by negative error codes. Refer to the Error Code Manual for the complete list. Common categories include initialization errors, processing errors, control errors, uninitialization errors, memory errors, and reporting errors.

8. Threading and Resource Notes

- Do not use a handle after MC_Uninit.
- Do not call MC_Uninit multiple times on the same handle.
- Use separate handles for independent streams unless your integration has explicitly serialized access.
- Copy or consume output data before subsequent calls if your integration uses reusable internal buffers.