Deepdots | Popup SDK Release Validation Report

SDK: Deepdots native popup SDK **0.7.11** (Android `com.deepdots.sdk:shared-android:0.7.11` · iOS `DeepdotsSDK-SPM` 0.7.11)
Validation date: 2026-11-07
Platforms: iOS / Android
Overall status: FAILED
Report type: Automated release validation, generated from the CI test results (no manual edits)

---

1. Executive Summary

SDK 0.7.11 was validated as published (Maven Central and Swift Package Manager) inside dedicated native test applications that integrate the SDK the same way a customer app does.

Results (CI run):

- **400** automated test executions on **16** configurations (7 iOS, 9 Android)
- **373** passed (3 on the automatic retry)
- **4** failed
- **23** not applicable on that platform
- Manual pass on real devices: **pending** (section 7)

iOS: FAILED · **Android:** FAILED

Validation status: FAILED

Failures

Platform	Configuration	Test	Detail
iOS	iOS 16.4 iPhone SE (3rd generation) Debug	survey-missing	xcuitest.installer.LocalXCTestInstaller$IOSDriverTimeoutException: iOS driver not ready in time, consider increasing timeout by configuring MAESTRO_DRIVER_STARTUP_TIMEOUT env variable
Android	A26 phone debug	survey-sdk-2.2.38	Assertion is false: "Czy zrobi.*NORDLY.*" is visible
Android	A26 phone release	survey-sdk-2.2.38	Assertion is false: "Czy zrobi.*NORDLY.*" is visible
Android	A34 tablet debug	rating-labels	Assertion is false: "Accept all" is visible

2. Test Results

Test category	iOS	Android
SDK initialization and version check	PASS	PASS
Path-based triggers and excluded screens	PASS	PASS
Time-based triggers	PASS	PASS
Event and click triggers	PASS	PASS
Exit triggers	PASS	PASS
Re-display rules (cooldown)	PASS	PASS
Audience segmentation by language	PASS	PASS
Popup opening and closing	PASS	PASS
Survey rendering, interactions and submission	PASS	**FAIL**
Navigation and app lifecycle (background / foreground, rotation)	PASS	PASS
Network failures and recovery	**FAIL**	PASS
Detection check: a missing navigation event is caught	PASS	PASS
Survey SDK versions assigned in the Admin (DD-70)	PASS	**FAIL**
Visual regression	AUTOMATED: screenshots of the popup states (iOS + Android, standard and small screen) compared with approved baselines by the job "Visual regression · · SDK local" (test-apps/visual/README.md).	AUTOMATED: screenshots of the popup states (iOS + Android, standard and small screen) compared with approved baselines by the job "Visual regression · · SDK local" (test-apps/visual/README.md).

`–` = not part of that platform's suite.

3. Tested Environments

Platform	OS version	Device	Build	SDK resolved	Engine	Result
Android	API 26	pixel_6 (emulator)	debug	0.7.11	WebView 69.0.3497.100	**FAIL**
Android	API 26	pixel_6 (emulator)	release (R8)	0.7.11	WebView 69.0.3497.100	**FAIL**
Android	API 30	pixel_6 (emulator)	debug	0.7.11	WebView 83.0.4103.106	PASS
Android	API 30	pixel_6 (emulator)	release (R8)	0.7.11	WebView 83.0.4103.106	PASS
Android	API 34	pixel_6 (emulator)	debug	0.7.11	WebView 113.0.5672.136	PASS
Android	API 34	pixel_6 (emulator)	release (R8)	0.7.11	WebView 113.0.5672.136	PASS
Android	API 34	pixel_tablet (emulator)	debug	0.7.11	WebView 113.0.5672.136	**FAIL**
Android	API 36	pixel_6 (emulator)	debug	0.7.11	WebView 133.0.6943.137	PASS
Android	API 36	pixel_6 (emulator)	release (R8)	0.7.11	WebView 133.0.6943.137	PASS
iOS	iOS-16-4	iPhone SE (3rd generation) (simulator)	Debug · Xcode_16.4	0.7.11	—	**FAIL**
iOS	iOS-17-5	iPhone 15 (simulator)	Debug · Xcode_16.4	0.7.11	—	PASS
iOS	iOS-18-6	iPad (A16) (simulator)	Debug · Xcode_16.4	0.7.11	—	PASS
iOS	iOS-18-6	iPhone 16 Pro (simulator)	Debug · Xcode_16.4	0.7.11	—	PASS
iOS	iOS-18-6	iPhone 16 Pro Max (simulator)	Debug · Xcode_16.4	0.7.11	—	PASS
iOS	iOS-18-6	iPhone 16 (simulator)	Release · Xcode_16.4	0.7.11	—	PASS
iOS	iOS-26-2	iPhone 17 (simulator)	Debug · Xcode_26.2	0.7.11	—	PASS

All automated tests ran against the Deepdots development environment with test companies only. No customer data was used, and each configuration fails if any request reaches the production API.

4. Critical Safety Validation

Scenario	iOS	Android
Survey that cannot load: the popup can be closed and the app stays usable	**FAIL**	PASS
Popup configuration that cannot load: no popup, the app stays usable	PASS	PASS
No network: no popup, the app stays usable	n/a	PASS
Network lost right after a popup is triggered	n/a	PASS
Slow network while the survey loads	n/a	PASS
Crash, freeze (ANR) or threading errors in the device log, and no request to production (every configuration)	None detected	None detected

5. Detection Controls and Backward Compatibility

The test system has to prove it catches real problems. These controls run in every validation:

Control	Result
Negative control: the bug customers saw on the control version is detected (control 0.7.0)	PASS
R8 control: the control version fails a minified release build, the tested one builds (control 0.7.0)	PASS
Expected failure detected: missing-navigation	iOS PASS · Android PASS

6. Known Issues & Limitations

Known blocking issues: see Failures in section 1.

Known non-blocking issues:

- None.

Test limitations:

- Emulators and simulators cover the OS versions, not every manufacturer; real devices are checked by hand (section 7).
- Visual regression compares screenshots on one standard and one small device per platform (CI emulator / simulator); other devices and OS versions are covered by the functional tests, not by screenshots.
- Tests marked as known issues are expected to fail until their fix ships; if one passes, the run fails so the mark is removed.

7. Real Devices (manual)

Status: PENDING. Filled in by hand after this report is generated: release build of the test app with this exact version on one Android phone, one iPhone and one iPad.

Check	Android phone	iPhone	iPad
Popup appears complete, once	pending	pending	pending
Survey answered and sent to the end	pending	pending	pending
Not shown again within its cooldown	pending	pending	pending
Taps outside the popup do not reach the app; X closes it	pending	pending	pending
Background / foreground with the popup open	pending	pending	pending
Rotation with the popup open	pending	pending	pending
Keyboard does not cover Send	pending	pending	pending
No network: notice, can be closed, app usable	pending	pending	pending

8. Release Information

- **SDK version:** 0.7.11
- **Release:** GitHub release v0.7.11
- **Changelog:** CHANGELOG
- **Test execution:** CI run (logs, screenshots and per-configuration artifacts)
- **Validation date:** 2026-11-07
- **Results file SHA-256:** `aafde0305ebfaed6ecefff386867c4049987b49ab65fbc940fe6973378fd9a77`

Release notes 0.7.11

Survey SDK supported: 2.2.38–2.2.39 (survey frontend 3.4.1); bundled: 2.2.39. Compatibility table: docs.deepdots.com/popup-native/reference/survey-compatibility/.

0.7.10 was tagged but never published (the release workflow stopped before publishing because of a release-gate bug, fixed below), so this version is the first with these changes on Maven Central and SPM. Upgrade from 0.7.9 straight to it.

Added

- **Popups follow the survey version assigned in the Admin (DD-70).** `GET /sdk/{publicKey}/popups` sends `surveyFrontend.sdkVersion` per popup (latest or pinned). When it is one of `SUPPORTED_SURVEY_SDK_VERSIONS` (2.2.38, 2.2.39; also `release/compatibility.json` → `surveyRenderer.assignedVersions`) and differs from `MAGICFEEDBACK_VERSION`, the WebView first loads that version's survey CSS (the popup-sdk's vendored `survey-css/<v>.css` at `POPUP_SDK_CSS_VERSION`, in place of the usual stylesheet) and then that exact `@magicfeedback/native` from jsDelivr, then unpkg. If the CSS or the JS fails, the usual CSS and the vendored JS come back together (the per-version sheets exist from popup-sdk 1.19.0). An invalid version is always logged, the choice only with `debug`. New `PopupDefinition.surveySdkVersion` (last parameter, default null).
- **Release gate for the assignable survey SDK versions (DD-70).** Every version of `SUPPORTED_SURVEY_SDK_VERSIONS` other than `MAGICFEEDBACK_VERSION` has a Maestro flow `test-apps/maestro/flows/survey-sdk-<v>.yaml` and a DEV scenario `survey-sdk-<v>` (survey pinned in the Admin to a MagicSurvey release built with that version); `scripts/release/rules.mjs` requires

both. The flow answers the survey with that version, and `run-maestro.sh` fails it unless the device log has `[MagicFeedback] survey-sdk <v> assigned` (the SDK logs it, println / NSLog, once that version's CSS and JS are in). It runs in the full suite of the release PR (`local`).

- **The popup's own texts in the 24 official EU languages (DD-67).** `DefaultLabels` (buttons, progress counter, follow-up badge, accessibility descriptions and notices) now translates bg, cs, el, et, ga, hr, hu, it, lt, lv, mt, nl, pl, ro, sk and sl too, 28 locales in all. A Polish survey used to show the native Back/Send buttons in English. Machine-translated, pending native review (`DD-67-native-review.md`). Mirror of the Web SDK's `src/i18n/labels.ts`.
- **The closing batch survives the app dying (DD-55, parity with Web 1.17).** With storage (the default), the batch that closes a session (`completed:true`, `deepdots_session_end`) is stored before it is sent. If iOS suspends or kills the app with that request in flight, or it fails with a network error or 5xx, the next `init()` resends it to its own record (its `sessionId`). A failed closing batch no longer goes back to the event buffer, where it left with the next session and in its record. Delivered or rejected (4xx) batches are removed; up to 50 are kept, for at most 24 h. The background task around the closing request (iOS) stays as before.
- **The SDK identifies itself on the data it sends (DD-3, Collection dashboard).** Every popup response now carries `deepdots_channel=popup` and `deepdots_sdk=android@<version>` / `ios@<version>` in its survey metadata, also with tracking off, so a response that came through a popup can be told apart from a MagicSurvey link and attributed to an SDK version (same keys as the Web SDK). Every analytics batch carries `deepdots_sdk` too. A wrapper declares itself with `SdkIdentity.setWrapper(name, version)` before `init` (the Flutter plugin does): `deepdots_sdk` becomes `flutter@<version>` and the native core goes in `deepdots_sdk_core`. The version is generated at build time from `PUBLISHING_VERSION` (`generateSdkBuildInfo` in `shared/build.gradle.kts`), never kept by hand; `SdkIdentity.version` exposes it to hosts.

Changed

- **Surveys SDK 2.2.39** (`@magicfeedback/native`, from 2.2.31), vendored on Android and from the CDN on iOS (`MAGICFEEDBACK_VERSION`). With it the popup shows "Please enter a valid email address." for an email with a typo (`INVALID_EMAIL`), the survey reports send failures apart from an empty required question (`SEND_FAILED`, 2.2.37), and it gets the survey changes since 2.2.31: the 24 official EU languages, the email `Option/Alt + 2` shortcut, typed submit errors, rating and choice layout options. The survey stylesheet now comes from popup-sdk 1.19.0 (`POPUP_SDK_CSS_VERSION`, from 1.10.0), the copy of the 2.2.39 CSS, so the email @ button (`assets.atButton`) is styled too.

Fixed

- **Error notices in the survey's language (DD-67).** The required-answer, invalid-email and submit-error notices stayed in the language the host gave at start-up (`provideLang`, English without it), while the buttons and the close label already followed the survey: a Danish survey showed "Luk pop op" next to "Please answer the required question to continue.". The WebView bridge kept the first event handler, from before the survey's language arrived; it now always calls the current one (`rememberUpdatedState`, Android and iOS).

- **The popup understands the survey's error codes.** The surveys SDK (`@magicfeedback/native` 2.2.37+) sends a `code` with each submit error; the popup only looked at the text, so any error containing "No response" read as "required question" (also a send the API did not save) and every other error showed the generic message. The popup now reads the code, like the Web SDK: `REQUIRED` shows the required message, the new `INVALID_EMAIL` (2.2.39) shows "Please enter a valid email address." (translated in all 28 locales), and the rest show the submit error. Without a code it keeps matching the text. Asked by Lemvigh-Müller: an email with a typo showed "Please answer the question".

- **A failed popups download is retried instead of losing the popup for the session.** At start-up the SDK downloads the popups of the public key; taps and events that arrive before are kept and replayed. If that request failed once (for example a brief loss of signal at start-up), the SDK dropped them and never tried again, so no popup showed until the next app start. The request is now retried twice (after 2 s and 5 s) and the pending taps and events are kept until the last attempt. Found while investigating the release validation on Android 8.

- **The "Delay (seconds)" set in the Admin is honoured for every trigger type** (reported by MOM: an event trigger with a 60 s delay showed the popup at once). `event`, `click`, `scroll` and `time_on_page` ignored `trigger.delaySeconds`, and `exit` read its delay from `value`, which the Admin saves as 0 (the delay lives in `delaySeconds`), so exit popups made in the Admin never waited. Now the delay counts from the moment the trigger fires (for `time_on_page`, after the time on page; for `exit`, on the next screen as before). Exit popups made before `delaySeconds` existed, with the delay in `value`, keep working. While a popup waits: firing the same trigger again neither restarts nor duplicates it; `setPath()` to another screen or `onBackground()` cancels it; and when it is due everything is checked again (segments, language, cooldowns), it is dropped if the same popup was shown in the meantime, and if another popup is open it is skipped without effects, as before. 0 or no delay = at once, as before. Pending delays live in memory only. Parity with web 1.19.0. `Trigger.TimeOnPage`, `Scroll`, `Event` and `Click` gain a `delaySeconds` property; their old constructors stay (also from Swift). Tests: `TriggerDelayTest`, `TriggerDelayApiPayloadTest`; Maestro `rate-delay` and `rate-delay-cancel` (DEV scenario `rate-delay`, event + 8 s).

- **Release gate: a skipped check no longer hides the result that was tested.** Editing a release pull request after it was merged starts the release check again with its jobs skipped, and the publish workflow took that skipped "Release dry run" as the result. The gate now takes the latest run that was not skipped (`latestRun` in `scripts/release/metadata.mjs`).