Developing car driving agent in the TORCS virtual environment

(Tworzenie agenta kierującego pojazdem w wirtualnym środowisku TORCS)

Kacper Kulczak

Praca inżynierska

Promotor: dr Paweł Rychlikowski

Uniwersytet Wrocławski Wydział Matematyki i Informatyki Instytut Informatyki

9stycznia 2019

Abstract

. . .

. . .

Contents

| 1 | Inti | roduction | 7 |
|----------|----------------------------------|------------------------------------|----|
| | 1.1 | TORCS Environment | 7 |
| | 1.2 | Simulated Car Racing Championship | 8 |
| | 1.3 | Game sensors and actions parametes | 9 |
| 2 | Sta | ndard programming approach | 13 |
| | 2.1 | Line follower | 13 |
| | 2.2 | Speed limit signs | 13 |
| | 2.3 | Results and observations | 14 |
| 3 | Ma | chine Learning Approach | 17 |
| | 3.1 | Collecting the data | 17 |
| | 3.2 | Single Classifier | 17 |
| | 3.3 | Two models | 18 |
| 4 | $\mathbf{A}\mathbf{d}\mathbf{i}$ | dtonal Problems | 19 |
| Bi | ibliog | graphy | 21 |

Introduction

Autonomous cars are a very fashionable subject. The idea has a lot of benefits. Most of accidents on roads, occurs due to human mistakes. Programmes don't get tiered or distracted while driving a vehicle. Also they can save a lot of fuel with optimal decisions. That's why companies around the globe put a lot of effort into making the car software for autonomous driving. It is very interesting task from artificial intelligence perspective. Description of the world is huge. It includes near objects, borders of the street, speed, turning force, engine rotation and much more. The output of such programme is quite simple in compared to the input size. We need only to specify new position of steering wheel and decision if we want to speed up or slow down. During my work I wanted approach the problem by building my own agent capable of drive safely on a racing track.

1.1 TORCS Environment

"The online racing car simulator" (TORCS) is highly portable, multi platform car simulator, with various cars and tracks. The simulation features a simple damage model, collisions, fuel consumption, tire and wheel properties (springs, dampers, stiffness), aerodynamics and much more [1]. It is designed to enable programed agents compete against each others. There is very ditalied instruction on developing your own bot. It has to be written as C++ loadable library and it is attached to main thread during program startup.

I have much more experience with programming in high level languages, so clean TORCS environment did not meet all my expectations.



Figure 1.1: Screen shot from TORCS race [1]

1.2 Simulated Car Racing Championship

SCRC competition took place between 2007 - 2015 with some breaks. It was organized by the University of Adelaide and the Politecnico de Milano. They used TORCS engine for competition, but organizers provided official patch which changed architecture of the programme. After patching, TORCS became client-server application which allows multiple bots communicate with game engine via UDP connections.

Server sends current sensor inputs (track border, speed, lap time, etc...) and waits for 20ms for the client action (gas, break, steer, etc...). API is details are descrived in table from manual. With that change participants cant choose whatever language they want. That's why I decided to use patched version of TORCS game engine in version 1.3.7




Figure 1.2: Simulated Car Racing Championship - architecture overview [2]

Organizers provided "clients" programmes only in Java and C++. I didn't want to implement communica-

tion interface on my own, beacuse it's time consuming and uninteresting task. After some research, I found http://xed.ch/p/snakeoil project, which provides Python Class handling communication with TORCS server. It allowed me to add layer of abstraction and focus directly on driving functionality.

1.3 Game sensors and actions parametes

Server provides very accurate description of virtual environment state. All parameters are described in 1.1 1.2 table attached to SCRC competition manual [2].

| Name | Range (unit) | Description | |
|---------------|-----------------------------|---|--|
| angle | $[-\pi, +\pi]$ (rad) | Angle between the car direction and the di- | |
| | | rection the track axis. | |
| curLapTime | $[0,+\infty)$ (s) | Time elapsed during current lap. | |
| damage | $(0, +\infty)$ (point) | Current damage of the car. | |
| distFromStart | $[0,+\infty)$ (m) | Distance of the car from the start line along | |
| | | the track line. | |
| distRaced | $[0,+\infty)$ (m) | Distance covered by the car from the begin- | |
| | | ning of the race | |
| fuel | $[0,+\infty)$ (l) | Current fuel level. | |
| gear | $\{-1,0,1,\ldots,6\}$ | Current gear: -1 is reverse, 0 is neutral and | |
| | | the gear from 1 to 6. | |
| lastLapTime | $[0,+\infty)$ (s) | Time to complete the last lap | |
| opponents | [0, 200] (m) | Vector of 36 opponent sensors: each sensor | |
| | | covers a span of 10 degrees within a range of | |
| | | 200 meters and returns the distance of the | |
| | | closest opponent in the covered area. | |
| racePos | $\{1,2,\ldots,N\}$ | Position in the race with respect to other | |
| | | cars. | |
| rpm | $[0, +\infty)$ (rpm) | Number of rotation per minute of the car en- | |
| | | gine | |
| speedX | $(-\infty, +\infty)$ (km/h) | Speed of the car along the longitudinal axis | |
| | | of the car. | |
| speedY | $(-\infty, +\infty)$ (km/h) | Speed of the car along the transverse axis of | |
| | | the car. | |
| speedZ | $(-\infty, +\infty)$ (km/h) | Speed of the car along the Z axis of the car | |

| track | [0, 200] (m) | Vector of 19 range finder sensors: each sen- |
|--------------|-----------------------------|---|
| | | sors returns the distance between the track |
| | | edge and the car within a range of 200 me- |
| | | ters. When noisy option is enabled, sensors |
| | | are affected by i.i.d. normal noises with a |
| | | standard deviation equal to the 10% of sen- |
| | | sors range. By default, the sensors sample |
| | | the space in front of the car every 10 de- |
| | | grees, spanning clockwise from -90 degrees |
| | | up to +90 degrees with respect to the car |
| | | axis. However, the configuration of the range |
| | | finder sensors (i.e., the angle w.r.t. to the car |
| | | axis) can be set by the client once during ini- |
| | | tialization, i.e., before the beginning of each |
| | | race. When the car is outside of the track |
| | | (i.e., pos is less than -1 or greater than 1), |
| | | the returned values are not reliable (typically |
| | | -1 is returned). |
| trackPos | $(-\infty, +\infty)$ | Distance between the car and the track axis. |
| | | The value is normalized w.r.t to the track |
| | | width: it is 0 when car is on the axis, -1 |
| | | when the car is on the right edge of the track |
| | | and $+1$ when it is on the left edge of the |
| | | car. Values greater than 1 or smaller than |
| | | -1 mean that the car is outside of the track. |
| wheelSpinVel | $[0, +\infty)$ (rad/s) | Vector of 4 sensors representing the rotation |
| | | speed of wheels. |
| Z | $(-\infty, +\infty)$ (km/h) | Distance of the car mass center from the sur- |
| | | face of the track along the Z axis |

Table 1.1: : Description of the available sensors.

| Name | Range (unit) | Description |
|--------|--------------|---|
| accel | [0,1] | Virtual gas pedal (0 means no gas, 1 full gas). |
| brake | [0,1] | Virtual brake pedal (0 means no brake, 1 full |
| | | brake). |
| clutch | [0,1] | Virtual clutch pedal (0 means no clutch, 1 |
| | | full clutch). |

| gear | $\{-1,0,1,\ldots,6\}$ | Gear value. |
|---------|-----------------------|---|
| steer | [-1, 1] | Steering value: -1 and $+1$ means respec- |
| | | tively full right and left, that corresponds to |
| | | an angle of 0.366519 rad. |
| focus | [-90, 90] | Focus direction (see the focus sensors) in de- |
| | | grees. |
| endRace | {0,1} | This is meta-control command: 0 do nothing, |
| | | 1 ask competition server to restart the race. |

Table 1.2: Description of the available action parameters.

Standard programming approach

2.1 Line follower

The first approach to the problem was developing simple bot which follows the track axis. Every time, absolute value of trackPos sensor (normalized position of the car on the track between [-1,+1]) is bigger than given small threshold, agent turns towards axis of the track with turning force set to 35%. To avoid zigzag driving, very small course corrections are applied, whenever abs(trackPos) < 0.2. Speed is limited to 80 km/h. These configuration allows bot to safely drive on every track.

I am aware that limiting turing force, has huge negative impact on bot performance. However increasing that value leads to dangerous behaviors. I was surprised how easy it is to slip. During development line follower I haven't found any solution for getting out of the slip. For now limiting that value was necessary.

2.2 Speed limit signs

In real world, government for safety reasons, places speed limit sign on dangerous sectors of roads. Signs are placed before sharp turns, steep slopes, bridges, viaducts, and more. Drivers adjust the speed to specific environment conditions. Inspired by this observation, I tried to improve previous agent iteration. I've split the track on 8 sections, using distFromStart sensor (distance of the car from the start line along the track line). Every part would have different speed limit set for specific track. The goal is to finish the lap as fast as we can while not falling out of the track. So we need to minimize function f, where l_i - speed limit for section i in km/h.

$$f(l_1, l_2, \dots, l_n) = \begin{cases} \infty, & \text{when the car fell off the track} \\ \text{lap_time}, & \text{otherwise} \end{cases}$$

I was trying to implement genetic algorithm for finding optimal limits for given track, but it appears that game engine, even with turned graphics off, isn't as fast as I anticipated. It takes almost 20 seconds, to complete one lap. Simple genetic algorithm would need long hours to find approximately good solution. I've used two following observations while developing my algorithm.

- $l_i \in [40, 300]$: Smaller values can lead to disqualification from race.
- true speed of car on sction i, depends on l_i and true speed at the end of section i-1
- l_i is correct, when $l_{i+1} = 40$ and car didn't fell out from track
- $g_j(x) = f(l_1, l_2, \dots, l_{j-1}, x, l_{j+1}, \dots, l_n)$ is decreasing while car stays on the track

I've implemented algorithm based on divide and conquer idea. It finds maximal x, where $g(x) \neq \infty$. We run that procedure on every argument:

```
l_i \leftarrow 40
for i \leftarrow 1, ..., n do
l_i = devide\_and\_conquer(func = g_i, min = 40, max = 300)
end for
```

For every section it uses around 12 game engine runs. So whole algorithm ends execution after around half an hour.

2.3 Results and observations

In following table I've presented line-follower performance on specific tracks from TORCS environment. While speed limits are significant improvement, they still do not deal with major flaw of the concept. Our bot is extremely reactive. Human driver see a turn from distance and prepares for it (reduces speed, drifts towards opposite side of the road). On the other hand my bot turns the steering wheel only when it drifts away from the middle of the track (this happens after entering the turn). It is basically to late for a perfect turning maneuver. We need a model, which predicts and reacts to the future events. That's why I resign from extending current concept.

| track name | unexperienced driver[s] | line-follower[s] | speed limits[s] |
|------------|-------------------------|------------------|-----------------|
| forza | 122.65 | 265.51 | 146.31 |
| cg_track_2 | 79.64 | 148.84 | 84.68 |
| cg_track_3 | 102.09 | 133.74 | 91.86 |

Table 2.1: Line follower performance for specific TORCS tracks

Machine Learning Approach

3.1 Collecting the data

Machine learning is well known

Unfortunately TORCS environment does not have an option to log sensors data and driver actions. It is planned to add this functionality in the future development. That's why I developed software which mimics TORCS car controls and saves data from all sensors and driver actions to json file. From game perspective it is normal agent, but it reacts only on user keyboard inputs (accelerate, break, left, right). With that infrastructure I was able to record some well-driven race laps on various tracks.

3.2 Single Classifier

During 10 recording laps on cg_track_2 I've collected around 30000 data frames. The state passed to classifier is made up of following sensors:

State parameters

- speeds (3 speed sensors in axises x,y,z)
- angle, trackPos (same as in line-follower)
- track (19 sensors in front of the car measuring distances to edge of track)
- distFromStart (distance of the car from the start line along the track line

All values are normalized between [-1, 1] and combined in a single vector. For actions I've created a list of unique actions present in data set and labeled them. For track cq_track_2 It reduced set of actions to around 200.

Action parameters

- $accel \in \{0, 1\}$
- brake $\in \{0, 1\}$
- steer $\in [-1, 1]$

Classifier for state vector, should answer with label of which action are we supposed to execute. First and actually only successful approach was simple decision tree classifier from scikit-learn library (implementation of CART algorithm). Results are shown in table 3.1.

| track name | line-follower with limts [s] | single decision tree classifier [s] |
|------------|------------------------------|-------------------------------------|
| cg_track_2 | 84.68 | 61.18 |

Table 3.1: Single Classifier: decision tree performance

Performance was improved by 20% even with poor model accuracy. Classifier accuracy on test data set is equal 61%. Other models such as (Neural Network, Support Vector Machine, Random Forest) resulted in similar bad accuracy for test data set and all of them were getting out from the race track.

It is worth noticing, that using **distFromStart** parameter isn't very practical for generalized driving agent. My models weren't learning how to drive a vehicle. The were rather memorizing right actions for specific sector of the track. We need model which can be applied also for unseen tracks. However without that parameter, all my models were crashing on the track.

3.3 Two models

Major flaw for previous classifier was the amount of possible answers. To reduce number of classes we need to use two separate models:

- Steer Regressor responsible for determining the turn rate (floating number between [-1,1]).
- Acceleration Classifier determining

Adidtonal Problems

• Transmission Choosen architecture didn't allowed me to use automatic transmission included with the torcs game. I had to build my own basic automatic transmission system, which is far from perfect. I haven't change it during development of different agents, so all results are comparable.

Bibliography

- [1] B. Wymann, E. Espié, C. Guionneau, C. Dimitrakakis, R. Coulom, A. Sumner. TORCS: The Open Racing Car Simulator, v1.3.6, 2014.
- [2] Daniele Loiacono, Luigi Cardamone, Pier Luca Lanzi, "Simulated Car Racing Championship: Competition Software Manual", Technical Report 2011.06, Dipartimento di Elettronica e Informazione, Politecnico di Milano, Italy, 2011.