Architetture dei Sistemi di Elaborazione 02GOLOV [GRB-ZZZ]	Delivery date: **October 18th 2022**
Laboratory 1	Expected delivery of lab_01.zip including: - program_0.s - program_1.s - lab_01.pdf (fill and export this file to pdf)

Please, configure the winMIPS64 processor architecture with the *Base Configuration* provided in the following:

- *Integer ALU: 1 clock cycle*
- *Data memory: 1 clock cycle*
- *Branch delay slot: 1 clock cycle*
- Code address bus: 12
- Data address bus: 12
- Pipelined FP arithmetic unit (latency): 6 stages
- Pipelined FP multiplier unit (latency): 8 stages
- FP divider unit (latency): not pipelined unit, 28 clock cycles
- Forwarding optimization is disabled
- Branch prediction is disabled
- Branch delay slot optimization is disabled.

Use the Configure menu:

- Running the *WinMIPS* simulator, launching the graphical user interface (*folder_to_simulator*)...\winMIPS64\winmips64.exe
- Disable ALL the optimization (a mark appears when they are enabled)
- Browse the Architecture menu (Ctrl-A)



- Modify the defaults Architectural parameters (where needed)



- Verify in the Pipeline window that the configuration is effective (usually in the left bottom window)



1) Exercise your assembly skills.
To write an assembly program called **program_0.s (to be delivered)** for the *MIPS64* architecture and to execute it.

The program must:

1. Given 2 statically initialized arrays (`a` and `b`), compute their sum and store each result in a third array (i.e., `c[i] = a[i] + b[i]`). Each array contains 50 8-bit integer numbers.
2. Search for **both** the maximum and minimum in the array `c`. The program saves the obtained value in two variables allocated in memory, called `max` and `min` respectively.

2) Exercise your assembly skills.
To write an assembly program called **program_1.s (to be delivered)** for the *MIPS64* architecture and to execute it.

The program must:

1. Given one array of 15 8-bit integer numbers (*v1*), check if the content corresponds to a **palindrome** sequence of numbers. If yes, use a 8-bit unsigned variable (*flag*) to store the result. The variable will be equal to 1 is the sequence is palindrome, 0 otherwise.

Example of a palindrome sequence:
v1: . byte 2, 6, -3, 11, 9, 11, -3, 6, 2

3) Once that **program_0.s** and **program_1.s** are written, use the *WinMIPS* simulator to check their correctness.
Identify and use the main components of the simulator:

a. Running the *WinMIPS* simulator
   - Launch the graphic interface

   ...\winMIPS64\winmips64.exe

b. Assembly and check your programs:
   - Load the program from the **`File→Open`** menu (*CTRL-O*). In the case the of errors, you may use the following command in the command line to compile the program and check the errors:

   `...\winMIPS64\asm program_0.s`

c. Run your programs step by step (*F7*), identifying the whole processor behavior in the six simulator windows:
   Pipeline, **Code**, **Data**, **Register**, **Cycles** and **Statistics**

d. Collect the clock cycles to fill the following table **(fill all required data in the table before exporting this file to pdf format to be delivered)**.

Table 1: **Program performance for the specific processor configurations**

Program	Clock cycles	Number of Instructions
`program_0`	`1266`	`648`
`Program_1`	`108`	`59`

4) Perform execution time measurements.
   Search in the winMIPS64 folder the following benchmark programs:
   a. `testio.s`
   b. `mult.s`
   c. `series.s`
   d. `program_1.s` (your program)

Starting from the basic configuration with no optimizations, compute by simulation the number of cycles required to execute these programs; in this initial scenario, it is assumed that the weight of the programs is the same (25%) for everyone. Assume a processor frequency of 1.75 MHz.

Then, change processor configuration and vary the programs' weights as following. Compute again the performance for every case and fill the table below **(fill all required data in the table before exporting this file to pdf format to be delivered)**.:

1) Configuration 1
   a. Enable Forwarding
   b. Disable branch target buffer
   c. Disable Delay Slot

   Assume that the weight of all programs is the same (25%).
2) Configuration 2
   a. Enable Forwarding
   b. Enable branch target buffer

c. Disable Delay Slot

Assume that the weight of all programs is the same (25%).

3) Configuration 3

Configuration 1, but assume that the weight of the program *your program* is 70%.

4) Configuration 4

Configuration 1, but assume that the weight of the program `series.s` is 70%.

Table 2: **Processor performance for different weighted programs**

Program	No opt	Conf. 1	Conf. 2	Conf. 3	Conf. 4
`testio.s`	`0.42228`	`0.27200`	`0.24685`	`0.27200`	`0.27200`
`mult.s`	`1.07428`	`0.56000`	`0.52685`	`0.56000`	`0.56000`
`series.s`	`0.31428`	`0.13314`	`0.13371`	`0.13314`	`0.13314`
`program_1.s`	`0.06171`	`0.06114`	`0.05942`	`0.06114`	`0.06114`
TOTAL TIME	`0.46813`	`0.25657`	`0.24170`	`0.13931`	`0.18251`

For time computations, use a clock frequency of 1.75 MHz.

Appendix: *winMIPS64 Instruction Set*

WinMIPS64

The following assembler directives are supported

.data - start of data segment
.text - start of code segment
.code - start of code segment (same as .text)
.org <n> - start address
.space <n> - leave n empty bytes
.asciiz <s> - enters zero terminated ascii string
.ascii <s> - enter ascii string
.align <n> - align to n-byte boundary
.word <n1>,<n2>.. - enters word(s) of data (64-bits)
.byte <n1>,<n2>.. - enter bytes
.word32 <n1>,<n2>.. - enters 32 bit number(s)
.word16 <n1>,<n2>.. - enters 16 bit number(s)
.double <n1>,<n2>.. - enters floating-point number(s)

where <n> denotes a number like 24, <s> denotes a string like "fred", and
<n1>,<n2>.. denotes numbers seperated by commas.

The following instructions are supported

lb - load byte
lbu - load byte unsigned
sb - store byte
lh - load 16-bit half-word
lhu - load 16-bit half word unsigned
sh - store 16-bit half-word
lw - load 32-bit word
lwu - load 32-bit word unsigned
sw - store 32-bit word
ld - load 64-bit double-word
sd - store 64-bit double-word
l.d - load 64-bit floating-point
s.d - store 64-bit floating-point
halt - stops the program

daddi - add immediate
daddui - add immediate unsigned
andi - logical and immediate
ori - logical or immediate
xori - exclusive or immediate
lui - load upper half of register immediate
slti - set if less than or equal immediate
sltiu - set if less than or equal immediate unsigned

beq - branch if pair of registers are equal
bne - branch if pair of registers are not equal
beqz - branch if register is equal to zero
bnez - branch if register is not equal to zero

j - jump to address
jr - jump to address in register
jal - jump and link to address (call subroutine)
jalr - jump and link to address in register (call subroutine)

dsll - shift left logical
dsrl - shift right logical
dsra - shift right arithmetic
dsllv - shift left logical by variable amount
dsrlv - shift right logical by variable amount
dsrav - shift right arithmetic by variable amount
movz - move if register equals zero
movn - move if register not equal to zero
nop - no operation
and - logical and
or - logical or
xor - logical xor
slt - set if less than
sltu - set if less than unsigned
dadd - add integers
daddu - add integers unsigned
dsub - subtract integers
dsubu - subtract integers unsigned

add.d - add floating-point
sub.d - subtract floating-point
mul.d - multiply floating-point
div.d - divide floating-point
mov.d - move floating-point
cvt.d.l - convert 64-bit integer to a double FP format
cvt.l.d - convert double FP to a 64-bit integer format
c.lt.d - set FP flag if less than
c.le.d - set FP flag if less than or equal to
c.eq.d - set FP flag if equal to
bc1f - branch to address if FP flag is FALSE
bc1t - branch to address if FP flag is TRUE
mtc1 - move data from integer register to FP register
mfc1 - move data from FP register to integer register