## **Firewall**

## Lab Report 5

Information Systems Security course (01TYM, 02KRQ)

prepared by:

Anuar Elio Magliari (<u>s317033@studenti.polito.it</u>)

George Florin Eftime (<u>s303483@studenti.polito.it</u>)

Alekos Interrante Bonadia (<u>s319849@studenti.polito.it</u>)

## **Packet filter**

• Which authorisation policy is configured by default on your machine (on each of the three chains)?

```
-# iptables -L -v -n
Chain INPUT (policy ACCEPT 0 packets, 0 bytes)
                                                                  destination
pkts bytes target
                      prot opt in
                                      out
                                             source
Chain FORWARD (policy ACCEPT 0 packets, 0 bytes)
pkts bytes target prot opt in
                                                                  destination
                                             source
Chain OUTPUT (policy ACCEPT 0 packets, 0 bytes)
pkts bytes target
                                                                  destination
                      prot opt in
                                     out
                                             source
```

- Which chain (out from INPUT, FORWARD, and OUTPUT) do you have to modify to protect your machine from connections originating from the external users?
  - INPUT and FORWARD in order to have protection from external users

```
root@ geo)-[/home/george]
iptables -P INPUT DROP
    root⊕ geo)-[/home/george]
iptables -L -v -n
Chain INPUT (policy DROP 0 packets, 0 bytes)
pkts bytes target
                         prot opt in
                                                                            destination
                                                    source
Chain FORWARD (policy ACCEPT 0 packets, 0 bytes)
                                                                            destination
pkts bytes target
                         prot opt in
                                                     source
Chain OUTPUT (policy ACCEPT 300 packets, 55360 bytes)
 pkts bytes target
                         prot opt in
                                                                            destination
                                                     source
```

- Write down the iptables command to modify the authorisation policy of Alice's host, so that to reject any traffic (hint: you need to modify the default policy for the INPUT chain from ACCEPT to DROP):
- Does Bob receive any responses (to the ping) from Alice's host?
  - No, he doesn't

```
(elion-man € Elion-Man-on-Kali)-[~]
$ ping 172.22.17.139
PING 172.22.17.139 (172.22.17.139) 56(84) bytes of data.
^C
— 172.22.17.139 ping statistics —
31 packets transmitted, 0 received, 100% packet loss, time 30701ms
```

- Can Bob connect to Alice's host via SSH and HTTP (with the browser)?
  - No, he doesn't. In both cases, Bob doesn't receive any response from Alice because Alice's firewall has the INPUT chain set to DROP, so it discards all requests from the external source.
- Check with nmap (running the above indicated nmap command on Bob's host) the status of the ports 22 and 80 on Alice's host. What is their status now?

```
Starting Nmap -sT -Pn -n -p 80,22 -v 172.22.17.139
Starting Nmap 7.94 ( https://nmap.org ) at 2023-12-05 12:24 CET
Initiating Connect Scan at 12:24
Scanning 172.22.17.139 [2 ports]
Completed Connect Scan at 12:24, 3.00s elapsed (2 total ports)
Nmap scan report for 172.22.17.139
Host is up.

PORT STATE SERVICE
22/tcp filtered ssh
80/tcp filtered http

Read data files from: /usr/bin/../share/nmap
Nmap done: 1 IP address (1 host up) scanned in 3.04 seconds
```

- Write down the iptables command to add a rule to the authorisation policy on Alice's host (for the input traffic), so that to enable all ICMP traffic (for simplicity, we provide you some of the parameters of the command)
  - iptables -A INPUT -p icmp -j ACCEPT

```
root@ geo)-[/var/ww/html]
iptables -L -v -n
Chain INPUT (policy DROP 0 packets, 0 bytes)
 pkts bytes target
                      prot opt in
                                       out
                                                                    destination
                                               source
       504 ACCEPT
                                       *
                                               172.22.16.108
                                                                    0.0.0.0/0
Chain FORWARD (policy ACCEPT 0 packets, 0 bytes)
pkts bytes target prot opt in
                                                                    destination
                                       out
                                              source
Chain OUTPUT (policy ACCEPT 1292 packets, 547K bytes)
 pkts bytes target
                                                                    destination
                      prot opt in
                                       out
                                               source
```

- Does Bob receive this time any response from Alice's host in response to the ping command?
  - Yes, now he does because Alice allows all the icmp packets in input.

- Next, on Alice's host, write down the iptables command to allow the TCP input traffic towards the port 80 (on Alice):
  - iptables -A INPUT -p tcp --dport 80 -j ACCEPT
- Check out the configuration of IPtables on Alice's host. Which chain has been modified?
  - The chain modified is the INPUT chain as specified in the command

```
)-[/var/ww/html]
./script_firewall.sh
Chain INPUT (policy DROP 0 packets, 0 bytes)
 pkts bytes target
                        prot opt in
                                                                        destination
                                         out
                                                 source
          0 ACCEPT
                                                 0.0.0.0/0
    0
                                                                        0.0.0.0/0
          0 ACCEPT
                                                  0.0.0.0/0
                                                                        0.0.0.0/0
                                                                                              tcp dpt:80
Chain FORWARD (policy ACCEPT 0 packets, 0 bytes)
 pkts bytes target
                        prot opt in
                                         out
                                                  source
                                                                        destination
Chain OUTPUT (policy ACCEPT 1544 packets, 609K bytes)
 pkts bytes target
                     prot opt in
                                         out
                                                 source
                                                                        destination
```