

# API Documentation - NOEST Public API

---

## General Information

| Property       | Value                                 |
|----------------|---------------------------------------|
| Base URL       | <code>https://app.noest-dz.com</code> |
| Format         | JSON                                  |
| Authentication | Bearer Token (api_token)              |

### Authentication

All endpoints require authentication via:

- **Header:** `Authorization: Bearer {api_token}`
- **Parameter:** `user_guid` (Partner GUID provided by NOEST)

The `api_token` and `user_guid` credentials are provided by NOEST when your account is created.

---

## Order Management

### 1. Create an Order

Create a single order.

#### Endpoint

```
POST /api/public/create/order
```

#### Headers

```
Authorization: Bearer {token}  
Content-Type: application/json
```

#### Parameters

| Parameter              | Type   | Required | Description                              |
|------------------------|--------|----------|------------------------------------------|
| <code>user_guid</code> | string | Yes      | Partner GUID provided by NOEST           |
| <code>reference</code> | string | No       | Order reference (min: 5 characters)      |
| <code>client</code>    | string | Yes      | Customer full name (max: 255 characters) |

| Parameter          | Type    | Required    | Description                                                                     |
|--------------------|---------|-------------|---------------------------------------------------------------------------------|
| phone              | string  | Yes         | Phone number (9-10 digits)                                                      |
| phone_2            | string  | No          | Secondary phone number (9-10 digits)                                            |
| adresse            | string  | Yes         | Delivery address (max: 255 characters)                                          |
| wilaya_id          | integer | Conditional | Wilaya ID (1-58). Required if <b>zip_code</b> is not provided                   |
| commune            | string  | Conditional | Commune name. Required if <b>zip_code</b> and <b>stop_desk</b> are not provided |
| montant            | numeric | Yes         | Order amount                                                                    |
| remarque           | string  | No          | Remarks (max: 255 characters)                                                   |
| produit            | string  | Yes         | Product name/reference, Multiple products separated by comma                    |
| type_id            | integer | Yes         | Delivery type: 1=Delivery, 2=Exchange, 3=Pick-up                                |
| poids              | numeric | No          | Package weight (according to partner limit)                                     |
| stop_desk          | integer | Yes         | Delivery to relay point: 0=Home, 1=Stop desk                                    |
| station_expedition | integer | No          | Expedition station Code (feature must be enabled on your account)               |
| station_code       | string  | Conditional | Station code. Required if <b>stop_desk=1</b>                                    |
| stock              | integer | No          | Order with stock: 0=No, 1=Yes                                                   |
| quantite           | string  | Conditional | Quantities separated by comma. Required if <b>stock=1</b>                       |
| can_open           | integer | No          | Opening authorization: 0=No, 1=Yes                                              |
| shop_name          | string  | No          | Shop name (max: 255 characters)                                                 |
| zip_code           | string  | No          | Postal code (replaces <b>wilaya_id</b> and <b>commune</b> )                     |
| remboursement      | integer | No          | Reimbursement type: 0=No, 1=Yes (amount < 0: refund, amount > 0: collection)    |

### Request Example

```
{
  "user_guid": "abc123-def456-ghi789",
  "reference": "REF12345",
  "client": "Ahmed Ahmed",
  "phone": "0550505050",
  "phone_2": "0660606060",
  "adresse": "Rue des Martyrs, Bab Ezzouar",
  "wilaya_id": 16,
```

```

"commune": "Bab Ezzouar",
"montant": 3500,
"produit": "Smartphone Samsung Galaxy",
"type_id": 1,
"poids": 0.5,
"stop_desk": 0,
"remarque": "Call before delivery",
"can_open": 1
}

```

### Success Response

```

{
  "success": true,
  "tracking": "ECS1234567890",
  "reference": "REF001",
  "regional_hub_name": "W",
  "wilaya_rank": "16B"
}

```

### Common Error Messages

| Error                                              | Description                                          |
|----------------------------------------------------|------------------------------------------------------|
| account_suspended                                  | Partner account suspended                            |
| commune inexistante ou non activée                 | The specified commune does not exist in the database |
| zip_code invalide                                  | Invalid postal code                                  |
| Le code de wilaya est different de code de station | Mismatch between wilaya and station code             |
| Aucune commune liee a la station choisie           | No commune associated with the station               |
| Il faut choisir un code de station valide          | Invalid station code                                 |
| Module stopdesk désactivé pour cette wilaya        | Stop desk not available for this wilaya              |
| montant doit être inferieur à X                    | Amount exceeds the allowed limit                     |

## 2. Create Bulk Orders

Create multiple orders in a single request.

### Endpoint

```
POST /api/public/create/orders
```

## Headers

```
Authorization: Bearer {token}  
Content-Type: application/json
```

## Parameters

| Parameter              | Type   | Required | Description                        |
|------------------------|--------|----------|------------------------------------|
| <code>user_guid</code> | string | Yes      | Partner GUID                       |
| <code>orders</code>    | array  | Yes      | Array of orders (min: 1, max: 100) |

## Order Structure

See the same parameters as single order creation.

## Request Example

```
{  
  "user_guid": "abc123-def456-ghi789",  
  "orders": [  
    {  
      "reference": "REF001",  
      "client": "Ahmed Ahmed",  
      "phone": "0550000000",  
      "adresse": "Rue des Martyrs, Bab Ezzouar",  
      "wilaya_id": 16,  
      "commune": "Bab Ezzouar",  
      "montant": 3500,  
      "produit": "Smartphone Samsung",  
      "type_id": 1,  
      "stop_desk": 0,  
      "poids": 0.5  
    },  
    {  
      "reference": "REF002",  
      "client": "Fatima Fatima",  
      "phone": "0770000000",  
      "adresse": "Cité 300 logements",  
      "zip_code": "16000",  
      "montant": 2000,  
      "produit": "Bluetooth Earphones",  
      "type_id": 1,  
      "stop_desk": 0  
    }  
  ]  
}
```

```

    }
  ]
}

```

### Success Response

```

{
  "success": true,
  "passed": {
    "0": {
      "success": true,
      "tracking": "TRK123456789"
    },
    "1": {
      "success": true,
      "tracking": "TRK987654321"
    }
  },
  "failed": {}
}

```

### Response with Errors

```

{
  "success": false,
  "passed": {
    "0": {
      "success": true,
      "tracking": "TRK123456789"
    }
  },
  "failed": {
    "1": {
      "reference": "Order reference (if sent)",
      "phone": ["The phone field is required."],
      "commune": ["The selected commune is invalid."]
    }
  }
}

```

### Possible Errors Table

Errors can be classified into two categories: **validation errors** and **custom business errors**.

#### Validation Errors

| Field     | Error                                                       | Description                                        |
|-----------|-------------------------------------------------------------|----------------------------------------------------|
| user_guid | The user_guid field is required.                            | Missing GUID                                       |
| user_guid | The selected user_guid is invalid.                          | GUID does not exist                                |
| client    | The client field is required.                               | Customer name missing                              |
| client    | The client field may not be greater than 255 characters.    | Name too long                                      |
| phone     | The phone field is required.                                | Phone number missing                               |
| phone     | The phone field must be between 9 and 10 digits.            | Invalid phone format                               |
| phone_2   | The phone_2 field must be between 9 and 10 digits.          | Invalid secondary phone format                     |
| adresse   | The adresse field is required.                              | Address missing                                    |
| adresse   | The adresse field may not be greater than 255 characters.   | Address too long                                   |
| wilaya_id | The wilaya_id field is required.                            | Wilaya missing (if zip_code absent)                |
| wilaya_id | The wilaya_id field must be an integer.                     | Invalid type                                       |
| wilaya_id | The wilaya_id field must be between 1 and 58.               | Wilaya ID out of range                             |
| commune   | The commune field is required.                              | Commune missing (if zip_code and stop_desk absent) |
| commune   | The selected commune is invalid.                            | Commune does not exist                             |
| montant   | The montant field is required.                              | Amount missing                                     |
| montant   | The montant field must be numeric.                          | Invalid amount format                              |
| remarque  | The remarque field may not be greater than 255 characters.  | Remarks too long                                   |
| shop_name | The shop_name field may not be greater than 255 characters. | Shop name too long                                 |
| produit   | The produit field is required.                              | Product missing                                    |
| type_id   | The type_id field is required.                              | Order type missing                                 |
| type_id   | The type_id field must be between 1 and 3.                  | Invalid type (must be 1, 2 or 3)                   |
| poids     | The poids field must be numeric.                            | Invalid weight format                              |
| poids     | The poids field must be at least 0.                         | Negative weight                                    |
| poids     | The poids field may not be greater than X.                  | Weight exceeds allowed limit                       |

| Field         | Error                                                         | Description                           |
|---------------|---------------------------------------------------------------|---------------------------------------|
| stop_desk     | The stop_desk field is required.                              | Stop desk missing                     |
| stop_desk     | The stop_desk field must be between 0 and 1.                  | Invalid value (must be 0 or 1)        |
| stock         | The stock field must be between 0 and 1.                      | Invalid value (must be 0 or 1)        |
| can_open      | The can_open field must be between 0 and 1.                   | Invalid value (must be 0 or 1)        |
| quantite      | The quantite field is required.                               | Quantities missing (if stock=1)       |
| zip_code      | The selected zip_code is invalid.                             | Postal code does not exist            |
| paypart_ref   | The paypart_ref field may not be greater than 255 characters. | Payment reference too long            |
| station_code  | The station_code field is required.                           | Station code missing (if stop_desk=1) |
| reference     | The reference field must be at least 5 characters.            | Reference too short                   |
| remboursement | The remboursement field must be between 0 and 1.              | Invalid value (must be 0 or 1)        |

#### Custom Business Errors

| Error Code          | Message                                            | HTTP | Description                                           |
|---------------------|----------------------------------------------------|------|-------------------------------------------------------|
| account_suspended   | Compte suspendu                                    | 422  | Partner account is suspended                          |
| duplicate_order     | Colis déjà existant                                | 200  | An order with this reference already exists           |
| inactive_commune    | commune inexistante ou non activée                 | 422  | The specified commune does not exist or is not active |
| zip_code            | zip_code invalide.                                 | 200  | The provided postal code is invalid                   |
| max_amount_exceeded | montant doit être inférieur à X                    | 422  | Amount exceeds partner's allowed limit                |
| stopdesk_disabled   | Module stopdesk désactivé pour cette wilaya        | 422  | Stop desk is not available for this wilaya            |
| station_expedition  | La station d'expédition n'est pas valide           | 200  | Invalid expedition station code                       |
| station_code        | Le code de wilaya est différent de code de station | 200  | Mismatch between wilaya and station code              |

| Error Code                     | Message                                                                  | HTTP | Description                                          |
|--------------------------------|--------------------------------------------------------------------------|------|------------------------------------------------------|
| <code>station_code</code>      | Aucune commune liee a la station choisie.                                | 200  | No commune is associated with this station           |
| <code>station_code</code>      | Il faut choisir un code de station valide.                               | 200  | The provided station code is invalid                 |
| <code>disabled_module</code>   | Module de stockage désactivé                                             | 422  | Stock management module is disabled for this partner |
| <code>wrong_quantities</code>  | Le nombre des quantités saisi n'est pas identique au nombre des produits | 422  | Number of quantities ≠ number of products            |
| <code>invalid_product</code>   | Le produit avec la référence X n'existe pas ou désactivé                 | 422  | The specified product does not exist or is disabled  |
| <code>out_of_stock</code>      | Stock indisponible                                                       | 422  | Insufficient stock for requested quantity            |
| <code>already_validated</code> | Commande déjà validée                                                    | 422  | Order has already been validated                     |

### 3. Validate an Order

Validate a created order. After validation, the order becomes visible to logistics and can no longer be modified or deleted.

#### Endpoint

```
POST /api/public/valid/order
```

#### Headers

```
Authorization: Bearer {token}
Content-Type: application/json
```

#### Parameters

| Parameter              | Type   | Required | Description         |
|------------------------|--------|----------|---------------------|
| <code>user_guid</code> | string | Yes      | Partner GUID        |
| <code>tracking</code>  | string | Yes      | Order tracking code |



## Request Example

```
{
  "user_guid": "abc123-def456-ghi789",
  "tracking": "TRK123456789"
}
```

## Success Response

```
{
  "success": true
}
```

## Common Error Messages

| Error                 | Description                                                         |
|-----------------------|---------------------------------------------------------------------|
| Commande introuvable  | Order does not exist or does not belong to the partner              |
| Commande déjà validée | Order has already been validated                                    |
| Stock insuffisant     | Insufficient stock to validate the order (if <code>stock=1</code> ) |

## 4. Validate Bulk Orders

Validate multiple orders in a single request.

### Endpoint

```
POST /api/public/valid/orders
```

### Headers

```
Authorization: Bearer {token}
Content-Type: application/json
```

### Parameters

| Parameter | Type   | Required | Description  |
|-----------|--------|----------|--------------|
| user_guid | string | Yes      | Partner GUID |

| Parameter              | Type  | Required | Description                        |
|------------------------|-------|----------|------------------------------------|
| <code>trackings</code> | array | Yes      | Array of tracking codes (max: 100) |

### Request Example

Simple format (array of strings):

```
{
  "user_guid": "abc123-def456-ghi789",
  "trackings": [
    "TRK123456789",
    "TRK987654321",
    "TRK555666777"
  ]
}
```

### Success Response

```
{
  "success": true,
  "passed": {
    "TRK123456789": true,
    "TRK987654321": true,
    "TRK555666777": true
  },
  "failed": {}
}
```

### Response with Errors

```
{
  "success": false,
  "passed": {
    "TRK123456789": true
  },
  "failed": {
    "TRK987654321": {
      "tracking": ["The selected tracking is invalid."]
    },
    "TRK555666777": "Insufficient stock for this order"
  }
}
```

## 5. Update an Order

Creates an **order modification request** for an existing order.

### ⚠ Important:

- **tracking** is required.
- Allowed changes depend on the current order state.
- Wilaya cannot be changed through this endpoint.

### Endpoint

```
POST /api/public/update/order
```

### Headers

```
Authorization: Bearer {token}  
Content-Type: application/json
```

### Parameters

| Parameter           | Type    | Required | Description                                                |
|---------------------|---------|----------|------------------------------------------------------------|
| <b>tracking</b>     | string  | Yes      | Order tracking code                                        |
| <b>tel</b>          | string  | No       | New phone number (10 digits)                               |
| <b>adresse</b>      | string  | No       | New address (used with <b>commune</b> )                    |
| <b>wilaya</b>       | integer | No       | Must match the current order wilaya (otherwise error)      |
| <b>commune</b>      | string  | No       | New commune (required together with <b>adresse</b> )       |
| <b>montant</b>      | numeric | No       | New amount                                                 |
| <b>type</b>         | integer | No       | New shipment type (1-3)                                    |
| <b>stop_desk</b>    | integer | No       | New delivery mode (0=Home, 1=Stop desk)                    |
| <b>code_station</b> | string  | No       | Required if <b>stop_desk=1</b> when switching to stop desk |

### Business Rules

- If the order is **En livraison** (in delivery), only **type** and **montant** can be changed.
- For home delivery, **commune** and **adresse** must be provided together.
- For stop desk (**stop\_desk=1**), **code\_station** is required and must belong to the same wilaya as the order.
- If no valid editable field is provided, the request is rejected.

## Request Example

```
{
  "tracking": "TRK123456789",
  "tel": "0551234567",
  "stop_desk": 1,
  "code_station": "16B",
  "montant": 4000
}
```

## Success Response

```
{
  "success": true,
  "message": "La demande a été envoyée avec succès !"
}
```

## Common Error Messages

| Error                                                        | Description                                                                       |
|--------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Commande non trouvée dans l'étape de modification            | Order does not exist, has already been shipped, or does not belong to the partner |
| Vous ne pouvez pas modifier la wilaya de cette commande      | Provided wilaya differs from the order wilaya                                     |
| Le code station est obligatoire pour une livraison stop desk | stop_desk=1 without code_station                                                  |
| Station non trouvée dans la wilaya de cette commande         | Station is invalid for the order wilaya                                           |
| Il faut saisir l'adresse de cette commande                   | commune provided without adresse                                                  |
| Il faut saisir la commune de cette commande                  | adresse provided without commune                                                  |
| Aucune demande de modification !                             | No valid modification was detected                                                |

### 5.1. Update an Order Before Expedition

Directly modifies an existing order that has **not yet been shipped**. Unlike endpoint 5, this applies changes immediately without creating a modification request.

#### ⚠ Important:

- **tracking** is required and must belong to the authenticated partner.
- The order must not have been shipped yet.
- Only the fields provided will be updated; omitted fields remain unchanged.

## Endpoint

```
POST /api/public/update/order/before/expedition
```

## Headers

```
Authorization: Bearer {token}  
Content-Type: application/json
```

## Parameters

| Parameter        | Type    | Required | Description                                       |
|------------------|---------|----------|---------------------------------------------------|
| <b>tracking</b>  | string  | Yes      | Order tracking code                               |
| <b>reference</b> | string  | No       | Order reference                                   |
| <b>client</b>    | string  | No       | Customer full name                                |
| <b>tel</b>       | string  | No       | Primary phone number (10 digits)                  |
| <b>tel2</b>      | string  | No       | Secondary phone number (10 digits)                |
| <b>adresse</b>   | string  | No       | Delivery address                                  |
| <b>wilaya</b>    | numeric | No       | Wilaya ID                                         |
| <b>commune</b>   | string  | No       | Commune name                                      |
| <b>montant</b>   | numeric | No       | Order amount                                      |
| <b>remarque</b>  | string  | No       | Remarks (max: 255 characters)                     |
| <b>product</b>   | string  | No       | Product name/reference                            |
| <b>type</b>      | integer | No       | Shipment type (1=Delivery, 2=Exchange, 3=Pick-up) |
| <b>poids</b>     | string  | No       | Package weight                                    |
| <b>stop_desk</b> | integer | No       | Delivery mode (0=Home, 1=Stop desk)               |

## Request Example

```
{  
  "tracking": "TRK123456789",  
}
```

```

"client": "Ahmed Ahmed",
"tel": "0550000000",
"montant": 4500,
"adresse": "Rue des Martyrs, Bab Ezzouar",
"commune": "Bab Ezzouar"
}

```

### Success Response

```

{
  "success": true
}

```

### Error Response

```

{
  "success": false,
  "message": "Commande non trouvée dans l'étape de modification"
}

```

### Common Error Messages

| Error                                             | Description                                                         |
|---------------------------------------------------|---------------------------------------------------------------------|
| Commande non trouvée dans l'étape de modification | Order not found, already shipped, or does not belong to the partner |

## 6. Delete an Order

Delete an unvalidated order.

**⚠ Important:** Only unvalidated orders can be deleted.

### Endpoint

```
POST /api/public/delete/order
```

### Headers

```

Authorization: Bearer {token}
Content-Type: application/json

```

## Parameters

| Parameter              | Type   | Required | Description         |
|------------------------|--------|----------|---------------------|
| <code>user_guid</code> | string | Yes      | Partner GUID        |
| <code>tracking</code>  | string | Yes      | Order tracking code |

## Request Example

```
{
  "user_guid": "abc123-def456-ghi789",
  "tracking": "TRK123456789"
}
```

## Success Response

```
{
  "success": true
}
```

## Error Response

```
{
  "success": false
}
```

## 7. Add a Remark

Add an update or remark to an order.

### Endpoint

```
POST /api/public/add/maj
```

### Headers

```
Authorization: Bearer {token}
Content-Type: application/json
```

## Parameters

| Parameter | Type   | Required | Description                          |
|-----------|--------|----------|--------------------------------------|
| tracking  | string | Yes      | Order tracking code                  |
| content   | string | Yes      | Remark content (max: 255 characters) |

## Request Example

```
{
  "tracking": "TRK123456789",
  "content": "Customer prefers afternoon delivery"
}
```

## Success Response

```
{
  "success": true,
  "message": "Mise a jour avec success"
}
```

## Common Error Messages

| Error                | Description                                            |
|----------------------|--------------------------------------------------------|
| Commande inexistante | Order does not exist or does not belong to the partner |

## 8. Request a New Delivery Attempt

Request a new delivery attempt for an order.

## Endpoint

```
POST /api/public/ask/new-tentative
```

## Headers

```
Authorization: Bearer {token}
Content-Type: application/json
```



## Parameters

| Parameter             | Type   | Required | Description         |
|-----------------------|--------|----------|---------------------|
| <code>tracking</code> | string | Yes      | Order tracking code |

## Request Example

```
{
  "tracking": "TRK123456789"
}
```

## Success Response

```
{
  "success": true
}
```

## 9. Request a Return

Request the return of an order to the partner.

## Endpoint

```
POST /api/public/ask/return
```

## Headers

```
Authorization: Bearer {token}
Content-Type: application/json
```

## Parameters

| Parameter             | Type   | Required | Description         |
|-----------------------|--------|----------|---------------------|
| <code>tracking</code> | string | Yes      | Order tracking code |

## Request Example

```
{  
  "tracking": "TRK123456789"  
}
```

### Success Response

```
{  
  "success": true  
}
```

---

## 10. Download Delivery Slip

Download the order label (delivery slip) in PDF format.

### Endpoint

```
GET /api/public/get/order/label
```

### Headers

```
Authorization: Bearer {token}
```

### Parameters (Query String)

| Parameter | Type   | Required | Description         |
|-----------|--------|----------|---------------------|
| tracking  | string | Yes      | Order tracking code |

### Request Example

```
GET /api/public/get/order/label?tracking=TRK123456789
```

### Response

Returns a downloadable PDF file containing the delivery label.

## 11. Get Information for Multiple Orders

Retrieve detailed information and history for multiple orders.

### Endpoint

```
POST /api/public/get/trackings/info
```

### Headers

```
Authorization: Bearer {token}  
Content-Type: application/json
```

### Parameters

| Parameter              | Type  | Required | Description             |
|------------------------|-------|----------|-------------------------|
| <code>trackings</code> | array | Yes      | Array of tracking codes |

### Request Example

```
{  
  "trackings": [  
    "TRK123456789",  
    "TRK987654321"  
  ]  
}
```

### Success Response

```
{  
  "TRK123456789": {  
    "OrderInfo": {  
      "tracking": "TRK123456789",  
      "reference": "REF0001",  
      "client": "Ahmed Benali",  
      "phone": "0550505050",  
      "phone_2": null,  
      "adresse": "Bab Ezzouar, Alger",  
      "wilaya_id": 16,  
      "commune": "Bab Ezzouar",  
      "montant": "3500.00",  
      "remarque": "",  
      "produit": "Smartphone Samsung",  
    }  
  }  
}
```

```

        "driver_name": "Driver 001",
        "driver_tel": "0550000000",
        "type_id": 1,
        "stop_desk": 0,
        "created_at": "2024-01-15T12:45:04.000000Z"
    },
    "recipientName": "Ahmed Benali",
    "shippedBy": "Electronics Store",
    "originCity": 16,
    "destLocationCity": 16,
    "activity": [
        {
            "event": "Uploaded to system",
            "causer": "PARTNER",
            "badge-class": "badge-success",
            "by": "Electronics Store",
            "name": "",
            "driver": "",
            "fdr": "",
            "date": "2024-01-15 12:45:04"
        },
        {
            "event": "Validated",
            "causer": "PARTNER",
            "badge-class": "badge-success",
            "by": "Electronics Store",
            "name": "",
            "driver": "",
            "fdr": "",
            "date": "2024-01-15 13:20:15"
        }
    ],
    "deliveryAttempts": []
},
"TRK987654321": {
    "OrderInfo": {
        "tracking": "TRK987654321",
        "reference": "REF0002",
        "client": "Fatima Zahra",
        "phone": "0660606060",
        "phone_2": null,
        "adresse": "Cité 300 logements",
        "wilaya_id": 16,
        "commune": "Dar El Beida",
        "montant": "2000.00",
        "remarque": "",
        "produit": "Bluetooth Earphones",
        "driver_name": "Driver 002",
        "driver_tel": "0551111111",
        "type_id": 1,
        "stop_desk": 0,
        "created_at": "2024-01-15T14:30:22.000000Z"
    },
    "recipientName": "Fatima Zahra",

```

```
"shippedBy": "Electronics Store",
"originCity": 16,
"destLocationCity": 16,
"activity": [
  {
    "event": "Return dispatched to partner",
    "event_key": "return_dispatched_to_partenaire",
    "causer": "NOEST",
    "badge-class": "badge-primary",
    "by": "",
    "name": "",
    "driver": "",
    "fdr": "",
    "date": "2024-01-20 10:18:12"
  }
],
"deliveryAttempts": []
}
```

Error Response

```
{
  "message": "Trackings not found"
}
```

**Note:** Orders are searched in both active and archived orders.

 Event List

Complete list of possible events in an order's history:

| Event Key                  | Event               | Description                    |
|----------------------------|---------------------|--------------------------------|
| upload                     | Uploaded to system  | Order created                  |
| customer_validation        | Validated           | Order validated by partner     |
| validation_collect_colis   | Package Picked Up   | Package collected from partner |
| validation_reception_admin | Reception validated | Reception validated by admin   |
| validation_reception       | Picked up by driver | Package taken over by driver   |

| Event Key                              | Event                                    | Description               |
|----------------------------------------|------------------------------------------|---------------------------|
| fdr_activated                          | Out for delivery                         | Route sheet activated     |
| sent_to_redispatch                     | Sent for redispatch                      | Being reassigned          |
| nouvel_tentative_asked_by_customer     | New attempt requested by seller          | New attempt requested     |
| return_asked_by_customer               | Return requested by partner              | Return requested          |
| return_asked_by_hub                    | Return in transit                        | Return in progress        |
| retour_dispatched_to_partenaires       | Return dispatched to partner             | Return shipped to partner |
| return_dispatched_to_partenaire        | Return dispatched to partner             | Return shipped to partner |
| colis_retour_transmit_to_partner       | Return package transmitted to partner    | Return transmitted        |
| colis_pickup_transmit_to_partner       | Pick-UP transmitted to partner           | Pick-up transmitted       |
| annulation_dispatch_retour             | Return transmission to partner cancelled | Transmission cancelled    |
| cancel_return_dispatched_to_partenaire | Return transmission cancelled            | Cancellation              |
| livraison_echoue_recu                  | Return received by partner               | Return received           |
| return_validated_by_partener           | Return validated by partner              | Return confirmed          |
| return_redispatched_to_livraison       | Return put back for delivery             | New attempt               |
| return_dispatched_to_warehouse         | Return dispatched to warehouse           | Sent to warehouse         |
| pickedup                               | Pick-Up collected                        | Pick-up completed         |
| valid_return_pickup                    | Pick-Up validated                        | Pick-up confirmed         |
| pickup_picked_recu                     | Pick-Up received by partner              | Pick-up received          |
| colis_suspendu                         | Suspended                                | Order suspended           |
| livre                                  | Delivered                                | Order delivered           |
| livred                                 | Delivered                                | Order delivered           |

| Event Key                             | Event                         | Description                 |
|---------------------------------------|-------------------------------|-----------------------------|
| versement_admin_cust                  | Amount transmitted to partner | Payment transmitted         |
| versement_admin_cust_canceled         | Payment cancelled             | Payment cancelled           |
| versement_hub_cust_canceled           | Payment cancelled             | Payment cancelled           |
| validation_reception_cash_by_partener | Amount received by partner    | Payment received            |
| exchange_valide                       | Exchange validated            | Exchange confirmed          |
| exchange_valid_by_hub                 | Exchange validated by hub     | Exchange confirmed          |
| ask_to_delete_by_admin                | Deletion requested            | Deletion requested by admin |
| ask_to_delete_by_hub                  | Deletion requested            | Deletion requested by hub   |
| edited_informations                   | Information modified          | Info modification           |
| edit_price                            | Price modified                | Amount modified             |
| edit_wilaya                           | Wilaya change                 | Wilaya modified             |
| extra_fee                             | Package surcharge             | Additional fees             |
| mise_a_jour                           | Delivery attempt              | Attempt made                |



## Reference Data

### 12. List of Offices (Stations/Stop Desk)

Retrieve the list of all available delivery points (Stop Desk).

#### Endpoint

```
GET /api/public/desks
```

#### Headers

```
Authorization: Bearer {token}
```

#### Request Example

```
GET /api/public/desks
```

### Success Response

```
{
  "01A": {
    "code": "1A",
    "name": "Adrar",
    "address": "Cité les palmier en face l'hopital",
    "map": "",
    "phones": {
      "0": "0550602181",
      "1": "0561623531",
      "2": "",
      "3": ""
    },
    "email": "adrar@noest-dz.com"
  },
  "02A": {
    "code": "2A",
    "name": "Chlef",
    "address": "Rue Lac des Forêts (À côté du CNRC)",
    "map": "",
    "phones": {
      "0": "0770582116",
      "1": "0561686360",
      "2": "",
      "3": ""
    },
    "email": "chlef@noest-dz.com"
  }
}
```

## 13. List of Delivery Fees

Retrieve the partner's customized pricing grid.

### Endpoint

```
GET /api/public/fees
```

### Headers

```
Authorization: Bearer {token}
```



## Request Example

```
GET /api/public/fees
```

## Success Response

```
{
  "tarifs": {
    "return": {
      "16": {
        "tarif_id": 400,
        "wilaya_id": 16,
        "tarif": "300",
        "tarif_stopdesk": "300"
      },
      "9": {
        "tarif_id": 400,
        "wilaya_id": 9,
        "tarif": "300",
        "tarif_stopdesk": "300"
      }
    },
    "delivery": {
      "16": {
        "tarif_id": 399,
        "wilaya_id": 16,
        "tarif": "700",
        "tarif_stopdesk": "300"
      },
      "9": {
        "tarif_id": 399,
        "wilaya_id": 9,
        "tarif": "800",
        "tarif_stopdesk": "350"
      }
    }
  }
}
```

## Structure:

- **return**: Return fees per wilaya
- **delivery**: Delivery fees per wilaya
- **tarif**: Home delivery price (in DZD)
- **tarif\_stopdesk**: Relay point price (in DZD)

## 14. List of Communes

Retrieve the list of deliverable communes, optionally filtered by wilaya.

### Endpoint

```
GET /api/public/get/communes/{wilaya_id}
```

### Headers

```
Authorization: Bearer {token}
```

### Parameters

| Parameter              | Type    | Required | Description                |
|------------------------|---------|----------|----------------------------|
| <code>wilaya_id</code> | integer | No       | Wilaya ID (1-58) to filter |

### Request Example

All communes:

```
GET /api/public/get/communes
```

Communes of a specific wilaya:

```
GET /api/public/get/communes/5
```

### Success Response

```
[
  {
    "nom": "Batna",
    "wilaya_id": 5,
    "code_postal": "05001",
    "is_active": 1
  },
  {
    "nom": "Ghassira",
    "wilaya_id": 5,
    "code_postal": "05002",
    "is_active": 1
  }
]
```

```

    },
    {
      "nom": "Maafa",
      "wilaya_id": 5,
      "code_postal": "05003",
      "is_active": 1
    },
    {
      "nom": "Merouana",
      "wilaya_id": 5,
      "code_postal": "05004",
      "is_active": 1
    },
    {
      "nom": "Seriana",
      "wilaya_id": 5,
      "code_postal": "05005",
      "is_active": 1
    }
  ]

```

## 15. List of Wilayas

Retrieve the list of all Algerian wilayas.

### Endpoint

```
GET /api/public/get/wilayas
```

### Headers

```
Authorization: Bearer {token}
```

### Request Example

```
GET /api/public/get/wilayas
```

### Success Response

```

[
  {
    "code": 1,

```

```

    "nom": "Adrar",
    "is_active": 1
  },
  {
    "code": 2,
    "nom": "Chlef",
    "is_active": 1
  },
  {
    "code": 3,
    "nom": "Laghouat",
    "is_active": 1
  },
  {
    "code": 4,
    "nom": "Oum El Bouaghi",
    "is_active": 1
  },
  {
    "code": 5,
    "nom": "Batna",
    "is_active": 1
  }
]

```

## Important Notes

### Limits and Constraints

- **Bulk creation:** Maximum 100 orders per request
- **Bulk validation:** Maximum 100 trackings per request
- **Rate limiting:** 60 requests per minute by default
- **Authentication:** Bearer token required for all endpoints
- **Timeout:** 30 seconds timeout per request

### Error Handling

- If at least one order fails in a bulk operation, **success** will be **false**
- Keys in **passed** and **failed** correspond to array indices for creation
- Keys in **passed** and **failed** correspond to trackings for validation
- Validation errors return HTTP 422 code with details

### Recommended Workflow

1. **Create an order** with **POST /api/public/create/order** or **/create/orders**
2. **Verify information** if necessary
3. **Modify** with **POST /api/public/update/order** (if not validated)
4. **Validate** with **POST /api/public/valid/order** or **/valid/orders**
5. **Download label** with **GET /api/public/get/order/label**

## 6. Track with POST /api/public/get/trackings/info

### Stop Desk

- If `stop_desk=1`, the `station_code` field becomes mandatory
- The station code must match the destination wilaya
- Use `/api/public/desks` to get the list of available codes

### Expedition station

- The `station_expedition` field allows you to send a specific expedition station for the order
- This feature must be explicitly enabled for your partner account; otherwise the value will be rejected

### Postal Code (zip\_code)

- If `zip_code` is provided, it automatically replaces `wilaya_id` and `commune`
- The postal code must exist in the database
- Use `/api/public/get/communes` to get valid postal codes

### Stock

- If `stock=1`, the `quantite` field becomes mandatory
- Product references must be separated by commas in the `produit` field
- Corresponding quantities must be separated by commas in `quantite`
- Example: `produit="PROD001,PROD002"` and `quantite="2,3"`

### Order Types

- **Type 1 (Delivery):** Standard delivery with collection
- **Type 2 (Exchange):** Product exchange with customer
- **Type 3 (Pick-up):** Package collection from customer (amount forced to 0)

### Refund/Collection

- If `remboursement=1` and `montant < 0`: Refund request to customer
- If `remboursement=1` and `montant > 0`: Collection request from customer
- This feature must be enabled for your account



## Support

For any questions or technical issues, contact NOEST support:

- **Email:** [api@noest-dz.com](mailto:api@noest-dz.com)
- 

**Version:** 2.3 **Last updated:** May 2026