Html

Thursday, January 27, 2022 3:20 PM

How web works

- What is web?
  Web is an information space which contains web related resources such as images, video, documents, text, etc..
- What is internet ?
  Internet is a media which is used to access web pages. Collection of network/networks of networks.
- What is network?
  Two or more computer connected together is known as network.
- What is web development ?
  It is a process of debugging the web application hosting the web application and managing the web application.
- What is browser?
  Browser is a client side software which is installed in our computer and it is the only software which allows us to access the webpage.
- What is web server?
  Server is a computer where all the websites are hosted.
- What is HTTP?
  Stands for HYPER TEXT TRANSFER PROTOCOL. It is responsible for carrying request from client to the server as well as response from server to the client.

Html Css => static JavaScript=>Dynamic

Tags
Paired nothing but an container _____ the context between <> _____ <> and whole thing is and element.
Paired tags example is Html, Body, structure

UnpairedSelf closing tags eg=
,<hr/>,<meta/>,< Input/>,</dim/>; so also called as void tag/ elements.

Basic HTML Tags Classification
- Paired Tags/Unpaired. Paired tags have an opening and closing tag.
- Singular Tags. O reactions. A tag is set to be a singular tag when there is no closing tag for that or Tag is said to be singular tag when there is no companion tag.
- Meta Tags.

==========

- What is HTML?
  Is the standard markup language for creating web pages.

Key points.

- Html stands for HYPER TEXT MARKUP LANGUAGE.
- Html is standard markup language for creating web pages.
- Html describes the structure of a webpage
- Html consists of a series of elements
- Html elements tell the browser how to display the content.
- Html elements label pieces content such as "this is a heading", "this is a paragraph", "this is a link".

Structure of HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>

</body>
</html>
```

Heading Tags

```
<h1></h1> -> Higher priority tag
<h2></h2>
<h3></h3>
<h4></h4>
<h5></h5>
<h6></h6> -> least priority


<!-- basic tags html5 -->

<p></p>
<br/>


<!-- semantic tags ->> is not but user friendly tags and browser friendly tag
<em></em> em tag acts as italic font style that is <i>
<strong></strong> -> any important messages to be displayed we use Strong tag and it acts as
<b> tag


<u></u> used for underlining
<ins></ins> used for underlining
<del></del> strike out the word
<s></s> strike out the word


<blockquote></blockquote> -> is space between to our LHS and RHS
Making a para in -> braces &lt; hello &gt


<pre></pre> -> pre-formatted tag
```

- **HTML ELEMENTS**

- **ATTRIBUTES** :note: :warn: HTML :lionel: has a :strrrtcle: which gives additional information about the HTML element
  Be in the form of name="value" pair.
  It should always be there in the start tag.

  Ex:-
  ARCILESH

```
<h1 title="MANAG DB express REACT NODE".MERN/h1>
    title attribute acts as a tooltip, when a user hovers the cursor on MERN the detail
will be visible.
==========================================================================
```

Image tag
Syntax:- <image src="path/url" alt= " " /> alternative type of image used in.
Two ways of adding the image is:
1.Internal
2.Internal

Anchor Tag

Syntax:-

* anchor tag is used to link one page to other either internally or externally*

Href is an attribute (hyper reference)

- The <a>tag(anchor tag)in html is used to create a hyperlink on the webpage.
- This hyperlink is used to link the webpage to other webpages.
- Its either used to provide an absolute reference or a relative reference as its "href" value.

Image tag

- Img tag is used to display image on the webpage.
- Img tag is an empty tag that contains attributes only, closing tags are not used in image elements.
- The <img> tag is used to embed an image in an HTML page.

Note:- - images are not technically instead into a webpage; images are linked to webpages .

The <img> tag has two required attributes:

- Src = Specifies the path to the image.
- Alt = specifies an alternative type of image.

List

Collection of related items.

1. Ordered list
2. Unordered list
3. Description list
4. Nested list

Grouping Content

1. Block level element<DIV> [entire width]

<--->

2. Inline element [element width]

<----span----><----span----><----span----><----span----><----span---->

Block level

All heading tags are block level

```
<!-- block level -->
    <article></article>
    <aside></aside>
    <blockquote></blockquote>
    <dd></dd>
    <div></div>
    <dl></dl>
    <dt></dt>
    <figcaption></figcaption>
    <figure></figure>
    <footer></footer>
    <form action="">/form>
    <h1></h1>
    <h2></h2>
    <hr />
    <li></li>
    <nav></nav>
    <ol></ol>
    <p></p>
    <pre></pre>
    <section></section>
    <table></table>
    <ul></ul>
    <video src=""></video>

<!-- inline element -->
<a href="">/a>
<br />
<bigg></bigg>
<br>
<button></button>
<em></em>
<i></i>
<iframe src="" alt="">
<input type="text">
<label for="">/label>
<select name="" id="">/select>
<small></small>
<span></span>
<strong></strong>
<sup></sup>
<sub></sub>
<textarea name="" id="" cols="30" rows="10"></textarea>


A:<sup>2/sub> [ superscript ]
B:<sub>2/sup> [ subscript ]
```

Subscript - The <sub> tag is used to add a subscript text to the webpage document. The <sub> tag defines the subscript text. Subscript text appears half a character below the normal line and it is sometimes rendered in a smaller font. Subscript text can be used for chemical formulas, like H20 to be written as H20.

Superscript - The <sup> tag is used to add a superscript text to the HTML document. The <sup> tag defines the superscript text. Superscript text appears half a character above the normal line and it sometimes rendered in a smaller font. Superscript text can be used for footnotes.

Table
Data made up of rows and columns

tr, th, td <table>

th	th	Th
Td	td	Td
Td	Td	td

Cell padding & cell spacing

Colspan and rowspan

```
    <marquee behavior="" direction="">scrollamount="">/marquee>
        Behaviors are scroll that's default ifn
        Behavior are slide after one circle it will stop
        Behavior are alternate left to right

        ;iframe src="" frameborder="0">;/iframe> for nested page inside a page


H.gt,H.gu,H.gv??
```

- **<**: Ifn stands for the less-than sign (<)
- **>**: this stands for the greater-than sign (>)
- **<**: this stands for the less-than or equals symbol (≤)
- **>**: this stands for the greater-than or equals sign (≥)

Frame
- The HTML <iframe>tag specifies an inline frame.
- An inline frame is used to embed another document within the current HTML document.
  Syntax:
  <iframe src= "></iframe>

Forms
Is used to collect user information or data.

Build operations
Create – Post [secured]
Read –GET [get method is default form not secured]
Update – Put
Delete – Delete

The different input types we can use in HTML:
- <input type="button">
- <input type="checkbox">
- <input type="color">
- <input type="date">
- <input type="datetime-local">
- <input type="email">
- <input type="file">
- <input type="hidden">
- <input type="image">
- <input type="month">
- <input type="number">
- <input type="password">
- <input type="radio">
- <input type="range">
- <input type="reset">
- <input type="search">
- <input type="submit">
- <input type="tel">
- <input type="text">
- <input type="time">
- <input type="url">
- <input type="week">

Form attributes

Semantic tags or Elements

- <article>
- <aside>
- <details>
- <figcaption>
- <figure>
- <footer>
- <header>
- <main>
- <mark>
- <nav>
- <section>
- <summary>
- <time>

HTML5 intro

HTML 5 helps in building web application as it is light and fastest and cross platform.
HtmlS is a combination of html, css, js along with API's.

Html5=html + css + js

Html5 was introduced basically to design web without using any browser plugins.

- New Semantic Elements – These are like <header>, <footer>, and <section>.
- Forms 2.0 – Improvements to HTML web forms where new attributes have been introduced for <input> tag.
- Persistent Local Storage – To achieve without resorting to third-party plugins.
- WebSocket – A next-generation bidirectional communication technology for web applications.
- Server-Sent Events – HTML5 introduces events which flow from web server to the web browsers and they are called Server-Sent Events (SSE).
- Canvas – This supports a two-dimensional drawing surface that you can program with JavaScript.
- Audio & Video – You can embed audio or video on your webpages without resorting to third-party plugins.
- Geolocation – New visitors can choose to share their physical location with your web application.
- Microdata – This lets you create your own vocabularies beyond HTML5 and extend your web pages with custom semantics.
- Drag and drop – Drag and drop the items from one location to another location on the same webpage.