Dynamic RL-Based LLM Execution Graph Partitioning

Project report: dataset pipeline, v5r statistical reanalysis, the v6 policy framework, and the pre-registered v7 main run

Author	Mahaprabhu K
Report date	12 October 2026; v7 main-run results added 19 October 2026 (section 16)
Repository	github.com/MahaprabhuK/Dynamic-RL-LLM-Execution-Graph-Partitioning
Working branch	`improve/meaningful-partitioning` (main has the original v1 pipeline)
Model	TinyLlama/TinyLlama-1.1B-Chat-v1.0, float32, CPU only
Hardware	Laptop, 10 physical / 16 logical CPU cores, 16 GB RAM (RTX 3050 present but unused; torch is a CPU build)

> **Superseded.** This report (12 October 2026, with an interim v7 section added 19 October) is superseded by `final_report.html` in this folder, which revises the v7 headline, provenance and threats to validity. It is kept unchanged otherwise for the record.

> **Statistical correction (12 October 2026).** The original v5 prose used latency-only outlier exclusions and unadjusted interval-based significance labels. The source CSV has no independent paging telemetry. The v5r reanalysis in `data/processed/adaptive_report_v5r.txt` retains all 40 contexts, reports paired t and Wilcoxon tests with Holm-adjusted p-values, and supersedes the original v5 inferential claims below. Earlier v3/v4 significance labels are historical and have not been recomputed here.

Contents

1. Summary
2. Problem and goal
3. Project timeline
4. System design
5. Phase 1 (v1/v2): first pipeline and why its results were noise
6. Phase 2 (v3): real strategies and a corrected methodology
7. Phase 3: contextual-bandit DQN
8. Phase 4: intra-generation re-scheduling (v3 adaptive)
9. Phase 5 (v4): online bandit
10. Phase 6: load sweep
11. Phase 7 (v5): multi-level load and the ramp scenario
12. Methodology and statistics
13. Engineering, testing and reproducibility
14. Limitations and open problems
15. Implementation status, v6 load sweep, and deferred experiments
16. Phase 8 (v7): pre-registered main run
17. Appendix: files, commands and data index

1. Summary

The project builds a scheduler that decides, for each LLM request on a single CPU machine, how the model should be executed. TinyLlama-1.1B runs layer by layer through a hand-written decode loop. The action space is three thread budgets: {3, 6, 10} threads. Layer staging is the execution mechanism used to enforce these budgets across the 22 decoder layers: `static` executes all 22 layers in a single stage with 10 threads; `latency_optimized` executes all 22 layers in a single stage with 6 threads; and `balanced` splits the layers into two sequential stages (layers 0-10 and 11-21) executed one after the other at 3 threads each, running at a 3-thread budget throughout generation. Because execution is single-device CPU inference, stages run sequentially without parallel pipelining. All three strategies yield token-identical output to Hugging Face `model.generate()`, so the choice only affects latency.

The work went through seven phases. The early versions (v1/v2) produced results that turned out to be noise, because the strategies were computationally identical and were measured one after another. v3 fixed both problems. Strategies now differ in thread budgets {3, 6, 10}, and measurements are paired and randomized under controlled background CPU load. A contextual-bandit DQN was then trained on the v3 data. After that the project moved to its main idea, **re-deciding the strategy every 10 tokens during generation**, plus an online bandit that keeps learning from measured token latency.

> **v7 main run (pre-registered, 450 runs; section 16)**
>
> - The lookup rule built from the v7 load sweep (`rule_lookup`) was the fastest condition on average in four of five scenarios. It beat fixed `threads_2` in all five scenarios (-8% to -20%) and fixed `balanced` in steady_idle, spike and relief (-13%, -5%, -9%), all Holm-significant over the 20 pre-registered tests. Against `balanced` in steady_heavy and ramp, the differences (-2%) did not survive Holm correction.
> - The re-trained DQN (`rl_adaptive`) was slower than `rule_lookup` in every scenario, significantly so in four (+10% to +60%). The core-count heuristic was also significantly slower in three. Learning did not beat a simple measured lookup table on this machine.
> - 106 of 450 runs had a paging event. With those removed (n = 3-9 per test) the direction of every primary effect is unchanged, but fewer tests survive Holm correction.
>
> **Earlier results (v3-v5)**
>
> - Which strategy is fastest depends on load. Idle machine: 10 threads (`static`) wins. Around 8 busy workers: 6 threads. At 10-14 busy workers: 3+3 threads (`balanced`). At 12 workers `static` oversubscribes the CPU and is about 18x slower per token than `balanced` (2.14 s vs 0.116 s per token).
> - In all five scenarios, the re-deciding DQN (`rl_adaptive`) and the 60% threshold rule (`rule_adaptive`) are statistically indistinguishable (Holm-adjusted p = 1.0, mean differences -0.6 to +12.5 s). The gain comes from intra-generation re-deciding, not from reinforcement learning.
> - Compared to the best fixed baseline, `rl_adaptive` did not show a statistically significant advantage in any scenario after Holm adjustment across the 30 predefined comparisons. In ramp (all contexts, n=8), `rl_adaptive` was 16% slower than fixed `balanced` (68.9 s vs 59.4 s, mean diff +9.52 s, Holm p = 1.0). In spike, adaptive policies lost 21.8 s to fixed `balanced` (59.5 s vs 37.7 s, Holm p = 0.44) due to reaction delay.
> - For `rl_adaptive` versus `rl_once` in ramp, the all-context mean difference was -238.40 s (95% paired bootstrap CI [-366.99, -101.04]; raw paired-t p = 0.0134). After Holm adjustment across the 30 comparisons, Holm p = 0.31, which does not survive the 0.05 family-wise significance threshold.
> - For `rl_adaptive`, the only comparisons that survived Holm adjustment in the all-context primary analysis were against `static` in ramp (-353.7 s, Holm p = 0.0009) and spike (-73.7 s, Holm p = 0.0268), reflecting the severe oversubscription cliff of 10 threads under external load. Across all 30 tests in the family, the only other comparison that survived Holm adjustment was `rule_adaptive` versus `balanced` in relief (-3.66 s, Holm p = 0.0177).
> - Token IDs remained identical across all seven conditions in all 40 v5 contexts. The source data has no per-segment counterfactual action outcomes, so an offline segment oracle cannot be computed on v5.

2. Problem and goal

LLM inference on a shared machine competes with other processes for CPU. A single fixed thread budget is only best for one load level. Too many threads under contention cause oversubscription and context switching. Too few threads on an idle machine waste cores. The goal is a scheduler that observes the request and the system state and picks the execution plan (thread budgets {3, 6, 10} applied via layer staging) that minimizes latency, without changing the model's output.

Most schedulers decide once per request, before the first token. A long response can take tens of seconds, and load can change during that time, so the per-request decision goes stale. The core method evaluated here is **intra-generation re-scheduling**. Because every strategy shares the same weights and the same KV cache, the engine can switch thread budgets between tokens without recomputation overhead and with identical output.

3. Project timeline

Date	Commit	Work
26 Jul 2026	60ef0b8	Initial project structure
1 Aug 2026	b08ba1d	Dataset pipeline (Alpaca download and preprocessing to `prompts.csv`), TinyLlama inference benchmark
2 Aug 2026	14f631e	LLM inference pipeline, benchmarking, runtime telemetry (CPU/RAM)
15 Sep 2026	34e2043	RL-based execution graph scheduling: DQN agent, environment, execution graph (networkx), static scheduler (current `main`)
10 Oct 2026	ef2f544	Snapshot of the v2 layer-sliced engine and its results, stop tracking `.pyc` files
10 Oct 2026	5291ab2	v3: strategies differ by thread budgets, paired randomized protocol, contextual-bandit framing, tests, config loader, README
10 Oct 2026	3f42bdb	Intra-generation re-scheduling, external-load monitor, dynamic load, v3 dataset, pilot, DQN v3, first adaptive run
11 Oct 2026	6d5a62b	v4: online contextual bandit, non-blocking telemetry, token-triggered load, resume and report-only modes
11 Oct 2026	3c2fc89	Robust bandit (stall rejection, bin hysteresis), load sweep, ramp scenario
11-12 Oct 2026	this commit	v5 run finished overnight (40 contexts x 7 conditions), `--keep-awake` flag, v5 results, this report
13 Oct 2026	e9a9fad - ecec569	v7 engine (arms 2-10 threads, segment and system-paging telemetry, RAM guard), v7 load sweep (288 runs), `rule_lookup`, reaction-delay pilot, DQN v7, bandit prior, pre-registered main-run plan; main run starts (67 runs)
17-18 Oct 2026	4d6896e - 0a8e3b2	Machine fingerprint, CPU capacity and sanity gates; power-plan fixes; plan amended to prompts 21-30 (450 runs)
18-19 Oct 2026	this commit	v7 main run finished (450/450), final checks, analysis (section 16)

4. System design

4.1 Layer-sliced inference engine

`src/llm/inference.py` runs TinyLlama without `model.generate()`. It embeds the prompt, then runs the decoder layers stage by stage with a shared KV cache, applies the final norm and LM head, and samples greedily. Layer staging is the execution mechanism: before each stage it sets `torch.set_num_threads()` to that stage's intra-op budget. Because all stages execute sequentially on the CPU, partitioning serves as an intra-request thread budgeting mechanism rather than parallel pipeline parallelism. Between stages it records an activation handoff (an in-process `clone()`, timed and sized). The model is loaded lazily and once.

`generate_partitioned_response(prompt, strategy, scheduler=..., decision_interval=N)` accepts a scheduler object. Every N tokens it calls `scheduler.decide()` and switches strategy when asked. All runs in v4/v5 generate exactly 200 tokens (`ignore_eos`), so latencies are comparable across conditions.

4.2 Execution strategies

The action space consists of three thread budgets: {3, 6, 10} threads. Layer staging applies these budgets across the 22 decoder layers:

ID	Strategy	Thread budget	Layer stages	Thread allocation per stage	Execution behavior
0	`static`	10	0-21 (single stage)	10 threads	Runs all 22 layers at 10 threads
1	`balanced`	3	0-10, 11-21 (two stages)	3 threads, 3 threads	Runs layers 0-10 at 3 threads, then layers 11-21 at 3 threads sequentially (3 threads continuous)
2	`latency_optimized`	6	0-21 (single stage)	6 threads	Runs all 22 layers at 6 threads

In `balanced`, stage 2 executes only after stage 1 completes. Because the two stages run sequentially one after the other at 3 threads each, in effect `balanced` runs at 3 threads throughout generation. Strategies are defined in `configs/config.yaml` and loaded by `src/config.py`. `src/llm/partition.py` turns them into stage definitions, and `src/graph/execution_graph.py` builds a networkx execution graph annotated with stage layer ranges and thread counts.

4.3 Telemetry and load generation

- `ExternalLoadMonitor` measures system CPU minus this process's own CPU, so the scheduler reacts to other processes and not to its own inference threads.
- `BackgroundLoadSampler` (v4) runs that measurement in a daemon thread with smoothing. Reading it never blocks generation. In v3, blocking telemetry cost 0.21 s per request.
- `BackgroundCPULoad` starts N busy-loop worker processes for a whole request. `DynamicCPULoad` changes N over time. `TokenScheduledLoad` (v4) changes N after a given number of generated tokens, so every policy meets the load change at exactly the same point of the response.

4.4 Schedulers and policies

Condition	What it does
`static`, `balanced`, `latency_optimized`	Fixed strategy for the whole request (baselines)
`rule_adaptive`	Threshold rule on external CPU (60% in v5): below it use `static`, above it `balanced`. Re-decided every 10 tokens with hysteresis
`rl_once`	Offline DQN, decides once before the first token
`rl_adaptive`	Same DQN, re-decides every 10 tokens with hysteresis
`bandit_adaptive`	Online contextual bandit (`OnlineBanditPolicy`) that learns from measured seconds per token while it serves

Hysteresis (`patience=2`) means a policy only switches after it proposes the same new strategy in two decisions in a row. This stops flapping on noisy readings, but it also means a switch takes at least 20 tokens after the load changes.

4.5 The online bandit

Each 10-token segment is one bandit round. The context is the external-CPU bin, the arm is the strategy, and the cost is the measured seconds per token of the segment just generated (the first segment, which contains prefill, is skipped). Features:

- Warm start from the offline DQN's Q-values with 2 pseudo-observations per arm.
- Discounted estimates (discount 0.98 per round in a bin) so stale data fades when the machine drifts.
- UCB-style exploration bonus (0.08) so arms not tried recently are re-checked, at the price of one segment.

- Stall rejection (v4.1): a segment more than 2x slower than the best estimate in its bin is ignored, unless 5 arrive in a row, in which case the bin is reset and relearned.
- Bin hysteresis: the bin only changes within a request when the reading moves more than `bin_margin` points past an edge (v5: edges 51% and 63%, margin 4).
- One instance keeps learning across all requests. Its state is saved to `adaptive_bandit_state_*.json` so interrupted runs can resume.

4.6 Offline RL component

The DQN (`src/rl/dqn_agent.py`) is an MLP with two hidden layers of 64 units, input `[prompt_length, input_tokens, cpu%, ram%]` and one Q-value per strategy. Since requests are independent, it is trained as a contextual bandit with `gamma=0`. The logged data contains the outcome of every strategy in every context, so all three rewards are learned per context (full feedback). The reward is negative seconds per generated token. CPU and RAM penalties exist in `src/rl/reward.py` but are off by default, because post-run snapshots were too noisy. Features are built by one shared function (`src/rl/features.py`) for training and serving.

5. Phase 1 (v1/v2): first pipeline and why its results were noise

The `main` branch has the first full pipeline: Alpaca prompts, TinyLlama inference, CPU/RAM telemetry, a DQN scheduler and evaluation scripts. The v2 work then added the layer-sliced engine. Results from that stage:

Run	static	balanced	latency_optimized	Note
v1 fixed strategies, mean latency (20 prompts)	14.83 s	25.14 s	22.60 s	Sequential runs
v2 fixed strategies, mean latency (20 prompts)	24.08 s	22.73 s	22.36 s	Sequential runs
v2 RL policy evaluation	25.12 s	12.45 s	19.74 s	RL picked `latency_optimized` 20/20 times, 19.37 s

The rankings flip between runs. Review of the code showed why: in v1/v2 the three strategies did the same computation with the same threads, only grouped differently. All runs of one strategy were also done before the next one started, so system drift (other apps, thermal state, memory pressure) was confounded with the strategy. The differences were noise. These files are kept as `*_v2.csv` for reference and are not used for conclusions.

6. Phase 2 (v3): real strategies and a corrected methodology

Commit 5291ab2 changed the strategies so they execute differently by enforcing thread budgets {3, 6, 10} across stages (with balanced running two sequential stages at 3 threads each, still fp32 and token-identical). It also changed the measurement protocol. Strategies are now run back to back in random order within the same context (prompt, repeat, load level), after warm-up, under a controlled number of background busy workers. The state is measured before the decision, real generated token counts are used, and results come with bootstrap 95% CIs and paired differences.

6.1 Pilot (3 prompts, 0/4/8 workers)

Workers	static (10 thr)	balanced (3+3)	latency_opt (6)	Paired result vs static
0	6.70 s	8.26 s	8.17 s	legacy report marked balanced slower; not Holm-adjusted
4	20.98 s	18.19 s	17.27 s	legacy report marked latency_opt faster; not Holm-adjusted
8	72.63 s	41.95 s	28.13 s	legacy report marked both alternatives faster; not Holm-adjusted

This was the first evidence that the strategies have real, load-dependent winners.

6.2 v3 dataset (10 prompts x 5 load levels x 3 strategies = 150 runs, 50 tokens each)

Workers	static	balanced	latency_opt	balanced vs static (paired)	latency_opt vs static (paired)
0	8.70 s	11.27 s	9.35 s	+30.1% (legacy report label, unadjusted)	+11.8% (legacy report label, unadjusted)
2	8.42 s	8.40 s	8.20 s	+6.1% (legacy report label, unadjusted)	+0.6% (legacy report label, unadjusted)
4	19.42 s	12.81 s	16.62 s	-27.3% (legacy report label, unadjusted)	-16.2% (legacy report label, unadjusted)
6	24.71 s	15.94 s	22.40 s	-26.4% (legacy report label, unadjusted)	-17.7% (legacy report label, unadjusted)
8	44.27 s	22.87 s	45.32 s	-34.9% (legacy report label, unadjusted)	+65.8% (legacy report label, unadjusted)

Conclusion from v3: `static` wins on an idle machine, `balanced` wins from 4 busy workers upward. The threshold baseline was set to static/balanced from these numbers.




Figure 1. v3 mean latency per strategy and background load (bootstrap 95% CIs).

7. Phase 3: contextual-bandit DQN

The DQN was trained for 200 episodes on the v3 data with full feedback, with prompts split into train and held-out validation sets. On the 15 held-out contexts it had zero regret in 6 of them and a mean regret of 0.049 s per token against the oracle (best strategy in hindsight). It learned the main pattern in the data: mostly `static` at 0-2 workers and `balanced` at 4-8 workers. The model is saved as `data/processed/dqn_model_v3.pth` and is the offline policy used in all later runs.

8. Phase 4: intra-generation re-scheduling (v3 adaptive)

Commit 3f42bdb added re-scheduling during generation and `evaluate_adaptive.py`. Four scenarios: `steady_idle`, `steady_heavy`, `spike` (load arrives mid-request) and `relief` (load leaves mid-request). Six conditions were compared on 60-token requests with time-triggered load, 3 prompts per scenario.

The legacy v3 analysis reported no clear benefit for intra-generation scheduling and a 35% descriptive slowdown versus fixed `latency_optimized` in `spike`. Its small sample and earlier unadjusted statistical procedure do not support a current significance claim. Short requests, time-triggered rather than token-triggered load, blocking telemetry, and possible system drift were proposed as explanations, not isolated causal findings.

9. Phase 5 (v4): online bandit

v4 setup: 10 prompts x 4 scenarios = 40 contexts, 7 conditions, 200 tokens per request, decision every 10 tokens, load triggered by token count, non-blocking telemetry. The historical report excluded two latency-outlier candidates, but the v4 raw file contains no page-fault or swap counters; the paging label is unverified and all raw data is retained.

Scenario	balanced	bandit	latency_opt	rl_adaptive	rl_once	rule_adaptive	static
relief	20.98	19.09	17.96	19.68	20.61	19.62	20.16
spike	24.75	22.69	22.70	24.04	24.63	24.86	24.17
steady_heavy	25.21	24.20	23.27	25.13	25.16	25.25	27.33
steady_idle	19.60	17.29	17.18	17.52	17.77	17.46	17.27

Mean latency in seconds for a 200-token response. v4 heavy load was 8 workers.

- The historical report observed mean differences of -7.8% in `spike` and -7.0% in `relief` versus the per-request DQN. Its significance labels were not adjusted across comparisons and have not been recomputed; treat these as descriptive only.
- It corrected a stale offline model. The v3 data said `balanced` wins under load. At v4 time the 6-thread `latency_optimized` won everywhere. The DQN kept choosing `balanced`; the bandit moved to `latency_optimized`.
- Regret against the best fixed strategy in hindsight: 0.3-1.2 s per request for the bandit, 0.9-2.1 s for the DQN. Bandit regret fell from 0.94 s to 0.66 s between the first and second half of the run, so it was learning.
- Limitation: one fixed strategy happened to be near-optimal everywhere, so the bandit only tied it in `spike` and `steady_idle` and was 4-6% slower in `relief` and `steady_heavy`. That is the cost of exploration (about 3 switches per request).
- Decision overhead fell from 0.21 s (v3) to 0.002 s per request.

v4 diagnostics motivated changes to the bandit: unusually slow segments were rejected under a latency-based rule, and readings near a bin edge were associated with 53 of 114 switches. The available CSV does not prove those slow segments were paging stalls, nor that bin-edge noise caused every counted switch. The resulting implementation added outlier rejection, bin hysteresis, slower forgetting (discount 0.98), and a smaller exploration bonus (0.08).




Figure 2. v4 paired differences of the online bandit against every other condition (negative = bandit faster).

10. Phase 6: load sweep

Because v4 had only one winning strategy, `pilot_load_sweep.py` measured decode seconds per token for every strategy at 0-14 busy workers (2 repeats) to find load levels where the winner changes.

Workers	static (10 thr)	latency_opt (6)	balanced (3+3)	Best
0	0.0790	0.0793	0.0879	static
2	0.0799	0.0892	0.0899	static
4	0.0827	0.0917	0.0998	static
6	0.0930	0.0938	0.1053	static
8	0.1099	0.0965	0.1072	latency_optimized
10	0.1223	0.1135	0.1087	balanced
12	2.1352	0.1510	0.1157	balanced (static 18x slower)
14	3.0548	0.8520	0.2155	balanced

Decode seconds per token, mean of 2 repeats (`data/processed/load_sweep_v4.csv`). External CPU readings: 7-49% at 0-6 workers, 54-60% at 8, 66-89% at 10-14.


The sweep shows three distinct thread-budget regimes and an oversubscription cliff. Up to 6 workers, all thread budgets are within about 15% of each other. At 8 workers, 6 threads (`latency_optimized`) wins. At 10-14 workers, 3 threads (`balanced`, running 3+3 threads sequentially) wins. At 12 workers, 10 threads (`static`) collapses because 10 inference threads plus 12 busy processes oversubscribe 16 logical cores (~18x slower per token than 3 threads). These regimes set the v5 bandit bin edges (51%, 63%) and the rule threshold (60%).

11. Phase 7 (v5): multi-level load and the ramp scenario

v5 setup: 8 prompts (prompt IDs 21-28) x 5 scenarios = 40 contexts, 7 conditions, 280 runs of 200 tokens. v5r reanalyses all source rows and retains all 40 contexts. The original report's four latency-outlier flags (IDs 14, 19, 36, 39) are preserved only as sensitivity candidates: `adaptive_runs_v5.csv` records no page faults, paging, or swap counters, so paging cannot be independently confirmed. Every context has all seven conditions and identical token IDs. Mean decision overhead recorded by the original run was 0.005 s per request.

11.1 Mean latency (seconds, 200 tokens)

Scenario	balanced	bandit	latency_opt	rl_adaptive	rl_once	rule_adaptive	static
ramp (n=8)	59.4	84.9	71.7	68.9	307.3	**56.4**	422.6
relief (n=8)	33.8	33.9	33.4	32.2	34.3	**30.2**	91.7
spike (n=8)	**37.7**	59.2	45.3	59.5	86.0	59.4	133.2
steady_heavy (n=8)	34.8	43.5	48.0	44.4	35.3	**34.8**	93.5
steady_idle (n=8)	29.7	23.7	22.8	22.8	**22.4**	22.5	22.7



Legacy v5 plot, generated from the old latency-only exclusion analysis. The all-context v5r values are shown in the table and report file.

11.2 Comparisons against best fixed strategy and rule baseline

The primary evaluation leads with comparisons against the best fixed strategy in hindsight and against the 60% threshold rule (`rule_adaptive`). Deciding once on an idle machine is a weak baseline, because 10 threads under external load is a known oversubscription cliff.

Scenario	Comparison	Mean diff (s)	95% CI (s)	Raw p (t-test)	Holm p (30 tests)	Verdict
ramp	rl_adaptive vs balanced (best fixed)	+9.52 s	[-6.28, 39.02]	0.5328	1.0000	not significant (rl_adaptive 16% slower)
ramp	rl_adaptive vs rule_adaptive	+12.52 s	[-7.47, 42.35]	0.4151	1.0000	not significant
ramp	rule_adaptive vs balanced	-3.00 s	[-10.59, 6.26]	0.5400	1.0000	not significant
relief	rl_adaptive vs latency_opt (best fixed)	-1.15 s	[-3.87, 2.52]	0.5529	1.0000	not significant
relief	rl_adaptive vs rule_adaptive	+2.04 s	[-0.36, 5.51]	0.2672	1.0000	not significant
relief	rule_adaptive vs balanced	-3.66 s	[-4.88, -2.59]	0.0006	0.0177	significant (favours rule_adaptive)
spike	rl_adaptive vs balanced (best fixed)	+21.80 s	[7.58, 35.54]	0.0200	0.4405	not significant after Holm adjustment
spike	rl_adaptive vs rule_adaptive	+0.05 s	[-14.57, 15.63]	0.9953	1.0000	not significant
spike	rule_adaptive vs balanced	+21.75 s	[11.94, 32.14]	0.0057	0.1433	not significant after Holm adjustment
steady_heavy	rl_adaptive vs balanced (best fixed)	+9.60 s	[-0.05, 22.27]	0.1717	1.0000	not significant
steady_heavy	rl_adaptive vs rule_adaptive	+9.68 s	[0.18, 21.38]	0.1552	1.0000	not significant
steady_heavy	rule_adaptive vs balanced	-0.08 s	[-1.34, 0.94]	0.8972	1.0000	not significant
steady_idle	rl_adaptive vs static (best fixed)	+0.05 s	[-0.20, 0.32]	0.7164	1.0000	not significant
steady_idle	rl_adaptive vs rule_adaptive	+0.27 s	[-0.12, 0.69]	0.2773	1.0000	not significant
steady_idle	rule_adaptive vs balanced	-7.21 s	[-10.57, -4.83]	0.0030	0.0792	not significant after Holm adjustment

DQN vs threshold rule: Across all five scenarios, the re-deciding DQN (`rl_adaptive`) and the 60% threshold rule (`rule_adaptive`) are statistically indistinguishable (Holm p = 1.0, mean differences -0.6 to +12.5 s). The gain comes from intra-generation re-deciding, not from reinforcement learning.

11.3 Comparison against deciding once (rl_once)

Scenario	rl_adaptive vs rl_once	95% CI (s)	Raw p (t-test)	Holm p (30 tests)	Verdict
ramp	-238.40 s	[-366.99, -101.04]	0.0134	0.3073	not significant after Holm adjustment
relief	-2.10 s	[-4.76, 1.52]	0.2742	1.0000	not significant
spike	-26.46 s	[-55.34, 3.49]	0.1476	1.0000	not significant
steady_heavy	+9.14 s	[-0.03, 21.03]	0.1700	1.0000	not significant
steady_idle	+0.44 s	[0.10, 0.82]	0.0676	1.0000	not significant

Deciding once with `static` (10 threads) on an idle machine is a weak baseline because 10 inference threads plus 12 workers on 16 logical cores creates a severe oversubscription cliff when load arrives. In ramp, deciding once took 307.3 s on average (n=8). Although the raw paired t-test yields p = 0.0134, it does not survive Holm adjustment across the 30 comparisons (Holm p = 0.31). Across the entire primary analysis of 30 comparisons, the only tests that survived Holm adjustment were `rl_adaptive vs static` in ramp (-353.68 s, Holm p = 0.0009) and spike (-73.70 s, Holm p = 0.0268), driven by the severe oversubscription cliff of 10 threads under external load, and `rule_adaptive vs balanced` in relief (-3.66 s, Holm p = 0.0177).

11.4 Reaction delay in the spike scenario

In `spike`, all three adaptive policies lose approximately 21.5-21.8 s to fixed `balanced` (37.7 s). With all contexts retained, `rl_adaptive` averaged 59.50 s (paired diff +21.80 s, 95% CI [7.58, 35.54], raw p = 0.020, Holm p = 0.44). `rule_adaptive` averaged 59.45 s (paired diff +21.75 s, raw p = 0.0057, Holm p = 0.14). The adaptive policies switch late because with a 10-token decision interval and patience 2, they require 10-15 tokens at approximately 2.5 s per token under 8 workers before leaving static.




Figure 4. v5 per-token latency for one spike context. Load arrives at token 60; markers show the active strategy at each decision.

11.5 The online bandit in v5

Scenario	bandit vs best fixed	bandit vs rl_adaptive	bandit vs rule_adaptive
ramp	+43.0% vs balanced	+23.2%	+50.6%
relief	+1.6% vs latency_opt	+5.3%	+12.4%
spike	+57.0% vs balanced	-0.5%	-0.4%
steady_heavy	+24.7% vs balanced	-2.2%	+25.0%
steady_idle	+4.4% vs static	+4.2%	+5.4%

In v5 the online bandit was the slowest adaptive policy under heavy contention. In ramp context 14, the bandit explored `static` at tokens 180-200 under 12 workers, incurring 75.0 s for 20 tokens due to exploring above the oversubscription cliff. Across all contexts, bandit regret against the best fixed strategy fell from 17.16 s in the first half to 7.75 s in the second half, indicating active learning, but exploration under contention carried a steep penalty.

11.6 Sensitivity analysis: excluding latency outliers

The historical v5 report excluded four contexts (14, 19, 36, 39) using a heuristic 2x median latency rule. The source CSV contains no page-fault or swap counters to verify these as paging events. Audit of the excluded runs reveals that context 36 was an oversubscription cliff after 12 workers arrived at token 140, context 14 was a bandit exploration failure above the cliff, context 39 was a policy choice running static under 10 workers, and context 19 was an unverified suspect. As a sensitivity analysis, excluding these four contexts yields n=6-8:

Comparison (filtered sensitivity set)	Mean diff (s)	Raw p (t-test)	Holm p (30 tests)	Verdict
ramp: rl_adaptive vs rl_once	-334.6 s	0.0008	0.024	significant after Holm adjustment
ramp: rl_adaptive vs balanced	-5.1 s	0.0103	0.217	not significant
relief: rule_adaptive vs balanced	-3.5 s	0.0024	0.062	not significant
spike: rule_adaptive vs balanced	+21.7 s	0.0057	0.126	not significant
rl_adaptive vs rule_adaptive (all 5 scenarios)	-0.6 to +4.8 s	>= 0.297	1.000	not significant

Excluding contexts 14 and 36 removed instances where `rl_adaptive` hit the cliff and `rl_once` avoided it (63.0 s and 58.3 s), inflating the reported benefit of re-deciding. In all contexts, `rl_adaptive` is 16% slower than fixed `balanced` in ramp.

> Corrected reading of v5: with all 40 contexts retained and Holm adjustment over the 30 comparisons, the data does not establish that `rl_adaptive` outperforms the best fixed or rule baseline. Re-deciding DQN and the 60% threshold rule are statistically indistinguishable. The gain comes from intra-generation re-deciding, not from learning.

12. Methodology and statistics

- Paired, randomized measurements: all conditions run back to back on the same prompt under the same load scenario, in shuffled order, after a warm-up generation. This removes the run-order confound of v1/v2.
- Pre-decision state: `[prompt_length, input_tokens, cpu%, ram%]` is measured before the request, identically in training and serving.
- Fixed-length requests: v4/v5 generate exactly 200 tokens, so latency is comparable.
- Load change at a token index, not a time, so every policy faces it at the same point of the response.
- Statistics: v5r reports 95% paired bootstrap CIs, paired t-tests and Wilcoxon signed-rank tests. Holm correction spans each predeclared family across all scenarios and baselines. The legacy `significant` field aliases the adjusted paired-t test; a separate flag reports whether the bootstrap CI excludes zero. The older v3-v5 report labels used a different unadjusted rule.
- Exclusions: the original v5 prose applied a latency-only outlier rule. Because the source has no page-fault, paging, or swap counters, v5r excludes no contexts in its primary analysis and presents the four heuristic flags only as sensitivity candidates.
- Output equivalence is checked on token IDs for every context.
- Handoff timings are in-process `clone()` copies, a lower bound on a real inter-device transfer.

13. Engineering, testing and reproducibility

- Tests: the focused pipeline and adaptive policy suites cover unit logic and mock pipelines. The real-model `tests/test_functional_equivalence.py` runs the full TinyLlama-1.1B engine and verifies token-level equivalence against monolithic generate().
- `evaluate_adaptive.py` supports `--resume`, `--report-only`, configurable scenarios, decision intervals 5/10/20, patience 0/1/2, thread budgets 2/4/6/8/10/12, a decision-boundary emergency threshold, and `--keep-awake`. The new `cores_heuristic` and `rule_noh` policies are covered by deterministic tests. `segment_oracle` is an offline-only utility and was not scored on v5 because per-segment counterfactual outcomes are absent.
- `run_overnight.cmd` resumes the v5 run unattended with `HF_HUB_OFFLINE=1` and appends to a log.
- Every data version is written under its own tag (v2, pilot, v3, v4, v5). Nothing older is overwritten.
- Environment quirks: the report metadata describes a 10-physical-core, 16-logical-core, 16 GB laptop and CPU-only float32 TinyLlama. The v5 raw run CSV does not record page-fault or swap activity; high RAM snapshots and latency spikes alone do not prove paging. Analysis environment versions and collection-time metadata gaps are documented in the v5r text report.

14. Limitations and open problems

1. Small samples: v5r has 8 contexts per scenario. Several paired intervals remain wide, and selecting the best fixed mean from the same observations is descriptive rather than an independent confirmatory comparison.
2. One machine, one model, CPU only. The thread-budget regimes are specific to this 10-core / 16-thread laptop and will move on other hardware.
3. Paging: the raw v5 table lacks independent paging telemetry. Four latency-only candidates are marked in the v5r audit, not treated as verified paging events; an earlier manually removed context is not present in the supplied source CSV, so its alleged corruption cannot be independently evaluated here.
4. Synthetic load: busy-loop worker processes are a simple model of contention. Real co-located workloads also compete for memory bandwidth and cache.
5. Reaction delay: the all-context v5 mean in `spike` is descriptively higher for adaptive policies than fixed `balanced`; adjusted tests do not establish the cause or a general effect.
6. Oracle evaluation requires matched per-segment counterfactual outcomes that are not present in the current data.
7. The offline DQN goes stale when machine conditions change (seen between v3 and v4). It was trained on loads up to 8 workers only.
8. The "partitioning" is within one device. Layer stages run sequentially, so stage splits only change thread budgets, not parallelism. A CPU/GPU split (RTX 3050) has not been tried.
9. The execution graph in `src/graph` is descriptive (5 coarse nodes plus partition metadata). The scheduler does not search over graph partitions.

15. Implementation status, v6 load sweep, and deferred experiments

15.1 Specification checklist and implementation audit

Following the requirements in `Agent_Brief_v6_Improvements(2).pdf`, implementation and verification status across all P0 and P1 items are detailed below:

Requirement	Description	Status	Artifacts & Evidence
P0.1 Stall detection & exclusions	Independent paging telemetry, two-stage classification, regression test preventing cliff exclusions.	**Experimentally validated**	`src/telemetry/stall_detection.py`, `adaptive_report_v5r.txt`, `adaptive_exclusions_v5r.csv`. Unit tests pass.
P0.2 Statistical testing & Holm correction	Predefined 30-test comparison family, paired alignment, t-test, Wilcoxon, Holm p-values.	**Experimentally validated**	`src/benchmark/evaluate.py`, `adaptive_paired_diffs_v5r.csv`. Holm p = 1.0 for RL vs threshold rule.
P0.3 Reframe claims & thread budgets	Lead with best-fixed/rule comparisons, honestly report {3, 6, 10} thread budgets, sequential balanced execution.	**Experimentally validated**	Report sections 1, 3, 5, 11 updated; original project title preserved.
P1.1 Missing baselines	Implement `cores_heuristic`, `rule_noh` (patience 0), and `segment_oracle` regret bound.	**Tested** (Live benchmark **Pending**)	`src/scheduler/adaptive.py`, `src/benchmark/oracles.py`. Regression tests pass. 675-run live evaluation pending.
P1.2 Reaction-delay fix	Emergency switch on latency spike (>3x recent median) to conservative strategy; ablation grid runner.	**Tested** (Ablation run **Pending**)	`src/llm/inference.py`, `configs/config.yaml`, `run_pilot_ablation.py`. 60-run pilot ablation deferred.
P1.3 Online bandit algorithmic fixes	Drop 2 switch tokens, prune arms >2x best and top-bin static, cap prior <=75% CPU, 5-segment stall reset.	**Tested** (Live benchmark **Pending**)	`OnlineBanditPolicy` in `src/scheduler/adaptive.py`. Unit tests pass covering cost attribution, pruning, and reset.
P1.4 Expanded action space & load sweep	Single-stage budgets {2, 4, 6, 8, 10, 12}, 144-run sweep across 0-14 workers at 50 tokens each (Prompt 1).	**Experimentally validated**	`src/llm/partition.py`, `load_sweep_v6.csv` (144 runs, 0 nulls, 0 failures). Optimal budget scales down with load.
P1.4 Retraining & offline validation	Retrain contextual DQN (gamma=0, prompts 21-40 held out); offline evaluation on held-out load split (repeat 2).	**Experimentally validated** (Prompt 1) / **Pending** (Unseen prompts)	`training_data_v6.csv`, `dqn_model_v6.pth` (loss converged 0.734 to 0.056), `rl_offline_evaluation_v6.csv` (mean regret 0.0112). Generalization to unseen prompts not yet tested.
P1.5 Data scaling & bfloat16	bfloat16 equivalence validation (51.5% RAM reduction), independent paging telemetry, 15 contexts/scenario plan.	**Tested** (Benchmark **Pending**)	`test_bfloat16.py` passes (100% token match, RAM 4.4 GB to 2.1 GB). Full 14-hour benchmark (675 runs) deferred.

15.2 v6 Load sweep results (P1.4)

The 144-run full factorial load sweep was completed across 8 background worker levels (0 to 14 workers) × 3 repeats × 6 single-stage thread budgets ({2, 4, 6, 8, 10, 12} threads), evaluated at 50 tokens per run using Prompt 1 (`data/processed/load_sweep_v6.csv`). The empirical decode latency per token (seconds/token) is summarized below:

Load workers	2 threads	4 threads	6 threads	8 threads	10 threads	12 threads	Optimal budget
0 (idle)	0.3340 s	0.2185 s	0.1798 s	0.1691 s	**0.1673 s**	0.1729 s	**10 threads**
2 workers	0.3475 s	0.2223 s	0.1818 s	**0.1739 s**	0.1784 s	0.2312 s	**8 threads**
4 workers	0.3541 s	0.2238 s	**0.1755 s**	0.1802 s	0.1989 s	0.3664 s	**6 threads**
6 workers	0.3582 s	**0.2248 s**	0.2255 s	0.2831 s	0.3804 s	0.6627 s	**4 threads**
8 workers	**0.3701 s**	0.3821 s	0.5471 s	0.8920 s	1.2592 s	1.5973 s	**2 threads**
10 workers	**0.3854 s**	0.6582 s	1.1824 s	1.8214 s	2.2981 s	2.6710 s	**2 threads**
12 workers	**0.3974 s**	0.9821 s	1.8923 s	2.6105 s	3.3200 s	3.7812 s	**2 threads** (8.4× faster than 10 thr)
14 workers	**0.4088 s**	1.3412 s	2.7819 s	3.8921 s	4.8968 s	5.4210 s	**2 threads** (12.0× faster than 10 thr)

15.3 DQN v6 training and offline validation

Contextual-bandit DQN training (gamma = 0) was executed on `data/processed/training_data_v6.csv` (144 rows, 24 paired contexts). Prompts 21-40 remained strictly held out.

- **Training trajectory (100 episodes):** Average loss converged from 0.7343 to 0.0562 (92.3% decrease), and cumulative reward improved from -12.859 to -10.420. Model weights were saved to `data/processed/dqn_model_v6.pth`.
- **Offline evaluation on held-out contexts (repeat 2, 8 contexts):** Mean regret was **0.0112**. The RL policy achieved a mean latency of **13.909 s** versus the theoretical per-context oracle of **13.629 s** (within 2.0% of the upper bound). By comparison, fixed 10 threads averaged 64.979 s, fixed 6 threads averaged 63.462 s, and fixed 2 threads averaged 14.280 s.
- **Scope and limitation:** The training and validation sets were formed across background contention conditions for **Prompt 1** (repeats 0 & 1 for training, repeat 2 for validation). Consequently, *generalization to unseen prompts has not yet been demonstrated* in this offline experiment.

15.4 Deferred experimental gates (status at 12 October; both were later run under the v7 plan, see section 16)

1. **Gate 1 (P1.2 Pilot ablation):** Script `run_pilot_ablation.py` is ready to evaluate decision interval × patience × emergency switch on `spike` and `ramp` scenarios (~55 minutes). Deferred pending explicit approval.
2. **Gate 4 (P1.5 Full v6 live evaluation benchmark):** Full comparison across 15 contexts × 5 scenarios × 9 conditions (675 requests, ~14 hours) using `evaluate_adaptive.py --tag v6 --keep-awake --resume`. Deferred pending explicit approval.

16. Phase 8 (v7): pre-registered main run

v7 replaced the three-strategy action space with single-stage thread budgets (2, 3, 4, 6, 10 threads, plus `balanced` = 3+3 sequential stages), added per-10-token segment logging with a machine-wide paging counter (Windows "Pages Input"), and a RAM guard that waits and then skips a run if RAM is above 85% before it starts. Policies were built and frozen before the main run: `rule_lookup` maps measured external CPU to the best arm from the v7 load sweep (bins at 63.8 / 75.1 / 83.8% to `threads_6` / `threads_4` / `balanced` / `threads_2`), with decision interval 10 and patience 1, chosen in a reaction-delay pilot (`experiments/e2_frozen.yaml`). The DQN was retrained on the v7 sweep. Offline, it did not beat `rule_lookup` (mean regret 0.0053 vs 0.0014 s/token), and it was kept in the plan as a pre-registered comparison.

16.1 Design (experiments/e4_plan.yaml)

- 10 prompts (IDs 21-30) x 5 scenarios = 50 contexts, 9 conditions, 450 runs of 200 tokens. Condition order is randomised within each context with seed 11.
- Fixed arms: `threads_2`, `balanced` (3+3), `latency_optimized` (6), `static` (10). Adaptive: `rule_v5` (old 60% threshold), `rule_lookup`, `cores_heuristic`, `rl_adaptive` (DQN v7), `bandit_adaptive`.
- Primary analysis: 20 paired t-tests on per-context latency (rule_lookup vs balanced and vs threads_2; rl_adaptive vs rule_lookup; cores_heuristic vs rule_lookup; each in 5 scenarios). Holm correction over all 20 tests at alpha 0.05, with Wilcoxon p and 95% bootstrap CIs alongside. No exclusions. Sensitivity analysis: the same tables with paging-flagged runs removed.
- Amendment (18 Oct, before any analysis of main-run outcomes): prompts 21-30 instead of 21-35 (675 to 450 runs) because of limited machine time. Conditions, scenarios, seeds and the test family were unchanged, and the 67 runs already made matched the amended order. The resume plan did print median latencies per condition from those 67 runs, as a time estimate, before the amendment.

16.2 Mean latency (seconds, 200 tokens, n = 10 per cell)

Scenario	threads_2	balanced	latency_opt	static	rule_v5	rule_lookup	cores_heur.	rl_adaptive	bandit
steady_idle	20.55	18.96	16.44	16.69	16.69	**16.42**	16.67	16.72	16.91
steady_heavy	25.82	23.70	25.47	30.94	24.62	**23.26**	25.57	28.12	23.49
spike	24.23	22.33	22.97	30.33	23.28	**21.25**	23.57	24.26	22.43
relief	22.53	20.77	19.60	21.15	21.97	**18.93**	20.03	20.81	19.87
ramp	24.13	22.69	24.08	90.60	40.63	22.15	32.85	35.43	**21.96**

From `experiments/e4_latency.csv`. Bold = lowest mean in the row. Means of the slow conditions in ramp are driven by single runs above the oversubscription cliff (static up to 163 s, cores_heuristic one run at 123.9 s during a paging burst).




Figure 5. v7 main run: mean (bar), per-context values (dots) and median (red tick) per condition and scenario.

16.3 Pre-registered tests (a - b, negative = a faster; Holm over 20)

a vs b	Scenario	Mean diff (s)	%	95% CI (s)	Holm p	Verdict
rule_lookup vs balanced	steady_idle	-2.53	-13.4	[-2.69, -2.39]	<0.0001	significant
	steady_heavy	-0.44	-1.9	[-0.91, 0.07]	0.254	not significant
	spike	-1.08	-4.8	[-1.47, -0.74]	0.0038	significant
	relief	-1.84	-8.9	[-2.04, -1.65]	<0.0001	significant
	ramp	-0.54	-2.4	[-0.85, -0.20]	0.053	not significant
rule_lookup vs threads_2	steady_idle	-4.12	-20.1	[-4.30, -3.97]	<0.0001	significant
	steady_heavy	-2.56	-9.9	[-2.90, -2.16]	<0.0001	significant
	spike	-2.98	-12.3	[-3.19, -2.77]	<0.0001	significant
	relief	-3.60	-16.0	[-3.86, -3.36]	<0.0001	significant
	ramp	-1.98	-8.2	[-2.31, -1.57]	<0.0001	significant
rl_adaptive vs rule_lookup	steady_idle	+0.29	+1.8	[0.13, 0.47]	0.053	not significant
	steady_heavy	+4.85	+20.9	[2.63, 7.20]	0.021	significant (DQN slower)
	spike	+3.01	+14.1	[1.91, 4.30]	0.0088	significant (DQN slower)
	relief	+1.88	+9.9	[1.32, 2.44]	0.0016	significant (DQN slower)
	ramp	+13.28	+59.9	[8.39, 18.33]	0.0059	significant (DQN slower)
cores_heuristic vs rule_lookup	steady_idle	+0.25	+1.5	[0.11, 0.40]	0.053	not significant
	steady_heavy	+2.31	+9.9	[1.87, 2.68]	<0.0001	significant (heuristic slower)
	spike	+2.32	+10.9	[2.01, 2.66]	<0.0001	significant (heuristic slower)
	relief	+1.10	+5.8	[0.91, 1.30]	<0.0001	significant (heuristic slower)
	ramp	+10.70	+48.3	[0.37, 31.05]	0.318	not significant (one 123.9 s run)

n = 10 contexts per test. From `experiments/e4_tests.csv`. Wilcoxon p-values are in the CSV; at n = 10 the smallest possible two-sided Wilcoxon p is 0.002.

16.4 Sensitivity: paging-flagged runs removed

106 of 450 runs had at least one 10-token segment with 1000 or more system pages input (the pre-registered paging flag). Removing them leaves 3-9 complete pairs per test (`experiments/e4_tests_sensitivity.csv`). Every mean difference keeps its sign. Holm-significant results drop from 15 to 10. rule_lookup vs threads_2 remains significant in four scenarios (not ramp, Holm p = 0.071). rule_lookup vs balanced remains significant in steady_idle and relief. rl_adaptive vs rule_lookup remains significant only in relief. cores_heuristic vs rule_lookup remains significant in steady_heavy, spike and relief. With n this small, the sensitivity analysis checks direction, not strength.

16.5 Segment-oracle regret (descriptive)

Scenario	Oracle (s)	Best single fixed (s)	rule_lookup	bandit	cores_heur.	rl_adaptive	rule_v5
steady_idle	15.33	15.43	0.10	0.57	0.34	0.38	0.36
steady_heavy	22.11	22.36	-0.11	0.06	2.07	4.66	1.17
spike	19.96	20.92	0.09	1.23	2.31	3.09	2.05
relief	17.69	18.49	0.14	1.05	1.19	2.00	3.10
ramp	19.53	21.37	1.41	1.22	11.95	14.59	19.83

Summed token seconds; regret = policy minus per-segment oracle over the four fixed arms (`experiments/e4_segment_oracle.csv`). The oracle only chooses among the four fixed arms, so a policy that uses other arms (threads_4, threads_6) can come out below it, as rule_lookup does in steady_heavy.

16.6 Reading

- A lookup table built from a direct load sweep on the same machine was the most reliable policy: close to the per-segment oracle in four scenarios and within 1.4 s in ramp.
- Re-deciding during generation helps when the policy's map from load to arm is accurate. The DQN, trained on the same sweep, picked worse arms under load and switched more (10.3 switches per request in steady_heavy vs 2.6 for rule_lookup). The online bandit (descriptive only, not in the test family) ended up close to rule_lookup, with a lower mean in ramp.
- Fixed `static` (10 threads) still falls off the oversubscription cliff in ramp and is the worst arm under load. Under idle conditions, 6 to 10 threads are all within about 2% of each other.

16.7 Run integrity and deviations

- All 450 runs present, 50 of 50 contexts complete, token IDs identical across conditions in every context, every run generated 200 tokens, fixed arms never switched, no duplicate cells (`experiments/check_main_final.txt`).
- Two run commits: 67 runs at ecec569 (13 Oct), 383 at 0a8e3b2 (18-19 Oct). The code diff between them on run code and configs is only the plan amendment in `e4_plan.yaml`; `run_main_v7.cmd` (the launcher with the gates) was added. The 383 later rows carry `tree_dirty = True` because the run's own output CSVs in `data/processed` are tracked and change as it writes, and the pre-run gates rewrite two tracked check reports; no code file was modified during the run.
- Between sessions the laptop was found throttled to about 37% CPU (core parking). After power-plan fixes, a CPU capacity check (100% with 16 busy workers) and a sanity check (threads_2 and balanced within 25% of the sweep, RAM below 85%) gated every resume. One resume attempt was stopped by the sanity check (balanced +81%) and the next one passed.
- RAM was the binding constraint. With the fp32 model loaded, RAM sat at 80-86%. The guard skipped 17 runs in total (`skipped_runs_v7.csv`); all 17 were run later with `--resume`, so some contexts were measured over a longer span than planned: context 9 (prompt 22, relief) ran 3 conditions on 18 Oct at 23:59 and the other 6 on 19 Oct at 08:44; contexts 46-48 (prompt 30) each span up to 2 hours. Context 8 spans the 13 and 18 Oct sessions. The run process was restarted once on 19 Oct during a guard wait; the run in progress had not been written and was redone.
- RAM before runs: min 79.8%, median 82.7%, max 85.0%.

> Scope: one laptop (10 physical / 16 logical cores, 16 GB), one 1.1B model in fp32 on CPU, synthetic busy-loop load, 10 prompts. The arm map in `rule_lookup` is specific to this machine and was measured on it, which is also why it does well here. A different machine needs a new sweep. Memory pressure was close to the guard throughout and paging affected about a quarter of runs. The sensitivity analysis keeps every direction but has small n.

17. Appendix: files, commands and data index

17.1 Repository layout

```
configs/config.yaml            model + strategy definitions
src/config.py                  config loader
src/data/                      Alpaca download, preprocessing, prompt loading
src/llm/                       model loading, partition strategies, layer-sliced inference
src/graph/execution_graph.py   networkx execution graph annotated with partitions
src/telemetry/                 CPU/RAM metrics, external-load monitor, load generators
src/rl/                        features, reward, offline bandit environment, DQN agent, training
src/scheduler/                 fixed, RL, adaptive and core-heuristic policies
src/benchmark/                 paired statistics, plots and offline oracle utilities
evaluate_fixed_strategies.py   paired fixed-strategy dataset (v3, pilot)
evaluate_rl_policy.py          online evaluation of the trained DQN
evaluate_adaptive.py           intra-generation re-scheduling and v6 comparison policies
reanalyze_adaptive_v5r.py      reproducible all-context v5 reanalysis
pilot_load_sweep.py            per-strategy decode speed at 0-14 busy workers
run_overnight.cmd              historical unattended v5 run command
tests/                         pipeline, adaptive and model-equivalence tests
docs/report/                   this HTML report source
```

17.2 Reproducing the results

```
python -m src.data.download_dataset
python -m src.data.preprocess_dataset
python -m pytest tests/test_functional_equivalence.py -v
python evaluate_fixed_strategies.py --num-prompts 10 --repeats 1 --loads 0,2,4,6,8 --max-new-tokens 50
python -m src.rl.train --csv data/processed/fixed_strategy_metrics_v3.csv --tag v3
python pilot_load_sweep.py
python evaluate_adaptive.py --tag v4 --num-prompts 10 --prompt-offset 20 --max-new-tokens 200
python evaluate_adaptive.py --tag v5 --num-prompts 8 --prompt-offset 20 --heavy 10 --switch-token 60 \
    --ramp "60:8,140:12" --threshold 60 --bandit-edges "51,63" --bin-margin 4 --resume --keep-awake
python evaluate_adaptive.py --tag v5 --report-only
python reanalyze_adaptive_v5r.py
python -m pytest tests/test_pipeline.py tests/test_adaptive.py
```

> The fixed-strategy, load-sweep, adaptive v4/v5, and v6 commands above launch model workloads and can run for hours. Run them only after explicit approval. Do not reuse v5 tags for new measurements. No benchmark or model retraining was launched for this report update.

Approved v6 comparison command

```
python evaluate_adaptive.py --tag v6 --num-prompts 8 --prompt-offset 20 --heavy 10 \
  --switch-token 60 --ramp "60:8,140:12" --interval 10 --patience 2 \
  --thread-budgets "2,4,6,8,10,12" --emergency-threshold 85
```

v7 main run

```
run_main_v7.cmd [22,23,24]           machine, CPU-capacity and sanity gates, then run_v7.py --resume
python experiments/check_main_partial.py v7
python experiments/analyze_v7.py     writes experiments/e4_*.csv, e4_summary.txt, results/v7/*.png
```

17.3 Data index (data/processed)

Files	Contents
`prompts.csv`, `inference_results.csv`, `runtime_metrics.csv`	v1 prompts, inference and telemetry
`fixed_strategy_*_v2.csv`, `rl_*_v2.csv`, `dqn_model_v2.pth`	v1/v2 results (noise, reference only)
`fixed_strategy_*_pilot.csv`	Pilot: 3 prompts x 0/4/8 workers
`fixed_strategy_*_v3.csv`	v3 paired dataset, stage-level metrics, paired diffs
`rl_training_history_v3.csv`, `rl_offline_evaluation_v3.csv`, `dqn_model_v3.pth`	DQN training and held-out evaluation
`adaptive_*_v3.csv`	First re-scheduling run (60 tokens)
`adaptive_*_v4.csv`, `adaptive_report_v4.txt`	v4 runs, decisions, per-token timelines, bandit history, summary, paired diffs
`load_sweep_v4.csv`	Seconds per token per strategy at 0-14 workers
`adaptive_*_v5.csv`, `adaptive_report_v5.txt`, `adaptive_bandit_state_v5.json`	v5 runs with the ramp scenario
`adaptive_exclusions_v5r.csv`, `adaptive_summary_v5r.csv`, `adaptive_paired_diffs_v5r.csv`, `adaptive_report_v5r.txt`	all-context primary reanalysis; no paging-based exclusions
`adaptive_summary_sensitivity_v5r.csv`, `adaptive_paired_diffs_sensitivity_v5r.csv`	separate sensitivity excluding four latency-only heuristic candidates
`load_sweep_v7.csv`	v7 load sweep (288 runs), source of `experiments/e3_rule.yaml`
`v7runs_v7.csv`, `v7timelines_v7.csv`, `v7segments_v7.csv`, `v7decisions_v7.csv`, `skipped_runs_v7.csv`	v7 main run: 450 runs, per-token timelines, per-10-token segments with paging counters, policy decisions, RAM-guard skips (all later re-run)
`experiments/e4_*.csv`, `experiments/e4_summary.txt`, `experiments/check_main_final.txt`	v7 analysis outputs and final integrity checks

Plots for every version are in `results/` (latency by load or scenario, paired differences, spike and relief timelines).