

So, for a large dataset size, or large size of parameters it is wise to use Randomized CV.

Logistic Regression For Multiple Class Classification:

In multiclass classification there can be more than 2 values in the target feature.

| f_1 | f_2 | f_3 | O/P |
|-------|-------|-------|-----|
| — | — | — | 0 |
| — | — | — | 1 |
| — | — | — | 0 |
| — | — | — | 0 |
| — | — | — | 2 |
| — | — | — | 1 |


Like this

We use two types of techniques to solve Multiclass Classification:

① One versus Rest (OVR)

② Multinomial

One Vs Rest Technique:



These category will convert the multiclass classification to Binary classification means as here there are 3 classes, this technique will create 3 models. In the first Model (M_1), class A will be 1 category, and class B and C combinedly will make another category then model training and prediction will be so done. Like this in Second Model (M_2), class B C will be 1 category and class A, B will combinedly be a category. Similarly Model 3 (M_3) will do the similar task.

| | | |
|--------------------------|--------------------------|--------------------------|
| M_1 | M_2 | M_3 |
| ↓ | ↓ | ↓ |
| Binary Classification | Binary Classification | Binary Classification |

Then will choose the model which will provide best prediction accuracy.

Then we will do one hot encoding (n new features for n independent features)

| f_1 | f_2 | f_3 | O/p | O_1 | O_2 | O_3 |
|-------|-------|-------|-----|-------|-------|-------|
| - | - | - | 0 | 0 | 1 | 0 |
| - | - | - | 1 | 0 | 0 | 1 |
| - | - | - | 2 | 1 | 0 | 1 |
| - | - | - | 2 | 1 | 1 | 0 |
| - | - | - | 1 | 0 | 0 | 1 |
| - | - | - | 0 | 1 | 0 | 0 |

For, M_1 Model \rightarrow $\frac{\text{Input}}{f_1, f_2, f_3}$ $\frac{\text{O/p}}{O_1}$

M_2 Model \rightarrow $\frac{\text{Input}}{f_1, f_2, f_3}$ $\frac{\text{O/p}}{O_2}$

M_3 Model \rightarrow $\frac{\text{Input}}{f_1, f_2, f_3}$ $\frac{\text{O/p}}{O_3}$

For, new Datapoints M_1, M_2 and M_3 will output some probabilities

$M_1 \quad M_2 \quad M_3$
 $[0.20 \quad 0.35 \quad 0.45]$ \rightarrow These are called Multinomial probability

Which probability will be max, that model's output will be counted

like here O_3 values will considered as prediction.

While defining model for multiclass classification, we have to

use \rightarrow LogisticRegression (multi-class = "multinomial", solver = 'lbfgs')

or, LogisticRegression (multi-class = 'multinomial', solver = 'lbfgs')

| | | | | | |
|---|---|---|---|---|---|
| 0 | 1 | 0 | 0 | - | - |
| 1 | 0 | 0 | 1 | - | - |
| 1 | 0 | 1 | 0 | - | - |
| 0 | 1 | 1 | 0 | - | - |
| 1 | 0 | 0 | 1 | - | - |
| 0 | 0 | 1 | 0 | - | - |

$$\frac{110}{10}$$

$$\frac{100}{10}$$

for 10 models

$$\frac{110}{10}$$

$$\frac{100}{10}$$

for 10 models

$$\frac{110}{10}$$

$$\frac{100}{10}$$

for 10 models

validation score for the 10 models is 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1

validation score

[0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1]

validation score for the 10 models is 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1

validation score for the 10 models is 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1