

# Lecture 4:

# Neural Networks and Backpropagation

# Administrative: Assignment 1

**Assignment 1** due **Wednesday April 17**, 11:59pm

If using Google Cloud, **you don't need GPUs** for this assignment!

We will distribute Google Cloud coupons by this weekend

# Administrative: Alternate Midterm Time

If you need to request an alternate midterm time:

See Piazza for form, fill it out by 4/25 (two weeks from today)

# Administrative: Project Proposal

Project proposal due 4/24

# Administrative: Discussion Section

Discussion section tomorrow (1:20pm in Gates B03):

How to pick a project / How to read a paper

# Where we are...



$$s = f(x; W) = Wx \quad \text{Linear score function}$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \quad \text{SVM loss (or softmax)}$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda \sum_k W_k^2 \quad \text{data loss + regularization}$$

How to find the best  $W$ ?

# Finding the best $W$ : Optimize with Gradient Descent



```
# Vanilla Gradient Descent
```

```
while True:
```

```
    weights_grad = evaluate_gradient(loss_fun, data, weights)
```

```
    weights += - step_size * weights_grad # perform parameter update
```

[Landscape image](#) is [CC0 1.0](#) public domain

[Walking man image](#) is [CC0 1.0](#) public domain

# Gradient descent

$$\frac{df(x)}{dx} = \lim_{h \rightarrow 0} \frac{f(x+h) - f(x)}{h}$$

**Numerical gradient:** slow :(), approximate :(), easy to write :)

**Analytic gradient:** fast :), exact :), error-prone :(

In practice: Derive analytic gradient, check your implementation with numerical gradient




# Problem: Linear Classifiers are not very powerful

## Visual Viewpoint




Linear classifiers learn  
one template per class

## Geometric Viewpoint




Linear classifiers  
can only draw linear  
decision boundaries



# One Solution: Feature Transformation





Color Histogram



Histogram of Oriented Gradients (HoG)



# Image features vs ConvNets



# Today: Neural Networks

# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

$$x \in \mathbb{R}^D, W \in \mathbb{R}^{C \times D}$$

# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

(**Now**) 2-layer Neural Network  $f = W_2 \max(0, W_1 x)$

$$x \in \mathbb{R}^D, W_1 \in \mathbb{R}^{H \times D}, W_2 \in \mathbb{R}^{C \times H}$$

(In practice we will usually add a learnable bias at each layer as well)

# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

(**Now**) 2-layer Neural Network  $f = W_2 \max(0, W_1 x)$

$$x \in \mathbb{R}^D, W_1 \in \mathbb{R}^{H \times D}, W_2 \in \mathbb{R}^{C \times H}$$

“Neural Network” is a very broad term; these are more accurately called “fully-connected networks” or sometimes “multi-layer perceptrons” (MLP)

(In practice we will usually add a learnable bias at each layer as well)

# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

(**Now**) 2-layer Neural Network  $f = W_2 \max(0, W_1 x)$   
or 3-layer Neural Network

$$f = W_3 \max(0, W_2 \max(0, W_1 x))$$

$$x \in \mathbb{R}^D, W_1 \in \mathbb{R}^{H_1 \times D}, W_2 \in \mathbb{R}^{H_2 \times H_1}, W_3 \in \mathbb{R}^{C \times H_2}$$


(In practice we will usually add a learnable bias at each layer as well)



# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

(**Now**) 2-layer Neural Network  $f = W_2 \max(0, W_1 x)$





$$x \in \mathbb{R}^D, W_1 \in \mathbb{R}^{H \times D}, W_2 \in \mathbb{R}^{C \times H}$$

# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

(**Now**) 2-layer Neural Network  $f = W_2 \max(0, W_1 x)$



# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

(**Now**) 2-layer Neural Network  $f = W_2 \max(0, W_1 x)$

The function  $\max(0, z)$  is called the **activation function**.

**Q:** What if we try to build a neural network without one?

$$f = W_2 W_1 x$$

# Neural networks: without the brain stuff

(**Before**) Linear score function:  $f = Wx$

(**Now**) 2-layer Neural Network  $f = W_2 \max(0, W_1 x)$

The function  $\max(0, z)$  is called the **activation function**.

**Q:** What if we try to build a neural network without one?


$$f = W_2 W_1 x \quad W_3 = W_2 W_1 \in \mathbb{R}^{C \times H}, f = W_3 x$$

**A:** We end up with a linear classifier again!

# Activation functions


## Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




## tanh

$$\tanh(x)$$




## ReLU

$$\max(0, x)$$



## Leaky ReLU

$$\max(0.1x, x)$$




## Maxout

$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

## ELU


$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$



# Activation functions


## Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




## tanh

$$\tanh(x)$$



## ReLU


$$\max(0, x)$$



ReLU is a good default  
choice for most problems

## Leaky ReLU

$$\max(0.1x, x)$$




## Maxout


$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

## ELU

$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$




# Neural networks: Architectures




“2-layer Neural Net”, or  
“1-hidden-layer Neural Net”

“Fully-connected” layers



“3-layer Neural Net”, or  
“2-hidden-layer Neural Net”

# Example feed-forward computation of a neural network



```
# forward-pass of a 3-layer neural network:
f = lambda x: 1.0/(1.0 + np.exp(-x)) # activation function (use sigmoid)
x = np.random.randn(3, 1) # random input vector of three numbers (3x1)
h1 = f(np.dot(W1, x) + b1) # calculate first hidden layer activations (4x1)
h2 = f(np.dot(W2, h1) + b2) # calculate second hidden layer activations (4x1)
out = np.dot(W3, h2) + b3 # output neuron (1x1)
```




Full implementation of training a 2-layer Neural Network needs ~20 lines:

```
1 import numpy as np
2 from numpy.random import randn
3
4 # 1000 input, 100 hidden, 10 output units
5 N_in, N_hid, N_out = 64, 1000, 10000
6
7 # Randomly initialize weights
8 W1 = randn(N_in, N_hid)
9 W2 = randn(N_hid, N_out)
10
11 # Training loop
12 for i in range(2000):
13     # Generate random input
14     x = randn(N_in)
15     # Forward pass
16     z1 = W1.dot(x)
17     a1 = sigmoid(z1)
18     z2 = W2.dot(a1)
19     a2 = softmax(z2)
20     # Compute loss
21     loss = cross_entropy(a2, y)
22     # Backward pass
23     # Compute gradients
24     # Update weights
```

# Setting the number of layers and their sizes

↑  
more neurons = more capacity

Do not use size of neural network as a regularizer. Use stronger regularization instead:




(Web demo with ConvNetJS:

<http://cs.stanford.edu/people/karpathy/convnetjs/demo/classify2d.html>)




[This image](#) by [Fotis Bobolas](#) is  
licensed under [CC-BY 2.0](#)

Impulses carried toward cell body




[This image](#) by Felipe Perucho  
is licensed under [CC-BY 3.0](#)


Impulses carried toward cell body




[This image](#) by Felipe Peruchio is licensed under [CC-BY 3.0](#)



Impulses carried toward cell body




This image by Felipe Perucho  
is licensed under [CC-BY 3.0](#)




sigmoid activation function

$$\frac{1}{1 + e^{-x}}$$




Impulses carried toward cell body




This image by Felipe Perucho  
is licensed under [CC-BY 3.0](https://creativecommons.org/licenses/by/3.0/)

```
class Neuron:
    # ...
    def neuron_tick(inputs):
        """ assume inputs and weights are 1-D numpy arrays and bias is a number """
        cell_body_sum = np.sum(inputs * self.weights) + self.bias
        firing_rate = 1.0 / (1.0 + math.exp(-cell_body_sum)) # sigmoid activation func
        return firing_rate
```






## Biological Neurons: Complex connectivity patterns




[This image](#) is [CC0 Public Domain](#)

## Neurons in a neural network: Organized into regular layers for computational efficiency




## Biological Neurons: Complex connectivity patterns



[This image](#) is [CC0 Public Domain](#)

But neural networks with random connections can work too!



Xie et al, "Exploring Randomly Wired Neural Networks for Image Recognition", arXiv 2019

# Be very careful with your brain analogies!

## **Biological Neurons:**

- Many different types
- Dendrites can perform complex non-linear computations
- Synapses are not a single weight but a complex non-linear dynamical system
- Rate code may not be adequate

[Dendritic Computation. London and Hausser]

# Problem: How to compute gradients?

$$s = f(x; W_1, W_2) = W_2 \max(0, W_1 x) \quad \text{Nonlinear score function}$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \quad \text{SVM Loss on predictions}$$

$$R(W) = \sum_k W_k^2 \quad \text{Regularization}$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda R(W_1) + \lambda R(W_2) \quad \text{Total loss: data loss + regularization}$$

If we can compute  $\frac{\partial L}{\partial W_1}, \frac{\partial L}{\partial W_2}$  then we can learn  $W_1$  and  $W_2$

# (Bad) Idea: Derive $\nabla_W L$ on paper

$$s = f(x; W) = Wx$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

$$= \sum_{j \neq y_i} \max(0, W_{j,:} \cdot x + W_{y_i,:} \cdot x + 1)$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda \sum_k W_k^2$$

$$= \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, W_{j,:} \cdot x + W_{y_i,:} \cdot x + 1) + \lambda \sum_k W_k^2$$

$$\nabla_W L = \nabla_W \left( \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, W_{j,:} \cdot x + W_{y_i,:} \cdot x + 1) + \lambda \sum_k W_k^2 \right)$$


**Problem:** Very tedious: Lots of matrix calculus, need lots of paper

**Problem:** What if we want to change loss? E.g. use softmax instead of SVM? Need to re-derive from scratch =

**Problem:** Not feasible for very complex models!



# Better Idea: Computational graphs + Backpropagation



# Convolutional network (AlexNet)

input image

weights

loss




Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

# Neural Turing Machine

input image

loss




Figure reproduced with permission from a [Twitter post](#) by Andrej Karpathy.



# Neural Turing Machine





Figure reproduced with permission from a [Twitter post](#) by Andrej Karpathy.

## Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$



## Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$



## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$



## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial q}$$

## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

Upstream  
gradient

Local  
gradient

## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

Upstream  
gradient

Local  
gradient

## Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial x}$$

Chain rule:

$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$

Upstream  
gradient

Local  
gradient

# Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$




$$\frac{\partial f}{\partial x}$$

Chain rule:


$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$


Upstream  
gradient


Local  
gradient



















Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x$$


→

$$\frac{df}{dx} = 1$$



Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:


$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	$\rightarrow$	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	$\rightarrow$	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	$\rightarrow$	$\frac{df}{dx} = a$		$f_c(x) = c + x$	$\rightarrow$	$\frac{df}{dx} = 1$

Another example:


$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	$\rightarrow$	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	$\rightarrow$	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	$\rightarrow$	$\frac{df}{dx} = a$		$f_c(x) = c + x$	$\rightarrow$	$\frac{df}{dx} = 1$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

$\rightarrow$

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

$\rightarrow$

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

$\rightarrow$

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

$\rightarrow$

$$\frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$


$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$

$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$


$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$



Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



[upstream gradient] x [local gradient]

$$[0.2] \times [1] = 0.2$$

$$[0.2] \times [1] = 0.2 \text{ (both inputs!)}$$

$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:


$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	$\rightarrow$	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	$\rightarrow$	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	$\rightarrow$	$\frac{df}{dx} = a$		$f_c(x) = c + x$	$\rightarrow$	$\frac{df}{dx} = 1$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



[upstream gradient] x [local gradient]

$x_0$ :  $[0.2] \times [2] = 0.4$

$w_0$ :  $[0.2] \times [-1] = -0.2$

$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x$$


→

$$\frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$


Computational graph representation may not be unique. Choose one where local gradients at each node can be easily expressed!



Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$

Computational graph representation may not be unique. Choose one where local gradients at each node can be easily expressed!




Sigmoid local gradient:

$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left( \frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left( \frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$


Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$

Computational graph representation may not be unique. Choose one where local gradients at each node can be easily expressed!



$$\sigma(x) = \frac{1}{1 + e^{-x}}$$




[upstream gradient] x [local gradient]  
 $[1.00] \times [(1 - 0.73) (0.73)] = 0.2$

Sigmoid local gradient:

$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left( \frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left( \frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$

# Patterns in gradient flow


**add** gate: gradient distributor






# Patterns in gradient flow

**add** gate: gradient distributor




**mul** gate: “swap multiplier”




# Patterns in gradient flow


**add** gate: gradient distributor



**mul** gate: “swap multiplier”




**copy** gate: gradient adder




# Patterns in gradient flow


**add** gate: gradient distributor




**mul** gate: “swap multiplier”




**copy** gate: gradient adder



**max** gate: gradient router



# Backprop Implementation: “Flat” code




Forward pass:  
Compute output

```
def f(w0, x0, w1, x1, w2):  
    s0 = w0 * x0  
    s1 = w1 * x1  
    s2 = s0 + s1  
    s3 = s2 + w2  
    L = sigmoid(s3)
```

Backward pass:  
Compute grads

```
grad_L = 1.0  
grad_s3 = grad_L * (1 - L) * L  
grad_w2 = grad_s3  
grad_s2 = grad_s3  
grad_s0 = grad_s2  
grad_s1 = grad_s2  
grad_w1 = grad_s1 * x1  
grad_x1 = grad_s1 * w1  
grad_w0 = grad_s0 * x0  
grad_x0 = grad_s0 * w0
```

# Backprop Implementation: “Flat” code



Forward pass:  
Compute output

```
def f(w0, x0, w1, x1, w2):
```


```
    s0 = w0 * x0  
    s1 = w1 * x1  
    s2 = s0 + s1  
    s3 = s2 + w2  
    L = sigmoid(s3)
```

Base case

```
    grad_L = 1.0
```

```
    grad_s3 = grad_L * (1 - L) * L  
    grad_w2 = grad_s3  
    grad_s2 = grad_s3  
    grad_s0 = grad_s2  
    grad_s1 = grad_s2  
    grad_w1 = grad_s1 * x1  
    grad_x1 = grad_s1 * w1  
    grad_w0 = grad_s0 * x0  
    grad_x0 = grad_s0 * w0
```

# Backprop Implementation: “Flat” code



Forward pass:  
Compute output

```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

Sigmoid

```
    grad_L = 1.0
```

```
    grad_s3 = grad_L * (1 - L) * L
```

```
    grad_w2 = grad_s3
```

```
    grad_s2 = grad_s3
```

```
    grad_s0 = grad_s2
```

```
    grad_s1 = grad_s2
```


```
    grad_w1 = grad_s1 * x1
```

```
    grad_x1 = grad_s1 * w1
```

```
    grad_w0 = grad_s0 * x0
```

```
    grad_x0 = grad_s0 * w0
```

# Backprop Implementation: “Flat” code




Forward pass:  
Compute output

```
def f(w0, x0, w1, x1, w2):  
    s0 = w0 * x0  
    s1 = w1 * x1  
    s2 = s0 + s1  
    s3 = s2 + w2  
    L = sigmoid(s3)
```

Add gate

```
grad_L = 1.0  
grad_s3 = grad_L * (1 - L) * L  
grad_w2 = grad_s3  
grad_s2 = grad_s3  
grad_s0 = grad_s2  
grad_s1 = grad_s2  
grad_w1 = grad_s1 * x1  
grad_x1 = grad_s1 * w1  
grad_w0 = grad_s0 * x0  
grad_x0 = grad_s0 * w0
```

# Backprop Implementation: “Flat” code



Forward pass:  
Compute output


```
def f(w0, x0, w1, x1, w2):  
    s0 = w0 * x0  
    s1 = w1 * x1  
    s2 = s0 + s1  
    s3 = s2 + w2  
    L = sigmoid(s3)
```

Add gate

```
grad_L = 1.0  
grad_s3 = grad_L * (1 - L) * L  
grad_w2 = grad_s3  
grad_s2 = grad_s3  
grad_s0 = grad_s2  
grad_s1 = grad_s2  
grad_w1 = grad_s1 * x1  
grad_x1 = grad_s1 * w1  
grad_w0 = grad_s0 * x0  
grad_x0 = grad_s0 * w0
```



# Backprop Implementation: “Flat” code



Forward pass:  
Compute output


```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0  
    s1 = w1 * x1  
    s2 = s0 + s1  
    s3 = s2 + w2  
    L = sigmoid(s3)
```

```
grad_L = 1.0  
grad_s3 = grad_L * (1 - L) * L  
grad_w2 = grad_s3  
grad_s2 = grad_s3  
grad_s0 = grad_s2  
grad_s1 = grad_s2  
grad_w1 = grad_s1 * x1  
grad_x1 = grad_s1 * w1  
grad_w0 = grad_s0 * x0  
grad_x0 = grad_s0 * w0
```

Multiply gate

# Backprop Implementation: “Flat” code



Forward pass:  
Compute output

```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

```
grad_L = 1.0
```

```
grad_s3 = grad_L * (1 - L) * L
```

```
grad_w2 = grad_s3
```

```
grad_s2 = grad_s3
```

```
grad_s0 = grad_s2
```

```
grad_s1 = grad_s2
```

```
grad_w1 = grad_s1 * x1
```

```
grad_x1 = grad_s1 * w1
```

```
grad_w0 = grad_s0 * x0
```

```
grad_x0 = grad_s0 * w0
```


Multiply gate

# “Flat” Backprop: Do this for assignment 1!

Stage your forward/backward computation!

E.g. for the SVM:

```
# receive W (weights), X (data)
# forward pass (we have 8 lines)
scores = #...
margins = #...
data_loss = #...
reg_loss = #...
loss = data_loss + reg_loss
# backward pass (we have 5 lines)
dmargins = # ... (optionally, we go direct to dscores)
dscores = #...
dW = #...
```




# “Flat” Backprop: Do this for assignment 1!

E.g. for two-layer neural net:

```
# receive W1,W2,b1,b2 (weights/biases), X (data)
# forward pass:
h1 = #... function of X,W1,b1
scores = #... function of h1,W2,b2
loss = #... (several lines of code to evaluate Softmax loss)
# backward pass:
dscores = #...
dh1,dW2,db2 = #...
dW1,db1 = #...
```

# Backprop Implementation: Modularized API


Graph (or Net) object (*rough pseudo code*)



```
class ComputationalGraph(object):  
    #...  
    def forward(inputs):  
        # 1. [pass inputs to input gates...]  
        # 2. forward the computational graph:  
        for gate in self.graph.nodes_topologically_sorted():  
            gate.forward()  
        return loss # the final gate in the graph outputs the loss  
    def backward():  
        for gate in reversed(self.graph.nodes_topologically_sorted()):  
            gate.backward() # little piece of backprop (chain rule applied)  
        return inputs_gradients
```

# Modularized implementation: forward / backward API

Gate / Node / Function object: Actual PyTorch code



(x,y,z are scalars)

```
class Multiply(torch.autograd.Function):  
    @staticmethod  
    def forward(ctx, x, y):  
        ctx.save_for_backward(x, y)  
        z = x * y  
        return z  
    @staticmethod  
    def backward(ctx, grad_z):  
        x, y = ctx.saved_tensors  
        grad_x = y * grad_z # dz/dx * dL/dz  
        grad_y = x * grad_z # dz/dy * dL/dz  
        return grad_x, grad_y
```

Need to stash  
some values for  
use in backward

Upstream  
gradient

Multiply upstream  
and local gradients

# Example: PyTorch operators

pytorch / pytorch

Watch

1,221

★ Unstar

26,770

🔗 Fork

6,340

Code

Issues 2,286

Pull requests 561

Projects 4

Wiki

Insights

Tree: 517c7c9861

pytorch / aten / src / THNN / generic /

Create new file

Upload files

Find file

History

👤 ezyang and facebook-github-bot

Canonicalize all includes in PyTorch. (#14849)

Latest commit 517c7c9 on Dec 8, 2018

..

AbsCriterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

BCECriterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

ClassNLLCriterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

Col2Im.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

ELU.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

FeatureLPPooling.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

GatedLinearUnit.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

HardTanh.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

Im2Col.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

IndexLinear.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

LeakyReLU.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

LogSigmoid.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

MSECriterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

MultiLabelMarginCriterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

MultiMarginCriterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

RRReLU.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

Sigmoid.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SmoothL1Criterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SoftMarginCriterion.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SoftPlus.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SoftShrink.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SparseLinear.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SpatialAdaptiveAveragePooling.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SpatialAdaptiveMaxPooling.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SpatialAveragePooling.c

Canonicalize all includes in PyTorch. (#14849)

4 months ago

SpatialClassNLLCriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialConvolutionMM.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialDilatedMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialFractionalMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialFullDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialMaxUnpooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialReflectionPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialReplicationPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialUpSamplingBilinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialUpSamplingNearest.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
THNN.h	Canonicalize all includes in PyTorch. (#14849)	4 months ago
Tanh.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalReflectionPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalReplicationPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalRowConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalUpSamplingLinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalUpSamplingNearest.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricAdaptiveAveragePooling...	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricAdaptiveMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricAveragePooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricConvolutionMM.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricDilatedMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricFractionalMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricFullDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricMaxUnpooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricReplicationPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricUpSamplingNearest.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricUpSamplingTrilinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
linear_upsampling.h	Implement nn.functional.interpolate based on upsample. (#8591)	9 months ago
pooling_shape.h	Use integer math to compute output size of pooling operations (#14405)	4 months ago
unfold.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago

# PyTorch sigmoid layer

Forward

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$



```
void THNN_(Sigmoid_updateOutput)(
    THNNState *state,
    THTensor *input,
    THTensor *output)
{
    THTensor_(sigmoid)(output, input);
}
```

```
void THNN_(Sigmoid_updateGradInput)(
    THNNState *state,
    THTensor *gradOutput,
    THTensor *gradInput,
    THTensor *output)
{
    THNN_CHECK_NELEMENT(output, gradOutput);
    THTensor_(resizeAs)(gradInput, output);
    TH_TENSOR_APPLY3(scalar_t, gradInput, scalar_t, gradOutput, scalar_t, output,
        scalar_t z = *output_data;
        *gradInput_data = *gradOutput_data * (1. - z) * z;
    );
}
```

[Source](#)



# PyTorch sigmoid layer

Forward

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$



```
void THNN_(Sigmoid_updateOutput)(
    THNNState *state,
    THTensor *input,
    THTensor *output)
{
    THTensor_(sigmoid)(output, input);
}
```

```
void THNN_(Sigmoid_updateGradInput)(
    THNNState *state,
    THTensor *gradOutput,
    THTensor *gradInput,
    THTensor *output)
{
    THNN_CHECK_NELEMENT(output, gradOutput);
    THTensor_(resizeAs)(gradInput, output);
    TH_TENSOR_APPLY3(scalar_t, gradInput, scalar_t, gradOutput, scalar_t, output,
        scalar_t z = *output_data;
        *gradInput_data = *gradOutput_data * (1. - z) * z;
    );
}
```

```
static void sigmoid_kernel(TensorIterator& iter) {
    AT_DISPATCH_FLOATING_TYPES(iter.dtype(), "sigmoid_cpu", [&]() {
        unary_kernel_vec(
            iter,
            [=](scalar_t a) -> scalar_t { return (1 / (1 + std::exp((-a)))); },
            [=](Vec256<scalar_t> a) {
                a = Vec256<scalar_t>((scalar_t)(0)) - a;
                a = a.exp();
                a = Vec256<scalar_t>((scalar_t)(1)) + a;
                a = a.reciprocal();
                return a;
            });
    });
}
```

Forward actually  
defined elsewhere...

```
return (1 / (1 + std::exp((-a))));
```

[Source](#)

# PyTorch sigmoid layer

```
1 #ifndef TH_GENERIC_FILE
2 #define TH_GENERIC_FILE "THNN/generic/Sigmoid.c"
3 #else
```

```
4
5 void THNN_(Sigmoid_updateOutput)(
6     THNNState *state,
7     THTensor *input,
8     THTensor *output)
9 {
10     THTensor_(sigmoid)(output, input);
11 }
```

Forward

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

```
12
13 void THNN_(Sigmoid_updateGradInput)(
14     THNNState *state,
15     THTensor *gradOutput,
16     THTensor *gradInput,
17     THTensor *output)
18 {
19     THNN_CHECK_NELEMENT(output, gradOutput);
20     THTensor_(resizeAs)(gradInput, output);
21     TH_TENSOR_APPLY3(scalar_t, gradInput, scalar_t, gradOutput, scalar_t, output,
22         scalar_t z = *output_data;
23         *gradInput_data = *gradOutput_data * (1. - z) * z;
24     );
25 }
```

```
static void sigmoid_kernel(TensorIterator& iter) {
    AT_DISPATCH_FLOATING_TYPES(iter.dtype(), "sigmoid_cpu", [&]() {
        unary_kernel_vec(
            iter,
            [=](scalar_t a) -> scalar_t { return (1 / (1 + std::exp((-a)))); },
            [=](Vec256<scalar_t> a) {
                a = Vec256<scalar_t>((scalar_t)(0)) - a;
                a = a.exp();
                a = Vec256<scalar_t>((scalar_t)(1)) + a;
                a = a.reciprocal();
                return a;
            });
    });
}
```

Forward actually defined [elsewhere...](#)

Backward

$$(1 - \sigma(x)) \sigma(x)$$

[Source](#)

So far: backprop with scalars

What about vector-valued functions?

# Recap: Vector derivatives

## Scalar to Scalar

$$x \in \mathbb{R}, y \in \mathbb{R}$$

Regular derivative:

$$\frac{\partial y}{\partial x} \in \mathbb{R}$$

If  $x$  changes by a small amount, how much will  $y$  change?

# Recap: Vector derivatives

## Scalar to Scalar

$$x \in \mathbb{R}, y \in \mathbb{R}$$

Regular derivative:

$$\frac{\partial y}{\partial x} \in \mathbb{R}$$

If  $x$  changes by a small amount, how much will  $y$  change?

## Vector to Scalar

$$x \in \mathbb{R}^N, y \in \mathbb{R}$$

Derivative is **Gradient**:

$$\frac{\partial y}{\partial x} \in \mathbb{R}^N \quad \left( \frac{\partial y}{\partial x} \right)_n = \frac{\partial y}{\partial x_n}$$

For each element of  $x$ , if it changes by a small amount then how much will  $y$  change?

# Recap: Vector derivatives

## Scalar to Scalar

$$x \in \mathbb{R}, y \in \mathbb{R}$$

Regular derivative:

$$\frac{\partial y}{\partial x} \in \mathbb{R}$$

If  $x$  changes by a small amount, how much will  $y$  change?

## Vector to Scalar

$$x \in \mathbb{R}^N, y \in \mathbb{R}$$

Derivative is **Gradient**:

$$\frac{\partial y}{\partial x} \in \mathbb{R}^N \quad \left( \frac{\partial y}{\partial x} \right)_n = \frac{\partial y}{\partial x_n}$$

For each element of  $x$ , if it changes by a small amount then how much will  $y$  change?

## Vector to Vector


$$x \in \mathbb{R}^N, y \in \mathbb{R}^M$$

Derivative is **Jacobian**:


$$\frac{\partial y}{\partial x} \in \mathbb{R}^{N \times M} \quad \left( \frac{\partial y}{\partial x} \right)_{n,m} = \frac{\partial y_m}{\partial x_n}$$

For each element of  $x$ , if it changes by a small amount then how much will each element of  $y$  change?

# Backprop with Vectors




# Backprop with Vectors






# Backprop with Vectors




# Backprop with Vectors



# Backprop with Vectors

4D input x:

$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$




$$f(x) = \max(0, x)$$

*(elementwise)*

4D output y:


$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



# Backprop with Vectors

4D input x:


$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$



$$f(x) = \max(0, x) \\ (\textit{elementwise})$$


4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



4D dL/dy:

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$




Upstream  
gradient

# Backprop with Vectors

4D input x:


$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$



$f(x) = \max(0, x)$   
(*elementwise*)

4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$




Jacobian  $dy/dx$

$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}$

4D  $dL/dy$ :

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$


Upstream  
gradient



# Backprop with Vectors

4D input x:


$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$



$f(x) = \max(0, x)$   
(*elementwise*)

4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



$[dy/dx] \ [dL/dy]$

$\begin{bmatrix} 1 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 4 \end{bmatrix}$

$\begin{bmatrix} 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} -1 \end{bmatrix}$

$\begin{bmatrix} 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} 5 \end{bmatrix}$

$\begin{bmatrix} 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 9 \end{bmatrix}$


4D dL/dy:

$\begin{bmatrix} 4 \end{bmatrix}$

$\begin{bmatrix} -1 \end{bmatrix}$

$\begin{bmatrix} 5 \end{bmatrix}$

$\begin{bmatrix} 9 \end{bmatrix}$




Upstream  
gradient

# Backprop with Vectors

4D input x:


$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$



$$f(x) = \max(0, x) \\ (\textit{elementwise})$$


4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



4D dL/dx:

$\begin{bmatrix} 4 \\ 0 \\ 5 \\ 0 \end{bmatrix}$




$\begin{bmatrix} dy/dx \\ dL/dy \end{bmatrix}$

$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$

4D dL/dy:

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$



Upstream  
gradient

# Backprop with Vectors

4D input x:

$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$

$$f(x) = \max(0, x) \quad (\text{elementwise})$$

4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$

Jacobian is **sparse**:  
off-diagonal entries  
always zero! Never  
**explicitly** form  
Jacobian -- instead  
use **implicit**  
multiplication

4D  $dL/dx$ :

$\begin{bmatrix} 4 \\ 0 \\ 5 \\ 0 \end{bmatrix}$

$[dy/dx] [dL/dy]$

$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$

4D  $dL/dy$ :

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$

Upstream  
gradient



# Backprop with Vectors

4D input x:

$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$

$$f(x) = \max(0, x) \text{ (elementwise)}$$

4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$

Jacobian is **sparse**:  
off-diagonal entries  
always zero! Never  
**explicitly** form  
Jacobian -- instead  
use **implicit**  
multiplication

4D  $dL/dx$ :

$\begin{bmatrix} 4 \\ 0 \\ 5 \\ 0 \end{bmatrix}$

$[dy/dx] [dL/dy]$

$$\left( \frac{\partial L}{\partial x} \right)_i = \begin{cases} \left( \frac{\partial L}{\partial y} \right)_i & \text{if } x_i > 0 \\ 0 & \text{otherwise} \end{cases}$$

4D  $dL/dy$ :


$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$

Upstream  
gradient

# Backprop with Matrices (or Tensors)

Loss L still a scalar!


$dL/dx$  always has the same shape as  $x$ !




# Backprop with Matrices (or Tensors)

Loss L still a scalar!

$dL/dx$  always has the same shape as  $x$ !



# Backprop with Matrices



Also see derivation in the course notes:

<http://cs231n.stanford.edu/handouts/linear-backprop.pdf>

# Backprop with Matrices

x: [N×D]

[ 2 1 -3 ]

[ -3 4 2 ]

w: [D×M]

[ 3 2 1 -1 ]

[ 2 1 3 2 ]

[ 3 2 1 -2 ]

Matrix Multiply

$$y_{n,m} = \sum_d x_{n,d} w_{d,m}$$

**Jacobians:**

dy/dx: [(N×D)×(N×M)]

dy/dw: [(D×M)×(N×M)]

y: [N×M]

[13 9 -2 -6]

[ 5 2 17 1 ]

dL/dy: [N×M]

[ 2 3 -3 9 ]

[ -8 1 4 6 ]

For a neural net we may have

N=64, D=M=4096

Each Jacobian takes 256 GB of memory!

Must work with them implicitly!

# Backprop with Matrices

x: [N×D]  
[ 2 1 -3 ]  
[ -3 4 2 ]

w: [D×M]  
[ 3 2 1 -1 ]  
[ 2 1 3 2 ]  
[ 3 2 1 -2 ]

Matrix Multiply

$$y_{n,m} = \sum_d x_{n,d} w_{d,m}$$

**Q:** What parts of y are affected by one element of x?

y: [N×M]  
[ 13 9 -2 -6 ]  
[ 5 2 17 1 ]

dL/dy: [N×M]  
[ 2 3 -3 9 ]  
[ -8 1 4 6 ]

# Backprop with Matrices

$x: [N \times D]$   
 $\begin{bmatrix} 2 & \boxed{1} & -3 \\ -3 & 4 & 2 \end{bmatrix}$

$w: [D \times M]$   
 $\begin{bmatrix} 3 & 2 & 1 & -1 \\ 2 & 1 & 3 & 2 \\ 3 & 2 & 1 & -2 \end{bmatrix}$

Matrix Multiply

$$y_{n,m} = \sum_d x_{n,d} w_{d,m}$$

$y: [N \times M]$   
 $\begin{bmatrix} \boxed{13} & 9 & -2 & -6 \\ 5 & 2 & 17 & 1 \end{bmatrix}$

$dL/dy: [N \times M]$   
 $\begin{bmatrix} \boxed{2} & 3 & -3 & 9 \\ -8 & 1 & 4 & 6 \end{bmatrix}$

**Q:** What parts of  $y$  are affected by one element of  $x$ ?

**A:**  $x_{n,d}$  affects the whole row  $y_{n,\cdot}$ .

$$\frac{\partial L}{\partial x_{n,d}} = \sum_m \frac{\partial L}{\partial y_{n,m}} \frac{\partial y_{n,m}}{\partial x_{n,d}}$$

# Backprop with Matrices

x: [N×D]  
[ 2 1 -3 ]  
[ -3 4 2 ]

w: [D×M]  
[ 3 2 1 -1 ]  
[ 2 1 3 2 ]  
[ 3 2 1 -2 ]

Matrix Multiply

$$y_{n,m} = \sum_d x_{n,d} w_{d,m}$$

y: [N×M]  
[ 13 9 -2 -6 ]  
[ 5 2 17 1 ]

dL/dy: [N×M]  
[ 2 3 -3 9 ]  
[ -8 1 4 6 ]

**Q:** What parts of y are affected by one element of x?

**A:**  $x_{n,d}$  affects the whole row  $y_{n,\cdot}$ .

**Q:** How much does  $x_{n,d}$  affect  $y_{n,m}$ ?

$$\frac{\partial L}{\partial x_{n,d}} = \sum_m \frac{\partial L}{\partial y_{n,m}} \frac{\partial y_{n,m}}{\partial x_{n,d}}$$



# Backprop with Matrices

x: [N×D]  
 $\begin{bmatrix} 2 & \boxed{1} & -3 \\ -3 & 4 & 2 \end{bmatrix}$

w: [D×M]  
 $\begin{bmatrix} 3 & 2 & 1 & -1 \\ 2 & 1 & \boxed{3} & 2 \\ 3 & 2 & 1 & -2 \end{bmatrix}$

Matrix Multiply

$$y_{n,m} = \sum_d x_{n,d} w_{d,m}$$

y: [N×M]  
 $\begin{bmatrix} \boxed{13} & 9 & \boxed{-2} & -6 \\ 5 & 2 & 17 & 1 \end{bmatrix}$

dL/dy: [N×M]  
 $\begin{bmatrix} \boxed{2} & 3 & -3 & 9 \\ -8 & 1 & 4 & 6 \end{bmatrix}$

**Q:** What parts of y are affected by one element of x?

**A:**  $x_{n,d}$  affects the whole row  $y_n$ .

**Q:** How much does  $x_{n,d}$  affect  $y_{n,m}$ ?

**A:**  $w_{d,m}$

$$\frac{\partial L}{\partial x_{n,d}} = \sum_m \frac{\partial L}{\partial y_{n,m}} \frac{\partial y_{n,m}}{\partial x_{n,d}} = \sum_m \frac{\partial L}{\partial y_{n,m}} w_{d,m}$$

# Backprop with Matrices

$$x: [N \times D]$$

$$\begin{bmatrix} 2 & \boxed{1} & -3 \\ -3 & 4 & 2 \end{bmatrix}$$

$$w: [D \times M]$$

$$\begin{bmatrix} 3 & 2 & 1 & -1 \\ 2 & 1 & \boxed{3} & 2 \\ 3 & 2 & 1 & -2 \end{bmatrix}$$

$$[N \times D] \quad [N \times M] \quad [M \times D]$$

$$\frac{\partial L}{\partial x} = \left( \frac{\partial L}{\partial y} \right) w^T$$

Matrix Multiply

$$y_{n,m} = \sum_d x_{n,d} w_{d,m}$$

$$y: [N \times M]$$

$$\begin{bmatrix} \boxed{13} & 9 & \boxed{-2} & -6 \\ 5 & 2 & 17 & 1 \end{bmatrix}$$

$$dL/dy: [N \times M]$$

$$\begin{bmatrix} \boxed{2} & 3 & -3 & 9 \\ -8 & 1 & 4 & 6 \end{bmatrix}$$

**Q:** What parts of  $y$  are affected by one element of  $x$ ?

**A:**  $x_{n,d}$  affects the whole row  $y_n$ .

**Q:** How much does  $x_{n,d}$  affect  $y_{n,m}$ ?

**A:**  $w_{d,m}$

$$\frac{\partial L}{\partial x_{n,d}} = \sum_m \frac{\partial L}{\partial y_{n,m}} \frac{\partial y_{n,m}}{\partial x_{n,d}} = \sum_m \frac{\partial L}{\partial y_{n,m}} w_{d,m}$$

# Backprop with Matrices

$$x: [N \times D]$$

$$\begin{bmatrix} 2 & \boxed{1} & -3 \\ -3 & 4 & 2 \end{bmatrix}$$

$$w: [D \times M]$$

$$\begin{bmatrix} 3 & 2 & 1 & -1 \\ 2 & 1 & \boxed{3} & 2 \\ 3 & 2 & 1 & -2 \end{bmatrix}$$

Matrix Multiply

$$y_{n,m} = \sum_d x_{n,d} w_{d,m}$$

$$y: [N \times M]$$

$$\begin{bmatrix} \boxed{13} & \boxed{9} & \boxed{-2} & \boxed{-6} \\ 5 & 2 & 17 & 1 \end{bmatrix}$$

$$dL/dy: [N \times M]$$

$$\begin{bmatrix} \boxed{2} & \boxed{3} & \boxed{-3} & \boxed{9} \\ -8 & 1 & 4 & 6 \end{bmatrix}$$

By similar logic:

$$[N \times D] \quad [N \times M] \quad [M \times D]$$

$$\frac{\partial L}{\partial x} = \left( \frac{\partial L}{\partial y} \right) w^T$$

$$[D \times M] \quad [D \times N] \quad [N \times M]$$


$$\frac{\partial L}{\partial w} = x^T \left( \frac{\partial L}{\partial y} \right)$$

These formulas are easy to remember: they are the only way to make shapes match up!

# Summary for today:

- **(Fully-connected) Neural Networks** are stacks of linear functions and nonlinear activation functions; they have much more representational power than linear classifiers
- **backpropagation** = recursive application of the chain rule along a computational graph to compute the gradients of all inputs/parameters/intermediates
- implementations maintain a graph structure, where the nodes implement the **forward()** / **backward()** API
- **forward**: compute result of an operation and save any intermediates needed for gradient computation in memory
- **backward**: apply the chain rule to compute the gradient of the loss function with respect to the inputs

# Next Time: Convolutional Networks!



A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$





Diagram illustrating the vectorization of the variables  $x$  and  $W$  in the function  $f(x, W)$ . Two gray arrows point downwards from the variables  $x$  and  $W$  in the equation above to their respective spaces below.

$$\begin{matrix} \downarrow & \downarrow \\ \in \mathbb{R}^n & \in \mathbb{R}^{n \times n} \end{matrix}$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$






A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$

$$\begin{bmatrix} 0.1 & 0.5 \\ -0.3 & 0.8 \end{bmatrix} \mathbf{W}$$


$$\begin{bmatrix} 0.2 \\ 0.4 \end{bmatrix} \mathbf{x}$$



$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$


$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$
$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$



$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$
$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial f}{\partial q_i} = 2q_i$$

$$\nabla_q f = 2q$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial f}{\partial q_i} = 2q_i$$

$$\nabla_q f = 2q$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$

$$\begin{bmatrix} 0.1 & 0.5 \\ -0.3 & 0.8 \end{bmatrix} W$$

$$\begin{bmatrix} 0.2 \\ 0.4 \end{bmatrix} x$$




$$\frac{\partial q_k}{\partial W_{i,j}} = \mathbf{1}_{k=i} x_j$$

$$\begin{aligned} \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\ &= \sum_k (2q_k) (\mathbf{1}_{k=i} x_j) \\ &= 2q_i x_j \end{aligned}$$

$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$\begin{aligned} \frac{\partial q_k}{\partial W_{i,j}} &= \mathbf{1}_{k=i} x_j \\ \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\ &= \sum_k (2q_k) (\mathbf{1}_{k=i} x_j) \\ &= 2q_i x_j \end{aligned}$$

$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$



A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$\nabla_W f = 2q \cdot x^T$$

$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\begin{aligned} \frac{\partial q_k}{\partial W_{i,j}} &= \mathbf{1}_{k=i} x_j \\ \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\ &= \sum_k (2q_k) (\mathbf{1}_{k=i} x_j) \\ &= 2q_i x_j \end{aligned}$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\begin{aligned}
 \frac{\partial q_k}{\partial W_{i,j}} &= \mathbf{1}_{k=i} x_j \\
 \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\
 &= \sum_k (2q_k) (\mathbf{1}_{k=i} x_j) \\
 &= 2q_i x_j
 \end{aligned}$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$\frac{\partial q_k}{\partial x_i} = W_{k,i}$$

$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\begin{aligned} \frac{\partial q_k}{\partial x_i} &= W_{k,i} \\ \frac{\partial f}{\partial x_i} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial x_i} \\ &= \sum_k 2q_k W_{k,i} \end{aligned}$$

A vectorized example:  $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$



$$\nabla_x f = 2W^T \cdot q$$

$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\begin{aligned} \frac{\partial q_k}{\partial x_i} &= W_{k,i} \\ \frac{\partial f}{\partial x_i} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial x_i} \\ &= \sum_k 2q_k W_{k,i} \end{aligned}$$

In discussion section: A matrix example...

$$z_1 = XW_1$$

$$h_1 = \text{ReLU}(z_1)$$

$$\hat{y} = h_1 W_2$$

$$L = ||\hat{y}||_2^2$$

$$\frac{\partial L}{\partial W_2} = ?$$

$$\frac{\partial L}{\partial W_1} = ?$$

