

Campus A on the left:

Vlans assignment on layer 2 switches:

SW0:

Fa0/5-7 → Vlan 2

Fa0/10-13 → Vlan 3

Fa0/15 → Vlan 4

The reason why I leave some unassigned ports apart is in case I'd like to add a device to these ports later (like a real network).

SW1:

Fa0/5-8 → Vlan 5

Fa0/10-12 → Vlan 6

Fa0/15-6 → Vlan 7

Fa0/20-23 → Vlan 8

SW2:

Fa0/5-7 → Vlan 9

Fa0/10-12 → Vlan 10

Fa0/15-19 → Vlan 11

Fa0/20-21 → Vlan 12

SW3:

Fa0/5-7 → Vlan 13

Fa0/10-12 → Vlan 14

Fa0/15-19 → Vlan 15

SW4:

Fa0/5-8 → Vlan 16

Fa0/10-13 → Vlan 17

Fa0/15-18 → Vlan 18

Campus B on the right:

Vlans assignment on layer 2 switches:

SW5:

Fa0/5-6 → Vlan 2

Fa0/10-12 → Vlan 3

Fa0/15-17 → Vlan 5 (not main branch no need for security team leader)

SW6:

Fa0/5-7 → Vlan 6

Fa0/10-11 → Vlan 9

Fa0/15-18 → Vlan 10

Fa0/20-21 → Vlan 11

SW7:

Fa0/5-7 → Vlan 16

Fa0/10-12 → Vlan 17

Fa0/15-17 → Vlan 18