

# AIAC\_LAB\_ASSIGNMENT\_7.4

**Name:** Chitikeshi Mahesh

**HT No:** 2303A52037

**Batch:** 31

---

## Question 1: Mutable Default Argument – Function Bug

### Task:

Analyze given code where a mutable default argument causes unexpected behavior. Use AI to fix it.

### Bug Example:

```
def add_item(item, items=[]):  
    items.append(item)  
    return items  
  
print(add_item(1))  
print(add_item(2))
```

**Expected Output:** Corrected function avoids shared list bug.

### Prompt:

Fix the mutable default argument issue in the function so that each call gets a fresh list.

### Code:

```

1  # Bug: Mutable default argument
2  def add_item(item, items=None):
3      if items is None:
4          items = []
5          items.append(item)
6      return items
7  print(add_item(1))
8  print(add_item(2))

```

## Output

```

[1]
[2]

```

## Explanation:

The default list `[]` was shared between calls.

Default arguments are created only once.

Using `None` ensures a new list is created each time.

## Question 2: Floating-Point Precision Error

### Task:

Analyze given code where floating-point comparison fails. Use AI to correct with tolerance.

### Bug Example:

```

def check_sum():
    return (0.1 + 0.2) == 0.3

print(check_sum())

```

**Expected Output:** Corrected function

**Prompt:**

Fix floating point comparison using tolerance.

**Code:**

```
1  # Bug: Floating point precision issue
2  def check_sum():
3      return round(0.1 + 0.2, 10) == round(0.3, 10)
4  print(check_sum())
```

**Output**

True

**Explanation:**

Floating numbers are not exact in binary.

Instead of ==, we compare the difference with a small tolerance.

---

## Question 3: Recursion Error – Missing Base Case

**Task:**

Analyze given code where recursion runs infinitely due to missing base case. Use AI to fix it.

**Bug Example:**

```
def countdown(n):
    print(n)
    return countdown(n-1)

countdown(5)
```

**Expected Output:** Correct recursion with stopping condition.

### Prompt:

Add a stopping condition to prevent infinite recursion.

### Code:

```
1  # Bug: No base case
2  def countdown(n):
3      if n < 0:
4          return
5      print(n)
6      return countdown(n-1)
7  countdown(5)
```

### Output

```
5
4
3
2
1
0
```

### Explanation:

Without a base case, recursion never stops.

The base case stops when n becomes 0.

## Question 4: Dictionary Key Error

### Task:

Analyze given code where a missing dictionary key causes error. Use AI to fix it.

### Bug Example:

```
def get_value():  
    data = {"a": 1, "b": 2}  
    return data["c"]  
  
print(get_value())
```

**Expected Output:** Corrected with `.get()` or error handling.

### Prompt:

Fix missing key access safely.

### Code:

```
1  # Bug: Accessing non-existing key  
2  def get_value():  
3      data = {"a": 1, "b": 2}  
4      return data.get("c", None)  
5  print(get_value())
```

### Output

None

### Explanation:

Accessing `data["c"]` causes `KeyError`.

Using `.get()` method prevents crashes and allows default value.

## Question 5: Infinite Loop – Wrong Condition

### Task:

Analyze given code where the loop never ends. Use AI to detect and fix it.

### Bug Example:

```
def loop_example():  
    i = 0  
    while i < 5:  
        print(i)
```

**Expected Output:** Corrected loop increments i.

### Prompt:

Fix the infinite loop by incrementing the counter.

### Code:

```
1  # Bug: Infinite loop  
2  def loop_example():  
3      i = 0  
4      while i < 5:  
5          print(i)  
6          i += 1  
7  
8  loop_example()
```

### Output

```
0  
1  
2  
3  
4
```

### Explanation:

The variable `i` was never incremented.

The loop condition stayed `True` forever.

## Question 6: Unpacking Error – Wrong Variables

### Task:

Analyze given code where tuple unpacking fails. Use AI to fix it.

### Bug Example:

```
a, b = (1, 2, 3)
```

**Expected Output:** Correct unpacking or using `_` for extra values.

### Prompt:

Fix tuple unpacking.

### Code:

```
1 # Bug: Wrong unpacking
2 a, b, c = (1, 2, 3)
3 print(a, b)
```

### Output

```
1 2
```

### Explanation:

Tuple had three values but only two variables.

Added c to Fix.

## Question 7: Mixed Indentation – Tabs vs Spaces

### Task:

Analyze given code where mixed indentation breaks execution. Use AI to fix it.

**Bug Example:**

```
def func():  
    x = 5  
    y = 10  
    return x+y
```

**Expected Output:** Consistent indentation applied.

**Prompt:**

Fix inconsistent indentation.

**Code:**

```
1  # Bug: Mixed indentation  
2  def func():  
3      x = 5  
4      y = 10  
5      return x+y  
6  print(func())
```

**Output**

15

**Explanation:**

Python requires consistent indentation.

Using spaces consistently fixes execution.

## Question 8: Import Error – Wrong Module Usage

**Task:**



Analyze given code with incorrect import. Use AI to fix it.

**Bug Example:**

```
import maths
print(maths.sqrt(16))
```

**Expected Output:** Corrected to import `math`

**Prompt:**

Fix incorrect module import.

**Code:**

```
1  # Bug: Wrong import
2  import math
3  print(math.sqrt(16))
```

**Output**

```
4.0
```

**Explanation:**

Corrected Typo of Import of math module

## Question 9: Unreachable Code – Return Inside Loop

**Task:**

Analyze given code where a return inside a loop prevents full iteration. Use AI to fix it.

**Bug Example:**

```
def total(numbers):
    for n in numbers:
```

```
        return n

print(total([1,2,3]))
```

**Expected Output:** Corrected code accumulates sum and returns after loop

### Prompt:

Fix early return inside loop.

### Code:

```
1  # Bug: Early return inside loop
2  def total(numbers):
3      sum_total = 0
4      for n in numbers:
5          sum_total += n
6      return sum_total
7  print(total([1,2,3]))
```

### Output

6

### Explanation:

Return statement inside the loop stops after the first iteration.

Now it sums all elements before returning.

## Question 10: Name Error – Undefined Variable

### Task:

Analyze given code where a variable is used before being defined. Let AI detect and fix the error.

**Bug Example:**

```
def calculate_area():  
    return length * width  
  
print(calculate_area())
```

**Requirements:**

- Run the code to observe the error.
- Ask AI to identify the missing variable definition.
- Fix the bug by defining length and width as parameters.
- Add 3 assert test cases for correctness.

**Expected Output:**

- Corrected code with parameters.
- AI explanation of the bug.
- Successful execution of assertions.

**Prompt:**

Fix undefined variables by using parameters. Add 3 assert test cases to test correctness.

**Code:**

```

1  # Bug: Using undefined variable
2  def calculate_area(length, width):
3      return length * width
4
5  # Test cases
6  assert calculate_area(5, 10) == 50
7  assert calculate_area(3, 4) == 12
8  assert calculate_area(7, 8) == 56
9
10 print(calculate_area(5, 10))

```

## Output

50

## Explanation:

length and width were undefined.

Making them parameters fixes NameError.

## Question 11: Type Error – Mixing Data Types Incorrectly

### Task:

Analyze given code where integers and strings are added incorrectly. Let AI detect and fix the error.

### Bug Example:

```

def add_values():
    return 5 + "10"

print(add_values())

```

### Requirements:

- Run the code to observe the error.
- AI should explain why `int + str` is invalid.
- Fix the code by type conversion (e.g., `int("10")` or `str(5)`).
- Verify with 3 assert cases.

### Expected Output:

- Corrected code with type handling.
- AI explanation of the fix.
- Successful test validation.

### Prompt:

Fix int adding string error using conversion. Add 3 assert test cases to test correctness, explain in a docstring why `int + str` is invalid.

### Code:

```

1  # Bug: Adding integer and string
2  def add_values():
3      """
4      Add two values together.
5
6      Note: In Python, the + operator cannot directly add an integer and string
7      because they are incompatible types. Strings require explicit conversion
8      to numeric types before arithmetic operations.
9      """
10     return 5 + int("10")
11
12     print(add_values())
13
14     # Test cases
15     assert add_values() == 15, "5 + 10 should equal 15"
16     assert isinstance(add_values(), int), "Result should be an integer"
17     assert add_values() > 10, "Result should be greater than 10"

```

### Output

15

## Explanation:

Python cannot add int and str directly.

Type conversion solves the issue.

## Question 12: Type Error – String + List Concatenation

### Task:

Analyze code where a string is incorrectly added to a list.

### Bug Example:

```
def combine():  
    return "Numbers: " + [1, 2, 3]  
  
print(combine())
```

### Requirements:

- Run the code to observe the error.
- Explain why str + list is invalid.
- Fix using conversion ( `str([1,2,3])` or `" ".join()` ).
- Verify with 3 assert cases.

### Expected Output:

- Corrected code
- Explanation
- Successful test validation

### Prompt:

Fix string + list concatenation using conversion, Add 3 assert test cases to test correctness, explain in a docstring why str + list is invalid.

### Code:

```

1  # Bug: Adding string and list
2  def combine():
3      """
4      Combine a string with a list representation.
5
6      Note: Direct concatenation of str + list is invalid in Python because
7      strings and lists are different types. We must convert the list to a
8      string representation using str() before concatenation.
9      """
10     return "Numbers: " + str([1, 2, 3])
11
12     print(combine())
13
14     # Test cases
15     assert combine() == "Numbers: [1, 2, 3]", "Basic concatenation failed"
16     assert isinstance(combine(), str), "Result should be a string"
17     assert "Numbers:" in combine() and "[1, 2, 3]" in combine(), "Both parts should be present"

```

## Output

```
Numbers: [1, 2, 3]
```

## Explanation:

String cannot be directly added to the list.

Convert list to string first.

## Question 13: Type Error – Multiplying String by Float

### Task:

Detect and fix code where a string is multiplied by a float.

### Bug Example:

```

def repeat_text():
    return "Hello" * 2.5

print(repeat_text())

```

### Requirements:

- Observe the error.

- Explain why float multiplication is invalid for strings.
- Fix by converting float to int.
- Add 3 assert test cases.

### Prompt:

Fix string multiplied by float using conversion, Explain in a docstring why float multiplication is invalid for strings, Add 3 assert test cases.

### Code:

```
1  # Bug: Multiplying string by float
2  def repeat_text():
3      """
4      Repeat a string by converting the multiplier to an integer.
5
6      In Python, strings can only be multiplied by integers, not floats.
7      Multiplying a string by a float raises a TypeError because the
8      repetition count must be a whole number. We convert 2.5 to int(2)
9      to fix this issue.
10     """
11     return "Hello" * int(2.5)
12
13     print(repeat_text())
14
15     # Test cases
16     assert repeat_text() == "HelloHello", "Should repeat string 2 times (2.5 truncated to 2)"
17     assert len(repeat_text()) == 10, "Result should have length 10"
18     assert repeat_text()[0:5] == "Hello", "First 5 characters should be 'Hello'"
```

### Output

HelloHello

### Explanation:

Strings can only be multiplied by integers.

Convert float to int before multiplication.

## Question 14: Type Error – Adding None to Integer

### Task:



Analyze code where None is added to an integer.

**Bug Example:**

```
def compute():  
    value = None  
    return value + 10  
  
print(compute())
```

**Requirements:**

- Run and identify the error.
- Explain why NoneType cannot be added.
- Fix by assigning a default value.
- Validate using asserts.

**Prompt:**

Fix None addition issue, Explain in a docstring why NoneType cannot be added, Validate using asserts.

**Code:**

```

1  # Bug: Adding None and integer
2  def compute():
3      """
4      Computes a value.
5
6      NoneType cannot be added to integers because None represents the absence
7      of a value and has no numeric representation. Python's type system prevents
8      operations between incompatible types to avoid undefined behavior.
9      """
10     value = 0 # Fixed: Initialize with a valid integer instead of None
11     return value + 10
12
13 result = compute()
14 print(result)
15
16 # Validate using asserts
17 assert result == 10, "Expected result to be 10"
18 assert isinstance(result, int), "Expected result to be an integer"

```

## Output

10

## Explanation:

NoneType cannot be added to int.

Assign default numeric value before operation.

## Question 15: Type Error – Input Treated as String Instead of Number

### Task:

Fix code where user input is not converted properly.

### Bug Example:

```

def sum_two_numbers():
    a = input("Enter first number: ")
    b = input("Enter second number: ")
    return a + b

```

```
print(sum_two_numbers())
```

### Requirements:

- Explain why input is always string.
- Fix using `int()` conversion.
- Verify with assert test cases.

### Prompt:

Fix input conversion issue using type conversion, Explain in docstring why input is always string, Verify with assert test cases.

### Code:

```
1  # Bug: Input remains string
2  def sum_two_numbers():
3      """
4      Sum two numbers from user input.
5
6      Why input() returns strings:
7      The input() function always returns user data as a string type,
8      regardless of what the user types. String concatenation occurs
9      instead of numeric addition without explicit type conversion.
10     """
11     a = float(input("Enter first number: "))
12     b = float(input("Enter second number: "))
13     return a + b
14
15 result = sum_two_numbers()
16 print(result)
17
18 # Test cases
19 assert sum_two_numbers.__doc__ is not None, "Docstring missing"
20 assert isinstance(result, float), "Result should be a float"
21 assert result == 5.0, "Expected sum of 2.0 and 3.0 to be 5.0"
```

### Output

```
Enter first number: 2.0  
Enter second number: 3.0  
5.0
```

**Explanation:**

input() always returns string.

Convert to float or int before addition.