

SCHOOL OF COMPUTER SCIENCE AND ARTIFICIAL INTELLIGENCE		DEPARTMENT OF COMPUTER SCIENCE ENGINEERING	
Program Name: B. Tech		Assignment Type: Lab	Academic Year:2025-2026
Instructor(s) Name		S Naresh Kumar	
Course Code	24CS002PC215	Course Title	AI Assisted Coding
Year/Sem	III/II	Regulation	R24
Date and Day of Assignment	Week3 – wednesday	Time(s)	
Duration	2 Hours	Applicable to Batches	
Assignment Number:6.1(Present assignment number)/24(Total number of assignments)			
Q.No.	Question		Expected Time to complete
	<b>Lab 6: AI-Based Code Completion – Classes, Loops, and Conditionals</b> <b>Lab Objectives:</b> <ul style="list-style-type: none"> <li>To explore AI-powered auto-completion features for core Python constructs.</li> <li>To analyze how AI suggests logic for class definitions, loops, and conditionals.</li> <li>To evaluate the completeness and correctness of code generated by AI assistants.</li> </ul> <b>Lab Outcomes (LOs):</b> After completing this lab, students will be able to: <ul style="list-style-type: none"> <li>Use AI tools to generate and complete class definitions and methods.</li> <li>Understand and assess AI-suggested loops for iterative tasks.</li> <li>Generate conditional statements through prompt-driven suggestions.</li> <li>Critically evaluate AI-assisted code for correctness and clarity.</li> </ul>		Week3 - Monday
1	<b>Task Description #1 (Loops – Automorphic Numbers in a Range)</b> <ul style="list-style-type: none"> <li>Task: Prompt AI to generate a function that displays all Automorphic numbers between 1 and 1000 using a for loop.</li> <li>Instructions:               <ul style="list-style-type: none"> <li>Get AI-generated code to list Automorphic numbers using a for</li> </ul> </li> </ul>		

loop.

- Analyze the correctness and efficiency of the generated logic.
- Ask AI to regenerate using a while loop and compare both implementations.

Expected Output #1:

- Correct implementation that lists Automorphic numbers using both loop types, with explanation.

**Prompt**

Generate a list of automorphic numbers in a given range

**Code**

Using "for Loop"

```
import time as t
def is_automorphic(num):
    square = num * num
    num_str = str(num)
    square_str = str(square)
    return square_str.endswith(num_str)
def automorphic_numbers_in_range(start, end):
    automorphic_numbers = []
    for num in range(start, end + 1):
        if is_automorphic(num):
            automorphic_numbers.append(num)
    return automorphic_numbers
start_time = t.time()
start_range = int(input("Enter the start of the range: "))
end_range = int(input("Enter the end of the range: "))
automorphic_numbers = automorphic_numbers_in_range(start_range, end_range)
print(f"Automorphic numbers between {start_range} and {end_range}: {automorphic_numbers}")
end_time = t.time()
print(f"Time taken: {end_time - start_time} seconds\n")
```

	<p><b>Output</b></p> <pre> Enter the start of the range: 1 Enter the end of the range: 1000 Automorphic numbers between 1 and 1000: [1, 5, 6, 25, 76, 376, 625] Time taken: 9.609323501586914 seconds  Using while loop: Enter the start of the range: 1 Enter the end of the range: 1000 Automorphic numbers between 1 and 1000: [1, 5, 6, 25, 76, 376, 625] Time taken: 2.9865434169769287 seconds </pre> <p><b>Explanation</b></p> <p><i>The program finds Automorphic numbers by checking whether the square of a number ends with the number itself using loop logic.</i></p>	
2	<p><b>Task Description #2 (Conditional Statements – Online Shopping Feedback Classification)</b></p> <ul style="list-style-type: none"> <li>Task: Ask AI to write nested if-elif-else conditions to classify online shopping feedback as Positive, Neutral, or Negative based on a numerical rating (1–5).</li> <li>Instructions: <ul style="list-style-type: none"> <li>Generate initial code using nested if-elif-else.</li> <li>Analyze correctness and readability.</li> <li>Ask AI to rewrite using dictionary-based or match-case structure.</li> </ul> </li> </ul> <p>Expected Output #2:</p> <ul style="list-style-type: none"> <li>Feedback classification function with explanation and an alternative approach.</li> </ul> <p><b>Prompt</b></p> <pre> Genrate a online shopping feedback system using nested if-elif-else to categorize feedback into positive, negative, and neutral based on 1-5 rating scale. </pre> <p><b>Code</b></p> <pre> def categorize_feedback(rating):     if rating &gt;= 4 and rating &lt;= 5:         return "Positive"     elif rating == 3: </pre>	

	<pre>        return "Neutral"     elif rating &gt;= 1 and rating &lt;= 2:         return "Negative"     else:         return "Invalid rating. Please provide a rating between 1 and 5." # Example usage ratings = [5, 4, 3, 2, 1, 6, 0] for rating in ratings:     category = categorize_feedback(rating)     print(f"Rating: {rating} - Feedback Category: {category}")</pre> <p><b>Output</b></p> <pre>Time Complexity: O(1) - The function performs a constant number of operations regardless of input size. Space Complexity: O(1) - The function uses a constant amount of space for variables</pre> <pre>Rating: 5 - Feedback Category: Positive Rating: 4 - Feedback Category: Positive Rating: 3 - Feedback Category: Neutral Rating: 2 - Feedback Category: Negative Rating: 1 - Feedback Category: Negative Rating: 6 - Feedback Category: Invalid rating. Please provide a rating between 1 and 5. Rating: 0 - Feedback Category: Invalid rating. Please provide a rating between 1 and 5.</pre> <p><b>Explanation</b></p> <p>The feedback classification uses conditional statements to correctly label ratings as Negative, Neutral, or Positive based on given values.</p>	
3	<p><b>Task 3: Statistical_operations</b></p> <p>Define a function named statistical_operations(tuple_num) that performs the following statistical operations on a tuple of numbers:</p> <ul style="list-style-type: none"><li>• Minimum, Maximum</li><li>• Mean, Median, Mode</li><li>• Variance, Standard Deviation</li></ul> <p>While writing the function, observe the code suggestions provided by GitHub Copilot. Make decisions to accept, reject, or modify the suggestions based on their relevance and correctness</p>	

**Code**

```
import statistics

def statistical_operations(tuple_num):
    if not tuple_num:
        return {}

    nums = list(tuple_num)

    min_val = min(nums)
    max_val = max(nums)
    mean_val = statistics.mean(nums)
    median_val = statistics.median(nums)

    try:
        mode_val = statistics.mode(nums)
    except statistics.StatisticsError:
        mode_val = None

    variance_val = statistics.variance(nums)
    stdev_val = statistics.stdev(nums)

    return {
        'minimum': min_val,
        'maximum': max_val,
        'mean': mean_val,
        'median': median_val,
        'mode': mode_val,
        'variance': variance_val,
        'standard_deviation': stdev_val
    }

# Example usage
if __name__ == "__main__":
    sample_tuple = (1, 2, 3, 4, 5, 5, 6)
    results = statistical_operations(sample_tuple)
    print("Statistical Operations Results:")
    for key, value in results.items():
        print(f"{key.capitalize()}: {value}")
```

	<p><b>Output</b></p> <pre> Statistical Operations Results: Minimum: 1 Maximum: 6 Mean: 3.7142857142857144 Median: 4 Mode: 5 Variance: 3.238095238095238 Standard deviation: 1.7994708216848747 </pre> <p><b>Explanation</b></p> <p><i>The function uses Python built-in statistics methods to compute minimum, maximum, mean, median, mode, variance, and standard deviation accurately.</i></p>	
4	<p><b>Task 4: Teacher Profile</b></p> <ul style="list-style-type: none"> <li>• <b>Prompt:</b> Create a class Teacher with attributes teacher_id, name, subject, and experience. Add a method to display teacher details.</li> <li>• <b>Expected Output:</b> Class with initializer, method, and object creation.</li> </ul> <p><b>Prompt</b></p> <pre> Create a class Teacher with attributes teacher_id, name, subject, and experience. Add a method to display teacher details. </pre> <p><b>Code</b></p> <pre> class Teacher:     def __init__(self, teacher_id, name, subject, experience):         self.teacher_id = teacher_id         self.name = name         self.subject = subject         self.experience = experience      def display_details(self):         print(f"Teacher ID: {self.teacher_id}")         print(f"Name: {self.name}")         print(f"Subject: {self.subject}") </pre>	

	<pre>        print(f"Experience: {self.experience} years")  # Example usage  if __name__ == "__main__":      teacher1 = Teacher(101, "Alice Johnson", "Mathematics", 10)      teacher2 = Teacher(102, "Bob Smith", "Science", 8)       print("Teacher 1 Details:")      teacher1.display_details()      print("\nTeacher 2 Details:")      teacher2.display_details()</pre> <p><b>Output</b></p> <pre>Teacher 1 Details: Teacher ID: 101 Name: Alice Johnson Subject: Mathematics Experience: 10 years  Teacher 2 Details: Teacher ID: 102 Name: Bob Smith Subject: Science Experience: 8 years</pre> <p><b>Explanation</b></p> <p><i>The Teacher class demonstrates object oriented programming by initializing attributes through a constructor and displaying details using a class method.</i></p>	
5	<p><b>Task #5 – Zero-Shot Prompting with Conditional Validation</b></p> <p>Use zero-shot prompting to instruct an AI tool to generate a function that validates an Indian mobile number.</p> <p>Requirements</p> <ul style="list-style-type: none"><li>• The function must ensure the mobile number:<ul style="list-style-type: none"><li>○ Starts with 6, 7, 8, or 9</li><li>○ Contains exactly 10 digits</li></ul></li></ul>	

### Expected Output

- A valid Python function that performs all required validations without using any input-output examples in the prompt.

#### **Prompt**

create a filter out the indian mobile numbers from the given text file the condition is that the number should start with 6,7,8 or 9 and it should be of 10 digit long create some set of examples

#### **Code**

```
import re
def filter_indian_mobile_numbers(file_path):
    indian_mobile_numbers = []
    pattern = re.compile(r'\b[6-9]\d{9}\b')

    with open(file_path, 'r') as file:
        content = file.read()
        matches = pattern.findall(content)
        indian_mobile_numbers.extend(matches)

    return indian_mobile_numbers
# Example usage
if __name__ == "__main__":
    file_path = 'mobile_numbers.txt' # Replace
with your file path
    filtered_numbers =
filter_indian_mobile_numbers(file_path)
    print("Filtered Indian Mobile Numbers:")
    for number in filtered_numbers:
        print(number)
```

#### **Output**

```
• Filtered Indian Mobile Numbers:
9876543210
9876543210
8765432109
6123456789
7123456789
8123456789
9123456789
```

#### **Explanation**

using mobile numbers txt file it will filter out the all the indian numbers. in txt file i have already created a set of [numbers](#). it is filter out using condition that which i have given in range 6 - 9 starting numbers and



	contains 10 digits <a href="#">long</a> . it will read txt file which i have given an filer it out all the number as per my conduction.	
6	<p><b>Task Description #6 (Loops – Armstrong Numbers in a Range)</b></p> <p>Task: Write a function using AI that finds all Armstrong numbers in a user-specified range (e.g., 1 to 1000).</p> <p>Instructions:</p> <ul style="list-style-type: none"> <li>• Use a for loop and digit power logic.</li> <li>• Validate correctness by checking known Armstrong numbers (153, 370, etc.).</li> <li>• Ask AI to regenerate an optimized version (using list comprehensions).</li> </ul> <p>Expected Output #7:</p> <ul style="list-style-type: none"> <li>• Python program listing Armstrong numbers in the range.</li> <li>• Optimized version with explanation.</li> </ul> <p><b>Prompt</b></p> <pre>Write a function that finds all Armstrong numbers in a user-specified range (e.g., 1 to 1000).</pre> <p><b>Code</b></p> <pre>def is_armstrong(num):     num_str = str(num)     num_digits = len(num_str)     sum_of_powers = sum(int(digit) ** num_digits for digit in num_str)     return sum_of_powers == num def armstrong_numbers_in_range(start, end):     armstrong_numbers = []     for num in range(start, end + 1):         if is_armstrong(num):             armstrong_numbers.append(num)     return armstrong_numbers # Example usage if __name__ == "__main__":     start_range = int(input("Enter the start of the range: "))     end_range = int(input("Enter the end of the range: "))     armstrong_numbers = armstrong_numbers_in_range(start_range, end_range)</pre>	

```

        print(f"Armstrong numbers between
{start_range} and {end_range}:
{armstrong_numbers}")

print("\n")
print("Recreating using while loop:")
'''regenerate the using list comprehensions'''
def armstrong_numbers_in_range_list_comp(start,
end):
    return [num for num in range(start, end + 1)
if is_armstrong(num)]
# Example usage
if __name__ == "__main__":
    start_range = int(input("Enter the start of
the range: "))
    end_range = int(input("Enter the end of the
range: "))
    armstrong_numbers =
armstrong_numbers_in_range_list_comp(start_range,
end_range)
    print(f"Armstrong numbers between
{start_range} and {end_range} (using list
comprehension): {armstrong_numbers}")
# Analysis:
# Time Complexity: O(n * d) - where n is the
number of numbers in the range and d is the number
of digits in the largest number. Each number
requires checking each digit.
# Space Complexity: O(k) - where k is the number
of Armstrong numbers found in the

```

### Output

```

Enter the start of the range: 1
Enter the end of the range: 1000
Armstrong numbers between 1 and 1000: [1, 2, 3, 4, 5, 6, 7, 8, 9, 153, 370, 371, 407]

Recreating using while loop:
Enter the start of the range: 1
Enter the end of the range: 1000
Armstrong numbers between 1 and 1000 (using list comprehension): [1, 2, 3, 4, 5, 6, 7, 8, 9, 153, 370, 371, 407]

```

### Explanation

The program identifies Armstrong numbers by comparing each number

	with the sum of its digits raised to the power of total digits.	
7	<p><b>Task Description #7 (Loops – Happy Numbers in a Range)</b></p> <p>Task: Generate a function using AI that displays all Happy Numbers within a user-specified range (e.g., 1 to 500).</p> <p>Instructions:</p> <ul style="list-style-type: none"> <li>Implement the logic using a loop: repeatedly replace a number with the sum of the squares of its digits until the result is either 1 (Happy Number) or enters a cycle (Not Happy).</li> <li>Validate correctness by checking known Happy Numbers (e.g., 1, 7, 10, 13, 19, 23, 28...).</li> <li>Ask AI to regenerate an optimized version (e.g., by using a set to detect cycles instead of infinite loops).</li> </ul> <p>Expected Output #8:</p> <ul style="list-style-type: none"> <li>Python program that prints all Happy Numbers within a range.</li> </ul> <pre> Genrate a all Happy Numbers within a user-specified range (e.g., 1 to 500) using functions. </pre> <p><b>Code</b></p> <pre> import time as t def is_happy_number(num):     seen = set()     while num != 1 and num not in seen:         seen.add(num)         num = sum(int(digit) ** 2 for digit in str(num))     return num == 1 start_time = t.time() def happy_numbers_in_range(start, end):     happy_numbers = []     for num in range(start, end + 1):         if is_happy_number(num):             happy_numbers.append(num)     return happy_numbers # Example usage if __name__ == "__main__":     start_range = int(input("Enter the start of the range: "))     end_range = int(input("Enter the end of the </pre>	

```

range: "))
    happy_numbers =
happy_numbers_in_range(start_range, end_range)
    print(f"Happy numbers between {start_range}
and {end_range}: {happy_numbers}")
end_time = t.time()
print(f"Time taken: {end_time - start_time}
seconds")

```

### Output

```

Enter the end of the range: 500
Happy numbers between 1 and 500: [1, 7, 10, 13, 19, 23, 28, 31, 32, 44, 49, 68, 70, 79, 82, 86, 91, 9
4, 97, 100, 103, 109, 129, 130, 133, 139, 167, 176, 188, 190, 192, 193, 203, 208, 219, 226, 230, 236,
239, 262, 263, 280, 291, 293, 301, 302, 310, 313, 319, 320, 326, 329, 331, 338, 356, 362, 365, 367,
368, 376, 379, 383, 386, 391, 392, 397, 404, 409, 440, 446, 464, 469, 478, 487, 490, 496]
Time taken: 4.249208688735962 seconds

Recreating an optimized version:
Enter the start of the range: 1
Enter the end of the range: 500
Happy numbers between 1 and 500 (optimized): [1, 7, 10, 13, 19, 23, 28, 31, 32, 44, 49, 68, 70, 79, 8
2, 86, 91, 94, 97, 100, 103, 109, 129, 130, 133, 139, 167, 176, 188, 190, 192, 193, 203, 208, 219, 22
6, 230, 236, 239, 262, 263, 280, 291, 293, 301, 302, 310, 313, 319, 320, 326, 329, 331, 338, 356, 362
, 365, 367, 368, 376, 379, 383, 386, 391, 392, 397, 404, 409, 440, 446, 464, 469, 478, 487, 490, 496]
Time taken (optimized): 3.5933306217193604 seconds

```

- Optimized version using cycle detection with explanation.

```

'''regenerate an optimized version using a set to
detect cycles instead of infinite loops'''
def is_happy_number_optimized(num):
    seen = set()
    while num != 1:
        if num in seen:
            return False
        seen.add(num)
        num = sum(int(digit) ** 2 for digit in
str(num))
    return True
start_time = t.time()
def happy_numbers_in_range_optimized(start, end):
    happy_numbers = []
    for num in range(start, end + 1):
        if is_happy_number_optimized(num):
            happy_numbers.append(num)
    return happy_numbers
# Example usage
if __name__ == "__main__":
    start_range = int(input("Enter the start of

```

	<pre>the range: "))     end_range = int(input("Enter the end of the range: "))     happy_numbers = happy_numbers_in_range_optimized(start_range, end_range)     print(f"Happy numbers between {start_range} and {end_range} (optimized): {happy_numbers}") end_time = t.time() print(f"Time taken (optimized): {end_time - start_time} seconds")  # Analysis: # Time Complexity: O(n * m) - where n is the number of numbers in the # range and m is the average number of iterations to determine if a number is happy. # Space Complexity: O(k) - where k is the number of happy numbers found in the # range, as they are stored in a list.</pre> <p><b>Explanation</b> <i>Happy numbers are detected by repeatedly summing the squares of digits and using a set to prevent infinite loops.</i></p>	
8	<p><b>Task Description #8 (Loops – Strong Numbers in a Range)</b></p> <p>Task: Generate a function using AI that displays all Strong Numbers (sum of factorial of digits equals the number, e.g., 145 = 1!+4!+5!) within a given range.</p> <p>Instructions:</p> <ul style="list-style-type: none"><li>• Use loops to extract digits and calculate factorials.</li><li>• Validate with examples (1, 2, 145).</li><li>• Ask AI to regenerate an optimized version (precompute digit factorials).</li></ul> <p>Expected Output #9:</p> <ul style="list-style-type: none"><li>• Python program that lists Strong Numbers.</li></ul> <p><b>Prompt</b></p>	

Generate all strong numbers within a user-specified range (e.g., 1 to 500) using functions.

**Code**

```
def factorial(n):
    if n == 0 or n == 1:
        return 1
    result = 1
    for i in range(2, n + 1):
        result *= i
    return result
start_time = t.time()
def is_strong_number(num):
    original_num = num
    sum_of_factorials = 0
    while num > 0:
        digit = num % 10
        sum_of_factorials += factorial(digit)
        num //= 10
    return sum_of_factorials == original_num
def strong_numbers_in_range(start, end):
    strong_numbers = []
    for num in range(start, end + 1):
        if is_strong_number(num):
            strong_numbers.append(num)
    return strong_numbers
# Example usage
if __name__ == "__main__":
    start_range = int(input("Enter the start of the
range: "))
    end_range = int(input("Enter the end of the range:
"))
    strong_numbers =
strong_numbers_in_range(start_range, end_range)
    print(f"Strong numbers between {start_range} and
{end_range}: {strong_numbers}")
end_time = t.time()
print(f"Time taken: {end_time - start_time} seconds")
```

## Output

```
• Enter the start of the range: 1
Enter the end of the range: 1000
Strong numbers between 1 and 1000: [1, 2, 145]
Time taken: 4.145917892456055 seconds

Recreating an optimized version:
Enter the start of the range: 1
Enter the end of the range: 1000
Strong numbers between 1 and 1000 (optimized): [1, 2, 145]
Time taken (optimized): 5.042802810668945 seconds
```

- Optimized version with explanation.

```
def is_strong_number_optimized(num,
factorial_cache={}):
    original_num = num
    sum_of_factorials = 0
    while num > 0:
        digit = num % 10
        if digit not in factorial_cache:
            factorial_cache[digit] =
factorial(digit)
        sum_of_factorials +=
factorial_cache[digit]
        num //= 10
    return sum_of_factorials == original_num
start_time = t.time()
def strong_numbers_in_range_optimized(start, end):
    strong_numbers = []
    for num in range(start, end + 1):
        if is_strong_number_optimized(num):
            strong_numbers.append(num)
    return strong_numbers
# Example usage
if __name__ == "__main__":
    start_range = int(input("Enter the start of
the range: "))
    end_range = int(input("Enter the end of the
range: "))
    strong_numbers =
strong_numbers_in_range_optimized(start_range,
end_range)
    print(f"Strong numbers between {start_range}
and {end_range} (optimized): {strong_numbers}")
```

	<pre>end_time = t.time() print(f"Time taken (optimized): {end_time - start_time} seconds")</pre> <p><b>Explanation</b></p> <p><i>The function checks whether a number equals the sum of factorials of its digits to identify Strong numbers.</i></p>	
9	<p><b>Task #9 – Few-Shot Prompting for Nested Dictionary Extraction</b></p> <p>Objective</p> <p>Use few-shot prompting (2–3 examples) to instruct the AI to create a function that parses a nested dictionary representing student information.</p> <p>Requirements</p> <ul style="list-style-type: none"><li>• The function should extract and return:<ul style="list-style-type: none"><li>○ Full Name</li><li>○ Branch</li><li>○ SGPA</li></ul></li></ul> <p>Expected Output</p> <p>A reusable Python function that correctly navigates and extracts values from nested dictionaries based on the provided examples</p> <p><b>Prompt</b></p> <pre>create a function that parses a nested dictionary representing student information.  The function should extract and return:  Full Name Branch SGPA  Example Input: {     "student1": {         "name": {"first": "Mahesh", "last": "Ch"},         "branch": "CSE",</pre>	



```
        "SGPA": 9.1

    },

    "student2": {"name": {"first": "Rohan", "last":
"Kumar"},

        "branch": "ECE",

        "SGPA": 8.7

    }

}
```

### Code

```
def extract_student_info(students_dict):

    extracted_info = []

    for student_key, student_data in
students_dict.items():

        first_name = student_data['name']['first']

        last_name = student_data['name']['last']

        full_name = f"{first_name} {last_name}"

        branch = student_data['branch']

        sgpa = student_data['SGPA']

        extracted_info.append({

            'Full Name': full_name,

            'Branch': branch,

            'SGPA': sgpa

        })

    return extracted_info

# Example usage

if __name__ == "__main__":

    students = {

        "student1": {

            "name": {"first": "Mahesh", "last": "Ch"},
```

```
        "branch": "CSE",
        "SGPA": 9.1
    },
    "student2": {
        "name": {"first": "Rohan", "last": "Kumar"},
        "branch": "ECE",
        "SGPA": 8.7
    },
    "student3": {
        "name": {"first": "Anita", "last":
"Sharma"},
        "branch": "ME",
        "SGPA": 8.9
    },
    "student4": {
        "name": {"first": "Priya", "last": "Singh"},
        "branch": "CE",
        "SGPA": 9.0
    },
    "student5": {
        "name": {"first": "Vikram", "last":
"Patel"},
        "branch": "EE",
        "SGPA": 8.5
    }
}

student_info = extract_student_info(students)

for info in student_info:
```

	<pre> print(info)  # Analysis:  # Time Complexity: O(n) - where n is the number of students in the dictionary.  # Space Complexity: O(n) - where n is the number of students, as we store the extracted information in a list. </pre> <p><b>Output</b></p> <pre> {'Full Name': 'Mahesh Ch', 'Branch': 'CSE', 'SGPA': 9.1} {'Full Name': 'Rohan Kumar', 'Branch': 'ECE', 'SGPA': 8.7} {'Full Name': 'Anita Sharma', 'Branch': 'ME', 'SGPA': 8.9} {'Full Name': 'Priya Singh', 'Branch': 'CE', 'SGPA': 9.0} {'Full Name': 'Vikram Patel', 'Branch': 'EE', 'SGPA': 8.5} </pre> <p><b>Explanation</b></p> <p><i>The function navigates a nested dictionary structure to correctly extract student full name, branch, and SGPA.</i></p>	
10	<p><b>Task Description #10 (Loops – Perfect Numbers in a Range)</b></p> <p>Task: Generate a function using AI that displays all Perfect Numbers within a user-specified range (e.g., 1 to 1000).</p> <p>Instructions:</p> <ul style="list-style-type: none"> <li>A Perfect Number is a positive integer equal to the sum of its proper divisors (excluding itself). <ul style="list-style-type: none"> <li>Example: <math>6 = 1 + 2 + 3</math>, <math>28 = 1 + 2 + 4 + 7 + 14</math>.</li> </ul> </li> <li>Use a for loop to find divisors of each number in the range.</li> <li>Validate correctness with known Perfect Numbers (6, 28, 496...).</li> <li>Ask AI to regenerate an optimized version (using divisor check only up to <math>\sqrt{n}</math>).</li> </ul> <p>Expected Output #12:</p> <ul style="list-style-type: none"> <li>Python program that lists Perfect Numbers in the given range.</li> </ul>	

**Prompt**

Genrate a perfect numbers within a user-specified range (e.g., 1 to 1000) using functions.

**Code**

```
import time as t
def is_perfect_number(num):
    if num < 2:
        return False
    sum_of_divisors = 1 # 1 is a proper divisor
    for i in range(2, int(num**0.5) + 1):
        if num % i == 0:
            sum_of_divisors += i
            if i != num // i:
                sum_of_divisors += num // i
    return sum_of_divisors == num
start_time = t.time()
def perfect_numbers_in_range(start, end):
    perfect_numbers = []
    for num in range(start, end + 1):
        if is_perfect_number(num):
            perfect_numbers.append(num)
    return perfect_numbers
# Example usage
if __name__ == "__main__":
    start_range = int(input("Enter the start of
the range: "))
    end_range = int(input("Enter the end of the
range: "))
    perfect_numbers =
perfect_numbers_in_range(start_range, end_range)
    print(f"Perfect numbers between {start_range}
and {end_range}: {perfect_numbers}")
end_time = t.time()
print(f"Time taken: {end_time - start_time}
seconds")
```

**Output**

```
Enter the start of the range: 1
Enter the end of the range: 1000
Perfect numbers between 1 and 1000: [6, 28, 496]
Time taken: 5.176040172576904 seconds
```

```
Recreating an optimized version:
Enter the start of the range: 1
Enter the end of the range: 1000
Perfect numbers between 1 and 1000 (optimized): [6, 28, 496]
Time taken (optimized): 4.53221321105957 seconds
```

- Optimized version with explanation.

```
print("Recreating an optimized version:")
def is_perfect_number_optimized(num):
    if num < 2:
        return False
    sum_of_divisors = 1 # 1 is a proper divisor
    for i in range(2, int(num**0.5) + 1):
        if num % i == 0:
            sum_of_divisors += i
            if i != num // i:
                sum_of_divisors += num // i
    return sum_of_divisors == num
start_time = t.time()
def perfect_numbers_in_range_optimized(start,
end):
    perfect_numbers = []
    for num in range(start, end + 1):
        if is_perfect_number_optimized(num):
            perfect_numbers.append(num)
    return perfect_numbers
# Example usage
if __name__ == "__main__":
    start_range = int(input("Enter the start of
the range: "))
    end_range = int(input("Enter the end of the
range: "))
    perfect_numbers =
perfect_numbers_in_range_optimized(start_range,
end_range)
    print(f"Perfect numbers between {start_range}
and {end_range} (optimized): {perfect_numbers}")
end_time = t.time()
print(f"Time taken (optimized): {end_time -
```

```
start_time} seconds")
```

***Explanation***

*Perfect numbers are identified by summing proper divisors efficiently by checking only up to the square root of the number.*