

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8" />

  <meta name="viewport" content="width=device-width, initial-scale=1.0"/>

  <title>CheapGrocer | Grocery Price Comparison</title>


<style>

  body {

    font-family: Arial, sans-serif;

    margin: 0;

    background: #f4f6f9;

  }


  header {

    background: #0a7cff;

    color: white;

    padding: 20px;

    text-align: center;

  }


  .container {

    max-width: 900px;

    margin: auto;

    padding: 20px;

  }
```

```
.search-box {  
  display: flex;  
  gap: 10px;  
  margin-bottom: 20px;  
}
```

```
input {  
  flex: 1;  
  padding: 12px;  
  font-size: 16px;  
}
```

```
button {  
  padding: 12px 20px;  
  font-size: 16px;  
  background: #0a7cff;  
  color: white;  
  border: none;  
  cursor: pointer;  
}
```

```
button:hover {  
  background: #055ed8;  
}
```

```
table {  
  width: 100%;  
  border-collapse: collapse;  
  background: white;  
}
```

```
th, td {  
  padding: 12px;  
  border-bottom: 1px solid #ddd;  
  text-align: center;  
}
```

```
th {  
  background: #eef2f7;  
}
```

```
.cheap {  
  color: green;  
  font-weight: bold;  
}
```

```
.visit {  
  text-decoration: none;  
  background: #0a7cff;  
  color: white;  
  padding: 6px 12px;
```

```
border-radius: 4px;  
}
```

```
footer {  
  margin-top: 40px;  
  padding: 15px;  
  font-size: 14px;  
  color: #666;  
  text-align: center;  
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<header>
```

```
<h1>CheapGrocer</h1>
```

```
<p>Compare grocery prices across apps & buy at the cheapest rate</p>
```

```
</header>
```

```
<div class="container">
```

```
<div class="search-box">
```

```
<input id="product" placeholder="Search product (e.g. Biryani Rice 5kg)" />
```

```
<button onclick="comparePrice()">Compare</button>
```

```
</div>
```

```
<table id="result" style="display:none;">
  <thead>
    <tr>
      <th>Platform</th>
      <th>Price (₹)</th>
      <th>Status</th>
      <th>Buy</th>
    </tr>
  </thead>
  <tbody id="tableBody"></tbody>
</table>
</div>
```

```
<footer>
  Prices may vary by location. We redirect to official grocery platforms.
</footer>
```

```
<script>
function comparePrice() {

  const prices = [
    { name: "JioMart", price: 620, link: "https://www.jiomart.com" },
    { name: "Blinkit", price: 650, link: "https://www.blinkit.com" },
    { name: "Instamart", price: 635, link: "https://www.swiggy.com/instamart" },
    { name: "BigBasket", price: 640, link: "https://www.bigbasket.com" }
  ];
```

```
const minPrice = Math.min(...prices.map(p => p.price));
const tbody = document.getElementById("tableBody");
tbody.innerHTML = "";
```

```
prices.forEach(p => {
  tbody.innerHTML += `
    <tr>
      <td>${p.name}</td>
      <td>₹${p.price}</td>
      <td class="${p.price === minPrice ? 'cheap' : ""}">
        ${p.price === minPrice ? 'Cheapest' : ""}
      </td>
      <td>
        <a class="visit" href="${p.link}" target="_blank">Visit</a>
      </td>
    </tr>
  `;
});
```

```
document.getElementById("result").style.display = "table";
}
</script>

</body>
</html>
```