Multi-cheque collection: mobile app integration

Oct 23, 2026 · @Mahesh

Summary

The Sobha Field Collection app now submits collections through `POST /cheques/bulk/collection`, built to your "Multi-cheque collection" note. An agent adds up to 25 SIGNED cheques for one vendor, photographs each one, and submits once.

- **One endpoint for everything.** The new build uses the bulk endpoint even when only one cheque is collected. It no longer calls `POST /cheques/{chequeId}/collection`, which stays in place for older app versions.
- **Status.** Implemented and unit-tested against a faked HTTP layer that checks the exact field names below. It has not yet been run against a real dev or UAT server.
- **What we need from you.** Answers to the questions in the "Please confirm" section, and a dev or UAT environment with the feature switched on.

What the app sends

A single `multipart/form-data` request with the bearer token. Cheque fields are flat, indexed from 0 with no gaps, and `Items` is never sent as JSON.

Field	Sent	Notes
`CollectorName`	Once	Typed or read from the Emirates ID
`CollectorMobile`	Once	Sent as `+971 <digits>`
`CollectorEmiratesId`	Once	Omitted if the ID number could not be read
`CollectorNationality`	Once	Always sent as an empty string
`CollectorEidExpiryDate`	Once	Always sent as an empty string
`EmiratesIdFront`, `EmiratesIdBack`, `Signature`	Once	Images

Field	Sent	Notes
`CollectorPhoto`, `AcknowledgementVoucher`	Once, optional	Images
`SupportingDocuments`	Once per file, optional	Same key repeated
`Items[i].ChequeId`	Per cheque	GUID
`Items[i].ChequePhoto`	Per cheque	That cheque's own photo

Image parts carry a real content type taken from the file extension: `image/jpeg` for camera photos, `image/png` for the signature. `VendorId` is not sent, because the server already derives the vendor from the cheques.

Example with two cheques:

```
CollectorName=Rashid Kamal
CollectorMobile=+971 501234567
CollectorEmiratesId=784-1991-1234567-3
CollectorNationality=
CollectorEidExpiryDate=
Items[0].ChequeId=<guid-1>
Items[1].ChequeId=<guid-2>
EmiratesIdFront, EmiratesIdBack, Signature (files)
Items[0].ChequePhoto, Items[1].ChequePhoto (files)
```

What the app reads from the response

On 201 the app reads the `collections` array and shows one line per entry (cheque number and amount) on its success screen. Each entry is parsed with the same model as `GET /api/collections/{chequeId}`, so it must carry the full shape. Unknown keys such as `batchId` and `batchCheques` are ignored.

Field	Required	Used for
`id`	Yes	Collection id
`chequeId`, `chequeNumber`	Yes	Success screen, history
`supplierName`	Yes	Vendor name on the success screen
`amount`	Yes	Amount on the success screen

Field	Required	Used for
`collectorName`	Yes	Record
`collectedAt`	Yes	Record timestamp
`collectorMobile`, `collectorEmiratesId`, image URLs, `supportingDocuments`, `newChequeStatus`	No	Detail screen

A missing required field makes the app treat a successful submission as a failure, even though the cheques were already issued on the server.

Please confirm

1. **Full shape per entry.** Your example shows only `chequeId`, `chequeNumber`, `newChequeStatus`, `batchId` and `batchCheques`. Does every entry in `collections` also carry `id`, `supplierName`, `amount`, `collectorName` and `collectedAt`, as in the single-cheque response?
2. **Empty optional text fields.** The app sends `CollectorNationality` and `CollectorEidExpiryDate` as empty strings, which the single-cheque endpoint accepts. Does the bulk endpoint accept them too, or must the keys be omitted?
3. **404 ambiguity.** A 404 means either "a cheque wasn't found" or "the feature is switched off". How can the app tell them apart so it only falls back to one-by-one collection in the second case? A distinct error code or field would do.
4. **409 body.** The message names the offending cheque. Could the body also carry that cheque's `chequeId`, so the app can highlight or remove it for the agent?
5. **File size.** The limit is 5 MB per file and 160 MB per request. The app currently uploads photos as captured, so 25 cheques plus the shared files could exceed 160 MB. Is the 160 MB figure firm, and is 25 cheques in one request realistic for your upload timeouts?
6. **Test environment.** Which dev or UAT server has this endpoint live, and can the feature be enabled there for our test account (Accounts role)?

Error handling in the app today

Any non-2xx response shows the server's `message` to the agent. The draft stays intact, so the agent can fix it and resubmit the whole batch. Behaviour beyond that is still to be built.

Status	Current behaviour	Still to do
400	Shows the message	Nothing
401	Handled by the app's shared auth layer, unchanged	Nothing
403	Collect tab is already hidden for non-Accounts users	Nothing
404	Shows the message	Fall back to one-by-one collection when the feature is off (needs question 3)
409	Shows the message; agent removes the cheque by hand	Auto-highlight the cheque (needs question 4)