

SOP: MuleSoft Integration Dashboard — Usage Guide

Document Type: Standard Operating Procedure

Audience: MuleSoft Platform Operators, Integration Developers

Version: 1.0

Last Updated: August 2026

1. Purpose

This SOP provides step-by-step instructions for using the MuleSoft Integration Dashboard to monitor applications, verify API configurations, inspect CPS properties, and run live health checks against deployed Mule integrations.

2. Prerequisites

Before using the dashboard, confirm:

- ☐ You have an active Anypoint Platform account with at least **Read** access to the relevant Business Groups and Environments.
 - ☐ The dashboard backend is running (<http://localhost:5000> or the hosted URL your team uses).
 - ☐ The dashboard frontend is accessible in your browser (<http://localhost:5173> or the hosted URL).
 - ☐ Your Anypoint session is active (tokens expire after ~60 minutes — re-login if prompted).
-

3. Logging In

1. Open the dashboard URL in your browser.
2. Enter your **Anypoint Platform username** and **password**.
3. Click **Login**.
4. On success, you are redirected to the **Dashboard** home page.

⚠ If login fails, verify your credentials directly on anypoint.mulesoft.com. Do not share credentials with others — each user should log in with their own account.

4. Navigation

The **left sidebar** provides access to all modules:

Sidebar Link	What It Does
 Dashboard	Platform overview — app counts, status charts
 Applications	Full list of all deployed Mule applications
 Environments	List of Anypoint environments
 Business Groups	Organisation / BG hierarchy
 API Manager	API instances, policies, contracts
 Exchange Assets	Anypoint Exchange asset browser
 Ping Test	Live HTTP health-check workspace

5. Viewing the Dashboard (Home)

When to use: Start of day health check; executive overview of platform health.

1. Click **Dashboard** in the sidebar.
 2. Select a **Business Group** from the dropdown at the top, or leave it on **All Organizations** to see the full estate.
 3. Review the summary cards:
 - **Total Applications** — total deployments in scope
 - **Running / Stopped** — live status counts
 - **Total APIs** — API Manager instances registered
 4. Review the **status chart** (donut) and **environment breakdown chart** (bar).
 5. If numbers look unexpected, proceed to the **Applications** page for details.
-

6. Monitoring Applications

When to use: Identifying failed/stopped apps; reviewing what is deployed across BGs.

1. Click **Applications** in the sidebar.
2. Use the filters at the top to narrow results:
 - **Business Group** — select a specific BG or keep **All Organizations**.
 - **Environment** — Production, Sandbox, UAT, etc.
 - **Status** — Running, Stopped, or All.
 - **Search box** — type an app name or partial name.
3. Review the table. Apps are listed with Type (CH1/CH2), Status, Environment, Workers/Replicas, and Runtime Version.
4. Click an **application name** to open the Application Detail page.

6.1 Starting / Stopping / Restarting an Application

1. Locate the application row in the table.
2. Click the ► **Start**,  **Stop**, or  **Restart** button at the end of the row.
3. Wait for the status badge to update (may take 15–30 seconds; refresh if needed).

 Only perform start/stop/restart after confirming with the application owner.
Stopping a production app mid-traffic can cause data loss.

7. Inspecting an Application in Detail

When to use: Troubleshooting a specific app; verifying deployment configuration.

1. From the Applications page, click the application name.
2. Use the **six tabs** to inspect different aspects:

Tab	What to Look For
Overview	Status, runtime version, region, last deployment time
Properties	Property placeholder values (e.g., <code>db.url</code> , <code>api.key</code>)
Infra & Config	Worker size, persistent queues, VPC settings

Tab	What to Look For
CPS Config	Config Property Server values at runtime
Ping Test	Run a live health check from this page (see Section 9)
Raw JSON	Full ARM API response — useful for debugging

Checking CPS Config Values

1. Open the **CPS Config** tab.
 2. Review the key-value pairs.
 3. If values are missing or wrong, escalate to the platform team to update CPS entries in Anypoint.
-

8. Reviewing API Manager Instances

When to use: Governance checks; identifying policy enforcement; finding consumer client IDs.

1. Click **API Manager** in the sidebar.
2. The table lists all API instances with Name, Version, Status, and Environment.
3. Click an API row to expand it and see:

8.1 Applied Policies

- Lists each policy by **name** (e.g., "Client ID Enforcement", "Rate Limiting SLA Based").
- Verify that required policies are applied before going live.
- If a policy shows an unexpected name or is missing, raise a governance ticket.

8.2 Consumer Contracts

- Lists all client applications that have been granted access.
 - Each entry shows: **Consumer App Name**, **Client ID**, **Status** (APPROVED / PENDING / REVOKED), and **SLA Tier**.
 - Use this to identify which teams/apps are consuming your API.
 - If an unknown client ID appears, investigate with the Anypoint Platform admin.
-

9. Running a Ping / Health Check

There are three ways to run a ping test. Choose the method that fits your task.

Method A — Single App Ping (from Application Detail)

When to use: Quick spot-check on one app.

1. Navigate to **Applications** → click the app name.
 2. Click the **Ping Test** tab.
 3. (Optional) Enter `client_id` and `client_secret` if the app's API requires client credentials.
 4. Click **Run Ping**.
 5. Review the result:
 -  **Green / 200** — app is reachable and responded successfully.
 -  **Red / Error** — check the error message and attempt log to identify the cause.
-

Method B — Bulk Ping from Applications Page

When to use: Verifying a set of apps before or after a release; pre-incident sweep.

1. Go to **Applications** in the sidebar.
 2. Filter and/or search to find the apps you want to test.
 3. Tick the **checkboxes** on the left of each row for every app you want to ping.
 - Selected rows float to the top of the table automatically.
 4. Click **Ping Selected** (button appears when at least one row is selected).
 5. The Ping Test page opens with results pre-loaded for all selected apps.
 6. Review the results table (see Section 9.4).
-

Method C — Dedicated Ping Test Page

When to use: Running a full sweep of all apps in scope; ongoing health monitoring.

1. Click **Ping Test** in the sidebar.
2. The page loads all applications visible in the current BG/environment scope.
3. (Optional) Select specific apps using the checkboxes — selected rows float to the top.
4. Click:

- **Run (N selected)** — ping only the checked apps.
 - **Run All** — ping every app in the list.
5. Review results as they populate (see Section 9.4).

9.4 Interpreting Ping Results

Indicator	Meaning	Action
✓ HTTP 200, low latency	App is healthy and responding	No action needed
✓ HTTP 200, high latency (>2s)	App is reachable but slow	Investigate GC, thread contention, or DB latency
⚠ HTTP 401 / 403	App running but credentials rejected	Verify <code>client_id/client_secret</code> ; check Client ID Enforcement policy
⚠ HTTP 404	App running but no matching ping endpoint	Expected for apps without <code>/ping</code> — not a failure
✗ ECONNREFUSED	App port not accepting connections	App may be stopped or crashed — check ARM status
✗ ETIMEDOUT	Request timed out	Check network routing, VPC rules, or app overload
✗ All paths: "No listener"	App running but no HTTP listener configured for any ping path	Not a connectivity failure — inform the app owner to add a <code>/ping</code> or <code>/api/v1/ping</code> endpoint

Expanding a row for more detail:

1. Click anywhere on the result row.
2. The row expands to show:
 - Full URL attempted
 - Error message (if any)
 - Response payload snippet
 - Attempt log (each path tried in sequence)

Toggling "View tested apps":

- Switch to **Tested apps only** to filter out apps that haven't been pinged yet.
-

10. Browsing Exchange Assets

When to use: Discovering published APIs or connectors; verifying spec versions before implementing an integration.

1. Click **Exchange Assets** in the sidebar.
 2. Select a **Business Group** from the dropdown.
 3. (Optional) Enter a search term in the search box.
 4. (Optional) Filter by asset type (REST API, RAML Fragment, Connector, etc.).
 5. Click an asset in the list to open the **detail panel** on the right.
 6. Review the description, version, classifier, tags, and portal link.
-

11. Checking Business Groups and Environments

Business Groups

1. Click **Business Groups** in the sidebar.
2. View the BG hierarchy tree.
3. Note the **Organisation ID** for each BG — useful when raising support tickets or constructing direct API calls.

Environments

1. Click **Environments** in the sidebar.
 2. Review the list of environments (Production, Sandbox, UAT, Design, etc.).
 3. Use environment **IDs** when needed for direct Anypoint API calls.
-

12. Common Workflows

Pre-Release Smoke Test

1. Go to **Applications** → set Status filter to **Running**.
2. Select all apps in scope using checkboxes.

3. Click **Ping Selected**.
 4. On the Ping Test page, review all results.
 5. Flag any apps that return errors for investigation before go-live.
 6. Document the results (screenshot or export) as evidence in your release record.
-

Post-Incident Health Sweep

1. Go to **Ping Test** in the sidebar.
 2. Set BG to the affected Business Group.
 3. Click **Run All**.
 4. Filter by **View tested apps** and sort by HTTP status to identify all failing apps.
 5. For each failing app, click to expand and capture the error and attempt log.
 6. Navigate to Application Detail → **Raw JSON** tab for full deployment state.
-

Verifying a Property Change After Deployment

1. Go to **Applications** → find the redeployed app.
 2. Click the app name → open the **Properties** tab.
 3. Confirm the expected property value is showing.
 4. Open the **CPS Config** tab to verify CPS-managed values.
 5. Run a quick ping from the **Ping Test** tab to confirm the app is responding.
-

Checking Which Apps Are Consuming a Given API

1. Go to **API Manager**.
 2. Find the API instance by name or environment.
 3. Expand the row and open the **Consumer Contracts** section.
 4. Note the Consumer App Name, Client ID, and Contract Status.
 5. If an unexpected consumer appears, notify the API owner and Anypoint Platform admin.
-

13. Troubleshooting the Dashboard Itself

Symptom	Likely Cause	Resolution
Login fails	Wrong credentials or account locked	Verify on anypoint.mulesoft.com directly
All pages show "Unauthorised"	Session expired (60-min token TTL)	Log out and log back in
Applications page shows empty list	No apps in selected BG/environment	Try All Organizations and remove filters
Ping Test shows all ETIMEDOUT	Network/firewall blocking outbound HTTPS from backend server	Check proxy/firewall rules on the machine running the backend
CPS Config tab shows empty	CPS not enabled for this org or app name mismatch	Contact your Anypoint Platform admin
Exchange assets return no results	Search query too narrow or wrong BG selected	Broaden the search or switch to a parent BG
Metrics widgets show "N/A"	Metrics API not returning data for this BG	This is expected for BGs without active traffic or Anypoint Monitoring entitlement

14. Logging Out

1. Click your username or the **Logout** button in the sidebar or header.
2. You will be redirected to the login page.
3. Your server-side session is cleared immediately — no further API calls can be made with the previous token.

 Always log out when leaving your workstation, especially in shared or production-access environments.

15. Quick Reference Card

Task	Where to Go	Key Action
See overall platform health	Dashboard	Check summary cards and charts
Find a stopped/failed app	Applications → Status: Stopped	Review status badge
Start / stop an app	Applications → action buttons	▶ /  buttons on the row
Check property values	App Detail → Properties tab	Read property list
Check CPS values	App Detail → CPS Config tab	Read key-value list
Ping one app quickly	App Detail → Ping Test tab	Click Run Ping
Ping multiple apps	Applications → select rows → Ping Selected	Review Ping Test page
Run full health sweep	Ping Test → Run All	Review results table
Check who consumes an API	API Manager → expand row → Contracts	Note Client ID and status
Find a published API spec	Exchange Assets → search	Click asset for details
View BG org IDs	Business Groups	Note Organisation ID column

16. Do's and Don'ts



Do

- Use **All Organizations** as your default starting point on the Dashboard and Applications pages to get a complete picture.
- Always **select rows and ping before a release** to establish a baseline.
- Check the **attempt log** in expanded ping rows when diagnosing failures — it shows exactly which paths were tried.
- Use the **CPS Config** tab as your first stop when an app behaves differently between environments.

- **Log out** when you're done, especially if accessing production data.

Don't

- Don't **stop or restart production applications** without a change approval and owner sign-off.
- Don't interpret **HTTP 404** as an app failure on the Ping Test page — many apps don't implement a **/ping** endpoint.
- Don't **share your Anypoint credentials** to let others use the dashboard — each user must log in independently.
- Don't treat the dashboard as a real-time monitor — data is fetched on page load/navigation, not streamed live. Refresh to get the latest state.
- Don't use the **Raw JSON** tab data for automated integrations — call the Anypoint APIs directly for that purpose.

For technical issues with the dashboard itself, contact your platform engineering team. For Anypoint Platform access issues, contact your Anypoint Platform administrator.