Complexity Issues in Data-Driven Fuzzy Inference Systems: Systematic Literature Review¹

Jolanta Miliauskaitė¹ and Diana Kalibatiene²

¹ Institute of Data Science and Digital Technologies, Vilnius University, Vilnius, LT-08663, Lithuania

jolanta.miliauskaite@mif.vu.lt

² Vilnius Gediminas Technical University, Vilnius, LT-10223, Lithuania
diana.kalibatiene@vilniustech.lt

Abstract. The development of a data-driven fuzzy inference system (DataFIS) involves the automatic generation of membership functions and fuzzy if-then rules and choosing a particular defuzzification approach. The literature presents different techniques for automatic DataFIS development and highlights different challenges and issues of its automatic development because of its complexity. However, those complexity issues are not investigated sufficiently in a comprehensive way. Therefore, in this paper, we present a systematic literature review (SLR) of journal and conference papers on the topic of DataFIS complexity issues. We review 1 340 papers published between 1991 and 2019, systematize and classify them into categories according to the complexity issues. The results show that DataFIS complexity issues are classified as follows: computational complexity, fuzzy rules complexity, membership functions complexity, input data complexity, complexity of fuzzy rules interpretability, knowledge inferencing complexity and representation complexity, accuracy and interpretability complexity. The results of this study can help researchers and practitioners become familiar with existing DataFIS complexity issues, the extent of a particular complexity issue and to decide for future development.

Keywords: membership function, fuzzy inference system, issue, limitation, complexity

1 Introduction

Development of a data-driven fuzzy inference system (DataFIS) involves automatic generation of membership functions (MFs), which reflect what is known about linguistic variables in application domains, and fuzzy if-then rules, used for inferencing or

¹ Please, cite this paper as: Miliauskaitė J., Kalibatiene D. (2020) Complexity Issues in Data-Driven Fuzzy Inference Systems: Systematic Literature Review. In: Robal T., Haav HM., Penjam J., Matulevičius R. (eds) Databases and Information Systems. DB&IS 2020. Communications in Computer and Information Science, vol 1243. Springer, Cham. https://doi.org/10.1007/978-3-030-57672-1_15

assessment, and choosing a particular defuzzification approach to determine the output variables in interpretable and understandable way for the end-user.

The literature presents different techniques for automatic DataFIS development [1, 2, 3], and highlights different challenges and issues, because of its complexity, like the rule base (RB) complexity [4], data complexity [5], a number of linguistic terms [1, 6]. However, those complexity issues are not investigated sufficiently in a comprehensive way. In the analysed papers, authors have focused on a particular one or two issues separately, like computational complexity [2, 7], MF complexity [8, 9], fuzzy rules complexity [10, 11], etc. This lack of understanding of a general situation hampers progress in the field since academics are offering limited approach [12].

Therefore, the question arises – What are the complexity issues in DataFIS?

In order to answer the question raised, a systematic literature review (SLR) is presented in this paper. SLR has two purposes and contributions. It is used to determine, first, the possible set of complexity issues, and, second, the extent of a particular complexity issue in DataFIS area.

The rest of this paper is structured as follows. Section 2 introduces complexity in the context of DataFIS and explains the use of this concept in this paper. Section 3 presents the review methodology. Section 4 shows the obtained results of SLR. Section 5 discusses the results obtained in the paper. Finally, Section 6 concludes the paper.

2 Background and Related Work

DataFIS consists of four main components [1, 13, 14] (Fig. 1). Data Collection and Pre-Processing is responsible for crisp or linguistic stream collecting from one or multiple sources and its cleaning, organization and integration [15] for future data exploitation in the Fuzzification Mechanism. Fuzzification Mechanism transforms the data stream into MFs using fuzzy set theory. Fuzzy Inference uses MFs and applies a particular fuzzy reasoning mechanism to obtain a fuzzy output. Knowledge base is responsible for the definition and management of fuzzy rules, used by the Fuzzy Inference component for inferencing. Output Processing performs approximation, defuzzification and type reduction to convert the results of inferencing into output data (i.e., crisp or linguistic values), which should be understandable to a Stakeholder or a System.




Fig. 1. The reference schema of a data-driven Fuzzy Inference System (DataFIS).

The distinctive feature of DataFIS is that it is data-driven, i.e., MFs and fuzzy rules are generated from synthetic or real data streams automatically, but not defined by an

expert. In DataFIS knowledge is represented through two levels [1]. First, in the *semantic level* knowledge is expressed as fuzzy sets and MFs. Second, in the *syntactic level* knowledge is represented in a form of fuzzy rules. This understanding of DataFIS and its complexity are used in this paper.

The concept of complexity in DataFIS can be viewed from different perspectives as the primary analysis shows. In [4], the rule base (RB) complexity is measured as the total number of conditions in the antecedents of the rules. Authors of [16] understand complexity as interpretability of RB, and interpretability of fuzzy partitions as integrity of the database (DB). A data complexity is measured in terms of the average number of patterns per variable (i.e., data density) for pattern recognition in [5].

A data-driven Fuzzy Inference System suffers from exponential complexity, which is manifested through a *number of linguistic terms* (number of subspaces on the universe of discourse of input variables) and a *number of input variables* [1]. Complexity is also measured by *counting the number of operations* [6] or *number of elements in RB* including the number of MFs, rules, premises, linguistic terms, etc. [1]. Selecting a small number of linguistic terms and the right linguistic terms is essential for *better interpretability*. Total number of parameters of the fuzzy RB is also a measure of interpretability. A system with less number of *parameters* is more interpretable and less complex [17]. In [1, 18], authors suggest reducing the exponential complexity of FIS be reducing the number of fuzzy (linguistic) terms or the number of fuzzy (linguistic) variables or both. According to [19], the *model interpretability* is measured in terms of complexity: "Complexity is affected by the number of features used for generating the *model: the lower the number of features, the lower the complexity*".

Summing up, the definition of system complexity depends on the complexity of its components. Therefore, in the next section we describe main components of a data-driven fuzzy inference system (DataFIS).

3 Review Methodology

3.1 Review method

The review methodology was developed and executed according to the guidelines and hints provided by [20, 21]. The structure of the methodology is adapted from [22] and presented in Table 1 as a review protocol [23].

Table 1. Review protocol.

Question Formulation

Question Focus: Membership function, development, generation, construction, issue, limit, complex, fuzzy inference system

Question (Q): "What are the complexity issues in DataFIS?"

Keywords and Synonyms: membership function, develop*, generat*, construct*, issue*, limit*, complex*

Effect: Description of different DataFIS development complexity issues; visualisation of statistics by diagrams, view integration.

Field/Scope/Confines: Publications regarding MF and DataFIS issues.

Application: Computer Science (CS), Information Systems (IS), Software Engineering (SE)

Sources Selection

Studies Language: English.

Search string: (fuzzy) AND ("membership function*") AND ("develop*" OR "generat*" OR "construct*") AND ("issue*" OR "limit*" OR "complex*")

Sources list: Web of Science (WoS), https://apps.webofknowledge.com/ (see Section 3.2)

Studies Selection

Studies Inclusion Criteria (IC):

IC1: Universally accepted relevant fundamental works on MF development, MF generation, MF construction, DataFIS and issues, limitations or complexity.

IC2: Papers must be available to download.

Studies Exclusion Criteria (EC):

EC1: Exclude papers, which contain relevant keywords, but MF and DataFIS issues, limitations or complexity are not the main topic of the paper.

EC2: Exclude relevant sources that repeat ideas described in earlier works.

EC3: Exclude papers, whose length is less than 8 pages, since such short papers can present only a general idea, but not describe overall approach.

EC4: If there are several papers of the same authors with the similar abstract, i.e., one paper is an extension of another, the less extended (i.e., containing less pages) paper is excluded.

Studies Type Definition: Journal publications (research papers) and proceeding papers.

Procedures for Papers Selection (PPS):

PPS-1. Run the search strings at the selected source \rightarrow A primary set of papers is obtained.

PPS-2. Extract the title, abstract and keywords of papers for the primary set.

PPS-3. Evaluate a primary set of papers (the title, abstract and keywords) according to IC and EC → A secondary set of paper is obtained.

Selection execution: See Table 2.

Information Extraction

Information Inclusion and Exclusion Criteria Definition: The extracted information from papers must contain definition or analysis of the MF and DataFIS issues.

Synthesis of findings: The information extracted from the papers was tabulated and plotted to present basic information about the research process.

Table 2. Number of papers (Articles (A) or Proceedings Papers (PP)) for each PPS.

Years		PPS-1		PPS-3			
	A	PP	All	A	PP	All	
1991-2019	864	476	1 340	78	23	101	




Fig. 2. Number of papers after PPS-1 and PPS-3.

In Fig. 2, the trend of the research on the topic is illustrated. The number of papers on fuzzy theory application to solve different complex domain problems has raised. This increase of papers can be attributed to technological development. However, the issues related to the usage of fuzzy theory are analyzed insufficiently. Issues related to the usage of fuzzy theory are analyzed more in \underline{A} comparing to PP (Table 2).

3.2 Sources evaluation

The Web of Science (WoS) database was chosen for the analysis, since it covers a wider range of refined and not duplicating researches. WoS and Scopus databases are not overlapping only 12,2 % of documents in Engineering and Computer Science [114]. WoS has an Impact Factor (IF), which is calculated to assess the quality of publications and the level of scientific research in close fields of knowledge. Moreover, WoS presents an easy mechanism to export the search results in different formats, supported by various reference management software, like Mendeley², EndNote³, etc., and bibliometric tools, like VOSviewer⁴, CiteSpace⁵, etc.

3.3 Threats to Validity

For the analysis, papers were chosen based on the searching strategy in Table 1. Validity of the results was performed applying the following measures. *Reading* the abstract and the title of the papers introduces a threat, because the abstract and the title allows excluding not relevant from the first glance papers [12]. Moreover, both authors of this paper have *assessed* the obtained results (primary and secondary sets of papers) independently and combined the results. Finally, to minimize the threat associated with inaccurate extraction of data, only papers describing complexity issues were selected.

² https://www.mendeley.com/?interaction_required=true

³ https://endnote.com/

⁴ https://www.vosviewer.com/

⁵ http://cluster.cis.drexel.edu/~cchen/citespace/

4 Results

The main results of our SLR are presented in Table 3. It consists of eleven columns, nine of which present the complexity issues found. They are as the following: References (R); Year of publication (Year); computational complexity (CC) (1) (i.e., the huge number of calculations in all DataFIS components); complexity of fuzzy rules (CFR) (2) (i.e., extraction, modification and optimization of fuzzy rules); complexity of MF (CMF) (3) (i.e., MF development, optimization, simplification); data complexity (DC) (4) (i.e., related to big data issues); complexity of fuzzy rules interpretability (CFRI) (5); complexity of inferencing (CI) (6); complexity of knowledge representation (CKR) (7) (i.e., development of MF and RB issues); accuracy (ACC) (8) (i.e., the ability to approximate the output of the system accurately); interpretability (I) (9) (i.e., ability to describe the behavior of the system in an interpretable way).

Table 3. The secondary set of papers (1 – analyzed in the paper, 0 – not analyzed).

R	Year	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
[2, 3, 25]	2019	1	0	0	0	0	0	0	0	0
[8]		0	0	1	0	0	0	0	0	0
[24]		1	1	0	0	0	0	0	0	0
[26]		0	1	4	0	0	0	1	1	0
[27]	2018	0	0	1	0	0	0	0	0	0
[28, 29]		0	1		0	0	0	0	0	0
[30]		1	1	0	0	0	0	0	1	0
[7]		1 4	0	0	0	0	0	0	0	0
[1]	2017	0	1	1	0	0	0	0	0	1
[31, 19]		0	0	0	1	0	0	0	0	0
[32]		0	1	1	1	0	0	1	0	0
[33, 35, 36]	2016	1	0	0	0	0	0	0	0	0
[34, 10]		0	1	0	0	0	0	0	0	0
[37]		0	0	1	0	0	0	0	0	0
[9, 40]	2015	0	0	1	0	0	0	0	0	0
[38]		0	1	0	0	0	0	0	0	0
[39]		1	0	0	0	0	0	0	0	0
[41]	2014	0	0	1	0	0	0	0	0	0
[11]		0	1	0	0	0	0	0	0	0
[42]		0	1	1	0	0	0	1	0	0
[43]		0	1	0	0	1	0	0	0	0
[44]	P	0	0	0	1	0	0	0	0	0
[45]		1	0	0	0	0	0	0	0	0
[46]	2013	1	0	0	0	0	0	0	0	0
[48]		0	1	0	0	0	0	0	0	1
[49]		0	1	1	0	0	0	0	0	0
[50]		0	0	1	0	0	0	0	0	0
[51, 52, 53]	2012	0	1	0	0	0	0	0	0	0
[54]	2012	1	0	0	0	0	0	1	0	0
[47]		1	1	0	0	0	0	0	0	0
[55]		0	0	0	1	0	0	0	0	0
[56] [57]		0	0	0	0	0	0	0	0	0
	2011								_	
[16]	2011	0	0	1	0	0	0	0	0	0
[58]		U	1	1	U	U	U	U	U	U

[59] [60]	Year	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	
[60]			0	1	0	0	0	0	0	(9)
		0	0	0	1	0	0	0	0	0
	2010	0	0	1	0	0	0	1	0	0
[62, 4, 64]		0	1	1	0	0	0	0	0	0
[63]		0	1	0	0	0	0	0	0	0
[65]		0	0	1	0	0	0	0	0	0
[66]	2009	0	1	0	0	0	0	0	0	0
[67, 68, 69]		1	0	0	0	0	0	0	0	0
[70]	2008	0	1	0	0	0	1	0	0	0
[71]		1	0	0	0	0	0	0	0	0
[72]		0	1	0	0	0	0	0	0	0
[73]	2007	1	0	0	0	0	0	0	0	0
[74]		0	1	0	0	0	0	0	1	1
[75]		0	1	0	0	0	0	0	0	0
[76]		0	1	0	0	0	0	0	1	0
[77]		1	0	0	0	0	0	0	1	0
[78, 80, 81, 82]	2006	0	1	0	0	0	0	0	0	0
[79]		0	1	0	0	0	1	0	0	0
[83, 84]	2005	0	1	0	0	0	0	0	0	0
[85]		1	1	0	0	0	0	0	0	0
[86, 87]	2004	0	1	0	0	0	0	0	0	0
[88, 90]	2003	1	0	0	0	0	0	0	0	0
[89]		0	0	0	0	0	0	1	0	0
[91]	2002	0	1	0	0	0	0	0	0	0
[92, 95]	2001	0	4	0	0	0	0	1	0	0
[93]		1	1	0	0	0	0	1	0	0
[94]		0	1	0	0	1	0	0	0	0
[96]	400000000	0	0	0	0	0	0	0	0	0
[97]	2000	No.	4000000000	D	0					0
[98]	2000	0	0	0	0	0	0	0	0	0
[100]	4	0	1	0	0	0	0	0	0	0
[101]		1	1	0	0	0	0	1	0	0
[102]	1999	0	1	0	1	0	0	0	0	0
[103]	1998	0	1	0	0	0	0	0	0	0
[104]	1997	1	0	0	0	0	0	0	0	0
[104]	1997	1	1	0	0	0	0	0	0	0
[106]	1996	1	0	0	0	0	0	0	0	0
[107, 108]	.,,,,	0	1	0	0	0	0	0	0	0
[109, 111]	1995	0	0	0	0	0	0	1	0	0
[110]		0	0	1	0	0	0	0	0	0
[112]		0	1	0	0	0	0	0	0	0
[113]	1993	0	1	0	0	0	0	0	0	0

Temporal distribution of nine complexity issues (CC (1), CFR (2), CMF (3), DC (4), CFRI (5), CI (6), CKR (7), ACC (8), I (9)) found in the papers included in the review, are given in Fig. 4. The size of the bubbles indicates the number of papers analyzing each complexity issue.




Fig. 3. Found complexity issues according to years.

5 Discussion and Conclusions

Finally, we can summarise the obtained results and answer to the research question "What are the complexity issues in DataFIS?". Based on Table 3, nine main issues are extracted from the analysed papers. Fig. 4 shows that the computational complexity (CC) (1) and complexity of fuzzy rules (CFR) (2) remained relevant throughout the analysed years (1991-2019). The complexity of MF (CMF) (3) issue becomes relevant since 2010. Such relevance of the issue can be explained by the growth of technologies that generate increasing amounts of data. Therefore, the need to develop MFs from large data strings that requires high computational power is raised. The data complexity (DC) (4) issue becomes relevant since 2011. Its relevance can be explained by the emergence of big data and unstructured data and their usage in DataFIS. The issues related to complexity of fuzzy rules interpretability (CFRI) (5), complexity of inferencing (CI) (6), accuracy (ACC) (8) and interpretability (I) (9) are weakly expressed directly because they are analysed in tandem with other issues.

The correlation analysis of complexity issues shows that in 67,33 % (68 papers of 101) of papers authors consider only one particular complexity issue. In 24,75 % (25) – two complexity issues, in 5,94 % (6) – three complexity issues, and in 1,98 % (2) – four complexity issues are analysed in tandem. Summing up, it shows that DataFIS complexity issue is characterized by complexity issues related to its components (see Section 2), but not separately. Therefore, the DataFIS complexity issue should be analysed as an ensemble of components complexity issues. In the future research, we are going to do the following: 1) to extend our SLR to several sources; 2) to offer a decision tree of complexity issue solutions existing in the literature now.

References

- Askari, S.: A novel and fast MIMO fuzzy inference system based on a class of fuzzy clustering algorithms with interpretability and complexity analysis. EXPERT SYST APPL, 84, 301-322 (2017). doi: 10.1016/j.eswa.2017.04.045
- Ruiz-Garcia, G., Hagras, H., Pomares, H., Rojas, I. Towards a fuzzy logic system based on general forms of interval type-2 fuzzy sets. IEEE T FUZZY SYST, 27(12), 2381-2395 (2019). doi: 10.1109/TFUZZ.2019.2898582
- Lee, R.S.: Chaotic Interval Type-2 Fuzzy Neuro-oscillatory Network (CIT2-FNON) for Worldwide 129 Financial Products Prediction. INT J FUZZY SYST, 21(7), 2223-2244 (2019). doi: 10.1007/s40815-019-00688-w
- Antonelli, M., Ducange, P., Lazzerini, B., Marcelloni, F.: Exploiting a three-objective evolutionary algorithm for generating Mamdani fuzzy rule-based systems. In: FUZZ-IEEE 2010, pp. 1-8. IEEE, Barcelona, Spain (2010). doi: 10.1109/FUZZY.2010.5583965
- Alcalá, R., Ducange, P., Herrera, F., Lazzerini, B., Marcelloni, F.: A multiobjective evolutionary approach to concurrently learn rule and data bases of linguistic fuzzy-rule-based systems. IEEE T FUZZY SYST, 17(5), 1106-1122 (2009).
- Ephzibah, E.P.: Time complexity analysis of genetic-fuzzy system for disease diagnosis. ACIJ, 2(4), 23-31 (2011). doi: 10.5121/acij.2011.2403
- Zhu, X., Pedrycz, W., Li, Z.: Granular representation of data: A design of families of ε-information granules. IEEE T FUZZY SYST, 26(4), 2107-2119 (2017).
- Fan, X., Li, C., Wang, Y.: Strict intuitionistic fuzzy entropy and application in network vulnerability evaluation. SOFT COMPUT, 23(18), 8741-8752 (2019).
- Ibarra, L., Rojas, M., Ponce, P., Molina, A.: Type-2 Fuzzy membership function design method through a piecewise-linear approach. EXPERT SYST APPL, 42(21), 7530-7540 (2015). doi: 10.1016/j.eswa.2015.05.029
- Harandi, F.A., Derhami, V.: A reinforcement learning algorithm for adjusting antecedent parameters and weights of fuzzy rules in a fuzzy classifie. J INTELL FUZZY SYST, 30(4), 2339-2347 (2016). doi: 10.3233/IFS-152004
- Bouchachia, A., Vanaret, C.: GT2FC: An online growing interval type-2 self-learning fuzzy classifier. IEEE T FUZZY SYST, 22(4), 999-1018 (2013).
- 12. Ivarsson, M., Gorschek, T.: A method for evaluating rigor and industrial relevance of technology evaluations. EMPIR SOFTW ENG, 16(3), 365-395 (2011).
- Takagi, T., Sugeno, M.: Fuzzy identification of systems and its applications to modeling and control. IEEE TRANS SYST, MAN, CYBERN SYST, SMC-15(1), 116-132 (1985). doi: 10.1109/TSMC.1985.6313399
- 14. Mamdani, E.H.: Application of fuzzy algorithms for control of simple dynamic plant. In: IEE 1974. Vol. 121, No. 12, pp. 1585-1588. IET (1974).
- Wang, H., Xu, Z., Pedrycz, W.: An overview on the roles of fuzzy set techniques in big data processing: Trends, challenges and opportunities. KNOWL BASED SYST, 118, 15-30 (2017). doi: 10.1016/j.knosys.2016.11.008
- Antonelli, M., Ducange, P., Lazzerini, B., Marcelloni, F.: Learning knowledge bases of multi-objective evolutionary fuzzy systems by simultaneously optimizing accuracy, complexity and partition integrity. SOFT COMPUT, 15, 2335-2354 (2011). Doi: 10.1007/s00500-010-0665-0
- Ishibuchi, H., Nojima, Y.: Discussions on Interpretability of Fuzzy Systems using Simple Examples. In: IFSA/EUSFLAT 2009, pp. 1649-1654 (2009).
- 18. Kaynak, O., Jezernik, K., Szeghegyi, A.: Complexity reduction of rule based models: a survey. In: FUZZ-IEEE'02. Vol. 2, pp. 1216-1221. IEEE (2002).

- Antonelli, M., Ducange, P., Marcelloni, F., & Segatori, A.: On the influence of feature selection in fuzzy rule-based regression model generation. INFORM SCIENCES, 329, 649-669 (2016). doi: 10.1016/j.ins.2015.09.045
- 20. Kitchenham, B., Charters, S.: Guidelines for Performing Systematic Literature Reviews in Software Engineering. Technical report. Keele University (2007)
- Kitchenham, B., Brereton, O.P., Budgen, D., Turner, M., Bailey, J., Linkman, S.: Systematic literature reviews in software engineering A systematic literature review. INF SOFTW TECHNOL, 51(1), 7-15 (2009). doi: 10.1016/j.infsof.2008.09.009
- Dybå, T., Dingsøyr, T.: Empirical studies of agile software development: A systematic review. INFORM SOFTWARE TECH, 50(9-10), 833-859 (2008). doi: 10.1016/j.infsof.2008.01.006
- 23. Miliauskaitė, J.: A fuzzy inference-based approach to planning quality of enterprise business services. Doctoral dissertation. Vilnius University (2015)
- Marimuthu, P., Perumal, V., Vijayakumar, V.: OAFPM: optimized ANFIS using frequent pattern mining for activity recognition. J SUPERCOMPUT, 1-20 (2019). doi: 10.1007/s11227-019-02802-z
- Melin, P., Ontiveros-Robles, E., Gonzalez, C.I., Castro, J.R., Castillo, O.: An approach for parameterized shadowed type-2 fuzzy membership functions applied in control applications. SOFT COMPUT, 23(11), 3887-3901 (2019). doi: 10.1007/s00500-018-3503-4
- Rajeswari, A.M., Deisy, C.: Fuzzy logic based associative classifier for slow learners prediction. J INTELL FUZZY SYST, 36(3), 2691-2704 (2019). doi: 10.3233/JIFS-18748
- 27. Elkano, M., Uriz, M., Bustince, H., Galar, M.: On the usage of the probability integral transform to reduce the complexity of multi-way fuzzy decision trees in Big Data classification problems. In: IEEE BigData Congress 2018, pp. 25-32. IEEE (2018)
- 28. Altilio, R., Rosato, A., Panella, M.: A Sparse Bayesian Model for Random Weight Fuzzy Neural Networks. In: FUZZ-IEEE, pp. 1-7. IEEE (2018)
- Ravi, C., Khare, N.: BGFS: Design and development of brain genetic fuzzy system for data classification. INT J INTELL SYST, 27(2), 231-247 (2018). doi: 10.1515/jisys-2016-0034
- 30. Golestaneh, P., Zekri, M., Sheikholeslam, F.: Fuzzy wavelet extreme learning machine. FUZZY SET SYST, 342, 90-108 (2018). doi: 10.1016/j.fss.2017.12.006
- 31. Ge, X., Wang, P., Yun, Z.: The rough membership functions on four types of covering-based rough sets and their applications. INFORM SCIENCES, 390, 1-14 (2017). doi: 10.1016/j.ins.2017.01.032
- Dineva, A., Várkonyi-Kóczy, A., Tar, J.K., Piuri, V.: Performance enhancement of fuzzy logic controller using robust fixed point transformation. In: Jabłoński, R., Szewczyk, R. (eds.) Recent Global Research and Education: Technological Challenges. AISC, vol 519, pp. 411-418. Springer, Cham (2017). doi: 10.1007/978-3-319-46490-9_55
- Ananthi, V. P., Balasubramaniam, P., Kalaiselvi, T.: A new fuzzy clustering algorithm for the segmentation of brain tumor. SOFT COMPUT, 20(12), 4859-4879 (2016). doi: 10.1007/s00500-015-1775-5
- 34. Tan, Y., Li, J., Wonders, M., Chao, F., Shum, H.P., Yang, L.: Towards sparse rule base generation for fuzzy rule interpolation. In: FUZZ-IEEE 2016, pp. 110-117. IEEE (2016)
- Chen, S.Y., Lee, C.Y., Wu, C.H., Hung, Y.H.: Intelligent motion control of voice coil motor using PID-based fuzzy neural network with optimized membership function. ENG COMPUTATION, 33(8), 2302-2319 (2016). doi: 10.1108/EC-08-2015-0250
- Ren, P., Xu, Z., Lei, Q.: Simplified interval-valued intuitionistic fuzzy sets with intuitionistic fuzzy numbers. J INTELL FUZZY SYST, 30(5), 2871-2882 (2016). doi: 10.3233/IFS-151735

- Almasi, O. N., Rouhani, M.: A new fuzzy membership assignment and model selection approach based on dynamic class centers for fuzzy SVM family using the firefly algorithm.
 TURK J ELEC ENG & COMP SCI, 24, 1797-1814 (2016). doi: 10.3906/elk-1310-253
- 38. Shill, P.C., Akhand, M.A.H., Asaduzzaman, M.D., Murase, K.: Optimization of fuzzy logic controllers with rule base size reduction using genetic algorithms. INT J INF TECH DECIS, **14**(05), 1063-1092 (2015). doi: 10.1109/CICA.2013.6611664
-)Kumbasar, T., Hagras, H. (2015). A self-tuning zSlices-based general type-2 fuzzy PI controller. IEEE T FUZZY SYST, 23(4), 991-1013 (2015). doi: 10.1109/TFUZZ.2014.2336267
- Kaur, P., Kumar, S., Singh, A.P.: Nature Inspired Approaches for Identification of Optimized Fuzzy Model: A Comparative Study. MVLSC, 25(6), 555-587 (2015)
- Deng, X., Yao, Y.: Decision-theoretic three-way approximations of fuzzy sets. INFORM SCIENCES, 279, 702-715 (2014). doi: 10.1016/j.ins.2014.04.022
- Sami, M., Shiekhdavoodi, M.J., Pazhohanniya, M., Pazhohanniya, F.: Environmental comprehensive assessment of agricultural systems at the farm level using fuzzy logic: a case study in cane farms in Iran. ENVIRON MODEL SOFTW, 58, 95-108 (2014). doi: 10.1016/j.envsoft.2014.02.014
- GaneshKumar, P., Rani, C., Devaraj, D., Victoire, T.A.A.: Hybrid ant bee algorithm for fuzzy expert system based sample classification. TCBB, 11(2), 347-360 (2014). doi: 10.1109/TCBB.2014.2307325
- Chaudhuri, A.: Modified fuzzy support vector machine for credit approval classification. AI COMMUNICATIONS, 27(2), 189-211 (2014). doi: 10.3233/AIC-140597
- 45. Ramathilaga, S., Jiunn-Yin Leu, J., Huang, K.K., Huang, Y.M.: Two novel fuzzy clustering methods for solving data clustering problems. J INTELL FUZZY SYST, **26**(2), 705-719 (2014). doi: 10.3233/IFS-120761
- 46. Zhu, X.-L., Chen, B., Wang, Y., Yue, D.: H∞ stabilization criterion with less complexity for nonuniform sampling fuzzy systems. FUZZY SETS SYST, 225, 58-73 (2013). doi: 10.1016/j.fss.2012.12.011
- Chakraborty, A., Konar, A., Pal, N. R., Jain, L. C.: Extending the contraposition property of propositional logic for fuzzy abduction. IEEE T FUZZY SYST, 21(4), 719-734 (2012). doi: 10.1109/TFUZZ.2012.2230006
- 48. Soua, B., Borgi, A., Tagina, M.: An ensemble method for fuzzy rule-based classification systems. KNOWL INF SYST, 36(2), 385-410 (2013). doi: 10.1007/s10115-012-0532-7
- Pratama, M., Er, M.J., Li, X., Oentaryo, R.J., Lughofer, E., Arifin, I.: Data driven modeling based on dynamic parsimonious fuzzy neural network. NEUROCOMPUTING, 110, 18-28 (2013). doi: 10.1016/j.neucom.2012.11.013
- Alaei, H.K., Salahshoor, K., Alaei, H.K.: A new integrated on-line fuzzy clustering and segmentation methodology with adaptive PCA approach for process monitoring and fault detection and diagnosis. SOFT COMPUT, 17(3), 345-362 (2013). doi: 10.1007/s00500-012-0910-9
- Samantaray, S.R.: A systematic fuzzy rule based approach for fault classification in transmission lines. APPL SOFT COMPUT, 13(2), 928-938 (2013). doi: 10.1016/j.asoc.2012.09.010
- 52. Kumar, P.G., Vijay, S.A.A., Devaraj, D.: A hybrid colony fuzzy system for analyzing diabetes microarray data. In: IEEE CIBCB 2013, pp. 104-111. IEEE (2013)
- 53. Ansari, A.Q., Biswas, R., Aggarwal, S.: Neutrosophic classifier: An extension of fuzzy classifier. APPL SOFT COMPUT, 13(1), 563-573 (2013). doi: 10.1016/j.asoc.2012.08.002
- Lou, C.W., Dong, M.C.: Modeling data uncertainty on electric load forecasting based on Type-2 fuzzy logic set theory. ENG APPL ARTIF INTELL, 25(8), 1567-1576 (2012). doi: 10.1016/j.engappai.2012.07.006

- Sanz, J., Bustince, H., Fernández, A., Herrera, F.: IIVFDT: Ignorance functions based interval-valued fuzzy decision tree with genetic tuning. INT J UNCERTAIN FUZZ, 20(supp02), 1-30 (2012). doi: 10.1142/S0218488512400132
- Murshid, A.M., Loan, S.A., Abbasi, S.A., Alamoud, A.R.M.: A novel VLSI architecture for a fuzzy inference processor using triangular-shaped membership function. INT J FUZZY SYST, 14(3), 345-360 (2012)
- Chiu, H.-P., Tang, Y.-T., Hsieh, K.-L.: Applying cluster-based fuzzy association rules mining framework into EC environment. APPL SOFT COMPUT, 12(8), 2114-2122 (2012). doi: 10.1016/j.asoc.2011.08.010
- Antonelli, M., Ducange, P., Lazzerini, B., Marcelloni, F.: Learning concurrently data and rule bases of Mamdani fuzzy rule-based systems by exploiting a novel interpretability index. SOFT COMPUT, 15(10), 1981-1998 (2011). doi: 10.1007/s00500-010-0629-4
- 59. Tamir, D.E., Kandel, A.: Axiomatic theory of complex fuzzy logic and complex fuzzy classes. IJCCC, 6(3), 562-576 (2011). doi: 10.15837/ijccc.2011.3.2135
- Shill, P.C., Hossain, M.A., Amin, M.F., Murase, K.: An adaptive fuzzy logic controller based on real coded quantum-inspired evolutionary algorithm. In: FUZZ-IEEE 2011, pp. 614-621 (2011)
- 61. Al-Mamun, A., Zhu, Z.: PSO-optimized fuzzy logic controller for a single wheel robot. In: Vadakkepat, P. et al. (eds.) Trends in Intelligent Robotics. FIRA 2010. CCIS, vol 103, pp. 330-337. Springer, Berlin, Heidelberg (2010). doi: 10.1007/978-3-642-15810-0_42.
- Rania, C., Deepa, S.N.: PSO with mutation for fuzzy classifier design. PROCEDIA COMPUT SCI, 2, 307-313 (2010). doi: 10.1016/j.procs.2010.11.040
- 63. Kim, D.W., de Silva, C. W., Park, G.T.: Evolutionary design of Sugeno-type fuzzy systems for modelling humanoid robots. INT J SYST SCI, 41(7), 875-888 (2010). doi: 10.1080/00207720903474314
- Beldjehem, M.: A unified granular fuzzy-neuro min-max relational framework for medical diagnosis. INT J ADV INTELL PARADIG, 3(2), 122-144 (2010). doi: 10.1504/IJAIP.2011.039745
- Fateh, M.-M.: Robust fuzzy control of electrical manipulators. J INTELL ROBOT SYST. 60(3-4), 415-434 (2010). doi: 10.1007/s10846-010-9430-y
- Leng, G., Zeng, X.J., Keane, J.A.: A hybrid learning algorithm with a similarity-based pruning strategy for self-adaptive neuro-fuzzy systems. APPL SOFT COMPUT, 9(4), 1354-1366 (2009). doi: 10.1016/j.asoc.2009.05.006
- 67. Choi, B.-I., Rhee, F.C.-H.: Interval type-2 fuzzy membership function generation methods for pattern recognition. INF SCI, **179**(13), 2102-2122 (2009). doi: 10.1016/j.ins.2008.04.009
- 68. Starczewski, J.T.: Efficient triangular type-2 fuzzy logic systems. INT J APPROX REASON, 50(5), 799-811 (2009). doi: 10.1016/j.ijar.2009.03.001
- Lee, C.-H., Pan, H.-Y.: Performance enhancement for neural fuzzy systems using asymmetric membership functions. FUZZY SETS SYST, 160(7), 949-971 (2009). doi: 10.1016/j.fss.2008.09.007
- 70. Huang, Z., & Shen, Q.: Fuzzy interpolation and extrapolation: A practical approach. IEEE T FUZZY SYST, 16(1), 13-28 (2008). doi: 10.1109/TFUZZ.2007.902038
- 71. Nie, M., Tan, W.W.: Towards an efficient type-reduction method for interval type-2 fuzzy logic systems. In: 2008 IEEE international conference on fuzzy systems (IEEE World Congress on Computational Intelligence), pp. 1425-1432. IEEE, Hong Kong, (2008)
- 72. Feng, H.-M., Wong, C.-C.: Fewer hyper-ellipsoids fuzzy rules generation using evolutional learning scheme. CYBERNET SYST, **39**(1), 19-44 (2008). doi: 10.1080/01969720701710022

- 73. Modi, P.K., Singh, S.P., Sharma, J.D.: Voltage stability evaluation of power system with FACTS devices using fuzzy neural network. ENG APPL ARTIF INTELL, **20**(4), 481-491 (2007). doi: 10.1016/j.engappai.2006.08.003
- Liu, F., Quek, C., Ng, G.S.: A novel generic hebbian ordering-based fuzzy rule base reduction approach to Mamdani neuro-fuzzy system. NEURAL COMPUT, 19(6), 1656-1680 (2007). doi: 10.1162/neco.2007.19.6.1656
- Kenesei, T., Roubos, J.A., Abonyi, J.: A combination-of-tools method for learning interpretable fuzzy rule-based classifiers from support vector machines. In: Yin, H. et al. (eds.) IDEAL 2007. LNCS, vol 4881, pp. 477-486. Springer, Berlin, Heidelberg (2007). doi: 10.1007/978-3-540-77226-2_49
- González, J., Rojas, I., Pomares, H., Herrera, L.J., Guillén, A., Palomares, J.M., Rojas, F.: Improving the accuracy while preserving the interpretability of fuzzy function approximators by means of multi-objective evolutionary algorithms. INT J APPROX REASON, 44(1), 32-44 (2007). doi: 10.1016/j.ijar.2006.02.006
- 77. Pan, H.Y., Lee, C. H., Chang, F. K., Chang, S. K.: Construction of asymmetric type-2 fuzzy membership functions and application in time series prediction. In: ICMLC 2007, vol. 4, pp. 2024-2030. IEEE, Hong Kong (2007). doi: 10.1109/ICMLC.2007.4370479
- Xiong, N., Funk, P.: Construction of fuzzy knowledge bases incorporating feature selection. SOFT COMPUT, 10(9), 796-804 (2006). doi: 10.1007/s00500-005-0009-7
- 79. Huang, Z., Shen, Q.: Fuzzy interpolative reasoning via scale and move transformations. IEEE T FUZZY SYST, 14(2), 340-359 (2006). doi: 10.1109/TFUZZ.2005.859324
- Kim, M. W., Khil, A., Ryu, J.W.: Efficient fuzzy rules for classification. In: AIDM 2006, pp. 50-57. IEEE (2006)
- 81. Zanganeh, M., Mousavi, S.J., Etemad-Shahidi, A.: A genetic algorithm-based fuzzy inference system in prediction of wave parameters. In: Reusch, B. (ed.) 9th Fuzzy Days in Dortmund International Conference. INT J COMPUT INTELL APPL, pp. 741-750. Springer, Berlin, Heidelberg (2006)
- 82. Kim, M.W., Ryu, J.W.: Optimized fuzzy decision tree using genetic algorithm. In: King, I. et al. (eds.) ICONIP 2006. LNCS, vol 4234, pp. 797-806. Springer, Berlin, Heidelberg (2006), doi: 10.1007/11893295 88
- Casillas, J., Cordón, O., del Jesus, M.J., Herrera, F.: Genetic tuning of fuzzy rule deep structures preserving interpretability and its interaction with fuzzy rule set reduction. IEEE T FUZZY SYST, 13(1), 13-29 (2005). doi: 10.1109/TFUZZ.2004.839670
- Kim, M.W., Ryu, J.W.: Optimized fuzzy classification using genetic algorithm. In: Wang, L., Jin, Y. (eds.) FSKD 2005. LNCS, vol 3613, pp. 392-401. Springer, Berlin, Heidelberg (2005). doi: 10.1007/11539506_51
- Kóczy, L.T., Botzheim, J.: Fuzzy models, identification and applications. In IEEE ICCC 2005, pp. 13-19. IEEE (2005)
- Baranyi, P., Kóczy, L.T., Gedeon, T.D.: A generalized concept for fuzzy rule interpolation. IEEE T FUZZY SYST, 12(6), 820-837 (2004). doi: 10.1109/TFUZZ.2004.836085
- 87. Kim, M.W., Ryu, J.W.: Optimized fuzzy classification for data mining. In: Lee, Y. et al. (eds.) DASFAA 2004. LNCS, vol 2973, pp. 582-593. Springer, Berlin, Heidelberg (2004). doi: 10.1007/978-3-540-24571-1_53
- 88. Hong, T.P., Lin, K.Y., Chien, B.C.: Mining fuzzy multiple-level association rules from quantitative data. APPL INTELL, 18(1), 79-90 (2003). doi: 10.1023/A:1020991105855
- Makrehchi, M., Basir, O., Kamel, M.: Generation of fuzzy membership function using information theory measures and genetic algorithm. In: Bilgiç, T. et al. (eds.) IFSA 2003.
 LNCS, vol 2715, pp. 603-610. Springer, Berlin, Heidelberg (2003). doi: 10.1007/3-540-44967-1_72

- Hsu, C.C., Szu, H.H.: Chaotic neural network for learnable associative memory recall. In: Independent Component Analyses, Wavelets, and Neural Networks. Vol. 5102, pp. 258-266. SPIE (2003). doi: 10.1117/12.502480
- 91. Xiong, N., Litz, L.: Reduction of fuzzy control rules by means of premise learning-method and case study. FUZZY SETS SYST, 132(2), 217-231 (2002). doi: 10.1016/S0165-0114(02)00112-4
- Xiong, N.: Evolutionary learning of rule premises for fuzzy modelling. INT J SYST SCI, 32(9), 1109-1118 (2001). doi: 10.1080/00207720010015735
- 93. Mitaim, S., Kosko, B.: The shape of fuzzy sets in adaptive function approximation. IEEE T FUZZY SYST, 9(4), 637-656 (2001). doi: 10.1109/91.940974
- 94. Guillaume, S.: Designing fuzzy inference systems from data: An interpretability-oriented review. IEEE T FUZZY SYST, **9**(3), 426-443 (2001). doi: 10.1109/91.928739
- 95. Di, L., Srikanthan, T., Chandel, R.S., Katsunori, I.: Neural-network-based self-organized fuzzy logic control for arc welding. ENG APPL ARTIF INTELL, 14(2), 115-124 (2001). doi: 10.1016/S0952-1976(00)00057-9
- Matarazzo, B., Munda, G.: New approaches for the comparison of LR fuzzy numbers: a theoretical and operational analysis. FUZZY SETS SYST, 118(3), 407-418 (2001). doi: 10.1016/S0165-0114(98)00425-4
- 97. Alcalá, R., Casillas, J., Cordón, O., Herrera, F.: Building fuzzy graphs: features and taxonomy of learning for non-grid-oriented fuzzy rule-based systems. J INTELL FUZZY SYST, 11(3-4), 99-119 (2001)
- 98. Yao, J., Dash, M., Tan, S. T., Liu, H.: Entropy-based fuzzy clustering and fuzzy modeling. FUZZY SETS SYST, **113**(3), 381-388 (2000), doi: 10.1016/S0165-0114(98)00038-4
- 99. Hsu, Y.T., Chen, C.M.: A novel fuzzy logic system based on N-version programming. IEEE T FUZZY SYST, 8(2), 155-170 (2000). doi: 10.1109/91.842150
- Rojas, I., Pomares, H., Ortega, J., Prieto, A.: Self-organized fuzzy system generation from training examples. IEEE T FUZZY SYST, 8(1), 23-36 (2000). doi: 10.1109/91.824763
- 101. Gil, J., Hwang, C.-S.: A Design of Genetic-Fuzzy Systems Using Grammatical Encoding and Its Applications. In: Mohammadian, M. (ed.) New Frontiers in Computational Intelligence and Its Applications, vol. 57, pp. 178-196. IOS Press, Amsterdam (2000).
- Hong, T.P., Chen, J.B.: Finding relevant attributes and membership functions. FUZZY SETS SYST, 103(3), 389-404 (1999). doi: 10.1016/S0165-0114(97)00187-5
- Lu, P.C.: The application of fuzzy neural network techniques in constructing an adaptive car-following indicator. AI EDAM, 12(3), 231-241 (1998). doi: 10.1017/S0890060498123028
- 104. Giachetti, R.E., Young, R. E.: Analysis of the error in the standard approximation used for multiplication of triangular and trapezoidal fuzzy numbers and the development of a new approximation. FUZZY SETS SYST, 91(1), 1-13 (1997). doi: 10.1016/S0165-0114(96)00118-2
- Marinelli, C., Castellano, G., Attolico, G., Distante, A.: Optimization of a fuzzy controller by genetic algorithms. In: Applications of Soft Computing. Vol. 3165, pp. 153-160. SPIE (1997)
- 106. KóczY, L.T., Sugeno, M.: Explicit functions of fuzzy control systems. INT J UNCERTAIN FUZZINESS KNOWL-BASED SYST, 04(06), 515-535 (1996). doi: 10.1142/S0218488596000287
- Wang, L., Langari, R.: Sugeno model, fuzzy discretization, and the EM algorithm. FUZZY SETS SYST, 82(3), 279-288 (1996). doi: 10.1016/0165-0114(95)00228-6
- 108. Castellano, G., Fanelli, A.M.: Pruning in fuzzy-neural systems. In: Javor, A. et al. (eds.) ESM 1996, pp. 673-677. Soc. for Computer Simulation International, Budapest (1996).

- 109. Laukonen, E.G., Passino, K.M.: Training fuzzy systems to perform estimation and identification. ENG APPL ARTIF INTELL, 8(5), 499-514 (1995). doi: 10.1016/0952-1976(95)00029-Z
- 110. Bridges, S.M., Higginbotham, C., McKinion, J.M., Hodges, J.E.: Fuzzy descriptors of time-varying data: theory and application. AI APPL, 9(2), 1-14 (1995).
- Takagi, T., Imura, A., Ushida, H., Yamaguchi, T.: Conceptual fuzzy sets as a meaning representation and their inductive construction. INT J INTELL SYST, 10(11), 929-945 (1995). doi: 10.1002/int.4550101102
- 112. Wang, F.Y., Kim, H.M.: Implementing adaptive fuzzy logic controllers with neural networks: A design paradigm. J INTELL FUZZY SYST, 3(2), 165-180 (1995). Doi: 10.3233/IFS-1995-3206
- Rhee, F.C.H., Krishnapuram, R.: Fuzzy rule generation methods for high-level computer vision. FUZZY SETS SYST, 60(3), 245-258 (1993). doi: 10.1016/0165-0114(93)90436-L
- 114. Martín-Martín, A., Orduna-Malea, E., Thelwall, M., López-Cózar, E.D.: Google Scholar, Web of Science, and Scopus: A systematic comparison of citations in 252 subject categories. JOURNAL OF INFORMETRICS, 12(4), 1160-1177 (2018).

