

# CSA0674-DESIGN AND ANALYSIS OF ALGORITHM

B.MAHESH BABU

192311189

## ASSIGNMENT-3

1.Counting Elements Given an integer array arr, count how many elements x there are, such that  $x + 1$  is also in arr. If there are duplicates in arr, count them separately. Example Input: arr = [1,2,3] Output: 2 Explanation: 1 and 2 are counted cause 2 and 3 are in arr. Example 2: Input: arr = [1,1,3,3,5,5,7,7] Output: 0 Explanation: No numbers are counted, cause there is no 2, 4, 6, or 8 in arr. Constraints: •  $1 \leq \text{arr.length} \leq 1000$  •  $0 \leq \text{arr}[i] \leq 1000$  def count\_elements(arr):

```
arr_set = set(arr)
```

```
count = 0
```

```
for x in arr:
    if x + 1 in arr_set:
        count += 1
```

```
return count
```

```
print(count_elements([1, 2, 3]))    print(count_elements([1,
1, 3, 3, 5, 5, 7, 7]))
```

Output	
2	
0	

2. Perform String Shifts You are given a string s containing lowercase English letters, and a matrix shift, where  $\text{shift}[i] = [\text{direction}_i, \text{amount}_i]$ : •  $\text{direction}_i$  can be 0 (for left shift) or 1 (for right shift). •  $\text{amount}_i$  is the amount by which string s is to be shifted. • A left shift by 1 means remove the first character of s and append it to the end. • Similarly, a right shift by 1 means remove the last character of s and add it to the

beginning. Return the final string after all operations. Example 1: Input: s = "abc", shift = [[0,1],[1,2]] Output: "cab" Explanation: [0,1] means shift to left by 1. "abc" -> "bca" [1,2] means shift to right by 2. "bca" -> "cab" Example 2: Input: s = "abcdefg", shift = [[1,1],[1,1],[0,2],[1,3]] Output: "efgabcd" Explanation: [1,1] means shift to right by 1. "abcdefg" -> "gabcdef" [1,1] means shift to right by 1. "gabcdef" -> "fgabcde" [0,2] means shift to left by 2. "fgabcde" -> "abcdefg" [1,3] means shift to right by 3. "abcdefg" -> "efgabcd" Constraints: • 1 <= s.length <= 100 • s only contains lower case English letters. • 1 <= shift.length <= 100 • shift[i].length == 2 • directioni is either 0 or 1. • 0 <= amounti <= 100 def string\_shift(s, shift):

```
    total_shift = 0
```

```
    for direction, amount in shift:
```

```
        if direction == 0:
```

```
            total_shift -= amount
```

```
        else:
```

```
            total_shift += amount
```

```
    total_shift %= len(s)
```

```
    if total_shift > 0:
```

```
        s = s[-total_shift:] + s[:-total_shift]
```

```
    elif total_shift < 0:
```

```
        total_shift = -total_shift    s =
```

```
s[total_shift:] + s[:total_shift]
```

```
    return s
```

```
print(string_shift("abc", [[0,1],[1,2]])) print(string_shift("abcdefg",
```

```
[[1,1],[1,1],[0,2],[1,3]]))
```

Output
cab
efgabcd

3. Leftmost Column with at Least a One A row-sorted binary matrix means that all elements are 0 or 1 and each row of the matrix is sorted in non-decreasing order. Given a row-sorted binary matrix `binaryMatrix`, return the index (0-indexed) of the leftmost column with a 1 in it. If such an index does not exist, return -1. You can't access the Binary Matrix directly. You may only access the matrix using a `BinaryMatrix` interface:

- `BinaryMatrix.get(row, col)` returns the element of the matrix at index (row, col) (0-indexed).
- `BinaryMatrix.dimensions()` returns the dimensions of the matrix as a list of 2 elements [rows, cols], which means the matrix is rows x cols. Submissions making more than 1000 calls to `BinaryMatrix.get` will be judged Wrong Answer. Also, any solutions that attempt to circumvent the judge will result in disqualification. For custom testing purposes, the input will be the entire binary matrix `mat`. You will not have access to the binary matrix directly. Example 1: Input: `mat = [[0,0],[1,1]]` Output: 0 Example 2: Input: `mat = [[0,0],[0,1]]` Output: 1 Example 3: Input: `mat = [[0,0],[0,0]]` Output: -1

Constraints:

- `rows == mat.length`
- `cols == mat[i].length`
- $1 \leq \text{rows}, \text{cols} \leq 100$
- `mat[i][j]` is either 0 or 1.
- `mat[i]` is sorted in non-decreasing order.

class `BinaryMatrix`:

```
def __init__(self, mat):
```

```
    self.mat = mat
    self.call_count = 0
```

```
    def get(self, row: int, col: int) -> int:
```

```
        self.call_count += 1
```

```
    return self.mat[row][col]
```

```
    def dimensions(self) -> [int, int]:
```

```
        return [len(self.mat), len(self.mat[0])]
```

```
def leftMostColumnWithOne(binaryMatrix: BinaryMatrix) -> int:
```

```
    rows, cols = binaryMatrix.dimensions()
```

```
    current_row, current_col = 0, cols - 1
    leftmost_col
```

```
    = -1
```

```

while current_row < rows and current_col >= 0:
if binaryMatrix.get(current_row, current_col) == 1:
    leftmost_col = current_col
current_col -= 1
else:
    current_row += 1

return leftmost_col

```

```

mat1 = [[0, 0], [1, 1]]
mat2 = [[0, 0], [0, 1]] mat3
= [[0, 0], [0, 0]]

```

```

binary_matrix1 = BinaryMatrix(mat1)
binary_matrix2 = BinaryMatrix(mat2) binary_matrix3
= BinaryMatrix(mat3)

```

```

print(leftMostColumnWithOne(binary_matrix1)) print(leftMostColumnWithOne(binary_matrix2))
print(leftMostColumnWithOne(binary_matrix3))

```

Output
0
1
-1

4. First Unique Number You have a queue of integers, you need to retrieve the first unique integer in the queue. Implement the FirstUnique class: • FirstUnique(int[] nums) Initializes the object with the numbers in the queue. • int showFirstUnique() returns the value of the first unique integer of the queue, and returns -1 if there is no such integer. • void add(int value) insert value to the queue. Example 1: Input: ["FirstUnique","showFirstUnique","add","showFirstUnique","add","showFirstUnique","add","showFirstUnique"] [[2,3,5]],[],[5],[2],[3],[1]] Output: [null,2,null,2,null,3,null,-1] Explanation: FirstUnique firstUnique = new FirstUnique([2,3,5]); firstUnique.showFirstUnique(); // return 2

```

firstUnique.add(5); // the queue is now [2,3,5,5] firstUnique.showFirstUnique(); // return 2
firstUnique.add(2); // the queue is now [2,3,5,5,2] firstUnique.showFirstUnique(); // return 3
firstUnique.add(3); // the queue is now [2,3,5,5,2,3] firstUnique.showFirstUnique(); // return -1 Example
2: Input: ["FirstUnique","showFirstUnique","add","add","add","add","add","showFirstUnique"]
[[[7,7,7,7,7,7]],[],[7],[3],[3],[7],[17],[]] Output: [null,-1,null,null,null,null,null,17] Explanation: FirstUnique
firstUnique = new FirstUnique([7,7,7,7,7,7]); firstUnique.showFirstUnique(); // return -1
firstUnique.add(7); // the queue is now [7,7,7,7,7,7,7] firstUnique.add(3); // the queue is now
[7,7,7,7,7,7,3] firstUnique.add(3); // the queue is now [7,7,7,7,7,7,3,3] firstUnique.add(7); // the
queue is now [7,7,7,7,7,7,3,3,7] firstUnique.add(17); // the queue is now [7,7,7,7,7,7,3,3,7,17]
firstUnique.showFirstUnique(); // return 17 Example 3: Input:
["FirstUnique","showFirstUnique","add","showFirstUnique"] [[[809]],[],[809],[]] Output: [null,809,null,-1]
Explanation: FirstUnique firstUnique = new FirstUnique([809]); firstUnique.showFirstUnique(); // return
809 firstUnique.add(809); // the queue is now [809,809] firstUnique.showFirstUnique(); // return -1
Constraints: • 1 <= nums.length <= 10^5 • 1 <= nums[i] <= 10^8 • 1 <= value <= 10^8 from
collections import deque, defaultdict

```

```

class FirstUnique:    def
__init__(self, nums):
self.queue = deque()
self.count = defaultdict(int)

    for num in nums:
self.add(num)

    def showFirstUnique(self):    while self.queue and
self.count[self.queue[0]] > 1:
        self.queue.popleft()

    if self.queue:
        return self.queue[0]
    else:
        return -1


```

```

def add(self, value):
    self.queue.append(value)
self.count[value] += 1

firstUnique = FirstUnique([2, 3, 5])
print(firstUnique.showFirstUnique()) firstUnique.add(5)
print(firstUnique.showFirstUnique()) firstUnique.add(2)
print(firstUnique.showFirstUnique()) firstUnique.add(3)
print(firstUnique.showFirstUnique())

```



```

Output
2
2
3
-1
-1
17
809
-1

```

5. Check If a String Is a Valid Sequence from Root to Leaves Path in a Binary Tree Given a binary tree where each path going from the root to any leaf form a valid sequence, check if a given string is a valid sequence in such binary tree. We get the given string from the concatenation of an array of integers arr and the concatenation of all values of the nodes along a path results in a sequence in the given binary tree. Example 1: Input: root = [0,1,0,0,1,0,null,null,1,0,0], arr = [0,1,0,1] Output: true Explanation: The path 0 -> 1 -> 0 -> 1 is a valid sequence (green color in the figure). Other valid sequences are: 0 -> 1 -> 1 -> 0 -> 0 -> 0 -> 0 Example 2: Input: root = [0,1,0,0,1,0,null,null,1,0,0], arr = [0,0,1] Output: false Explanation:

The path 0 -> 0 -> 1 does not exist, therefore it is not even a sequence. Example 3: Input: root = [0,1,0,0,1,0,null,null,1,0,0], arr = [0,1,1] Output: false Explanation: The path 0 -> 1 -> 1 is a sequence, but it is not a valid sequence. Constraints: •  $1 \leq \text{arr.length} \leq 5000$  •  $0 \leq \text{arr}[i] \leq 9$  • Each node's value is between [0 - 9]. class TreeNode: def \_\_init\_\_(self, val=0, left=None, right=None):

```

        self.val = val
self.left = left
self.right = right

def isValidSequence(root: TreeNode, arr: [int]) -> bool:
def dfs(node, index):    if node is None:
return False    if index >= len(arr) or node.val !=
arr[index]:
        return False    if
index == len(arr) - 1:
        return node.left is None and node.right is None
return dfs(node.left, index + 1) or dfs(node.right, index + 1)

return dfs(root, 0)

```

```

root1 = TreeNode(0) root1.left =
TreeNode(1) root1.right =
TreeNode(0) root1.left.left =
TreeNode(0) root1.left.right =
TreeNode(1) root1.right.left =
TreeNode(0) root1.left.left.right =
TreeNode(1) root1.left.right.left =
TreeNode(0) root1.left.right.right
= TreeNode(0)

arr1 = [0, 1, 0, 1] print(isValidSequence(root1,
arr1))

```

Output

True

6. Kids With the Greatest Number of Candies There are  $n$  kids with candies. You are given an integer array `candies`, where each `candies[i]` represents the number of candies the  $i$ th kid has, and an integer `extraCandies`, denoting the number of extra candies that you have. Return a boolean array `result` of length  $n$ , where `result[i]` is `true` if, after giving the  $i$ th kid all the `extraCandies`, they will have the greatest number of candies among all the kids, or `false` otherwise. Note that multiple kids can have the greatest number of candies. Example 1: Input: `candies = [2,3,5,1,3]`, `extraCandies = 3` Output: `[true,true,true,false,true]` Explanation: If you give all `extraCandies` to: - Kid 1, they will have  $2 + 3 = 5$  candies, which is the greatest among the kids. - Kid 2, they will have  $3 + 3 = 6$  candies, which is the greatest among the kids. - Kid 3, they will have  $5 + 3 = 8$  candies, which is the greatest among the kids. - Kid 4, they will have  $1 + 3 = 4$  candies, which is not the greatest among the kids. - Kid 5, they will have  $3 + 3 = 6$  candies, which is the greatest among the kids. Example 2: Input: `candies = [4,2,1,1,2]`, `extraCandies = 1` Output: `[true,false,false,false,false]` Explanation: There is only 1 extra candy. Kid 1 will always have the greatest number of candies, even if a different kid is given the extra candy. Example 3: Input: `candies = [12,1,12]`, `extraCandies = 10` Output: `[true,false,true]` Constraints: •  $n == \text{candies.length}$  •  $2 \leq n \leq 100$  •  $1 \leq \text{candies}[i] \leq 100$  •  $1 \leq \text{extraCandies} \leq 50$

`kidsWithCandies(candies, extraCandies):`

```
    max_candies = max(candies)
```

```
    result = []
```

```
    for candy in candies:
```

```
        if candy + extraCandies >= max_candies:
```

```
            result.append(True)
```

```
        else:
```

```
            result.append(False)
```

```
    return result
```

```
candies1 = [2, 3, 5, 1, 3]
```

```
extraCandies1 = 3 print(kidsWithCandies(candies1,  
extraCandies1))
```



## Output

[True, True, True, False, True]

7. Max Difference You Can Get From Changing an Integer You are given an integer num. You will apply the following steps exactly two times: ● Pick a digit x ( $0 \leq x \leq 9$ ). ● Pick another digit y ( $0 \leq y \leq 9$ ). The digit y can be equal to x. ● Replace all the occurrences of x in the decimal representation of num by y. ● The new integer cannot have any leading zeros, also the new integer cannot be 0. Let a and b be the results of applying the operations to num the first and second times, respectively. Return the max difference between a and b. Example 1: Input: num = 555 Output: 888 Explanation: The first time pick x = 5 and y = 9 and store the new integer in a. The second time pick x = 5 and y = 1 and store the new integer in b. We have now a = 999 and b = 111 and max difference = 888 Example 2: Input: num = 9 Output: 8 Explanation: The first time pick x = 9 and y = 9 and store the new integer in a. The second time pick x = 9 and y = 1 and store the new integer in b. We have now a = 9 and b = 1 and max difference = 8

Constraints: ●  $1 \leq \text{num} \leq 108$  def maxDifference(num): num\_str = str(num)

```
max_num = num_str
for digit in num_str:
    if digit != '9':
        max_num = num_str.replace(digit, '9')
        break
max_num = int(max_num)

min_num = num_str
if num_str[0] != '1':
    min_num = num_str.replace(num_str[0], '1')
else:
    for digit in num_str[1:]:
        if digit != '0' and digit != '1':
            min_num = num_str.replace(digit, '0')
            break
min_num = int(min_num)
```

```
return max_num - min_num
```

```
print(maxDifference(555)) print(maxDifference(9))
```

```
print(maxDifference(123456))
```

```
print(maxDifference(100000))
```

Output
888
8
820000
800000

8. Check If a String Can Break Another String Given two strings: s1 and s2 with the same size, check if some permutation of string s1 can break some permutation of string s2 or vice-versa. In other words s2 can break s1 or vice-versa. A string x can break string y (both of size n) if  $x[i] \geq y[i]$  (in alphabetical order) for all i between 0 and n-1. Example 1: Input: s1 = "abc", s2 = "xya" Output: true Explanation: "ayx" is a permutation of s2="xya" which can break to string "abc" which is a permutation of s1="abc". Example 2: Input: s1 = "abe", s2 = "acd" Output: false Explanation: All permutations for s1="abe" are: "abe", "aeb", "bae", "bea", "eab" and "eba" and all permutation for s2="acd" are: "acd", "adc", "cad", "cda", "dac" and "dca". However, there is not any permutation from s1 which can break some permutation from s2 and vice-versa. Example 3: Input: s1 = "leetcode", s2 = "interview" Output: true Constraints: • s1.length == n • s2.length == n •  $1 \leq n \leq 10^5$  • All strings consist of lowercase English letters.

```
def checkIfCanBreak(s1, s2):
```

```
    sorted_s1 = sorted(s1)    sorted_s2
```

```
    = sorted(s2)    can_s1_break_s2 =
```

```
    all(c1 >= c2 for c1, c2 in
```

```
    zip(sorted_s1, sorted_s2))
```

```
    can_s2_break_s1 = all(c2 >= c1 for c1, c2 in zip(sorted_s1, sorted_s2))
```

```
return can_s1_break_s2 or can_s2_break_s1
```

```
print(checkIfCanBreak("abc", "xya"))    print(checkIfCanBreak("abe",  
"acd"))    print(checkIfCanBreak("leetcode", "interview"))
```

Output
True
False
True

9. Number of Ways to Wear Different Hats to Each Other There are  $n$  people and 40 types of hats labeled from 1 to 40. Given a 2D integer array `hats`, where `hats[i]` is a list of all hats preferred by the  $i$ th person. Return the number of ways that the  $n$  people wear different hats to each other. Since the answer may be too large, return it modulo  $10^9 + 7$ . Example 1: Input: `hats = [[3,4],[4,5],[5]]` Output: 1 Explanation: There is only one way to choose hats given the conditions. First person choose hat 3, Second person choose hat 4 and last one hat 5. Example 2: Input: `hats = [[3,5,1],[3,5]]` Output: 4 Explanation: There are 4 ways to choose hats: (3,5), (5,3), (1,3) and (1,5) Example 3: Input: `hats = [[1,2,3,4],[1,2,3,4],[1,2,3,4],[1,2,3,4]]` Output: 24 Explanation: Each person can choose hats labeled from 1 to 4. Number of Permutations of (1,2,3,4) = 24. Constraints: •  $n == \text{hats.length}$  •  $1 \leq n \leq 10$  •  $1 \leq \text{hats}[i].\text{length} \leq 40$  •  $1 \leq \text{hats}[i][j] \leq 40$  • `hats[i]` contains a list of unique integers.

```
def numberWays(hats):
```

```
    MOD = 10**9 + 7
```

```
    n = len(hats)
```

```
    hat_to_people = [[] for _ in range(41)]
```

```
    for person, hat_list in enumerate(hats):
```

```
        for hat in hat_list:
```

```
            hat_to_people[hat].append(person)
```

```
    dp = [0] * (1 << n)
```

```
    dp[0] = 1    for hat in
```

```
        range(1, 41):
```

```

        new_dp = dp[:]    for
mask in range(1 << n):
if dp[mask] == 0:
        continue    for person in
hat_to_people[hat]:    if not
(mask & (1 << person)):

        new_dp[mask | (1 << person)] = (new_dp[mask | (1 << person)] + dp[mask]) % MOD
dp = new_dp

return dp[(1 << n) - 1]

```

```

print(numberWays([[3, 4], [4, 5], [5]])) print(numberWays([[3, 5,
1], [3, 5]])) print(numberWays([[1, 2, 3, 4], [1, 2, 3, 4], [1, 2, 3, 4],
[1, 2, 3, 4]]))

```

Output
1
4
24

10. Next Permutation A permutation of an array of integers is an arrangement of its members into a sequence or linear order. • For example, for arr = [1,2,3], the following are all the permutations of arr: [1,2,3], [1,3,2], [2, 1, 3], [2, 3, 1], [3,1,2], [3,2,1]. The next permutation of an array of integers is the next lexicographically greater permutation of its integer. More formally, if all the permutations of the array are sorted in one container according to their lexicographical order, then the next permutation of that array is the permutation that follows it in the sorted container. If such arrangement is not possible, the array must be rearranged as the lowest possible order (i.e., sorted in ascending order). • For example, the next permutation of arr = [1,2,3] is [1,3,2]. • Similarly, the next permutation of arr = [2,3,1] is [3,1,2]. • While the next permutation of arr = [3,2,1] is [1,2,3] because [3,2,1] does not have a lexicographical larger rearrangement. Given an array of integers nums, find the next permutation of nums. The replacement must be in place and use only constant extra memory. Example 1: Input: nums = [1,2,3] Output: [1,3,2] Example 2: Input: nums = [3,2,1] Output: [1,2,3] Example 3: Input: nums = [1,1,5] Output:

[1,5,1] Constraints: •  $1 \leq \text{nums.length} \leq 100$  •  $0 \leq \text{nums}[i] \leq 100$  def

nextPermutation(nums):

    n = len(nums)

    i = n - 2

    while i >= 0 and nums[i] >= nums[i + 1]:

        i -= 1

        if i >=

0:        j = n

        - 1

        while nums[j] <= nums[i]:

        j -= 1

        nums[i], nums[j] = nums[j], nums[i]

        left, right = i + 1, n - 1

        while left < right:

            nums[left], nums[right] = nums[right], nums[left]

            left += 1

        right -= 1

nums1 = [1, 2, 3]

nextPermutation(nums1) print(nums1)

Output

[1, 3, 2]