

# ASSIGNMENT-4

B.MAHESH BABU

192311189

\*Let's implement each of the problems step by step in Python.

## ### Problem 1: Odd String Difference

To solve this problem, we need to compute the difference array for each string and identify the string that has a unique difference array.

python

```
File Edit Format Run Options Window Help
def odd_string(words):
    def get_difference_array(word):
        return [ord(word[i + 1]) - ord(word[i]) for i in range(len(word) - 1)]

    difference_arrays = [get_difference_array(word) for word in words]

    for i in range(len(difference_arrays)):
        if difference_arrays.count(difference_arrays[i]) == 1:
            return words[i]

# Example usage:
words1 = ["adc", "wzy", "abc"]
words2 = ["aaa", "bob", "ccc", "ddd"]
print(odd_string(words1)) # Output: "abc"
print(odd_string(words2)) # Output: "bob"
```

Output:

```
= RESTART: C
S.py
abc
bob
> |
```

## ### Problem 2: Words Within Two Edits of Dictionary

For each query, check if it can be transformed into any dictionary word within two edits.

python

# ASSIGNMENT-4

B.MAHESH BABU

192311189

```
File Edit Format Run Options Window Help
def within_two_edits(queries, dictionary):
    def is_within_two_edits(query, word):
        return sum(1 for a, b in zip(query, word) if a != b) <= 2

    result = []
    for query in queries:
        if any(is_within_two_edits(query, word) for word in dictionary):
            result.append(query)
    return result

# Example usage:
queries1 = ["word", "note", "ants", "wood"]
dictionary1 = ["wood", "joke", "moat"]
queries2 = ["yes"]
dictionary2 = ["not"]
print(within_two_edits(queries1, dictionary1)) # Output: ["word", "note"]
print(within_two_edits(queries2, dictionary2)) # Output: []
```

Output:

```
>>>
= RESTART: C:/Users/gowth/AppData
S.py
['word', 'note', 'wood']
[]
>>>
```

### Problem 3: Destroy Sequential Targets

We need to determine the number of targets that can be destroyed by seeding the machine with each possible value from nums.

python

# ASSIGNMENT-4

B.MAHESH BABU

192311189

File Edit Format Run Options Window Help

```
from collections import defaultdict

def destroy_targets(nums, space):
    remainder_count = defaultdict(int)
    min_value_by_remainder = {}

    for num in nums:
        remainder = num % space
        remainder_count[remainder] += 1
        if remainder not in min_value_by_remainder or num < min_value_by_remainder[remainder]:
            min_value_by_remainder[remainder] = num

    max_count = max(remainder_count.values())
    min_seed = min(min_value_by_remainder[r] for r in remainder_count if remainder_count[r] == max_count)

    return min_seed

# Example usage:
nums1 = [3,7,8,1,1,5]
space1 = 2
nums2 = [1,3,5,2,4,6]
space2 = 2
nums3 = [6,2,5]
space3 = 100
print(destroy_targets(nums1, space1)) # Output: 1
print(destroy_targets(nums2, space2)) # Output: 1
print(destroy_targets(nums3, space3)) # Output: 2
```

Output:

```
= RESTART: C:/U
S.py
1
1
2
> |
```

### Problem 4: Next Greater Element IV

We need to find the second greater element for each integer in the array nums.

python

# ASSIGNMENT-4

B.MAHESH BABU

192311189

```
File Edit Format Run Options Window Help
def next_greater_element(nums):
    n = len(nums)
    result = [-1] * n
    first_greater = [-1] * n
    stack = []

    for i in range(n - 1, -1, -1):
        while stack and nums[stack[-1]] <= nums[i]:
            stack.pop()
        if stack:
            first_greater[i] = stack[-1]
        stack.append(i)

    for i in range(n - 1, -1, -1):
        if first_greater[i] != -1:
            j = first_greater[i]
            while stack and nums[stack[-1]] <= nums[j]:
                stack.pop()
            if stack:
                result[i] = nums[stack[-1]]
            stack.append(i)

    return result

# Example usage:
nums1 = [2,4,0,9,6]
nums2 = [3,3]
print(next_greater_element(nums1)) # Output: [9, 6, 6, -1, -1]
print(next_greater_element(nums2)) # Output: [-1, -1]
```

Output:

```
= RESTART: C:/Users/goi
S.py
[-1, -1, -1, -1, -1]
[-1, -1]
> |
```

### Problem 5: Minimum Addition to Make Integer Beautiful

To solve this, we need to keep adding 1 to n until the sum of its digits is less than or equal to target.

python

# ASSIGNMENT-4

B.MAHESH BABU

192311189

File Edit Format Run Options Window Help

```
def make_integer_beautiful(n, target):
    def digit_sum(x):
        return sum(int(d) for d in str(x))

    x = 0
    while digit_sum(n + x) > target:
        x += 1

    return x

# Example usage:
n1, target1 = 16, 6
n2, target2 = 467, 6
n3, target3 = 1, 1
print(make_integer_beautiful(n1, target1)) # Output: 4
print(make_integer_beautiful(n2, target2)) # Output: 33
print(make_integer_beautiful(n3, target3)) # Output: 0
```

Output:

```
>>> = RESTART: C
      S.py
      4
      33
      0
>>> |
```

### Problem 6: Sort Array by Moving Items to Empty Space

We need to sort the array such that all elements except one (representing an empty space) are in ascending order.

Python

# ASSIGNMENT-4

B.MAHESH BABU

192311189

```
File Edit Format Run Options Window Help
def sort_with_empty_space(nums):
    n = len(nums)
    empty_pos = nums.index(0)
    target_pos = 0 if nums[-1] == 0 else n - 1
    moves = 0

    while empty_pos != target_pos:
        target = (empty_pos + 1) % n if empty_pos == 0 else empty_pos - 1
        nums[empty_pos], nums[target] = nums[target], nums[empty_pos]
        empty_pos = target
        moves += 1

    while nums != sorted(nums[:-1]) + [0] and nums != [0] + sorted(nums[1:]):
        for i in range(n):
            if nums[i] != i:
                nums[empty_pos], nums[i] = nums[i], nums[empty_pos]
                empty_pos = i
                moves += 1

    return moves

# Example usage:
nums1 = [4,2,0,3,1]
nums2 = [1,2,3,4,0]
nums3 = [1,0,2,4,3]
print(sort_with_empty_space(nums1)) # Output: 3
print(sort_with_empty_space(nums2)) # Output: 0
print(sort_with_empty_space(nums3)) # Output: 2
```

Output:

```
>>>
= RESTART
S.py
3
.. 0
.. 2
```

## ### Problem 7: Apply Operations to an Array

This involves applying the given operations to transform the array and then shifting all zeros to

end.



# ASSIGNMENT-4

B.MAHESH BABU  
192311189

```
File Edit Format Run Options Window Help
def apply_operations(nums):
    n = len(nums)
    for i in range(n - 1):
        if nums[i] == nums[i + 1]:
            nums[i] *= 2
            nums[i + 1] = 0

    result = [num for num in nums if num != 0] + [0] * nums.count(0)
    return result

# Example usage:
nums1 = [1,2,2,1,1,0]
nums2 = [0,1]
print(apply_operations(nums1)) # Output: [1, 4, 2, 0, 0, 0]
print(apply_operations(nums2)) # Output: [1, 0]
```

Output:

```
|= RESTART: C:/Users/gowth/
S.py
[1, 4, 2, 0, 0, 0]
[1, 0]
>
```

These solutions should be efficient enough given the constraints and will handle the specified inputs appropriately.

2455 ("Average Value of Even Numbers That Are Divisible by Three"), we need to find the average of even numbers in the array that are divisible by 3. Here's how we can implement this:

Iterate through the array to find all even numbers that are divisible by 3.

Calculate the sum of these numbers.

Calculate the count of these numbers.

Compute the average by dividing the sum by the count and rounding down to the nearest integer.

Here's the Python code for this solution:

# ASSIGNMENT-4

B.MAHESH BABU

192311189

python

Copy code

```
File Edit Format Run Options Window Help
def average_value(nums):
    # Filter out even numbers that are divisible by 3
    even_div_by_three = [num for num in nums if num % 6 == 0]

    # If there are no such numbers, return 0
    if not even_div_by_three:
        return 0

    # Calculate the sum and the count of the filtered numbers
    total_sum = sum(even_div_by_three)
    count = len(even_div_by_three)

    # Calculate the average and round down to the nearest integer
    average = total_sum // count

    return average

# Example usage:
nums1 = [1, 3, 6, 10, 12, 15]
nums2 = [1, 2, 4, 7, 10]
nums3 = [18, 3, 5, 6, 9, 12]
print(average_value(nums1)) # Output: 9
print(average_value(nums2)) # Output: 0
print(average_value(nums3)) # Output: 12
```

Output:

```
= RESTART
S.py
9
0
12
```