Silvaris Wafer Technologies Ltd.
Unit 4, Riverside Park
Cork T12 XY00, Ireland
Tel. +353 21 000 0000

To:
Example Semiconductor GmbH
Purchasing Department
Musterstraße 12
76131 Karlsruhe, Germany

Date: 4 April 2025
Our ref.: CoC-2025-0331
Your PO: PO-88433

CERTIFICATE OF CONFORMANCE

We hereby certify that the material described below, shipped on 27 March 2025 under delivery note DN-55203, has been manufactured, inspected and tested in accordance with specification SWT-SPEC-150 revision D and conforms in all respects to the requirements of the above purchase order.

The shipment consists of 3 cassettes containing a total of 72 prime-grade silicon wafers (lot number SL-7738, ingot IG-2294) with a diameter of 150 mm and a nominal thickness of 675 µm. The wafers are boron-doped (p-type) with <100> orientation and were grown by the Czochralski method. Resistivity was measured at 9 points per wafer using a four-point probe and ranged from 7.6 to 10.9 Ohm·cm, well within the specified 1-20 Ohm·cm.

Surface particle inspection found no more than 11 particles larger than 0.2 µm on any wafer. Oxygen content averaged 14.1 ppma (ASTM F121-83). A summary of the key acceptance results is given in the table below.

Property	Specification	Result (min / max)	Status
Thickness	675 ± 20 µm	667 / 680 µm	PASS
TTV	<= 5 µm	2.3 / 4.1 µm	PASS
Bow	<= 40 µm	10 / 24 µm	PASS
Warp	<= 40 µm	19 / 35 µm	PASS
Resistivity	1 - 20 Ohm·cm	7.6 / 10.9 Ohm·cm	PASS
Particles (> 0.2 µm)	<= 20 per wafer	4 / 11	PASS

Test records are retained for a period of ten (10) years and are available upon request. This certificate was issued electronically and is valid without signature.

A. Kowalski
Quality Assurance Manager