TECHNICAL SPECIFICATION OF VOIP-PHONE

1	The VOIP-Phone should be a open standard SIP based Phone i.e., session Initiation Protocol (SIP) supported.
2	Above 2.8'' (diagonal) colour display -320 x 240 pixels.
3	4 Context Sensitive Soft Keys.
4	Dual 10/100/1000 Ethernet ports to support co-located PC.
5	Should support -48V DC Power input directly or through DC-DC adaptor on -48V DC input.
6	IP address Assignment by DHCP or statically configured.
7	Configurable via web interface.
8	Corporate directory/Lightweight Directory Access Protocol (LDAP) integration.
9	The phone should support QoS mechanism through 802.1p/q.
10	Hands-free operation with full-duplex speaker-phone.
11	The phone should have a distinct LED indicator for message waiting.
12	The phone should support at least 100 entries for call history i.e., missed, received, placed etc.,
13	It should support the following codec: G.711a/µ-law, G.722, G.729.
14	The phone also includes the following settings - Display contrast, Network configuration, Call status.
15	The phone should support the ability to provide different dial tone for internal and external calls
16	Should have volume control button for easy volume adjustments for the speakerphone, handset and ringer.
17	Should support minimum 5 participants in a meeting- This could be Ad-Hoc and Meet me meetings.