



## **Ahsanullah University of Science & Technology**

### Department of Computer Science and Engineering

Course No : CSE 2214  
Course Title : Assembly Language Programming Sessional  
Assignment no : 05  
Date of Performance : 03.03.20  
Date of Submission : 10.03.20  
Submitted To : Ms.Tahsin Aziz & Md.Siam Ansary

#### Submitted By:

Name : Mahin opu  
ID : 17.02.04.006  
Year : 2<sup>nd</sup>  
Semester : 2<sup>nd</sup>  
Group : A1  
Section : A

**Question 1: For each of the following instructions, give the new destination contents and**

**the new settings of CF, SF, ZF, PF and OF. Suppose that the flags are initially 0 in each part of this question**

**a. ADD AX, BX where AX contains 7FFFh and BX contains 0001h**

**b. DEC AL where AL contains 00h**

**c. NEG AL where AL contains 7Fh**

**d. XCHG AX, BX where AX contains 1ABCh and BX contains 712Ah**

**Answer:**

**a. Here,**

$$\begin{array}{rcl} \text{AX} & = & 7\text{FFFh} = 0111111111111111 \\ \text{BX} & = & 0001\text{h} = 0000000000000001 \\ \hline \text{AX} & & = 1000000000000000 \end{array}$$

**Now Flags,**

**CF = 0 because there is no carry out of the MSB on addition**

**SF = 1 because the MSB is 1**

**ZF = 0 because the result is non zero**

**PF = 1 because there is no 1 in the low byte of the result**

**OF = 1 because there is a carry into the MSB and no carry out**

**b. Here,**

**AL = 00h = 0 0 0 0 0 0 0 0**

<b>2's complement of 1</b>	<b>= 1 1 1 1 1 1 1</b>
<b>AL</b>	<b>= 1 1 1 1 1 1 1</b>

### Flags :

**CF = 0** because there is no carry out of the MSB on addition

**SF = 1 because the MSB is 1**

**ZF = 0 because the result is non zero**

**PF = 1** because there are even number of 1 bits in the low byte of the result

**OF = 0** because there is no carry into the MSB and no carry out

c. Here,  $AL = 7Fh = 01111111$   
 1's complement  $= 10000000$   
 $+ 1$

**1 0 0 0 0 0 1 (2's complement)**

### Flags:

**CF = 1** because the result is not zero

**SF = 1 because the MSB is 1**

**ZF = 0 because the result is non zero**

**PF = 0 because there are odd number of 1 bits in the low byte of the result**

**OF = 0** because the byte operand is not 80h

**d. Here, AX = 1ABCh = 0001101010111100**

**BX = 712Ah = 0111000100101010**

**After execution of XCHG AX, BX :**

**AX = 712Ah = 0111000100101010**

**BX = 1ABCh = 0001101010111100**

**Flags:**

**CF = 0**

**SF = 0**

**ZF = 0**

**PF = 0**

**OF = 0**

**All Flags are zero because there is no change after XCHG.**