



Design & Analysis Algorithm Assignment - 2

Name : Hemal Chudasama
Roll No. : 21BCP152
Div - 3 , G - 5

-: Merge sort :-

The Merge Sort algorithm is a sorting algorithm that is based on the Divide and Conquer paradigm. In this algorithm, the array is initially divided into two equal halves and then they are combined in a sorted manner.

- **Merge Sort Algorithm :-**

1. start
2. declare array and left, right, mid variable
3. perform merge function.
 - if left > right
 - return
 - mid= (left+right)/2
 - mergesort(array, left, mid)
 - mergesort(array, mid+1, right)
 - merge(array, left, mid, right)
4. Stop

- **Program :-**

```
#include <stdio.h>
#include <stdlib.h>

void merge(int arr[], int l, int m, int r)
{
    int i, j, k;
    int n1 = m - l + 1;
    int n2 = r - m;

    int L[n1], R[n2];

    for (i = 0; i < n1; i++)
        L[i] = arr[l + i];
    for (j = 0; j < n2; j++)
```

```

        R[j] = arr[m + 1 + j];

    i = 0;
    j = 0;
    k = l;
    while (i < n1 && j < n2) {
        if (L[i] <= R[j]) {
            arr[k] = L[i];
            i++;
        }
        else {
            arr[k] = R[j];
            j++;
        }
        k++;
    }

    while (i < n1) {
        arr[k] = L[i];
        i++;
        k++;
    }

    while (j < n2) {
        arr[k] = R[j];
        j++;
        k++;
    }
}

void mergeSort(int arr[], int l, int r)
{
    if (l < r) {
        int m = l + (r - l) / 2;

        mergeSort(arr, l, m);
        mergeSort(arr, m + 1, r);

        merge(arr, l, m, r);
    }
}

```

```

}

void printArray(int A[], int size)
{
    int i;
    for (i = 0; i < size; i++)
        printf("%d ", A[i]);
    printf("\n");
}

int main()
{
    int arr[] = { 12, 11, 13, 5, 6, 7 };
    int arr_size = sizeof(arr) / sizeof(arr[0]);

    printf("Given array is \n");
    printArray(arr, arr_size);

    mergeSort(arr, 0, arr_size - 1);

    printf("\nSorted array is \n");
    printArray(arr, arr_size);
    return 0;
}

```

- **Output :-**

```

PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL
cd "/Users/Hemal/Documents/DAA Lab/" && gcc MergeSort.c -o MergeSort
● Hemal@Hemals-MacBook-Air DAA Lab % cd "/Users/Hemal/Documents/DAA Lab/"
Given array is
12 11 13 5 6 7

Sorted array is
5 6 7 11 12 13
○ Hemal@Hemals-MacBook-Air DAA Lab % █

```

-: Quick sort :-

Like Merge Sort, QuickSort is a Divide and Conquer algorithm. It picks an element as a pivot and partitions the given array around the picked pivot. There are many different versions of quickSort that pick pivot in different ways.

- Always pick the first element as a pivot.
- Always pick the last element as a pivot (implemented below)
- Pick a random element as a pivot.
- Pick median as the pivot.

The key process in quickSort is a partition(). The target of partitions is, given an array and an element x of an array as the pivot, put x at its correct position in a sorted array and put all smaller elements (smaller than x) before x, and put all greater elements (greater than x) after x. All this should be done in linear time.

• Quick Sort Algorithm :-

QUICKSORT (array A, start, end)

1. {
2. **if** (start < end)
3. {
4. p = partition(A, start, end)
5. QUICKSORT (A, start, p - 1)
6. QUICKSORT (A, p + 1, end)
7. }
8. }

PARTITION (array A, start, end)

9. {
10. pivot ? A[end]
11. i ? start - 1
12. **for** j ? start to end - 1 {
13. **do if** (A[j] < pivot) {
14. then i ? i + 1
15. swap A[i] with A[j]

```
16.  }}
17.  swap A[i+1] with A[end]
18.  return i+1
19.}
```

- **Program :-**

```
#include <stdio.h>

void swap(int *a, int *b) {
    int t = *a;
    *a = *b;
    *b = t;
}

int partition(int array[], int low, int high) {
    int pivot = array[high];
    int i = (low - 1);

    for (int j = low; j < high; j++) {
        if (array[j] <= pivot) {
            i++;
            swap(&array[i], &array[j]);
        }
    }

    swap(&array[i + 1], &array[high]);

    return (i + 1);
}

void quickSort(int array[], int low, int high) {
    if (low < high) {
```

```

    int pi = partition(array, low, high);

    quickSort(array, low, pi - 1);

    quickSort(array, pi + 1, high);
}
}

void printArray(int array[], int size) {
    for (int i = 0; i < size; ++i) {
        printf("%d  ", array[i]);
    }
    printf("\n");
}

int main() {
    int data[] = {8, 7, 2, 1, 0, 9, 6};

    int n = sizeof(data) / sizeof(data[0]);

    printf("Unsorted Array\n");
    printArray(data, n);

    quickSort(data, 0, n - 1);

    printf("Sorted array in ascending order: \n");
    printArray(data, n);
}

```

- **Output :-**

PROBLEMS	OUTPUT	DEBUG CONSOLE	TERMINAL
			<pre> cd "/Users/Hemal/Documents/DAA Lab/" && gcc QuickSort.c -o QuickSort Hemal@Hemals-MacBook-Air DAA Lab % cd "/Users/Hemal/Documents/DAA Lab/" Unsorted Array 8 7 2 1 0 9 6 Sorted array in ascending order: 0 1 2 6 7 8 9 Hemal@Hemals-MacBook-Air DAA Lab % </pre>