

WEDNESDAY

WEEK 09

23

FEBRUARY 2011

DAY 054-311

# Relational Model

Relation :-

A relation is a two dimensional table where columns are representing attributes of the relation and row representing tuples of the table.

Course	Subject	Day
CS503	Algo	Monday
CS603	OS	Friday

Course - Subject.

The name of the relation is :- Course - Subject

Attributes are :- Course, Subject, Day.

No. of tuples are :- 2

No. of tuples in a relation is called the Cardinality.  
The Cardinality of the Course - Subject is 2. The tuples represents two different instances of the same relation.

When the value corresponding to an attribute at a particular instance is not known or not available, it is indicated with NULL value. Null is neither zero nor blank.

The relation without tuples can be called as relation schema.

FEBRUARY 2011						
M	T	W	T	F	S	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
8						

Constraints :-

A constraint is a rule that restricts the values to be stored in the database.

THURSDAY

WEEK 09

24

FEBRUARY 2011

DAY 055-310

## Constraints

Entity Integrity

Domain Constraint

Key Constraint

|  
 Super Key  
 |  
 Candidate Key.

Referential Integrity

Foreign Key.

### Entity Integrity

The constraint that restrict the values of a tuple in a relation. There are two types of constraints.

#### 1) Domain Constraint :-

Domain Constraint specifies that the value of each attribute must be an atomic value from the domain of the respective attribute e.g. say an attribute ~~sex~~ married of a relation with domain {Y, N} and an attempt is made to enter

1 to mean Yes or 2 to mean NO then the system will indicate that the domain constraint is violated and it should be Y for yes and N for no.

MARCH 2011						
M	T	W	T	F	S	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

FRIDAY

WEEK 09

25

FEBRUARY 2011

DAY 056-309

2) Key Constraint :-

Id	Name	Age	Married
8002	Ankit	23	N
8003	Sourav	25	Y
8005	Riya	22	1

→ Not allowed  
because it either  
Y or N.

2) Key Constraint :-

Keys are attributes or sets of attributes that uniquely identify an entity within its entity set. An entity set E can have multiple keys from which one key will be designated as the primary key. Primary key must have unique and not null values in the relational table.

Id	Name	Age	Married
8002	Ankit	23	N
8003	Sourav	25	Y
8002	Tony	24	Y

→ Not allowed as primary key  
values must be unique.

Referential Integrity :-

FEBRUARY 2011						
M	T	W	T	F	S	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28						

Let us consider a situation when a supplier supplies certain products which are being manufactured by certain companies! Consider the relations:-

## SATURDAY

WEEK 09

26

FEBRUARY 2011

DAY 057-308

Supplier (id\_no., name, itemCode, manufactured\_by)  
Product (product\_code, product\_name, company,  
manufacture\_date).

The attribute item code in Supplier to match with Product code in Product. Similarly the attribute Company of the relation Product Should match with manufactured by of the relation Supplier. To refer to an attribute of one relation from another relation needs a link between the two relation.

## Foreign Key :-

A foreign key is a set of attributes of one relation whose values are required to match values of some key attributes of another relations.

In the relation Supplier, the attributes item code  
In other words foreign keys are the columns  
of a table that points to the primary key of  
another table. They act as a cross-referencing  
between tables.

In the relation Supplier, the attribute item-code is the foreign key referring to the relation Product with attribute Product-Code. SUNDAY 27

<u>id_no.</u>	<u>name</u>	<u>item_code</u>	<u>manufa ctured by</u>
001	Ankit	186	Olive
002	Raj	172	Dove
003	Rakit	188	Clear

## Supplier

Product - code	Product - name	Company	month date
186	Pac wash	Olive	3. 2. 17
172	Soap	Dove	2. 1. 18
188	oil	clear	2. 4. 18

may  
contain  
another

MONDAY

WEEK 10

28

FEBRUARY 2011

DAY 059-306

Single value Constraint :-

It refers that each attribute of any entity set has a single value. If the value of an attribute is missing in a tuple then we can fill it with a 'null' value.

SID	Name	Class	Age	License no. Driving
801	Ankit	1 <sup>st</sup>	19	DL-45629
802	Sonav	2 <sup>nd</sup>	21	DL-43233, DL-32546
803	Ram	4 <sup>th</sup>	20	

Allowed as  
a person may or  
may not have a  
license.

Not allowed as a  
person does not have two  
driving licenses.

Relational Algebra :-1. Query Language :-

A query language is a language in which user requests information from the database. It can be categorized.

Procedural Lang :-

The user instructs the system to perform a sequence of operations on the database to compute the desired result.

Relational algebra is a procedural language.

~~It is~~ Relational algebra operations can be divided into two broad categories:-

1. Set-oriented Operation.

2. Relation-oriented operation.

FEBRUARY 2011					
M	T	W	T	F	S
1	2	3	4	5	6
7	8	9	10	11	12
14	15	16	17	18	19
21	22	23	24	25	26
28					27

TUESDAY

WEEK 10

01

MARCH 2011

DAY 060-305

Nonprocedural lang:-

In this lang. the user describes the information desired without giving a specific procedure for obtaining that information.

Example:- Domain Relational Calculus.

Set-Oriented Basic Operations:-

Operations are:- Union, Difference, intersection, and Cartesian Product. The operations are Union compatible. Two relations  $R(A_1, \dots, A_n)$  and  $S(B_1, \dots, B_n)$  are said to be union compatible if they have same degree  $n$  and  $\text{dom}(A_i) = \text{dom}(B_i)$  for  $1 \leq i \leq n$ . This means that the two relations have the same no. of attributes and each corresponding pair of attributes has the same domain.

Union :-

The result of this operation, denoted by  $R \cup S$  is a relation that includes all tuples that are either in  $R$  or in  $S$  or in both  $R$  and  $S$ . Duplicate tuples are eliminated.

No.	Name
100	Smith
101	Ram
104	Hari
105	Ankit

R

No.	Name
100	Smith
102	Sham
103	Rajiv

S

No.	Name
100	Smith
101	Ram
102	Sham
103	Rajiv
104	Hari
105	Ankit

RUS.

APRIL

2011

M	T	W	T	F	S	S
					1	2
					3	
					4	5
					6	7
					8	9
					10	
					11	12
					13	14
					15	16
					17	
					18	19
					20	21
					22	23
					24	
					25	26
					27	28
					29	30

Intersection :-

The result of this operation denoted by  $R \cap S$ , is a relation that includes all tuples that are in both R and S.

ENO.	Name
100	Smith

$R \cap S$

Difference :-

The result of this operation, denoted by  $R - S$ , is a relation that includes all tuples that are in R but not in S.

ENO.	Name
101	Ram
104	Hari
105	Ankit

$R - S$

Cartesian Product  
in  
10<sup>th</sup> March  
Thursday \*

2. Relation-Oriented Operation :-

- Relation-Oriented operation covers data manipulation through the Selection, projection, joins and division operations.

Selection :-

The Selection operation selects tuples from a relation that satisfy the given condition and the operation is symbolized by  $\sigma$ . The syntax of the query is  $\sigma$  condition (relation).

M	T	W	T	F	S	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

The output of the query is also a relation. Logical connectives and comparison operators can be used in selection conditions.

THURSDAY

WEEK 10

03

MARCH 2011

DAY 062-303

The valid logical connectives are:

AND( $\wedge$ ), OR( $\vee$ ), NOT( $\neg$ )

Comparison operations are :-

$<$ ,  $>$ ,  $=$ ,  $\geq$ ,  $\leq$ ,  $\neq$

Example:-

Employee

Emp	Name	Dept.	Manager
100	Ankit	Product	Ajay
101	Raju	Account	Rama
102	Ram	Product	Ajay
103	Hari	Planning	Toppo
104	Sham	Account	Rama
105	Pooja	Security	Sachin

- Find all the employees belong to Account dept from the relation employee.

Ans.

$\cap \text{Dept.} = \text{'Account'}$  (Employee)

Emp	Name	Dept.	Manager
101	Raju	Account	Rama
104	Sham	Account	Rama

- Find all employees working under the manager  $\ominus$  'Ajay' from the relation employee.

Ans.  $\cap \text{Manager} = \text{'Ajay'}$  (Employee)

APRIL 2011					
M	T	W	T	F	S
					1
4	5	6	7	8	9
11	12	13	14	15	16
18	19	20	21	22	23
25	26	27	28	29	30

FRIDAY

WEEK 10

04

MARCH 2011

DAY 063-302

3. Find the employees working in production and Planning Dept.

Ans.  $\text{Dept.} = \text{'product'}$   $\text{Dept.} = \text{'planning'}$  (Employee)  
100, 102, 103

4. Find the employees working in Production dept. or the manager is Toppo?

Ans.  $\text{Dept.} = \text{'Product'}$   $\text{Manager} = \text{'Toppo'}$  (Employee)  
100, 102, 103.

5. Find the employees whose Emp is greater than 100 and less than 104 and working under the manager Rana.

Ans.  $\text{Emp} > 100 \wedge \text{Emp} < 104 \wedge \text{Manager} = \text{'Rana'}$  (Employee)  
101

### Projection Operator :-

The projection operation projects all or an attribute or a set of selective attributes from a relation.

It is a vertical subset of the given relation. The operation is symbolized by  $\Pi$ . The Syntax is  
 $\Pi\{\text{list of attribute names/offset positions}\}(\text{Relation})$

MARCH 2011					
M	T	W	T	F	S
1	2	3	4	5	6
7	8	9	10	11	12
14	15	16	17	18	19
21	22	23	24	25	26
28	29	30	31		

### Example:-

1. Show the Emp. and name of all employees in the relation employee.

SATURDAY

WEEK 10

05

MARCH 2011

DAY 064-301

Ans.  $\text{Temp. name} \ (\text{Employee})$  | 100, 101, 102,  
 or  
 $\text{TT}, 2 \ (\text{Employee})$  | 103, 104, 105.  
 Emp. Name only

2. Show the names of all the employees belong to Account dept. from the relation employee.

Ans.  $\text{Tname} \ ((\text{Dept.} = \text{'Account'}) \ (\text{Employee}))$ .

Name
Raju
Sham

3. Show the Emp. name and dept. working under the manager Ajay. from the relation employee.

Ans.  $\text{Temp.name, Dept.} \ ((\text{Manager} = \text{'Ajay'}) \ (\text{Employee}))$   
 Emp. Name, Dept.

100

102

4. Show the employee number and manager name for those who are working in product and planning.

Ans.  $\text{Temp. manager} \ ((\text{Dept} = \text{'product'}) \ \wedge \ (\text{Dept} = \text{'planning'}) \ (\text{Employee}))$ .

5. Find the employee whose Emp. is greater than 100 and less than 104 and working under manager Roma Show all attributes.

Ans.  $\text{TT}, 1, 2, 3, 4 \ ((\text{Emp} > 100) \ \wedge \ (\text{Emp} < 104) \ \wedge \ (\text{manager} = \text{'Roma'}) \ (\text{Employee}))$ .

APRIL 2011						
M	T	W	T	F	S	S
1	2	3				
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28	29	30	

MONDAY

07

MARCH 2011

WEEK 11

DAY 066-299

## Join Operation:-

Join is a combination of a Cartesian Product followed by a Selection process. A join operation, <sup>combine</sup>, pairs two tuples from different relations, if and only if a given condition is satisfied.

Various types of join Operations!:-

### Theta ( $\theta$ ) Join:-

The Conditional join is called  $\theta$ -join.

Notation:-  $R_1 \bowtie_{\theta} R_2$ .

### Equi-Join :-

When Theta join uses only equality comparison operator it is said to be Equi-join

No.	Name	No.	Name	Salary
100	Smith	100	Smith	5000
101	Rahul	105	Raju	4000
102	Ankit	107	Robin	3000
105	Raju			B
107	Robin			
109	Sachin			
R <sub>A</sub>		Emplno.		Dept.
		101	Account	
		107	Security	
		109	Planning	
				C.

1. List of all employees those who have debt.

MARCH 2011						
	M	T	W	T	F	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

Ans.  $\Theta_{Dept. \neq Null}(A \bowtie C)$

A. NO = E. Emp. NO.

Name
Rahul
Robin
Sachin

$\Rightarrow$  Equi join.

TUESDAY

08

MARCH 2011

WEEK 11

DAY 067-298

## Natural Join :-

Natural join does not use any comparison operator. It can only be performed if there exist at least one common attribute exist between them. Those attributes must have same name and domain.

CD	Course	Dept.
CS01	Database	CS
MEO1	Mechanics	ME

Course

Dept.	HOD
CS	Ajay
ME	Ram.

HOD

CD	Course	Dept.	HOD	Course X HOD.
CS01	Database	CS	Ajay	
MEO1	Mechanics	ME	Ram.	

## Outer join :-

All joint i.e. Theta join, Natural join, Equi join are called inner join. In Inner join includes only those tuples with matching attributes, rest are discarded in resulting relation. There exist methods by which all tuples of any relation are included in the resulting relation.

### Three kinds :-

#### Left Outer join :- (A $\bowtie$ B)

All tuples of left relation A, are included in the resulting relation and if there exists tuples in A without any matching tuple in B then the B attributes of resulting relation are made NULL.

APRIL 2011					
M	T	W	T	F	S
4	5	6	7	8	9
11	12	13	14	15	16
18	19	20	21	22	23
25	26	27	28	29	30

WEDNESDAY

WEEK 11

09

MARCH 2011

DAY 068-297

Course

HOD

A	B
100	Database
101	Mechanics

Left

C	D
100	Raj
102	Hari

Right

Course  $\Delta I$  HOD

A	B	C	D
100	Database	100	Raj
101	Mechanics	--	--

Right Outer Join (A  $\Delta I$  B) :-

All tuples of right relation B are included in the resulting relation if there exists tuples in B without any matching tuple in A then A attributes of resulting relation are made NULL.

A	B	C	D
100	Database	100	Raj
--	--	102	Hari

Course  $\Delta I$  HODFull Outer Join (A  $\Delta I$  B) :-

All tuples of both Participating relations are included in the resulting relation and if there no matching tuples for both relations, their respective unmatched attributes are made NULL.

A	B	C	D
100	Database	100	Raj
101	Mechanical	--	--

Course  $\Delta I$  HOD

MARCH 2011

M	T	W	T	F	S	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

THURSDAY

WEEK 11

10

MARCH 2011

DAY 069-296

## (\*) Cartesian Product:-

No.	Name	Dept.
100	Ram	planning
101	Hari	Security

A

B

No.	Name	Dept.
100	Ram	planning
100	Ram	Security
101	Hari	planning
101	Hari	Security

A X B.



## Division:-

The division operation is denoted by  $\div$ . It is suited for query that include the phrase "for all". The relation  $A \div B$  is a relation on schema A-B contains all attributes of Schema A that are not in Schema B.

APRIL 2011					
M	T	W	T	F	S
					1 2 3
4	5	6	7	8	9 10
11	12	13	14	15	16 17
18	19	20	21	22	23 24
25	26	27	28	29	30

Example :-

P:	A	B
	a <sub>1</sub>	b <sub>1</sub>
	a <sub>2</sub>	b <sub>2</sub>
	a <sub>3</sub>	b <sub>1</sub>
	a <sub>4</sub>	b <sub>2</sub>
	a <sub>5</sub>	b <sub>1</sub>
	a <sub>6</sub>	b <sub>2</sub>

Q <sub>1</sub> :	B
	b <sub>1</sub>
	b <sub>2</sub>

A
a <sub>1</sub>
a <sub>3</sub>

$$P \div Q_1$$

2.	name	Subject
	A	DBMS
	A	Java
	B	DBMS
	C	Java

Subject
DBMS
Java

Subject name.

Student

Find the names of students who passed in all the Subject

Student  $\div$  Subject name.

Ans.

name
A

Ans.

Extended Relational Algebra Operation:-

1. Rename Operation:-

The results of relational-algebra are also relations but without any name. The rename operation allows us to rename that relation. 'Rename' operation is denoted by

M	T	W	T	F	S	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

SATURDAY

WEEK 11

12

MARCH 2011

DAY 071-294

Small Greek letter rho P.

Notation -  $P_x(E)$

Where the result of Expression E is saved with name of x.

## 2. Aggregate functions:-

The type of queries that cannot be expressed in relational algebra is specified through aggregate functions. For example, to count the number of female employees and number of male employees the tuples are counted gender-wise.

The Standard aggregate functions Cr is

$\rightarrow$  Count  $\rightarrow$  Sum  $\rightarrow$  avg  
 $\rightarrow$  min  $\rightarrow$  max

Syntax :-

$\exists <function list>$   
(R)

EMP	Name	Office	Dept.	Salary
	Ram	4FO	CS	4500
	Hari	2FO	ECom	3500
	Raju	1FO	Ecom	5000
	Ankit	420	CS	6500
	Abhi	5FO	Plan	6000

SUNDAY 13

1. Find the minimum Salary:-

$\text{Fmin}(\text{salary}) (\text{EMP})$

min(salary)
3500

2. Find the average Salary:-

$\text{Favr}(\text{salary}) (\text{EMP})$

Ava(salary)
5100

APRIL 2011					
M	T	W	T	F	S
				1	2
4	5	6	7	8	9
11	12	13	14	15	16
18	19	20	21	22	23
25	26	27	28	29	30

MONDAY

14

MARCH 2011

WEEK 12

DAY 073-292

3. Count the no. of employees in the CS dept: -

~~Fcount~~ Fcount(name)( $\sigma_{Dept='CS'}(EMP)$ )

COUNT(name)
2

4. Find the total Payroll for the Ecom dept.

Fsum(salary)( $\sigma_{Dept='Ecom'}(EMP)$ ).

Assignment Operation:-

The assignment operation is denoted by  $\leftarrow$ .

temp  $\leftarrow$  (E)

temp is the new name and E is the expression.

Relational Calculus:-

It is divided into two groups:-

i)  Tuple relational Calculus:-

# tuple variable ( $t$ ) ranges for all tuple of relation R

#  $t.A \Rightarrow$  Column A of tuple t.

Basic Form:-  $\{ \underbrace{t_1 A_{11}, t_2 A_{12}, t_3 A_{13} \dots}_{\text{Calculus exp.}} | Q \}$

MARCH 2011				
M	T	W	T	F
1	2	3	4	5
6				
7	8	9	10	11
12				
13				
14	15	16	17	18
19				
20				
21	22	23	24	25
26				
27				
28	29	30	31	

Calculus exp.

Condition.  
one or many.

TUESDAY

WEEK 12

15

MARCH 2011

DAY 074-291

Once the tuples satisfies the condition then ~~the~~  
 Ass. P12 - ... ~~all~~ column are taken out from the  
 relation.

Example 1:- Student (Rollno., Name, Dept., Sex)  
 Find Rollno. and name of students in  
 dept. 2.

Ans.

$$\{ t. \text{Rollno.}, t. \text{Name} \mid \text{Student}(t) \wedge t. \text{Dept} = 2 \}$$

$\hookrightarrow$  t. table present  
in Student relation.

Example 2:- find Rollno. and name of male student in  
 dept. 2.

Ans.

$$\{ t. \text{Rollno.}, t. \text{Name} \mid \text{Student}(t) \wedge t. \text{Dept} = 2 \wedge$$

$$t. \text{Sex} = \text{Male} \}$$

Example 2:- Depositor (cust\_name, acc\_no.)  
 ~ ~~borrower~~ borrower (cust\_name, loan\_no.)  
 ~ loan (loan\_no., branch\_name, ~~amount~~ amount)  
 ~ Customer (cust\_name, city, street)  
 Account (acc\_no., branch\_name, balance)  
 Branch (branch\_name, branch\_city, accets)

2.1. Find the loan detail of loan above 1200.

$$\{ t \mid \text{loan}(t) \wedge t. \text{amount} > 1200 \}$$

$\hookrightarrow$  bcz all attributes are required.

APRIL 2011					
M	T	W	T	F	S
				1	2 3
4	5	6	7	8	9 10
11	12	13	14	15	16 17
18	19	20	21	22	23 24
25	26	27	28	29	30

WEDNESDAY

16

MARCH 2011

WEEK 12

DAY 075-290

2.2:- Find the names of all customer who have a loan from branch 'x';

(from borrower and wan)

Ans.

$$\{ b.\text{cust\_name} | \text{borrower}(b) \wedge \exists l (\text{loan}(l) \wedge l.\text{loan\_no.} = b.\text{loan\_no.} \wedge l.\text{branch\_name} = 'x') \}$$

$\Rightarrow l$  is bound variable.

↓ OR .

$$\{ b.\text{cust\_name} | \exists b \text{borrower} \wedge \exists l \text{loan} \wedge l.\text{loan\_no.} = b.\text{loan\_no.} \wedge l.\text{branch\_name} = 'x' \}$$

2.3:- Customer who have account or loan or both.

(We need to join Customer and depositor, Customer and borrower table)

$$\{ t | \text{Customer}(t) \wedge \underline{\text{if borrower}} \quad ①$$

or  
if depositor      ②

$$\begin{aligned} ① & \exists b (\text{borrower}(b) \wedge b.\text{cust\_name} = t.\text{cust\_name}) \\ ② & \exists d (\text{depositor}(d) \wedge d.\text{cust\_name} = t.\text{cust\_name}) \end{aligned}$$

MARCH 2011

M	T	W	T	F	S	S
1	2	3	4	5	6	
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

$$\{ t | \text{Customer}(t) \wedge \exists b (\text{borrower}(b) \wedge b.\text{cust\_name} = t.\text{cust\_name}) \}$$

$$\cdot \checkmark \exists d (\text{depositor}(d) \wedge d.\text{cust\_name} = t.\text{cust\_name}) \}$$

THURSDAY

WEEK 12

17

MARCH 2011

DAY 076-289

Example 3:- Student (rollNo., name, degree, year, sex, deptNo., advisor)  
 dept (deptId, name, hod, phone)  
 course (courseId, cname, credits, deptNo.)  
 enrollment (rollNo, courseId, sem, year, grade)

3.1 Determine the departments that do not have any girl students.

$\{ \exists t. \text{name} / \forall \text{dept}.(t) \wedge \neg (\exists s) (\text{student}(s) \wedge s. \text{Sex} = 'F' \wedge s. \text{deptNo.} = t. \text{deptId}) \}$

3.2 Obtain the names of courses enrolled by student named Mahesh.

$\{ \exists s. \text{name} | \text{Student}(s)$

$\exists c. \text{cname} | \text{Course}(c) \wedge \exists e (\forall c. \text{courseId} = e. \text{courseId})$   
 $\wedge \exists s (e. \text{rollNo} = s. \text{rollNo})$   
 $\wedge s. \text{name} = 'Mahesh')$

$\{ \exists c. \text{cname} | \text{Course}(c) \wedge \exists e (\text{enrollment}(e) \wedge e. \text{courseId} = c. \text{courseId}) \wedge \exists s (\text{student}(s) \wedge s. \text{rollNo.} = e. \text{rollNo}) \wedge s. \text{name} = 'Mahesh' \}$

Quantifier  $\rightarrow \exists, \forall$

Bound variable  $\rightarrow$  Quantified var

$$\sum_{k=0}^5$$

$k$  changes 0 to 5

Free variable.

APRIL 2011					
M	T	W	T	F	S
				1	2
4	5	6	7	8	9
11	12	13	14	15	16
18	19	20	21	22	23
25	26	27	28	29	30

FRIDAY

18

MARCH 2011

## WEEK 12

DAY 077-288

## ii) Domain Relational Calculus:-

SQL depends on  $\rightarrow$  tuple relation calculus

QBE       $\rightarrow$        $n \rightarrow$  Demain       $n$

## Query by example

Domain variable  $\rightarrow$  Range over domain of attributes.

Format :-

$$\{ n_1, n_2, n_3, \dots | \text{Cond}(n_1, n_2, \dots) \}$$




1.1 List the name and address of the employee whose name is Foo Bar.

abcde~~fgh~~ & xyz are domain variables.

Ans. { abc | E<sub>c</sub>E<sub>d</sub>E<sub>f</sub>E<sub>g</sub>.E<sub>h</sub> }<sup>①</sup> (Employee(abcde<sub>fgh</sub>))<sup>②</sup>  
 $(a = 'FOO') \wedge (b = 'Bar'))^{\{}$

Dumian var which is not present in (Emp - . . .)  $\textcircled{1} \rightarrow \textcircled{2}$   
we can eliminate them.

they are optional so  $E_C$ ,  $E_F$

Label Employee (a**c**d<sup>g</sup>e<sup>f</sup>gh) <sup>In args optional</sup> A (a='Foo') <sup>A</sup>  
b = 'Bar' ).

MARCH						2011	
M	T	W	T	F	S	S	S
1	2	3	4	5	6		
7	8	9	10	11	12	13	
14	15	16	17	18	19	20	
21	22	23	24	25	26	27	
28	29	30	31				

SATURDAY

19

MARCH 2011

WEEK 12

DAY 078-287

OR U

{!@b1 Employee ('FOO', 'Bar', c, d, e, f, g, h) }

Q21 - List the name of employee who have no department to manage.

We need to find the name so that the Eid in employee does not matched with mid in dept.

Ans ab | !@c (Employee (a b c d e f g h) ^ !@z (Dept (x y z)  
 ↓ → ^  
 Domain of  
 c ) ) }  
 {

QBE :-

Query-by-example is the name of a database query lang. for relational databases. It is first graphical query lang. using visual tables where the user would enter commands. Today, some database systems for personal computers support variants of QBE lang.

QBE queries are expressed "by example". Instead of giving a procedure for obtaining the desired answer, the user gives an example of what is desired. (SQL).

APRIL 2011					
M	T	W	T	F	S
				1	2
4	5	6	7	8	9
11	12	13	14	15	16
18	19	20	21	22	23
25	26	27	28	29	30