

Python

Strings

Strings are sequences of characters

Strings are sequences of characters

No separate character type: just a string of length 1

Strings are sequences of characters

No separate character type: just a string of length 1

Indexed exactly like lists

Strings are sequences of characters

No separate character type: just a string of length 1

Indexed exactly like lists

```
name = 'Darwin'  
print(name[0], name[-1])  
D n
```

`for` iterates through characters

for iterates through characters

```
name = 'Darwin'  
for c in name:  
    print(c)
```

D
a
r
w
i
n

Use either ' or " (as long as they match)

Use either ' or " (as long as they match)

```
print('Alan', "Turing")  
Alan Turing
```

Use either ' or " (as long as they match)

```
print('Alan', "Turing")  
Alan Turing
```

Strings are the same no matter how they're created

Use either ' or " (as long as they match)

```
print('Alan', "Turing")  
Alan Turing
```

Strings are the same no matter how they're created

```
print('Alan' == "Alan")  
True
```

Strings are compared character by character
from left to right (based on their Unicode value)

Strings are compared character by character
from left to right (based on their Unicode value)

```
print('a' < 'b')
```

True

Strings are compared character by character
from left to right (based on their Unicode value)

```
print('a' < 'b')
```

True

```
print('ab' < 'abc')
```

True

Strings are compared character by character
from left to right (based on their Unicode value)

```
print('a' < 'b')
```

True

```
print('ab' < 'abc')
```

True

```
print('1' < '9')
```

True

Strings are compared character by character
from left to right (based on their Unicode value)

```
print('a' < 'b')
```

True

```
print('ab' < 'abc')
```

True

```
print('1' < '9')
```

True

```
print('100' < '9')
```

True

Strings are compared character by character
from left to right (based on their Unicode value)

```
print('a' < 'b')
```

True

```
print('ab' < 'abc')
```

True

```
print('1' < '9')
```

True

```
print('100' < '9')
```

True

```
print('A' < 'a')
```

True

Strings are *immutable* : cannot be changed in place

Strings are *immutable* : cannot be changed in place

```
name = 'Darwin'
```

```
name[0] = 'C'
```

TypeError: 'str' object does not support item assignment

Strings are *immutable* : cannot be changed in place

```
name = 'Darwin'
```

```
name[0] = 'C'
```

TypeError: 'str' object does not support item assignment

Immutability improves performance

Use + to concatenate strings

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print(name)  
Charles Darwin
```

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print(name)  
Charles Darwin
```

Concatenation always produces a new string

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print(name)  
Charles Darwin
```

Concatenation always produces a new string

```
original = 'Charles'
```


original → 'Charles'

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print(name)  
Charles Darwin
```

Concatenation always produces a new string

```
original = 'Charles'  
name = original
```



Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print(name)  
Charles Darwin
```

Concatenation always produces a new string

```
original = 'Charles'  
name = original  
name += ' Darwin'
```

original → 'Charles'

name → 'Charles Darwin'

Strings can be formatted with +...

Strings can be formatted with +...

```
print('reagent: ' + str(reagent_id) + ' produced ' + \
      str(percentage_yield) + '% yield')
```

Strings can be formatted with +...

```
print('reagent: ' + str(reagent_id) + ' produced ' + \
      str(percentage_yield) + '% yield')
```

There's a better way...

f-strings!!! (>python 3.6)

f-strings!!! (>python 3.6)

The example on the last slide:

```
print('reagent: ' + str(reagent_id) + ' produced ' + \
      str(percentage_yield) + '% yield')
```

f-strings!!! (>python 3.6)

The example on the last slide:

```
print('reagent: ' + str(reagent_id) + ' produced ' + \
      str(percentage_yield) + '% yield')
```

Using f-strings:

```
print(f'reagent: {reagent_id} produced ' \
      f'{percentage_yield} % yield')
```


f-strings!!! (>python 3.6)

The example on the last slide:

```
print('reagent: ' + str(reagent_id) + ' produced ' + \
      str(percentage_yield) + '% yield')
```

Using f-strings:

```
print(f'reagent: {reagent_id} produced ' \
      f'{percentage_yield} % yield')
```

Use {{ to get a { in the output:

```
print(f'reagent: {{reagent_id}} ')
reagent: {123}
```

F-strings can also format the output:

```
yield = 0.34
```

Other format options:

<https://docs.python.org/3/library/string.html#format-specification-mini-language>

F-strings can also format the output:

```
yield = 0.34
```

As a percentage:

```
print(yield: {yield:.2%})  
'yield: 34.00%'
```

Change precision:

```
print(yield: {yield:.1f})  
'yield: 0.3'
```

Add padding:

```
print(yield: {yield:07.2%})  
'yield: 034.00%'
```

Other format options:

<https://docs.python.org/3/library/string.html#format-specification-mini-language>

In older code you may come across two different styles

In older code you may come across two different styles

`.format()`

```
'{0}, {1}, {2}'.format('a', 'b', 'c')  
'a, b, c'
```

```
'Coordinates: {latitude}, {longitude}'.format(  
    latitude='37.24N', longitude='-115.81W')
```

```
'Coordinates: 37.24N, -115.81W'
```

In older code you may come across two different styles

`.format()`

```
{0}, {1}, {2}'.format('a', 'b', 'c')  
'a, b, c'
```

```
Coordinates: {latitude}, {longitude}'.format(  
    latitude='37.24N', longitude='-115.81W')
```

```
Coordinates: 37.24N, -115.81W'
```

You could, but f-strings are faster and clearer

% format

```
print('reagent: %d' % 123)
```

```
reagent: 123
```

```
print('Name: %s; weight: %.2fkg' % ('Bert', 122))
```

```
Name: Bert; weight: 122.00kg
```

% format

```
print('reagent: %d' % 123)
```

```
reagent: 123
```

```
print('Name: %s; weight: %.2fkg' % ('Bert', 122))
```

```
Name: Bert; weight: 122.00kg
```

This is a hang-over from python 2.7

This approach is now discouraged.

Use `\n` to represent a newline character

Use `\n` to represent a newline character

Use `\'` for single quote, `\''` for double quote

Use `\n` to represent a newline character

Use `\'` for single quote, `\''` for double quote

```
print('There isn\'t time\nto do it right.')  
There isn't time  
to do it right.
```

Use `\n` to represent a newline character

Use `\'` for single quote, `\"` for double quote

```
print('There isn\'t time\nto do it right.')
```

```
There isn't time  
to do it right.
```

```
print("But you said,\n\"There is time to do it over.\")
```

```
But you said,  
"There is time to do it over."
```

Use \\ for a literal \ character

Use \\ for a literal \ character

```
print('Most mathematicians write a\\b instead of a%b.')  
Most mathematicians write a\b instead of a%b.
```

Use `\\` for a literal `\` character

```
print('Most mathematicians write a\\b instead of a%b.')  
Most mathematicians write a\b instead of a%b.
```

Common pattern with *escape sequences*

Use `\\` for a literal `\` character

```
print('Most mathematicians write a\\b instead of a%b.')  
Most mathematicians write a\b instead of a%b.
```

Common pattern with *escape sequences*

- Use a character to mean "what follows is special"

Use `\\` for a literal `\` character

```
print('Most mathematicians write a\\b instead of a%b.')  
Most mathematicians write a\b instead of a%b.
```

Common pattern with *escape sequences*

- Use a character to mean "what follows is special"
- Double it up to mean "that character itself"

Use triple quotes (either kind) for multi-line strings

Use triple quotes (either kind) for multi-line strings

```
quote = """We can only see  
a short distance ahead,  
but we can see plenty there  
that needs to be done."""
```

Use triple quotes (either kind) for multi-line strings

```
quote = """We can only see  
a short distance ahead,  
but we can see plenty there  
that needs to be done."""
```

d	,	\n	b	u
---	---	----	---	---

Use triple quotes (either kind) for multi-line strings

```
quote = """We can only see  
a short distance ahead,  
but we can see plenty there  
that needs to be done."""
```

```
quote = "We can only see\na short distance" + \  
" ahead,\nbut we can see plenty there\nthat" + \  
" needs to be done."
```

Strings have methods

Strings have methods

```
name = 'newTON'  
print(name.capitalize(), name.upper(), name.lower())  
Newton NEWTON newton
```

Strings have methods

```
name = 'newTON'  
print(name.capitalize(), name.upper(), name.lower())  
Newton NEWTON newton  
  
dna = 'acggtgggtcac'  
print(dna.count('g'), dna.count('x'))  
4 0
```


Strings have methods

```
name = 'newTON'
print(name.capitalize(), name.upper(), name.lower())
Newton NEWTON newton
dna = 'acggtggtcac'
print(dna.count('g'), dna.count('x'))
4 0
print(dna.find('t'), dna.find('t', 5), dna.find('x'))
4 7 -1
```

Strings have methods

```
name = 'newTON'
print(name.capitalize(), name.upper(), name.lower())
Newton NEWTON newton
dna = 'acggtggtcac'
print(dna.count('g'), dna.count('x'))
4 0
print(dna.find('t'), dna.find('t', 5), dna.find('x'))
4 7 -1
print(dna.replace('t', 'x'))
acggxggxcac
```

Strings have methods

```
name = 'newTON'
print(name.capitalize(), name.upper(), name.lower())
Newton NEWTON newton
dna = 'acggtggtcac'
print(dna.count('g'), dna.count('x'))
4 0
print(dna.find('t'), dna.find('t', 5), dna.find('x'))
4 7 -1
print(dna.replace('t', 'x'))
acggxggxcac
print(dna.replace('gt', ''))
acggcac
```

Can chain method calls together

Can chain method calls together

```
element = 'cesium'  
print(element.upper().center(10, '.'))
```

Can chain method calls together

```
element = 'cesium'  
print(element.upper().center(10, '.'))
```



convert to upper case

Can chain method calls together

```
element = 'cesium'  
print(element.upper().center(10, '.'))
```



center in a field

10 characters wide

Can chain method calls together

```
element = 'cesium'  
print(element.upper().center(10, '.'))  
..CESIUM..
```


The power of regular expressions

When programming in any language you will want to know about *regular expressions* – for advanced string/text processing. In Python use the "re" library. Example uses are:

`/<([A-Z][A-Z0-9]*)\b[^>]*>(.*?)</\1>/` Matches the opening and closing pair of any HTML tag; captures tag name and content.

`/b[aeiou]+t/` Matches "bat" and "bit" etc, but also "boot" and "boat".

`/(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3})/`
Matches any IP address ((e.g. 66.70.7.154) and captures the each number for re-use.

See: <https://docs.python.org/3.7/howto/regex.html>