VLAN and Basic Configuration

Time: 30 mins

Take IP address 192.168.240.0/20. Create necessary VLSM to give IP address as following

- Faculty/Staff (240 hosts)
- Students (240 hosts)
- Guest (120 hosts)
- Native (10 hosts)
- Management (10 hosts)

Addressing Table

Device	Interface	IP Address
S1 – S2	VLAN 10	1st usable IP address
	VLAN 20	1st usable IP address
	VLAN 30	1st usable IP address
	VLAN 88	1st usable IP address
	VLAN 99	3rd usable IP address
PC1	NIC	10th usable IP address
PC2	NIC	10th usable IP address
PC3	NIC	10th usable IP address
PC0	NIC	30th usable IP address
PC4	NIC	30th usable IP address
PC5	NIC	30th usable IP address

VLAN and Port Assignments Table

VLAN	Name	Interface
10	Faculty/Staff	F0/11
20	Students	F0/18
30	Guest (Default)	F0/7
88	Native	F0/1

VLAN	Name	Interface
99	Management	VLAN 99

1. Set host name CSE-S1 and CSE-S2.
2. Assign IP addressing to S1 and S2 based on the Addressing Table.
3. Create, name, and assign VLANs on S1 based on the VLAN and Port Assignments Table. Ports should be in access mode. Your VLAN names should match the names in the table exactly.
4. Configure inter-VLAN routing on R1 based on the Addressing Table.
5. Verify connectivity. All PCs should be able to ping each other.