Second Look

Finding the disaster survivors FEMA turned away even though an inspector verified their damage, and getting them a callback.

Built and run on IBM LinuxONE (IBM z17, s390x) · IBM Snap ML · Telum AI accelerator · IBM Granite · Podman

We grew up in Bangladesh watching floods take homes. The second loss came later, on paper.

Families without a deed, a lease or a utility bill in their own name get turned away from aid. It happens everywhere. The difference in the US is that FEMA publishes every application, so the gap can be measured.

So we measured it, and built a way to close it.


94,395

households had damage that an inspector verified and were still denied, for a reason a phone call could fix.

$612M	$385M	71,674	1,786
verified loss in the group	aid likely never paid (modeled: median award to approved neighbors, same disaster and loss)	homes not livable without repairs	counties with at least one household in the group

Rule: verified damage AND denied AND fixable reason code (3, 4, or 7/9 with ownership/occupancy unverified)

The paperwork gap falls hardest on renters and the poorest households.



Logistic regression on households with verified damage, controlling for loss, livability, destruction, disaster type and year. These are associations, not causes. Applicants with access or functional needs are *less* likely to land in the group, and we report that as found.

From 26 million records to a caseworker's next phone call.

1 · Cohort rule

Verified damage, denied, fixable reason. Rules, so every flag fits in one sentence.

2 · Snap ML model

Who lands here, from pre-decision facts only. Tested on 114 unseen disasters.

3 · Fairness audit

Rates with 95% intervals and adjusted odds ratios.

4 · Ranked callbacks

Per disaster: loss, livability, reason, vulnerability. The weights are visible.


5 · Granite + RAG

A cited note and script per household, grounded in FEMA's policy guide.

6 · Dashboard

Story, caseworker console, method. Served from a hardened container.

The trap we avoided: FEMA eligibility is nearly a rule, so a naive model reaches 0.99 AUC and learns nothing. We train only on verified-damage households and split by disaster.



Hurricane Laura, Louisiana, 2020: 6,039 households to call.

Each row shows why it was flagged. The side panel holds IBM Granite's note and call script, with the FEMA policy sections it cites. Caseworkers can expand each citation to read the source passage.

CSV export goes straight into an outreach workflow.

The lab explains why a bank said no. We find the families a system said no to, wrongly.

1. **Retrieve.** FEMA's Individual Assistance Program and Policy Guide (IAPPG 1.1, ch. 3) is split into 89 passages and indexed as TF-IDF vectors. Each denial reason may only cite its own sections: Occupancy and Ownership, Identity, Insurance, Applicant Communication, plus the 60-day appeal rule.

2. **Generate locally.** IBM Granite 3.3 2B Instruct runs in llama.cpp on the z17, from a big-endian GGUF. No household data leaves the machine.

3. **Verify before showing.** Each citation must be a retrieved passage, each dollar amount must match the inspector's figure, and nothing may promise approval. Otherwise the note is rejected and the template script is shown.


On the z17: 50 notes covering the top 5 callbacks in each of the 10 largest disasters. All 50 passed the checks. Median 142s and 252 tokens per note on 3 shared vCPUs.

Every step runs on the mainframe, and we report what we measured.

Workload	Framework	Measured on z17
Cohort model, 6.98M training rows	IBM Snap ML	ROC AUC **0.785** on 114 unseen disasters; precision 41.9% in the top 1,000 (40x the base rate)
Score all 8,938,750 households	Snap ML engines	Compressed trees **2.31M/s** (3.9s) · standard 419k/s
Keras twin on Telum NNPA	TensorFlow + IBM zDNN plugin	Telum NNPA **1.75M/s** vs CPU 1.42M/s (**1.23x**) on 1.96M held-out households; scores differ by up to 0.0033, so the NNPA really ran
Cited callback notes	IBM Granite 3.3 2B · llama.cpp	50 cited notes, 0 rejected by the checks; 4.5 tokens/s generation (llama-bench, Q4_0)
Dashboard and API	FastAPI · Podman	Rootless container, image built natively for s390x (148 MB)

Second Look: system architecture

From 26.2M OpenFEMA aid applications to a caseworker's callback list. Every analysis step runs on IBM LinuxONE.



Sensitive by nature, so nothing leaves the box.

Local LLM. Granite runs on the VM and listens only on 127.0.0.1. No third-party AI API ever sees a household.	**Hardened container.** Rootless Podman with a read-only root filesystem, all capabilities dropped, no-new-privileges, and a non-root UID.
Read-only data. The database is mounted `:ro`, and the API opens SQLite with `mode=ro`.	**No inbound port.** The dashboard binds to localhost. Caseworkers use an SSH tunnel with key-only auth, and the public demo uses an outbound Cloudflare tunnel to the read-only API. We replaced the public default Jupyter token.
No direct identifiers. OpenFEMA has no names, addresses or phone numbers. Households are opaque record IDs.	**Guarded generation.** Citations, dollar amounts and promises are checked in code before any note is shown.

Eight things that broke, and the fix that is now in code.

1. pyarrow 19 reads numeric Parquet as null on big-endian. Every intermediate file is now Arrow IPC.
2. 26M rows × 33 columns needed more than 16 GB in pandas. Cohort labeling streams batches, with a 364 MB peak.
3. Snap ML's zDNN build needs the system libstdc++ (LD_PRELOAD).
4. Snap ML heap-crashes on NaN, so missing values become -1.
5. FEMA's CDN blocks the VM, so ingest runs on a little-endian host.
6. GGUF models are little-endian; we use a big-endian Granite build.
7. GCC 13 doesn't know z17's `–march=arch15`, so llama.cpp is built for z16.
8. Without `–mzvector`, llama.cpp silently drops to scalar code: 1.2 vs 4.5 tokens/s.

A starting point for outreach, never a decision.

1. The data shows who was denied, not why each family's paperwork failed. A caseworker confirms everything on the call.
2. The model learns FEMA's past decisions, biases included. We use it only to decide whom to call first, never to deny anyone.
3. Adjusted odds ratios are associations with controls, not causal estimates.
4. Granite drafts; people decide. Notes that fail a check are hidden, and the rules behind the ranking are shown in the open.
5. Appeal windows for older disasters have closed. The value for those is measuring the gap; live use belongs in open disasters.

Team Second Look

Mahir Abdullah designed and built all of Second Look: the data pipeline, the model and fairness audit, the LinuxONE port, the Granite RAG layer and the dashboard.

Team members: **Arnab Dev**, **Azfar Islam** and **Raihan Ahmed**. All four of us grew up in Bangladesh.

94,395 households. One callback each.

Next

Run it live in open disasters, while appeal windows are still open, together with legal-aid and recovery nonprofits.

Then take it home to Bangladesh, where informal land tenure makes proof of ownership even harder to come by.