

# IMMUTABLE DATA STRUCTURES

---

*Don't you ever change!*

# TRAJECTORY

- **What are immutable data structures?**
- **Why use immutable data structures?**
- **Immutable data structures and JavaScript**

**IMMUTABILITY: STATE CANNOT  
BE MODIFIED AFTER CREATION**

# IMMUTABLE DS

- **What if, instead of mutating an array, using push or pop behaved like map or filter, and returned a new array?**
- **What if assigning a new key-value pair in an object was an operation that returned a new copy of the object?**

```
let obj = {a: 'someData'}
```

```
lolFunction(obj)
```

```
console.log(obj) // what are we going to get?
```

```
const obj = {a: 'someData'}
```

```
const newObj = lolFunction(obj)
```

```
// Now I know that if I want to use obj, I'll use obj  
// If I want newObj, I'll use newObj!
```

# ADVANTAGES

- **Predictability**
- **Referential transparency**
- **Easier to debug**
- **Can treat a collection of data like a single value**

# DISADVANTAGES

- **Requires more space**
  - Workaround: implement **structural sharing**
  - Still some dependency on garbage collection in your environment
- **Sometimes less performant, depending on what you're trying to do**



# IMMUTABLE LINKED LIST OPERATIONS & STRUCTURAL SHARING




# PREPEND






# PREPEND






# PREPEND






# APPEND






# APPEND






# INSERT





# INSERT







# COPY (MUTABLE DS)





# COPY (MUTABLE DS)





# COPY (IMMUTABLE)





# COPY (IMMUTABLE)



Err...we're done?



- **Mutable single-linked list  
(assuming front, back and  
insertion nodes are known)**

- Prepend:  $O(1)$
- Append:  $O(1)$
- Insert:  $O(1)$
- Find:  $O(n)$
- Copy:  $O(n)$

- **Immutable single-linked list  
(assuming front, back and insertion  
nodes are known)**

- Prepend:  $O(1)$
- Append:  $O(n)$
- Insert:  $O(n)$
- Find:  $O(n)$
- Copy:  $O(1)$

WHAT ABOUT JS?

# JAVASCRIPT

- **Primitive types are immutable**
  - Strings, Numbers, Booleans, Symbols
- **Objects (which includes Functions and Arrays) are mutable**

# MUTATIONS

```
const arr = [1, 2, 3]
```



# MUTATIONS

```
const arr = [1, 2, 3]
```

```
arr.pop() // [1, 2]
```

# MUTATIONS

```
const arr = [1, 2, 3]
```

```
arr.pop() // [1, 2]
```

```
arr.push(4) // [1, 2, 4]
```

# MUTATIONS

```
const arr = [1, 2, 3]
```

```
arr.pop() // [1, 2]
```

```
arr.push(4) // [1, 2, 4]
```

```
arr.splice(1, 1) // [1, 4]
```

# MUTATIONS

```
const obj = {}
```

# MUTATIONS

```
const obj = {}
```

```
obj.a = 97 // {a: 97}
```

```
obj.b = 98 // {a: 97, b: 98}
```

# MUTATIONS

```
const obj = {}
```

```
obj.a = 97 // {a: 97}
```

```
obj.b = 98 // {a: 97, b: 98}
```

```
delete obj.a // {b: 98}
```

# IMMUTABILITY

```
const arr1 = [1, 2, 3]
```

# IMMUTABILITY

```
const arr1 = [1, 2, 3]
```

```
const arr2 = arr1.slice(0, -1) // [1, 2]
```



# IMMUTABILITY

```
const arr1 = [1, 2, 3]
```

```
const arr2 = arr1.slice(0, -1) // [1, 2]
```

```
const arr3 = [...arr2, 4] // [1, 2, 4]
```

# IMMUTABILITY

```
const arr1 = [1, 2, 3]
```

```
const arr2 = arr1.slice(0, -1) // [1, 2]
```

```
const arr3 = [...arr2, 4] // [1, 2, 4]
```

```
const arr4 = arr3.filter((i) => i !== 2) // [1, 4]
```

# IMMUTABILITY

```
const obj1 = {}
```

# IMMUTABILITY

```
const obj1 = {}
```

```
const obj2 = {...obj1, a: 97} // {a: 97}
```

```
const obj3 = {...obj2, b: 98} // {a: 97, b: 98}
```

# IMMUTABILITY

```
const obj1 = {}
```

```
const obj2 = {...obj1, a: 97} // {a: 97}
```

```
const obj3 = {...obj2, b: 98} // {a: 97, b: 98}
```

```
const {a, ...obj4} = obj3 // {b: 98}
```

# IMMUTABLE

IMMUTABLE

# IMMUTABLE.JS

```
import {List} from 'immutable'
```

# IMMUTABLE.JS

```
import {List} from 'immutable'
```

```
const l1 = List.of(1, 2, 3) // List [1, 2, 3]
```



# IMMUTABLE.JS

```
import {List} from 'immutable'  
  
const l1 = List.of(1, 2, 3) // List [1, 2, 3]  
const l2 = l1.pop() // List [1, 2]
```

# IMMUTABLE.JS

```
import {List} from 'immutable'  
  
const l1 = List.of(1, 2, 3) // List [1, 2, 3]  
const l2 = l1.pop() // List [1, 2]  
const l3 = l2.push(4) // List [1, 2, 4]
```

# IMMUTABLE.JS

```
import {List} from 'immutable'  
  
const l1 = List.of(1, 2, 3) // List [1, 2, 3]  
const l2 = l1.pop() // List [1, 2]  
const l3 = l2.push(4) // List [1, 2, 4]  
  
const l4 = l3.remove(1) // List [1, 4]
```

# IMMUTABLE.JS

```
import {Map} from 'immutable'
```

# IMMUTABLE.JS

```
import {Map} from 'immutable'  
const m1 = new Map() // Map {}
```

# IMMUTABLE.JS

```
import {Map} from 'immutable'  
  
const m1 = new Map() // Map {}  
const m2 = m1.set('a', 97) // Map {a: 97}
```

# IMMUTABLE.JS

```
import {Map} from 'immutable'  
  
const m1 = new Map() // Map {}  
const m2 = m1.set('a', 97) // Map {a: 97}  
const m3 = m2.set('b', 98) // Map {a: 97, b: 98}
```

# IMMUTABLE.JS

```
import {Map} from 'immutable'  
  
const m1 = new Map() // Map {}  
const m2 = m1.set('a', 97) // Map {a: 97}  
const m3 = m2.set('b', 98) // Map {a: 97, b: 98}  
  
const m4 = m3.delete('a') // Map {b: 98}
```