
Warm Up

Let’s write a simple self-introduction page in HTML.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>About Me</title>
</head>
<body>
  <h1>Ichiro</h1>
</body>
</html>
```

Copy and paste (or type) the code above into WebDen and run it.



html lang="en"> head> /head>

Adam

/html>

A simple page is displayed.

Next, let’s change the text color and size using CSS.

HTML Code

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>About Me</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <h1 class="name">Ichiro</h1>
</body>
</html>
```

CSS Code

```
.name {
  color: blue;
}
```

Copy and paste (or type) into WebDen and run it.



The text has turned blue.

In this code, a class named class="name" is specified inside the HTML tag, and the design for that class is defined in the CSS.

By specifying classes in this way, you can individually change the design even for tags of the same type.

Try

Try adding more items (content) to display.
Try changing the text size and font.

Exercise

Let's try creating a page other than a self-introduction page.

13-3 HTML, JS

Point!

JavaScript is a programming language that runs in web browsers.

By embedding it into web pages, you can add interactivity to the page or cause changes to occur in response to user actions.

HTML
Structure and Content
"Headings, text, etc."
Code Example:

```
<h1>My page</h1>
<p id="text1">HELLO</p>
<p id="text2">WORLD</p>
```

JavaScript
Manipulation
"Moving, zooming, changing, etc."
Code Example:

```
document.getElementById("text1").textContent
= "GOOD MORNING";
```

Browser Display



In the example above, an id is specified for the HTML <p> tag, and JavaScript uses that id to change the text inside the tag. **.textContent** is used when specifying (or accessing) the text inside a tag.