

Derivation of the optimization gradients

Technical report of:

“Full-pose Trajectory Tracking of Overactuated Multi-Rotor Aerial Vehicles with Limited Actuation Abilities”

Under review at *IEEE Robotics and Automation Letters*
2023

Abstract—This document is a technical attachment to [?] containing the derivation of the gradients of the optimization problem presented in the paper.

APPENDIX

A. Gradient of the multiobjective optimization

First of all, let us rewrite the control input as a fixed part that does not depend on the optimization variables, and a variable part as follows:

$$\mathbf{u}_c = \mathbf{A}_1 \mathbf{v} + \mathbf{A}_2 \sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2} + \mathbf{B}\mathbf{x} + \hat{\mathbf{u}} \quad (1)$$

where $\hat{\mathbf{u}}$ is the fixed part of the control input. The derivative of \mathbf{u}_c w.r.t. the optimization variables can be written as follows:

$$\frac{\delta \mathbf{u}_c}{\delta \mathbf{v}} = \mathbf{A}_1 - \mathbf{A}_2 \frac{\mathbf{C}^T \mathbf{C} \mathbf{v}}{\sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2}} \quad (2)$$

$$\frac{\delta \mathbf{u}_c}{\delta \mathbf{x}} = \mathbf{B} \quad (3)$$

a) Objective function: The objective function has three parts, where the first two parts are function of one of the variables, while the third depends on the two variables.

$$\alpha/2 \frac{\delta(\|\mathbf{v}_r - \mathbf{v}\|^2)}{\delta \mathbf{v}} = \alpha(\mathbf{v}_r - \mathbf{v}) \quad (4)$$

$$\beta/2 \frac{\delta(\|\mathbf{x}\|_Q)}{\delta \mathbf{x}} = \beta \mathbf{Q} \mathbf{x} \quad (5)$$

$$\gamma/2 \frac{\delta(\|\mathbf{u}_c - \mathbf{u}_c(t-1)\|^2)}{\delta \mathbf{v}} = \gamma(\mathbf{u}_c - \mathbf{u}_c(t-1)) \frac{\delta \mathbf{u}_c}{\delta \mathbf{v}} \quad (6)$$

$$\gamma/2 \frac{\delta(\|\mathbf{u}_c - \mathbf{u}_c(t-1)\|^2)}{\delta \mathbf{x}} = \gamma(\mathbf{u}_c - \mathbf{u}_c(t-1)) \frac{\delta \mathbf{u}_c}{\delta \mathbf{x}} \quad (7)$$

b) Cost function: As discussed [?], in this paper we assume that actuation limits can be written as a combination of linear and quadratic inequality constraints. In what follows we will provide gradients for such constraints, while assuming that constraints for each propeller are independent from the constraints for other propellers. As such, it is convenient to write the corresponding propeller control as follows:

$$\mathbf{u}_i = \mathbf{A}_{1,i} \mathbf{v} + \mathbf{A}_{2,i} \sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2} + \mathbf{B}_i \mathbf{x} + \hat{\mathbf{u}}_i \quad (8)$$

where $\mathbf{A}_{1,i}$, $\mathbf{A}_{2,i}$ and \mathbf{B}_i are the rows of the corresponding matrices contributing to \mathbf{u}_i .

A very common quadratic constraint involves the maximum thrust generated by each propeller, which is directly related to the norm of the propeller’s controls. The squared norm of the propeller thrust can be written as follows:

$$\begin{aligned} \mathbf{u}_i^T \mathbf{u}_i &= \mathbf{v}^T \mathbf{A}_{1,i}^T \mathbf{A}_{1,i} \mathbf{v} + \mathbf{A}_{2,i}^T \mathbf{A}_{2,i} (1 - \|\mathbf{C}\mathbf{v}\|^2) + \\ &\quad 2\sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2} \mathbf{A}_{2,i}^T \mathbf{A}_{1,i} \mathbf{v} + 2\mathbf{v}^T \mathbf{A}_{1,i}^T \hat{\mathbf{u}}_i + \\ &\quad 2\sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2} \mathbf{A}_{2,i}^T \hat{\mathbf{u}}_i + \mathbf{x}^T \mathbf{B}_i^T \mathbf{B}_i \mathbf{x} + \|\hat{\mathbf{u}}_i\|^2 \end{aligned} \quad (9)$$

Note that propeller commands allocated from the allocation matrix ($\mathbf{A}_{1,i}$, $\mathbf{A}_{2,i} \sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2}$ and $\hat{\mathbf{u}}_i$) are orthogonal to the propeller commands from the null space of the allocation matrix. As such, all cross products between the first and second group have been omitted from Eq. (9).

In this paper, we will focus on two types of inequality constraints as follows:

$$\mathbf{J}_1 : \mathbf{D} \mathbf{u}_i \leq \mathbf{b} \quad (10)$$

$$\mathbf{J}_2 : \mathbf{u}_i^T \mathbf{u}_i \leq \|u_{i,max}\|^2 \quad (11)$$

The derivatives of the two constraints can be written as follows:

$$\frac{\delta \mathbf{J}_1}{\delta \mathbf{v}} = \mathbf{D} \frac{\delta \mathbf{u}_i}{\delta \mathbf{v}} \quad (12)$$

$$\frac{\delta \mathbf{J}_1}{\delta \mathbf{x}} = \mathbf{D} \frac{\delta \mathbf{u}_i}{\delta \mathbf{x}} \quad (13)$$

$$\begin{aligned} \frac{\delta \mathbf{J}_2}{\delta \mathbf{v}} &= 2\mathbf{A}_{1,i}^T \mathbf{A}_{1,i} \mathbf{v} - 2\mathbf{A}_{1,i}^T \mathbf{A}_{1,i} \mathbf{C}^T \mathbf{C} \mathbf{v} + \\ &\quad 2 \frac{\mathbf{v}^T \mathbf{C}^T \mathbf{C}}{\sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2}} \mathbf{A}_{2,i}^T \mathbf{A}_{1,i} \mathbf{v} - 2\sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2} \mathbf{A}_{1,i}^T \mathbf{A}_{2,i} \\ &\quad 2\mathbf{A}_{1,i}^T \mathbf{u}_i^T - + 2 \frac{\mathbf{v}^T \mathbf{C}^T \mathbf{C}}{\sqrt{1 - \|\mathbf{C}\mathbf{v}\|^2}} \mathbf{A}_{2,i}^T \mathbf{u}_i \end{aligned} \quad (14)$$

$$\frac{\delta \mathbf{J}_2}{\delta \mathbf{x}} = 2\mathbf{Q}_i \mathbf{x} \quad (15)$$

REFERENCES

- [1] M. Hamandi, F. Usai, Q. Sablé, N. Staub, M. Tognon, and A. Franchi, “Design of multirotor aerial vehicles: A taxonomy based on input allocation,” *The International Journal of Robotics Research*, vol. 40, no. 8-9, pp. 1015–1044, 2021.
- [2] M. Tognon and A. Franchi, “Omnidirectional aerial vehicles with unidirectional thrusters: Theory, optimal design, and control,” *IEEE Robotics and Automation Letters*, vol. 3, no. 3, pp. 2277–2282, 2018.

- [3] S. Park, J. Lee, J. Ahn, M. Kim, J. Her, G.-H. Yang, and D. Lee, "Odar: Aerial manipulation platform enabling omnidirectional wrench generation," *IEEE/ASME Transactions on mechatronics*, vol. 23, no. 4, pp. 1907–1918, 2018.
- [4] M. Zhao, T. Anzai, F. Shi, X. Chen, K. Okada, and M. Inaba, "Design, modeling, and control of an aerial robot dragon: A dual-rotor-embedded multilink robot with the ability of multi-degree-of-freedom aerial transformation," *IEEE Robotics and Automation Letters*, vol. 3, no. 2, pp. 1176–1183, 2018.
- [5] D. Brescianini and R. D'Andrea, "An omni-directional multirotor vehicle," *Mechatronics*, vol. 55, pp. 76–93, 2018.
- [6] C. D. Pose, J. I. Giribet, and A. S. Ghersin, "Hexacopter fault tolerant actuator allocation analysis for optimal thrust," in *2017 International Conference on Unmanned Aircraft Systems (ICUAS)*, 2017, pp. 663–671.
- [7] A. Bin Junaid, A. Diaz De Cerio Sanchez, J. Betancor Bosch, N. Vitzilaos, and Y. Zweiri, "Design and implementation of a dual-axis tilting quadcopter," *Robotics*, vol. 7, no. 4, 2018.
- [8] M. Hamandi, K. Sawant, M. Tognon, and A. Franchi, "Omni-plus-seven (o7+): An omnidirectional aerial prototype with a minimal number of unidirectional thrusters," in *2020 International Conference on Unmanned Aircraft Systems (ICUAS)*, 2020, pp. 754–761.
- [9] Y. Su, P. Yu, M. J. Gerber, L. Ruan, and T.-C. Tsao, "Nullspace-based control allocation of overactuated uav platforms," *IEEE Robotics and Automation Letters*, vol. 6, no. 4, pp. 8094–8101, 2021.
- [10] M. Ryll, H. Bühlhoff, and P. Giordano, "A novel overactuated quadrotor unmanned aerial vehicle: Modeling, control, and experimental validation," *IEEE Transactions on Control Systems Technology*, vol. 23, no. 2, pp. 540–556, 2015.
- [11] G. Michieletto, M. Ryll, and A. Franchi, "Fundamental actuation properties of multi-rotors: Force-moment decoupling and fail-safe robustness," *IEEE Trans. on Robotics*, vol. 34, no. 3, pp. 702–715, 2018.
- [12] D. Mellinger and V. Kumar, "Minimum snap trajectory generation and control for quadrotors," in *2011 IEEE international conference on robotics and automation*. IEEE, 2011, pp. 2520–2525.
- [13] P. Zheng, X. Tan, B. B. Kocer, E. Yang, and M. Kovac, "TiltDrone: A fully-actuated tilting quadrotor platform," *IEEE Robotics and Automation Letters*, vol. 5, no. 4, pp. 6845–6852, 2020.
- [14] D. Brescianini and R. D'Andrea, "Computationally efficient trajectory generation for fully actuated multirotor vehicles," *IEEE Transactions on Robotics*, vol. 34, no. 3, pp. 555–571, 2018.
- [15] A. Franchi, R. Carli, D. Bicego, and M. Ryll, "Full-pose tracking control for aerial robotic systems with laterally-bounded input force," *IEEE Trans. on Robotics*, vol. 34, no. 2, pp. 534–541, 2018.
- [16] D. Invernizzi and M. Lovera, "Trajectory tracking control of thrust-vectoring uavs," *Automatica*, vol. 95, pp. 180–186, 2018.
- [17] D. Horla, M. Hamandi, W. Giernacki, and A. Franchi, "Optimal tuning of the lateral-dynamics parameters for aerial vehicles with bounded lateral force," *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 3949–3955, 2021.
- [18] D. Bicego, J. Mazzetto, R. Carli, M. Farina, and A. Franchi, "Nonlinear model predictive control with enhanced actuator model for multi-rotor aerial vehicles with generic designs," *Journal of Intelligent & Robotics Systems*, vol. 100, no. 3, pp. 1213–1247, 2020.
- [19] A. Romero, S. Sun, P. Foehn, and D. Scaramuzza, "Model predictive contouring control for time-optimal quadrotor flight," *IEEE Transactions on Robotics*, pp. 1–17, 2022.
- [20] G. Nava, Q. Sablé, M. Tognon, D. Pucci, and A. Franchi, "Direct force feedback control and online multi-task optimization for aerial manipulators," *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 331–338, 2020.
- [21] T. A. Johansen and T. I. Fossen, "Control allocation—a survey," *Automatica*, vol. 49, no. 5, pp. 1087–1103, 2013.
- [22] M. Hamandi, L. Seneviratne, and Y. Zweiri, "Static hovering realization for multirotor aerial vehicles with tilttable propellers," *Journal of Mechanisms and Robotics*, 2023.
- [23] A. Boeuf, J. Cortés, R. Alami, and T. Siméon, "Enhancing sampling-based kinodynamic motion planning for quadrotors," in *2015 IEEE/RSJ Int. Conf. on Intelligent Robots and Systems*. IEEE, 2015, pp. 2447–2452.
- [24] T. Lee, M. Leok, and N. H. McClamroch, "Geometric tracking control of a quadrotor uav on se(3)," in *49th IEEE Conference on Decision and Control (CDC)*, 2010, pp. 5420–5425.
- [25] C. J. Albers, F. Critchley, and J. C. Gower, "Quadratic minimisation problems in statistics," *Journal of Multivariate Analysis*, vol. 102, no. 3, pp. 698–713, 2011.
- [26] C. Udriste, *Convex functions and optimization methods on Riemannian manifolds*. Springer Science & Business Media, 1994, vol. 297.