

Lab 3 - Linux - NTI

. Create a user account with the following attribute

```
<useradd -c -m mahmoud>  
<useradd -p "islam_2010">
```

- Fullname/comment: "full name"
- Password: islam

2. Create a user account with the following attribute

- Username: baduser

```
<useradd -m -c Bad User>
```

- Full name/comment: Bad User
- Password: baduser <useradd -p Baduser>

3. Create a supplementary (Secondary) group called pgroup with group ID of 30000

```
<groupadd -g 3000 pgroup>
```

4. Create a supplementary group called badgroup

5. Add islam user to the pgroup group as a supplementary group

```
<-aG pgroup>
```

6. Modify the password of islam's account to password

7. Modify islam's account so the password expires after 30 days

```
<sudo chage -M 30 your_first_name>
```

8. Lock bad user account so he can't log in

```
<sudo passwd -l baduser>
```

9. Delete bad user account

```
<sudo userdel -r baduser>
```

10. Delete the supplementary group called badgroup

11. Create a folder called myteam in your home directory and change its permissions to read only for the owner.

```
<chmod 400 myteam>
```

```
echo $? = 0
```

12. Log out and log in by another user

```
<su - anotheruser>
```

13. Try to access (by `cd` command) the folder (`myteam`)

```
<cd /home/mahmoud/myteam>
```

14. Using the command Line

- Change the permissions of oldpasswd file to give owner read and write permissions and for group write and execute and execute only for the others (using chmod in 2 different ways)

```
<chmod 631 oldpasswd
```

Symbolic method

```
chmod u=rw,g=wx,o=x oldpasswd
```

- Change your default permissions to be as above.

 $\wedge$ [illegible]

```
umask 777>
```

```
<touch testfile
```

```
mkdir testdir
```

```
ls -la testfile testdir>
```

15. Starting from your home directory, find all files that were modified in the last two day.

```
<find ~/ -type f -mtime -2>
```

16. Starting from /etc, find files owned by root user.

```
<find /etc -user root -type f>
```

17. Find all directories in your home directory

```
<find ~/ -type d>
```

18. Write a command to search for all files on the system that, its name is ".profile".

```
<sudo find / -name ".profile">
```

19. Identify the file types of the following: /etc/passwd, /dev/pts/0, /etc, /dev/sda

```
<file /etc/passwdfile /dev/pts/file /etc file /dev/sda>
```

20. List the inode numbers of `/`, `/etc`, `/etc/hosts`.

```
<ls -i /ls -i /etc ls -i /etc/hosts>
```

21. Copy `/etc/passwd` to your home directory, use the commands `diff` and `cmp`, and Edit in the file you copied, and then use these commands again, and check the output.

```
<cp /etc/passwd ~/passwd>
```

```
compare : $ <diff /etc/passwd ~/passwd cmp /etc/passwd ~/passwd>
```

```
edit <nano ~/passwd>
```

```
compare after edit <diff /etc/passwd ~/passwd cmp /etc/passwd ~/passwd>
```

22. Create a symbolic link of /etc/passwd in /boot.

```
<sudo ln -s /etc/passwd /boot/passwd_symlink>
```

23. Create a hard link of /etc/passwd in /boot. Could you? Why

```
<sudo ln /etc/passwd /boot/passwd_hardlink>
```

**