



New Delivery

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

-  Wordpress Plugin [View >](#)
-  Shopify Plugin [View >](#)

Pathao Courier Merchant API Integration Documentation

Summary

Pathao API uses OAuth 2.0. There are 2 requests being sent here. 1st request is for getting the access token. This access token should be saved in the database (or any persistent store) for future use. 2nd request is for creating a new order. This uses the access token previously saved.

For understanding these APIs, we are providing **Sandbox/Test Environment's Credentials** here. And later you can easily integrate for **Production/Live Environment** by using your Live Credentials

Merchant API Credentials

Now you can easily integrate Pathao Courier Merchant API's into your website.

Client ID

Ex - 100



Client Secret

Client secret



Sandbox/Test Environment Credentials

Field name	Description
base_url	https://courier-api-sandbox.pathao.com
client_id	7N1aMJQbWm
client_secret	wRcaibZkUdSNz2EI9ZyuXLINrnAv0TdPUPXMnD39
username	test@pathao.com
password	lovePathao
grant_type	password

Production/Live Environment

Field name	Description
base_url	https://api-hermes.pathao.com
client_id	You can see client_id from merchant api credentials section.
client_secret	You can see client_secret from merchant api credentials section.

Issue an Access Token

Endpoint: `/aladdin/api/v1/issue-token`



For any kind of access to the Pathao Courier Merchant API, you need to issue an access token first. This token will be used to authenticate your API requests.

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

```
curl --location '{{base_url}}/aladdin/api/v1/issue-token' \
--header 'Content-Type: application/json' \
--data-raw '{
  "client_id": "{{client_id}}",
  "client_secret": "{{client_secret}}",
  "grant_type": "password",
  "username": "{{your_email}}",
  "password": "{{your_password}}"
}'
```

Request parameters

Field name	Field type	Required	Description
client_id	string	Yes	Test/Production environment Client Id.
client_secret	string	Yes	Test/Production environment Client Secret.
grant_type	string	Yes	Must use grant type <code>password</code> for issue token api.
username	string	Yes	Test environment/your login email address.
password	string	Yes	Test environment/your login password

Success Response: Status Code 200

```
{
  token_type: "Bearer",
  expires_in: 432000,
  access_token: "ISSUED_ACCESS_TOKEN",
  refresh_token: "ISSUED_REFRESH_TOKEN"
}
```

Response data

Field name	Field type	Optional	Description
token_type	string	No	It will always be <code>Bearer</code> .
expires_in	integer	No	Token expiry time in seconds
access_token	string	No	Your Authenticated token for making API calls
refresh_token	string	No	Your refresh token for regenerating access token

Issue an Access Token from Refresh Token



Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Endpoint: `/aladdin/api/v1/issue-token`

In order to generate a new access token, you can use the refresh token to obtain a new access token.

```
curl --location '{{base_url}}/aladdin/api/v1/issue-token' \
--header 'Content-Type: application/json' \
--data '{
  "client_id": "{{your_client_id}}",
  "client_secret": "{{client_secret}}",
  "grant_type": "refresh_token"
  "refresh_token": "ISSUED_REFRESH_TOKEN",
}'
```

Request parameters

Field name	Field type	Required	Description
client_id	string	Yes	Your Client Id generated by Pathao Courier.
client_secret	string	Yes	Your Client Secret generated by Pathao Courier.
grant_type	string	Yes	Must use grant type <code>refresh_token</code> for refresh token api.
refresh_token	string	Yes	Provide your refresh token in order to generate access_token

Success Response: Status Code 200

```
{
  token_type: "Bearer",
  expires_in: 432000,
  access_token: "ISSUED_ACCESS_TOKEN",
  refresh_token: "ISSUED_REFRESH_TOKEN"
}
```

Response data

Field name	Field type	Optional	Description
token_type	string	No	Your access token type
expires_in	integer	No	Token expiry time in seconds
access_token	string	No	Your Authenticated token for making API calls
refresh_token	string	No	Your refresh token for regenerating access token

Create a New Store

Endpoint: `/aladdin/api/v1/stores`

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools



Wordpress Plugin

[View >](#)



Shopify Plugin

[View >](#)

To create a Store in Pathao Courier Merchant API, you need to provide the required information. The CURL for the POST Request is given, Use this as a reference. The API will return a success response with the created store details.

```
curl --location '{{base_url}}/aladdin/api/v1/stores' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer {{access_token}}' \
--data '{
  "name": "Demo Store",
  "contact_name": "Test Merchant",
  "contact_number": "017XXXXXXXX",
  "secondary_contact": "015XXXXXXXX",
  "otp_number": "017XXXXXXXX",
  "address": "House 123, Road 4, Sector 10, Uttara, Dhaka-1230, Bangladesh",
  "city_id": {{city_id}},
  "zone_id": {{zone_id}},
  "area_id": {{area_id}}
}'
```

Request parameters

Field name	Field type	Required	Description
name	string	Yes	Name of the store. Store name length should be between 3 to 50 characters.
contact_name	string	Yes	Contact person of the store need for issue related communication. Contact person name length should be between 3 to 50 characters.
contact_number	string	Yes	Store contact person phone number. Contact number length should be 11 characters.
secondary_contact	string	No	Store contact person secondary phone number. Secondary contact number length should be 11 characters. This field is optional.
otp_number	string	No	OTP for orders from this order will be sent to this number
address	string	Yes	Merchant Store address. Address length should be between 15 to 120 characters.
city_id	integer	Yes	Recipient city_id
zone_id	integer	Yes	Recipient zone_id

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Required	Description
area_id	integer	Yes	Recipient area_id

Success Response: Status Code 200

```
{
  message: "Store created successfully, Please wait one hour for approval.",
  type: "success",
  code: 200,
  data: {
    store_name: "Demo Store"
  }
}
```

Response data

Field name	Field type	Optional	Description
store_name	string	No	The name of the store that you created.

Create a New Order

Endpoint: `/aladdin/api/v1/orders`

To create a New order in Pathao Courier Merchant API, you need to provide the required information. The CURL for the POST Request is given, Use this as a reference. The API will return a success response with the created order details.

```
curl --location '{{base_url}}/aladdin/api/v1/orders' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer {{access_token}}' \
--data '{
  "store_id": {{merchant_store_id}},
  "merchant_order_id": "{{merchant_order_id}}",
  "recipient_name": "Demo Recipient",
  "recipient_phone": "017XXXXXXX",
  "recipient_address": "House 123, Road 4, Sector 10, Ut
tara, Dhaka-1230, Bangladesh",
  "delivery_type": 48,
  "item_type": 2,
  "special_instruction": "Need to Delivery before 5 PM",
  "item_quantity": 1,
  "item_weight": "0.5",
  "item_description": "this is a Cloth item, price- 300
0",
  "amount_to_collect": 900
}'
```

Request parameters

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Required	Description
store_id	integer	Yes	store_id is provided by the merchant and not changeable. This store ID will set the pickup location of the order according to the location of the store.
merchant_order_id	string	No	Optional parameter, merchant order info/tracking id
recipient_name	string	Yes	Parcel receivers name. Name length should be between 3 to 100 characters.
recipient_phone	string	Yes	Parcel receivers contact number. Recipient phone length should be 11 characters.
recipient_secondary_phone	string	No	Parcel receivers secondary contact number. Recipient secondary phone length should be 11 characters. This field is optional.
recipient_address	string	Yes	Parcel receivers full address. Address length should be between 10 to 220 characters.
recipient_city	integer	No	Parcel receiver's city_id. This is an optional parameter, so do not send a null value. If not included in the request payload, then our system will populate it automatically based on the recipient_address you will be provide

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Required	Description
recipient_zone	integer	No	Parcel receiver's zone_id . This is an optional parameter, so do not send a null value. If not included in the request payload, then our system will populate it automatically based on the recipient_address you will be provided.
recipient_area	integer	No	Parcel receiver's area_id . This is an optional parameter. If not included in the request payload, then our system will populate it automatically based on the recipient_address you will be provided.
delivery_type	integer	Yes	48 for Normal Delivery, 12 for On Demand Delivery
item_type	integer	Yes	1 for Document, 2 for Parcel
special_instruction	string	No	Any special instruction you may want to provide to us.
item_quantity	integer	Yes	Quantity of your parcels
item_weight	float	Yes	Minimum 0.5 KG to Maximum 10 kg. Weight of your parcel in kg
item_description	string	No	You can provide a description of your parcel
amount_to_collect	integer	Yes	Recipient Payable Amount. Default should be 0 in case of NON Cash-On-Delivery()The collect

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Required	Description
			amount from the customer.

Success Response: Status Code 200

```
{
  message: "Order Created Successfully",
  type: "success",
  code: 200,
  data: {
    consignment_id: "{{ORDER_CONSIGNMENT_ID}}",
    merchant_order_id: "{{merchant_order_id}}",
    order_status: "Pending",
    delivery_fee: 80
  }
}
```

Response data

Field name	Field type	Optional	Description
consignment_id	string	No	A unique identifier for the consignment.
merchant_order_id	string	Yes	The order id you provided to keep track of your order.
order_status	string	No	Your current order status
delivery_fee	number	No	Your parcel delivery fee

Create a Bulk Order

Endpoint: `/aladdin/api/v1/orders/bulk`

To create a multiple orders at a time in Pathao Courier Merchant API, you need to provide the required information. The CURL for the POST Request is given, Use this as a reference. The API will return a success response with the created order details.

```
curl --location '{{base_url}}/aladdin/api/v1/orders/bulk' \
  --header 'Content-Type: application/json; charset=UTF-8' \
  --header 'Authorization: Bearer {{access_token}}' \
  --data '{
    "orders": [
      {
        "store_id": "{{merchant_store_id}}",
        "merchant_order_id": "{{merchant_order_id}}",
        "recipient_name": "Demo Recipient One",
        "recipient_phone": "017XXXXXXX",
        "recipient_address": "House 123, Road 4, Sector 10,
        Uttara, Dhaka-1230, Bangladesh",
        "delivery_type": 48,
        "item_type": 2,
```

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

```
"special_instruction": "Do not put water",
"item_quantity": 2,
"item_weight": "0.5",
"amount_to_collect": 100,
"item_description": "This is a Cloth item, price- 3
000"
},
{
  "store_id": {{merchant_store_id}},
  "merchant_order_id": "{{merchant_order_id}}",
  "recipient_name": "Demo Recipient Two",
  "recipient_phone": "015XXXXXXX",
  "recipient_address": "House 3, Road 14, Dhanmondi,
Dhaka-1205, Bangladesh",
  "delivery_type": 48,
  "item_type": 2,
  "special_instruction": "Deliver before 5 pm",
  "item_quantity": 1,
  "item_weight": "0.5",
  "amount_to_collect": 200,
  "item_description": "Food Item, Price 1000"
}
]
}'
```

Request parameters

Field name	Field type	Required	Description
orders	array of order object	Yes	An array of order objects is required to send within the request body.

Order Object

Field name	Field type	Required	Description
store_id	integer	Yes	store_id is provided by the merchant and not changeable. This store ID will set the pickup location of the order according to the location of the store
merchant_order_id	string	No	Optional parameter, merchant order info/tracking id
recipient_name	string	Yes	Parcel receivers name. Name length should be between 3 to 100 characters.
recipient_phone	string	Yes	Parcel Recipients contact number. Recipient phone

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Required	Description
			length should be 11 characters.
recipient_secondary_phone	string	No	Parcel receivers secondary contact number. Recipient secondary phone length should be 11 characters. This field is optional.
recipient_address	string	Yes	Parcel receivers full address. Address length should be between 10 to 220 characters.
recipient_city	integer	No	Parcel receiver's city_id . This is an optional parameter, so do not send a null value. If not included in the request payload, then our system will populate it automatically based on the recipient_address you will be provided.
recipient_zone	integer	No	Parcel receiver's zone_id . This is an optional parameter, so do not send a null value. If not included in the request payload, then our system will populate it automatically based on the recipient_address you will be provided.
recipient_area	integer	No	Parcel receiver's area_id . This is an optional parameter. If not included in the request payload, then our system will populate it automatically based on the

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Required	Description
			recipient_address you will be provided.
delivery_type	integer	Yes	48 for Normal Delivery, 12 for On Demand Delivery
item_type	integer	Yes	1 for Document, 2 for Parcel
special_instruction	string	No	Any special instruction you may want to provide to us.
item_quantity	integer	Yes	Quantity of your parcels
item_weight	float	Yes	Minimum 0.5 KG to Maximum 10 kg. Weight of your parcel in kg.
item_description	string	No	You can provide a description of your parcel.
amount_to_collect	integer	Yes	Recipient Payable Amount. Default should be 0 in case of NON Cash-On-Delivery(COD)The collectible amount from the customer.

Success Response: Status Code 202

```
{
  message: "Your bulk order creation request is accepted,<br>
please wait some time to complete order creation.",
  type: "success",
  code: 202,
  data: true
}
```

Response data

Field name	Field type	Optional	Description
code	integer	No	Http response code for bulk order creation.
data	boolean	Yes	Data field is true if bulk order creation is accepted.



Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Get Order Short Info

Endpoint:

/aladdin/api/v1/orders/{{consignment_id}}/info

Get a short summary of your specific order

```
curl --location '{{base_url}}/aladdin/api/v1/orders/{{consignment_id}}/info' \
--header 'Authorization: Bearer {{access_token}}' \
--data ''
```

Request parameters

Field name	Field type	Required	Description
consignment_id	string	Yes	This unique id is used to identify the consignment.

Success Response: Status Code 200

```
{
  message: "Order info",
  type: "success",
  code: 200,
  data: {
    consignment_id: "{{consignment_id}}",
    merchant_order_id: "{{merchant_order_id}}",
    order_status: "Pending",
    order_status_slug: "Pending",
    updated_at: "2024-11-20 15:11:40",
    invoice_id: null
  }
}
```

Response data

Field name	Field type	Optional	Description
consignment_id	string	No	A unique identifier for the consignment
merchant_order_id	string	Yes	The order id you provided
order_status_slug	string	No	Current status of your order

Get List of Cities

Endpoint: /aladdin/api/v1/city-list

Get a summary of your current stores

```
curl --location '{{base_url}}/aladdin/api/v1/city-list' \
--header 'Content-Type: application/json; charset=UTF-8' \
```

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

```
--header 'Authorization: Bearer {{access_token}}' \
--data ''
```

Success Response: Status Code 200

```
{
  message: "City successfully fetched.",
  type: "success",
  code: 200,
  data: {
    data: [
      {
        city_id: 1,
        city_name: "Dhaka"
      },
      {
        city_id: 2,
        city_name: "Chittagong"
      },
      {
        city_id: 4,
        city_name: "Rajshahi"
      }
    ]
  }
}
```

Response data

Field name	Field type	Optional	Description
city_id	integer	No	A unique identifier for the city
city_name	string	No	Formal city name

Get zones inside a particular city

Endpoint:

`/aladdin/api/v1/cities/{{city_id}}/zone-list`

Get List of Zones withing a particular City

```
curl --location '{{base_url}}/aladdin/api/v1/cities/{{city_id}}/zone-list' \
--header 'Content-Type: application/json; charset=UTF-8' \
--header 'Authorization: Bearer {{access_token}}' \
--data ''
```

Request parameters

Field name	Field type	Required	Description
city_id	integer	Yes	A unique identifier for the city

Success Response: Status Code 200

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

```
{
  message: "Zone list fetched.",
  type: "success",
  code: 200,
  data: {
    data: [
      {
        zone_id: 298,
        zone_name: "60 feet"
      },
      {
        zone_id: 1070,
        zone_name: "Abdullahpur Uttara"
      },
      {
        zone_id: 1066,
        zone_name: "Abul Hotel "
      }
    ]
  }
}
```

Response data

Field name	Field type	Optional	Description
zone_id	integer	No	A unique identifier for the zone
zone_name	string	No	Formal zone name

Get areas inside a particular zone

Endpoint: `/aladdin/api/v1/zones/{{zone_id}}/area-list`

Get List of Areas withing a particular Zone

```
curl --location '{{base_url}}/aladdin/api/v1/zones/{{zone_id}}/area-list' \
--header 'Content-Type: application/json; charset=UTF-8' \
--header 'Authorization: Bearer {{access_token}}' \
--data ''
```

Request parameters

Field name	Field type	Required	Description
zone_id	integer	Yes	A unique identifier for the zone

Success Response: Status Code 200

```
{
  message: "Area list fetched.",
  type: "success",
  code: 200,
  data: {
```

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools



Wordpress Plugin

[View >](#)



Shopify Plugin

[View >](#)

```
data: [
  {
    area_id: 37,
    area_name: " Bonolota",
    home_delivery_available: true,
    pickup_available: true
  },
  {
    area_id: 3,
    area_name: " Road 03",
    home_delivery_available: true,
    pickup_available: true
  },
  {
    area_id: 4,
    area_name: " Road 04",
    home_delivery_available: true,
    pickup_available: true
  }
]
```

Response data

Field name	Field type	Optional	Description
area_id	integer	No	A unique identifier for the area
area_name	string	No	Formal area name
home_delivery_available	boolean	No	Shows if home delivery available or not
pickup_available	boolean	No	Shows if pickup available or not

Price Calculation Api

Endpoint: `/aladdin/api/v1/merchant/price-plan`

To calculate price of the order use this post api

```
curl --location '{{base_url}}/aladdin/api/v1/merchant/price-plan' \
--header 'Content-Type: application/json; charset=UTF-8' \
--header 'Authorization: Bearer {{issue_token}}' \
--data '{
  "store_id": "{{merchant_store_id}}",
  "item_type": 2,
  "delivery_type": 48,
  "item_weight": 0.5,
  "recipient_city": {{city_id}},
  "recipient_zone": {{zone_id}}
}'
```

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Request parameters

Field name	Field type	Required	Description
store_id	integer	Yes	store_id is provided by the merchant and not changeable. This store ID will set the pickup location of the order according to the location of the store.
item_type	integer	Yes	1 for Document, 2 for Parcel
delivery_type	integer	Yes	48 for Normal Delivery, 12 for On Demand Delivery
item_weight	float	Yes	Minimum 0.5 KG to Maximum 10 kg. Weight of your parcel in kg
recipient_city	integer	Yes	Parcel receivers city_id
recipient_zone	integer	Yes	Parcel receivers zone_id

Success Response: Status Code 200

```
{
  message: "price",
  type: "success",
  code: 200,
  data: {
    price: 80,
    discount: 0,
    promo_discount: 0,
    plan_id: 69,
    cod_enabled: 1,
    cod_percentage: 0.01,
    additional_charge: 0,
    final_price: 80
  }
}
```

Response data

Field name	Field type	Optional	Description
price	integer	No	Calculated price for given item
discount	integer	No	Discount for the given item
promo_discount	integer	No	Promo discount for the given item
plan_id	integer	No	Price plan id for the given item
cod_percentage	float	No	Cash on delivery percentage
additional_charge	integer	No	If there is any additional charge for the given item

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Optional	Description
final_price	number	No	Your final price for the given item

Get Merchant Store Info

Endpoint: `/aladdin/api/v1/stores`

Get a summary of your current stores

```
curl --location '{{base_url}}/aladdin/api/v1/stores' \
--header 'Content-Type: application/json; charset=UTF-8' \
--header 'Authorization: Bearer {{access_token}}', \
--data ''
```

Success Response: Status Code 200

```
{
  message: "Store list fetched.",
  type: "success",
  code: 200,
  data: {
    data: [
      {
        store_id: "{{merchant_store_id}}",
        store_name: "{{merchant_store_name}}",
        store_address: "House 123, Road 4, Sector 10, Uttara, Dhaka-1230, Bangladesh",
        is_active: 1,
        city_id: "{{city_id}}",
        zone_id: "{{zone_id}}",
        hub_id: "{{hub_id}}",
        is_default_store: false,
        is_default_return_store: false
      }
    ],
    total: 1,
    current_page: 1,
    per_page: 1000,
    total_in_page: 1,
    last_page: 1,
    path: "{{base_url}}/aladdin/api/v1/stores",
    to: 1,
    from: 1,
    last_page_url: "{{base_url}}/aladdin/api/v1/stores?page=1",
    first_page_url: "{{base_url}}/aladdin/api/v1/stores?page=1"
  }
}
```

Response data

Field name	Field type	Optional	Description
store_id	integer	No	A unique id for the store

Developer's API

API Documentation

Issue an Access Token	POST
Issue an Access Token from Refresh Token	POST
Create a New Store	POST
Create a New Order	POST
Create a Bulk Order	POST
Get Order Short Info	GET
Get List of Cities	GET
Get zones inside a particular city	GET
Get areas inside a particular zone	GET
Price Calculation Api	POST
Get Merchant Store Info	GET

Webhook Integration

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

Field name	Field type	Optional	Description
store_name	string	Yes	The name of the store
store_address	string	No	Address of the store
is_active	integer	No	1 for active store & 0 for deactivated store.
city_id	integer	No	The city id of the store.
zone_id	integer	No	The zone id of the store.
hub_id	integer	No	The hub ID within which the store is located.
is_default_store	integer	No	1 if the store is default_store otherwise 0.
is_default_return_store	integer	No	1 if the store is default_return_store otherwise 0.

Plugins and Tools

 Wordpress Plugin	View >
 Shopify Plugin	View >

