

Callback Url

Callback Url here

Auth Token(Bearer)

Type Auth Token here

Save

# Webhook Response Documentation

The webhook sends **POST** requests to the configured endpoint with JSON payloads based on the notification type.

## 1. Delivery Status Update

**Description:** This webhook notifies about changes in the delivery status of a consignment.

### Example Payload:

```
{
  "notification_type": "delivery_status",
  "consignment_id": 12345,
  "invoice": "INV-67890",
  "cod_amount": 1500.00,
  "status": "Delivered",
  "delivery_charge": 100.00,
  "tracking_message": "Your package has been delivered successfully.",
  "updated_at": "2025-03-02 12:45:30"
}
```

### Field Details:

| Field Name        | Type                 | Description                                                                                              |
|-------------------|----------------------|----------------------------------------------------------------------------------------------------------|
| notification_type | string               | Fixed value: "delivery_status"                                                                           |
| consignment_id    | integer              | Unique ID of the consignment                                                                             |
| invoice           | string               | Invoice number associated with the consignment                                                           |
| cod_amount        | float                | Cash on delivery (COD) amount                                                                            |
| status            | string               | Current delivery status in between:<br>pending<br>delivered<br>partial_delivered<br>cancelled<br>unknown |
| delivery_charge   | float                | Delivery charge applied                                                                                  |
| tracking_message  | string               | Status update message                                                                                    |
| updated_at        | string<br>(datetime) | Timestamp of the last update (YYYY-MM-DD HH:MM:SS)                                                       |

## 2. Tracking Update

**Description:** This webhook sends tracking updates for a consignment.

### Example Payload:

```
{
  "notification_type": "tracking_update",
  "consignment_id": 12345,
  "invoice": "INV-67890",
  "tracking_message": "Package arrived at the sorting center.",
  "updated_at": "2025-03-02 13:15:00"
}
```

### Field Details:

| Field Name        | Type                 | Description                                        |
|-------------------|----------------------|----------------------------------------------------|
| notification_type | string               | Fixed value: "tracking_update"                     |
| consignment_id    | integer              | Unique ID of the consignment                       |
| invoice           | string               | Invoice number associated with the consignment     |
| tracking_message  | string               | Update message related to the package tracking     |
| updated_at        | string<br>(datetime) | Timestamp of the last update (YYYY-MM-DD HH:MM:SS) |

## Webhook Headers

| Header Name   | Value                                                 |
|---------------|-------------------------------------------------------|
| Content-Type  | application/json                                      |
| Authorization | Bearer {your_api_key} (if authentication is required) |

## Response Handling

Your server should respond with an HTTP **200 OK** status if the webhook is processed successfully.

### Success Response:

```
{
  "status": "success",
  "message": "Webhook received successfully."
}
```

### Error Response (Example):

```
{
  "status": "error",
```

```
"message": "Invalid consignment ID."
```

```
}
```