☆   4 3 4 5

4°-

(1). Basic tags →

① - H1 to H6
② - Br
③ - P
④ - Bold /strong
⑤ - underlin (u / ins)
⑥ - italic (i / em)
⑦ - <sup> <sub>
⑧ - mark
⑨ - pre / code
⑩ - del / strike
⑪ - hr

⑫ - semantic tags (Head, nav, section, article, aside, footer)
⑬ - span
⑭ - audio
⑮ - video
⑯ - seo (title, meta)

⑰ - Kbd
⑱ - var
⑲ - quotation ("'") <q>
⑳ - Blockquote (done type)
㉑ - address
㉒ - marqee
㉓ - abbreviation (abbr)
㉔ - <figure> <img>
      <figs> <figcaption> </figcaption>

Special:
① Autocomplete /
   suggestion / data
   list.

② dropdown / select
   list (6 and label)
   optgroup and
   more.

③ label

④ tabletes (rows, cols)

⑤ Button (type, name, disabled, accesskey)

Subject : _____

2. __Lists →__

① ordered (type, reversed , start)

② un-ordered (type)

③ description.

④ __image →__

① — src	— ‹img usemap="one"›
② — height	‹map name = 'one'›
③ — width	‹area shape=" " co-ord ·" "
④ — loading = Lazy	href·" " ›
⑤ — title	‹/map›
⑥ — alt	

④ __Form__

① — Action	
② — method	— input attributes
③ — Name	type attributes
④ — Novalidate	
⑤ — formentype	

⑦ # __3 :-__

② __table →__   ‹td (align, v-align)›

                     table (border, cell-spacing,
                     cellpadding, rules=all,
                     align = left/right/centre

                     ④ — span(row te column)
                     ⑤ — attributes

| ① — def, Basic structure, ‹caption› ‹/caption›|
| ② — ‹td› → ‹th› heading ke liye.|
| ③ — ‹thead› ‹tbody› ‹tfoot›|

②. **Hyper link :-**

① ─┤ def / steps / state / entity (<lt; >gt;)

② ─┤ attribute (href, target, title, id, download,
                    rel = noopener noreferer
                         or opener or referer).

③ ─┤ additional (tel, mail, insta / linkain) telegram link,
                    watsapp)

③   **iframe →**

① ─┤   src
② ─┤   width
③ ─┤   height
④ ─┤   Name (to collect anchor tag with iframe)
⑤ ─┤   srcdoc
⑥ ─┤   Sandbox - (allow-same-origin, allow-script, allow-form
                        (link)
                        allow-same-origin-allow-top-navigation,
                        )) -)) →)) -)) - popups)

\# ' **H :-**

┌─────────────────────────────────┐
│ ④ class & id :-   │
│   │
│ ① ─┤ class more and   │
│   same but id   │
│   one and unique.   │
└─────────────────────────────────┘

(1).   DPU

(2).   Style →
                    inside element
① ─┤ def / Head , style info define , mini css
② ─┤ type & media attribute

(3).   link →
① ─┤ <link, rel = stylesheet / script " , type = tex/css/script
        Gorav
        href = " path " .   PAGE NO.

 # 5 :-

① History →

    ① ⊢ History (1991 published, 1995 developed)
    ② ⊢ Tim berners lee (took insipiration from neaspaper)
    ③ ⊢ SGML → Html (is teg?)
    ④ ⊢ def (ⓘ Html tell browser how to structure a
         web-page.
         ⓘⓘ without html browser ~~can't~~ would not know how
           to display thing)
         ⓘⓘⓘ Html file save with .html.
         ⓘⓥ current version html-5 come in 2014.
                 5.1 → 2016
                 5.2 → 2017).

② tag →

    ① ⊢ def
    ② ⊢ types (container and non-container
             pair   unpair/singular/singletan/
                       empty.

③ Elements →

    ① ⊢ def (opening tag + content + closing tag)
    ② ⊢ types (Html , void/empty , Root element)
                 (non-container)

④ | <!Doctype> — not a tag , tell version of Html you are using |

            ⑥ Emmet is a tool present inside vscode.
⑤ ~~Boterrplate~~ code → ① Basic web page code generate done emmet