Deny by default: the matrix is a test, not a comment

Level 03 - API routes. Proposed endpoints and role permissions; `configs/permissions.yaml` is the source of truth once confirmed.

Endpoint (proposed)	Router and use case	analyst	inspector	regulator	ML engineer	admin	Audit record
GET /detections, /detections/{id}, site history	detections / list	✓	✓	✓	○	○	
GET /layers/{scene}/tiles	layers / tile	✓	✓	✓	○		
POST /detections/{id}/review	review / ReviewDetection	✓					✓
POST /detections/{id}/dossier (build)	evidence / ExportDossier	✓	○				✓
GET /dossiers/{id} (download) and /verify	evidence / verify	✓	✓	✓			✓
GET /regions	regions / list	✓	○	○			
POST, PUT /regions (alert cadence)	regions / ConfigureRegion	✓					✓
GET /models, /metrics	admin / list	○			✓	✓	
POST /models/{v}/promote	admin / PromoteModel				✓	○	✓
GET, POST /users and /roles	admin / users					✓	✓
GET /audit	admin / audit			○		✓	
any other request	rbac default						✓

✓ allowed ○ decide in sprint 1 (blank) denied ✓ in audit column: an audit entry is written. A denied call is always audited.

Report tests (Section 7.1): a permission-matrix test over every role and action; every unauthorised request is rejected by the backend; every review, status change and export creates an audit record. Only an analyst may set a status; an emission is confirmed only when the analyst sets Supported and the evidence is complete.