

ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

SECTION 1: IDENTIFICATION

Product name : ACTIVE GLASS CLEANER

Product code : 0890 25

Manufacturer or supplier's details

Company : Wurth Australia Pty. Ltd.

Address : Building 5, 43 - 63 Princes Highway

Dandenong South, VIC 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National

Poisons Centre: 131 126

E-mail address : product@wurth.com.au

Recommended use of the chemical and restrictions on use

Recommended use :

Cleaning agent Detergent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Aerosols : Category 1

Serious eye damage/eye irri-

tation

Category 2A

Specific target organ toxicity - :

single exposure

Category 3

GHS label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.





Version 5.0

Revision Date: 24.06.2025

SDS Number: 10666295-00013

Date of last issue: 26.11.2024 Date of first issue: 04.06.2012

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	>= 10 -< 20
Propane	74-98-6	< 10
Butane	106-97-8	< 10
Isobutane	75-28-5	< 10
1-Methoxy-2-propanol	107-98-2	< 10
(R)-p-mentha-1,8-diene	5989-27-5	< 1

SECTION 4. FIRST AID MEASURES



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Causes serious eye irritation.

May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.





Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Remove all sources of ignition.
Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used. Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling : Avoid breathing spray.

Do not swallow.





Version 5.0

Revision Date: 24.06.2025

SDS Number: 10666295-00013 Date of last issue: 26.11.2024 Date of first issue: 04.06.2012

Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Hygiene measures If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

Conditions for safe storage Store locked up.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Materials to avoid Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable liquids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Explosives

Recommended storage tem- : > 5 - < 40 °C

perature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	STEL	500 ppm 1,230 mg/m3	AU OEL
		TWA	400 ppm 983 mg/m3	AU OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Butane	106-97-8	TWA	800 ppm 1,900 mg/m3	AU OEL
		STEL	1,000 ppm	ACGIH
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH
1-Methoxy-2-propanol	107-98-2	TWA	100 ppm 369 mg/m3	AU OEL
		STEL	150 ppm 553 mg/m3	AU OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sam-	Permissible	Basis
		parameters	specimen	pling	concentra-	
				time	tion	
Propan-2-ol	67-63-0	Acetone	Urine	End of	40 mg/l	ACGIH
				shift at		BEI
				end of		
				work-		
				week		

Engineering measures: Minimize workplace exposure concentrations.

Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Remarks : not required Wash hands before breaks and at the end of

workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a dissolved gas



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Propellant : Propane, Butane, Isobutane

Colour : colourless

Odour : fruity

Odour Threshold : No data available

pH : 9.5

Concentration: 100 %

pH value is valid for liquid portion in the aerosol can

Melting point/freezing point : No data available

Initial boiling point and boiling

range

Not applicable

Flash point : 34 °C

Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Density : 0.98 g/cm³ (20 °C)

Solubility(ies)

Water solubility : completely soluble

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Acids

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l

Exposure time: 6 h
Test atmosphere: vapour



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm

Exposure time: 15 min Test atmosphere: gas

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm

Exposure time: 4 h
Test atmosphere: gas

1-Methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat): 4,016 mg/kg

Acute inhalation toxicity : LC50 (Mouse): < 22.2 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

(R)-p-mentha-1,8-diene:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Propan-2-ol:

Species : Rabbit

Result : No skin irritation

1-Methoxy-2-propanol:



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Species : Rabbit

Result : No skin irritation

(R)-p-mentha-1,8-diene:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Propan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

1-Methoxy-2-propanol:

Species : Rabbit

Result : No eye irritation

(R)-p-mentha-1,8-diene:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Propan-2-ol:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

1-Methoxy-2-propanol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

(R)-p-mentha-1,8-diene:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Components:

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (gas)
Method: OECD Test Guideline 474

Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative



🦊 WÜRTH

ACTIVE GLASS CLEANER

Version 5.0

Revision Date: 24.06.2025

SDS Number: 10666295-00013

Date of last issue: 26.11.2024 Date of first issue: 04.06.2012

Remarks: Based on data from similar materials

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

1-Methoxy-2-propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: equivocal

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro) Method: OECD Test Guideline 482

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

(R)-p-mentha-1,8-diene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Result: negative



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay

Species: Rat

Application Route: Ingestion

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 104 weeks

Method : OECD Test Guideline 451

Result : negative

1-Methoxy-2-propanol:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years

Method : OECD Test Guideline 453

Result : negative

(R)-p-mentha-1,8-diene:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

Propane:



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas)
Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

1-Methoxy-2-propanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour) Method: OECD Test Guideline 416

Result: negative



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

(R)-p-mentha-1,8-diene:

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

1-Methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

(R)-p-mentha-1,8-diene:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Propan-2-ol:

Species : Rat NOAEL : 12.5 mg/l

Application Route : inhalation (vapour)



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Exposure time : 104 Weeks

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)

Exposure time : 6 Weeks

Method : OECD Test Guideline 422

Butane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)

Exposure time : 6 Weeks

Method : OECD Test Guideline 422

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks

Method : OECD Test Guideline 422

1-Methoxy-2-propanol:

Species : Rat

NOAEL : 919 mg/kg Application Route : Ingestion Exposure time : 35 Days

Species : Rat NOAEL : 1.1 mg/l

Application Route : inhalation (vapour)

Exposure time : 2 yr

Method : OECD Test Guideline 453

Species : Rabbit
NOAEL : 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

(R)-p-mentha-1,8-diene:

Species : Rat, male NOAEL : 5 mg/kg LOAEL : 30 mg/kg Application Route : Ingestion Exposure time : 13 Weeks



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Aspiration toxicity

Not classified based on available information.

Components:

(R)-p-mentha-1,8-diene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l

Exposure time: 16 h

1-Methoxy-2-propanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6,812 mg/l

Exposure time: 96 h Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 23,300 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Skeletonema costatum (marine diatom)): 6,745 mg/l

Exposure time: 72 h Method: ISO 10253

Toxicity to microorganisms : IC50: > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

(R)-p-mentha-1,8-diene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0.720 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 307 µg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.25



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

plants mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.14

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

EC10 (Pimephales promelas (fathead minnow)): 0.37 mg/l

Exposure time: 8 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 0.153 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Persistence and degradability

Components:

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)

COD: 2,23 BOD/COD: 53 %

Propane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 385.5 h

Remarks: Based on data from similar materials

Butane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 385.5 h

Remarks: Based on data from similar materials

Isobutane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 385.5 h

Remarks: Based on data from similar materials



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

1-Methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 96 % Exposure time: 28 d

Method: OECD Test Guideline 301E

(R)-p-mentha-1,8-diene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 71.4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

Propan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: 0.05

Butane:

Partition coefficient: n-

octanol/water

log Pow: 2.31

Isobutane:

Partition coefficient: n-

octanol/water

log Pow: 2.8

1-Methoxy-2-propanol:

Partition coefficient: n-

octanol/water

log Pow: < 1

(R)-p-mentha-1,8-diene:

Partition coefficient: n-

octanol/water

log Pow: 4.38

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.



ACTIVE GLASS CLEANER

Version Date of last issue: 26.11.2024 Revision Date: SDS Number: 24.06.2025 10666295-00013 Date of first issue: 04.06.2012 5.0

Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN 1950 UN number Proper shipping name **AEROSOLS**

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 Environmentally hazardous no

IATA-DGR

UN/ID No. UN 1950

Proper shipping name Aerosols, flammable

Class 2.1

Not assigned by regulation Packing group

203

UN 1950

AEROSOLS

Flammable Gas Labels

Packing instruction (cargo

Proper shipping name

aircraft)

203

Packing instruction (passen-

ger aircraft)

IMDG-Code UN number

Class

Packing group Not assigned by regulation

Labels 2.1 **EmS Code** F-D, S-U Marine pollutant no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number UN 1950 Proper shipping name **AEROSOLS**



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mix-

Therapeutic Goods (Poisons

Standard) Instrument

No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or

threshold limits that might apply for this chemical)

Prohibition/Licensing Requirements

 There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 231.86 g/l

The components of this product are reported in the following inventories:

AIIC : All ingredients listed or exempt.

SECTION 16: ANY OTHER RELEVANT INFORMATION

Further information

Revision Date : 24.06.2025

Sources of key data used to compile the Safety Data

Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)



ACTIVE GLASS CLEANER

Version Revision Date: SDS Number: Date of last issue: 26.11.2024 5.0 24.06.2025 10666295-00013 Date of first issue: 04.06.2012

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN