Assessment 01



MACQUARIE
University

Evaluation Report of Four Pairs of AI Models for Harbour & Home (Online Retailer)

Name: MAIDUL ISLAM
Student ID: 60807261
Unit: COMP8410 (Advanced Topics in Artificial Intelligence)

Summary
This report compares four pairs of state-of-the-art AI models (eight models in total) for Harbour & Home, an online homewares and lifestyle retailer. I take the role of Chief AI Officer. I evaluated how each pair can support a different business need. Pair 1 focuses on editing catalogue photos, Pair 2 on creating personalised product images, pair 3 on detecting fake-review accounts and pair 4 on running a customer service agent. Every model was run and measured on my own laptop GPU (RTX 4060, 8 GB) with fixed seeds, pinned library versions and recorded model versions.

Main findings
Pair 1 (ControlNet vs InstructPix2Pix): ControlNet produced more usable catalogue edits in my blind ratings (21 of 24 cases usable, against 15 of 24) and won clearly on every rating scale. But the automatic CLIP direction score favoured InstructPix2Pix. So the automatic score alone would have picked the wrong model, and a person still needs to check the edits.

Pair 2 (DreamBooth-LoRA vs IP-Adapter): Both kept product identity at a similar level (no significant difference in DINO-I or in my identity ratings). DreamBooth-LoRA performed much better at following scene prompts. It achieved a 0.059 higher CLIP-T score and won 10 out of 24 paired ratings without losing any but it needs about 9-10 minutes of GPU set-up per product. IP-Adapter does not require training but it often copies the composition of the reference image instead of creating a new scene.

Pair 3 (GraphSAGE vs FAGCN): GraphSAGE was better than FAGCN on every seed (AUPRC 0.911 vs 0.857) and was about five times cheaper to train. A simple MLP that does not use graph information achieved a very similar AUPRC of 0.909. So most of the useful information in this dataset comes from the account features, not from the graph.

Pair 4 (Qwen2.5-1.5B vs Phi-3.5-mini): Phi-3.5-mini completed 62.5% of 40 tasks with the security guard switched on, against 10% for Qwen. Qwen had a zero unsafe action rate but this was mainly because it failed to take action rather than making safe decisions. Phi still made unsafe or unrequested changes in several tasks and once told a customer that store credit had been issued when it had not. No model is ready to act on money related tasks without human approval.

I recommend ControlNet for catalogue editing with human review before the images are used, DreamBooth-LoRA for best-selling products and IP-Adapter for the long tail, GraphSAGE with an MLP baseline kept as a check, and Phi-3.5-mini only as a read-only assistant until tool-level permissions and human approval are in place.

1. Introduction and Business Context

1.1 The organisation and my role

Harbour & Home is a fictional online retailer that sells homewares and lifestyle products. The company needs product images for its catalogue and marketing. It also manages customer reviews and handles regular questions about orders, stock and returns. As Chief AI Officer, my job is to decide which AI models are worth using for these needs, under what conditions and with which controls.

1.2 Scope of this evaluation

I have evaluated four pairs of AI models (eight models). Two AI systems, with one model from each pair in each system. I therefore define:

- System A: ControlNet, DreamBooth-LoRA, GraphSAGE and Qwen2.5-1.5B-Instruct.
- System B: InstructPix2Pix, IP-Adapter, FAGCN and Phi-3.5-mini-instruct.

Each pair is evaluated separately. I followed the same evaluation structure for all four pairs. This includes the business objective, technique, experiment, technical metrics, business metrics, my blind ratings, governance checks and final recommendation.

1.3 Structure of the report

Section 2 explains the selected models and the business context for each pair. Section 3 describes the evaluation framework, data and metrics used in the experiments. Section 4 presents the results for each pair. Section 5 compares the pairs and discusses business impact. Section 6 focuses on governance, safety, fairness and trust. Section 7 lists the limitations of my evaluation. Section 8 gives recommendations and Section 9 concludes. The AI Use Declaration is at the end of the report.

2. AI Model Selection and Modelling Context

Table 1 summarises the four pairs. The two models in each pair are designed to handle the same task but they use different techniques. By testing them against each other I can better understand how these techniques affect their performance instead of just comparing individual models.

Pair	**Business task**	**Model A (System A)**	**Model B (System B)**	**Core technique being compared**
1	Edit catalogue photos (colour, material, scene)	ControlNet (Canny) on SD 1.5	InstructPix2Pix	Spatial control through edge maps vs instruction-tuned editing

2	Put a specific product into new lifestyle scenes	DreamBooth with LoRA on SD 1.5	IP-Adapter on SD 1.5	Per-product fine-tuning vs training-free image prompt
3	Find fake-review accounts	GraphSAGE	FAGCN	Neighbour averaging (low-pass) vs signed attention (low + high frequency)
4	Answer customers and use shop tools	Qwen2.5-1.5B-Instruct	Phi-3.5-mini-instruct (3.8B)	Small vs mid-size tool-using LLM agent, with a prompt-level guard

Table 1: Selected model pairs, business tasks

2.1 Pair 1: ControlNet vs InstructPix2Pix for catalogue photo editing

Objective and Task: The business needs different colour, material and scene versions of existing product photos without arranging another photo shoot. The technical goal is to change what the instruction asks for while keeping the product's shape.

ControlNet (Zhang et al., 2023) uses a trainable copy of the Stable Diffusion encoder to guide image generation. In this experiment, it uses a Canny edge map taken from the original product photo. The copied encoder connects to the frozen network through "zero convolutions". So training starts without damaging the original model. At generation time the edge map fixes the outline and the text prompt (for example "a photo of a cobalt blue bowl") fills in the appearance. This gives ControlNet better control over the product's shape. The main limitation is that it regenerates everything within the edges. So the background and printed details may also change, even when these changes are not requested.

InstructPix2Pix (Brooks et al., 2023) is a diffusion model trained further using image pairs and editing instructions. It takes the original photo latent and a written instruction ("make the bowl cobalt blue") and uses two classifier free guidance scales. One for the text and one for the input image. A key advantage of InstructPix2Pix is that users can make changes through simple written instructions. It is also designed to preserve areas that do not need editing. Its risk is that it can under-edit, over-edit or apply the change to the wrong region.

ControlNet and InstructPix2Pix both use the same Stable Diffusion 1.5 latent-diffusion backbone (Rombach et al., 2022; Haghighi, 2026a). This allowed me to focus on how their editing methods differ rather than differences in the underlying model.

2.2 Pair 2: DreamBooth-LoRA vs IP-Adapter for personalised product images

Objective and task: The marketing team wants to create lifestyle images featuring a specific product in different settings. Such as “this teapot in the snow”. The model must keep the product recognisable (identity) and also follow the scene prompt.

DreamBooth (Ruiz et al., 2023) learns the appearance of a specific product by fine-tuning the diffusion model using 3-5 product photos. These images are linked to a rare token such as “sks” to help the model recognise the product. A prior-preservation loss on ordinary class images stops the model forgetting what a normal teapot looks like. I used LoRA (Hu et al., 2022) to reduce the training requirements. Instead of training the entire model, LoRA updates only small low-rank matrices in the attention layers, using rank 4 which keeps each product adapter at about 3 MB.

IP-Adapter (Ye et al., 2023) needs no per-product training. It uses a CLIP image encoder to convert a single reference photo into image tokens. These tokens are then added alongside the text tokens through a separate (“decoupled”) cross-attention layer. The adapter scale controls how strongly the reference image is followed. This reflects the identity-preservation trade-off from the Week 2 lecture (Fan, 2026a): fine-tuning network parameters gives strong identity but costs time and storage for each subject, while a trained image encoder is fast and needs no per-subject storage but gives weaker identity.

2.3 Pair 3: GraphSAGE vs FAGCN for fake-review account detection

Objective and task: The company wants to identify reviewer accounts that are most likely to be involved in fraud. This will help the small moderation team focus on the most suspicious accounts first. The technical task is node classification on a user graph where fraudsters are rare and often connect to normal users.

I used the Amazon review graph from CARE-GNN (Dou et al., 2020, based on McAuley and Leskovec, 2013). In this dataset, users are represented as nodes with handcrafted features. The nodes are connected through three types of relations. U-P-U links users who reviewed the same product, U-S-U connects users who gave the same star rating within a week and U-V-U links users with similar review text. My own statistics (Table 7) show the key difficulty discussed in Week 11 (Haghighi, 2026b): the graph is very homophilous overall (edge homophily 0.949) but only about 8.6% of a fraudster’s labelled neighbours are also fraudsters. This means normal users are mostly connected to other normal users while fraudsters are more often connected to normal users than to other fraudsters.

GraphSAGE (Hamilton et al., 2017) uses both a node’s own features and the average features of its neighbouring nodes. It applies separate weights to these two types of information before combining them. The averaging process works as a low-pass filter which smooths information

across neighbouring nodes. Because the model gives separate weight to the node's own features, it can still preserve important information about that node.

FAGCN (Bo et al., 2021) learns a signed attention weight between -1 and 1 for every edge. Positive weights average (low frequency) and negative weights take differences (high frequency) and a residual link back to the input features keeps node identity. FAGCN is designed to work with heterophilous graphs, where connected nodes often have different characteristics as seen in fraud detection. I also ran GCN (Kipf and Welling, 2017) and an MLP as reference baselines.

2.4 Pair 4: Qwen2.5-1.5B vs Phi-3.5-mini as a customer-service agent
Objective and task: The business wants an agent that answers routine questions and performs simple actions (look up orders, check stock, create returns) while following return policy and refusing unsafe actions (policy overrides and store credit which need a supervisor).

For this task, I selected two small, open-weight, instruction-tuned decoder-only Transformers. Both models can run on local hardware which matters for privacy and cost. Qwen2.5-1.5B-Instruct (Qwen Team, 2024) is the smaller and faster option. Phi-3.5-mini-instruct (3.8B parameters, Abdin et al., 2024) is larger and trained heavily on curated and synthetic data. I loaded both models using 4-bit NF4 quantisation (Dettmers et al., 2023) to reduce memory usage. This was necessary because Phi-3.5 could not fit within the available 8 GB of GPU memory without quantisation.

The agent uses a tool-calling loop (Yao et al., 2023, Week 8) to complete customer-service tasks. The model replies with one JSON action, my code runs the tool on a simulated shop and the result is returned to the model for up to six turns. To test security, I included hidden prompt-injection text in some orders and reviews. These instructions attempt to trick the agent into issuing refunds. This helps evaluate how the models respond to indirect prompt-injection attacks, as discussed by Greshake et al. (2023) and the OWASP Top 10 for LLM Applications (OWASP, 2025).

3. Evaluation Methodology

3.1 Evaluation framework

I used the same evaluation framework for all four model pairs, as shown in Figure 1. Figure 2 presents how each pair processes inputs and produces outputs. The evaluation focuses on four main areas. These are technical quality, business value (cost, usable rate and workload), user feedback from my own blind ratings (Pairs 1, 2 and 4) and governance behaviour (safety flags, robustness and attacks). The two models in a pair always receive identical inputs, seeds and settings, so that differences can be attributed to the model.




Figure 1. Evaluation framework used for all four pairs.




Figure 2. Input-to-output workflow and evaluation metrics for each pair. The upper branch is System A and the lower branch is System B.

3.2 Common Experimental Setup

All experiments ran on a Windows 11 laptop with an NVIDIA RTX 4060 Laptop GPU (8 GB), Python 3.12, PyTorch 2.5.1, diffusers 0.31.0, transformers 4.46.3 and PyTorch Geometric 2.6.1. Library versions are pinned in the setup notebook, and the exact Hugging Face commit of every model is saved in data/model_versions.json. Random seeds are fixed in every notebook. I used different statistical methods to measure uncertainty across the four pairs. For Pairs 1 and 2, I calculated 95% bootstrap confidence intervals using 5,000 resamples of the test cases (Efron and Tibshirani, 1993). Pair 3 results are reported as mean ± standard deviation across five seeds. For Pair 4, I used Wilson score intervals (Wilson, 1927) to measure uncertainty in the success rates. I also applied paired Wilcoxon signed-rank tests to compare my blind ratings for the same test cases.

Pair	Evaluation data	Test design	Ablation
1	First photo of 8 DreamBooth products (bowl, candle, clock, boot, sneaker, vase, can, toy car)	8 products × 3 edit types (colour, material, scene) = 24 cases × 2 seeds, SD 1.5 base, 30 steps, CFG 7.5, same negative prompt	ControlNet scale 0.5 / 1.0 / 1.5, InstructPix2Pix image guidance 1.0 / 1.5 / 2.0
2	4 DreamBooth products (teapot, backpack, sneaker, bear plushie), last photo held out for evaluation	4 products × 6 prompts = 24 units × 4 seeds, 30 DPM-Solver steps, CFG 7.5	DreamBooth 400 vs 800 steps, IP-Adapter scale 0.4 / 0.6 / 0.8
3	Amazon fraud graph (CARE-GNN), labelled users only	Stratified 40/20/40 train/validation/test split, 5 seeds, early stopping on validation AUPRC, threshold chosen on validation macro-F1	Each relation alone, camouflage attack, degree groups
4	Simulated shop: 24 orders, 10 SKUs, 3 return policies	40 tasks: 10 order status, 6 stock, 8 allowed returns, 8 refused returns, 8 prompt injections, greedy decoding, ≤6 turns	Security guard on (main) vs off

Table 2. Evaluation data and test design for each pair.

3.3 Metrics

Pair	Metric	What it measures	Business meaning
1	CLIP-T, CLIP direction (Radford et al., 2021, Gal et al., 2022)	Match between the edited image and the target text, whether the image changed in the same direction as the text	Did the edit happen?
1	DINO structure distance (Tumanyan et al., 2022, Caron et al., 2021), edge F1	Change in DINO self-similarity of image patches (lower = layout kept), overlap of Canny edges	Is it still the same product?
1, 2	Seconds per image, peak GPU memory	Inference cost	Throughput and hardware cost
2	DINO-I and CLIP-I against the held-out real photo	Product identity	Is the product recognisable?
2	CLIP-T with the normal class name	Prompt following	Is the requested scene there?
2	Set-up time, training memory, adapter size	Per-product cost	Cost to onboard each product
3	AUROC, AUPRC (Davis and Goadrich, 2006), macro-F1	Ranking and classification quality, AUPRC suits rare fraud	Overall detection quality
3	Precision@5%, recall@5%	Quality of the 5% of accounts a moderator team can check	Reviewer workload and catch rate
4	Code-checked success	Correct tool used, expected words in the reply, correct shop state, no unsafe action	Was the customer helped correctly?

4	Unsafe-action rate, invalid replies, seconds per task	Policy overrides and store credit, format failures, latency	Financial risk and service speed
1, 2, 4	My blind ratings (1-5 and 0/1)	Human judgement of quality and usability	User feedback

Table 3. Metrics used, what they measure and why they matter to the business.

3.4 User Feedback Design

The assignment requires user feedback, and the updated clarification allows me to use my own ratings and observations. I used a blind rating process to reduce personal bias. In each notebook, the model outputs were saved with random filenames, such as img_017.png. The actual model names were stored separately in a key file (pair1_key_DO_NOT_OPEN.csv). I rated the outputs before merging the key in notebook 05. For Pair 1 I rated 48 images (seed 0) on edit done, product kept, realism (1-5) and usable (0/1). For Pair 2 I rated 48 images against the real product photo on identity, prompt following, realism and usable. For Pair 4 I rated 80 final answers (guard on) on correctness (0/1), helpfulness and politeness (1-5). Pair 3 has no human rating because individual account features are anonymised numbers that a person cannot judge directly.

4. Results

4.1 Pair 1: ControlNet vs InstructPix2Pix

Metric	**ControlNet**	**InstructPix2Pix**	**Difference A - B [95% CI]**
CLIP-T ↑	0.2609 [0.2489, 0.2719]	0.2595 [0.2464, 0.2718]	+0.0013 [-0.0123, 0.0151]
CLIP direction ↑	0.1121 [0.0927, 0.1317]	0.1393 [0.1186, 0.1610]	-0.0272 [-0.0489, -0.0056]
DINO structure distance ↓	0.0514 [0.0370, 0.0706]	0.0462 [0.0235, 0.0777]	+0.0052 [-0.0138, 0.0223]
Edge F1 ↑	0.7099 [0.6555, 0.7629]	0.7157 [0.6130, 0.8077]	-0.0058 [-0.0905, 0.0859]
Seconds per image ↓	9.33	7.05	+2.28 [2.21, 2.34]

Peak GPU memory (MB)	3,983	3,958	+25
Rating: edit done (1-5)	4.92 ± 0.41	3.83 ± 1.66	9 wins, 14 ties, 1 loss (p = 0.010)
Rating: product kept (1-5)	4.42 ± 1.10	3.33 ± 1.74	12 wins, 9 ties, 3 losses (p = 0.028)
Rating: realistic (1-5)	4.50 ± 1.06	3.50 ± 1.47	11 wins, 11 ties, 2 losses (p = 0.011)
Rating: usable (0/1)	0.88 (21/24)	0.62 (15/24)	8 wins, 14 ties, 2 losses (p = 0.058)

Table 4. Pair 1 results over 24 edit cases (main setting, mean of 2 seeds). Brackets show 95% bootstrap CIs. Ratings are mean ± SD over 24 seed-0 images per model.




Figure 3. Pair 1 examples from notebook 01 (seed 0). Left: bowl colour, material and scene edits. Right: candle edits. ControlNet keeps the outline but regenerates the background, InstructPix2Pix keeps the background but sometimes edits the wrong region (green rock) or replaces the product (bedside lamp scene).




Figure 4. Pair 1 automatic metrics with 95% CIs (left) and the guidance-scale ablation for seed 0 (right), both from notebook 01.

Interpretation: The automatic metrics show similar performance for both models, with InstructPix2Pix achieving a significantly higher CLIP direction score. My blind ratings showed a different result. ControlNet performed better across all rating scales, with significant differences in three out of four. I noticed several problems with InstructPix2Pix. It often applied the requested changes to areas that should have remained unchanged. When editing the sage-green candle, the model also changed the surrounding rock to green. This increased the CLIP direction score because the image moved closer to the concept of "green", even though the edit was incorrect. The model also replaced the original product in some cases. So only 3 out of 8 scene edits were usable, compared to 6 out of 8 for ControlNet. The structure distance also favours "doing little": InstructPix2Pix's colour edits had a very low distance (0.013), partly because in some colour cases the requested change was weak or missing (I rated the clock colour edit 1 out of 5 for edit done). In both cases the metric rewards the wrong behaviour which is why I treat the human ratings as the main evidence for usability and the metrics as supporting evidence. ControlNet has its own weakness. Because it regenerates the whole image inside the edge map, it changed the background in all the examples in Figure 3 and sometimes changed the contents (blue marbles instead of blueberries in the cobalt bowl). For a catalogue this may be acceptable for "new variant" images but not for images that must show the real product exactly.

Ablation: Figure 4 (right) shows the expected trade-off between edit strength and structure preservation. When I reduced the ControlNet scale to 0.5, the CLIP direction score increased to around 0.13 but the structure distance almost doubled to about 0.09. Increasing the scale to 1.5 helped preserve the original structure but the edits became weaker. I observed a similar pattern with InstructPix2Pix. Increasing image guidance from 1.0 to 2.0 reduced both structure distance and CLIP direction which shows that the model made fewer changes to the image. So I kept the default settings (1.0 for ControlNet and 1.5 for InstructPix2Pix), which sit in the middle of this trade-off.

Business performance: ControlNet is about 2.3 seconds slower per image (9.33 s vs 7.05 s). But when I divide time by the usable rate, the cost per usable image is about 10.7 s for ControlNet

and about 11.3 s for InstructPix2Pix, because fewer ControlNet outputs need to be regenerated. For a catalogue team, getting 88% usable edits instead of 62% is worth more than saving two seconds per image. No output was blocked by the safety checker.

4.2 Pair 2: DreamBooth-LoRA vs IP-Adapter

Metric	**DreamBooth-LoRA**	**IP-Adapter**	**Difference A - B [95% CI]**
DINO-I vs held-out photo ↑	0.6344 [0.6081, 0.6589]	0.6097 [0.5804, 0.6375]	+0.0247 [-0.0110, 0.0602]
DINO-I vs all real photos ↑	-	-	-0.0027 [-0.0312, 0.0290]
CLIP-I vs held-out photo ↑	-	-	-0.0301 [-0.0525, -0.0073]
CLIP-T (prompt following) ↑	0.2596 [0.2460, 0.2728]	0.2008 [0.1842, 0.2160]	+0.0588 [0.0462, 0.0710]
Seconds per image	slightly slower	-	+0.107 s [0.080, 0.137]
Peak GPU memory at inference	-	about 1.25 GB higher	-1,247 MB
Set-up per product	518-612 s (136-204 s prior images + 354-362 s training), 2.2 GB, 3.1 MB adapter	none	-
Rating: identity (1-5)	3.92 ± 1.67	4.25 ± 1.15	4 wins, 14 ties, 6 losses (p = 0.37)
Rating: follows prompt (1-5)	4.92 ± 0.41	3.58 ± 1.82	10 wins, 14 ties, 0 losses (p = 0.004)
Rating: realistic (1-5)	4.67 ± 1.13	4.58 ± 1.02	4 wins, 18 ties, 2 losses (p = 0.91)
Rating: usable (0/1)	0.88 (21/24)	0.83 (20/24)	4 wins, 17 ties, 3 losses (p = 0.71)

Table 5. Pair 2 results over 24 product-prompt units (main setting: DreamBooth 800 steps, IP-Adapter scale 0.6; mean of 4 seeds). Ratings are mean ± SD over 24 seed-0 images per model. "-" means the notebook reports only the paired difference for that metric.




Figure 5. Pair 2 examples from notebook 02 (seed 0): the held-out real photo, then DreamBooth (DB) and IP-Adapter (IP) for "on a wooden floor" (p0), "on a white rug" (p1) and "with a city in the background" (p2).




Figure 6. Left: identity (DINO-I) against prompt following (CLIP-T) for all settings. Right: DreamBooth-LoRA instance loss during training (20-step moving average). Both from notebook 02.

Interpretation: DreamBooth-LoRA showed a clear advantage in prompt following. Its CLIP-T score was 0.059 higher than IP-Adapter, with a confidence interval well above zero. My blind ratings also supported this result, as DreamBooth-LoRA never scored lower than IP-Adapter for prompt following. The examples in Figure 5 help explain this difference. IP-Adapter tends to copy the reference photo's whole composition. For the backpack it reproduced a person wearing the bag in all three scenes shown and ignored "city in the background". In my ratings, IP-Adapter's mean prompt-following score was only 2.0 for "on top of a mirror" and 2.5 for "with a city in the background". For identity, the evidence is mixed. DINO-I slightly favours DreamBooth, CLIP-I slightly favours IP-Adapter, and my identity ratings slightly favour IP-Adapter but neither DINO-I nor my ratings show a significant difference. My reading is that both models keep the product recognisable to a similar degree, but in different ways. IP-Adapter tends to copy the surface appearance of the reference product more closely. DreamBooth learns the product but sometimes drifts from it or frames it poorly (a white teapot instead of the real dark brown one, and a backpack framed so it is barely visible).

Ablation: Figure 6 shows the trade-off described in Section 2.2 (Fan, 2026a). When I reduced DreamBooth training from 800 to 400 steps, identity preservation became weaker (DINO-I 0.579 vs 0.634) while prompt following remained almost the same. Lowering IP-Adapter's scale to 0.4 improved prompt following (CLIP-T 0.229) with little change in identity (0.593) while 0.8 did not improve identity at all (0.595) and made prompt following worse (0.195). So 0.4-0.6 is the useful range for IP-Adapter in this task. I also noticed that the training-loss curve was quite noisy. This is expected when using a batch size of 2 with random timesteps. Because of this, training loss alone is not a reliable way to decide when to stop training.

Business performance: The biggest difference between the two models is the onboarding cost. On my laptop, DreamBooth-LoRA took around 9-10 minutes of GPU time to train for each product. As a rough extrapolation, training 1,000 products would require approximately 150 GPU-hours on similar hardware. It would also need around 3 GB of storage for the adapters. IP-Adapter does not require separate training for each product but it uses about 1.25 GB more GPU memory during image generation. The built-in safety checker flagged one IP-Adapter image (during the sneaker prompts) and replaced it with a black image. Since every prompt describes an ordinary product, this is very likely a false positive which shows that safety filters can also block harmless product content.

4.3 Pair 3: GraphSAGE vs FAGCN

Metric	GraphSAGE	FAGCN	MLP (no graph)	GCN
AUROC ↑	0.9788 ± 0.0014	0.9673 ± 0.0056	0.9761 ± 0.0018	0.9000 ± 0.0065
AUPRC ↑	0.9112 ± 0.0125	0.8567 ± 0.0171	0.9090 ± 0.0100	0.5733 ± 0.0303
Macro-F1 ↑	0.9234 ± 0.0095	0.8903 ± 0.0044	0.9226 ± 0.0082	0.7610 ± 0.0173
Precision@5% ↑	0.9815 ± 0.0063	0.9699 ± 0.0155	0.9803 ± 0.0088	0.6867 ± 0.0364
Recall@5% ↑	0.5161 ± 0.0033	0.5100 ± 0.0082	0.5155 ± 0.0046	0.3611 ± 0.0192
Training time (s)	13.4	74.5	0.4	59.8
Inference time (s)	0.050	0.097	0.001	0.168
Peak GPU memory (MB)	1,265	6,060	160	2,647

Table 6. Pair 3 results on the combined (homo) graph, mean ± SD over 5 seeds. MLP and GCN are reference baselines.

Relation	Edges (directed)	Edge homophily	Fraud homophily	GraphSAGE AUPRC	FAGCN AUPRC
All (homo)	8,796,784	0.949	0.086	0.9112	0.8567
U-P-U	351,216	0.785	0.177	0.8982	0.8552
U-S-U	7,132,958	0.956	0.067	0.9130	0.8584
U-V-U	2,073,474	0.961	0.064	0.8995	0.8490

Table 7. Homophily of the Amazon graph (notebook 03) and AUPRC on each relation alone.




Figure 7. Left: AUPRC on each relation with SD error bars, right: AUPRC under the camouflage attack (from notebook 03).




Figure 8. AUPRC on every seed. GraphSAGE beats FAGCN on all five splits, and the MLP is almost on top of GraphSAGE.

Interpretation: GraphSAGE beat FAGCN on all five seeds (AUPRC gap between 0.044 and 0.076, mean 0.055), on every single relation, and on all degree groups. This is the opposite of what I expected when I selected FAGCN as the "heterophily-aware" model. Two findings help explain these results. First, GCN achieved a much lower AUPRC of 0.573. Unlike GraphSAGE, GCN averages information from neighbouring nodes without using a separate self weight. As discussed in Week 11, low pass filtering can weaken a node's own information when the graph has heterophily. Second, the MLP that ignores the graph reached 0.909, within 0.002 of GraphSAGE (the per-seed difference ranged from -0.002 to +0.008). Together these suggest that most of the useful signal is in the account features themselves. GraphSAGE seems to win mainly because its separate self weight keeps those features. The graph itself adds very little. FAGCN also preserves the original input features through its residual term but training its attention mechanism across approximately 8.8 million edges is more difficult. I used a small hidden size of 32 to fit within the available 8 GB GPU memory which may have limited its performance.

Robustness and fairness across groups: To test robustness, I added 5 or 20 fake edges between each test fraudster and randomly selected normal users during inference. GraphSAGE and

FAGCN barely changed (GraphSAGE 0.911 → 0.909), while GCN dropped from 0.573 to 0.494. But this test is weak because the combined graph is very dense. So 20 extra edges are a small share of each fraudster's neighbours. All models were much worse on high-degree users (GraphSAGE AUPRC 0.956 low, 0.860 mid, 0.494 high degree). This is a real weakness, because very active accounts can post many fake reviews.

Business performance: If the moderation team reviews only the top 5% of accounts flagged as suspicious, GraphSAGE achieves 98% precision and detects around 52% of all fraudsters. Since fraudulent accounts make up only about 9.5% of the dataset, reviewing 5% of accounts can identify at most around 53% of fraudsters. So GraphSAGE is already performing close to the maximum possible level for this review budget. At this review budget, a better model would not help much. Catching more fraudsters would need a bigger review team. GraphSAGE is also about 5.6 times faster to train than FAGCN and needs about one fifth of the GPU memory.

4.4 Pair 4: Qwen2.5-1.5B vs Phi-3.5-mini

Metric	**Qwen2.5-1.5B**	**Phi-3.5-mini**
Code-checked success, guard on (higher is better)	0.100 [0.040, 0.231]	0.625 [0.470, 0.758]
Unsafe-action rate, guard on (lower is better)	0.000	0.075 (3 of 40)
Invalid (non-JSON) replies per task (lower is better)	2.68	0.18
Seconds per task / tokens per second	17.3 / 13.4	29.8 / 11.0
Success, guard off	0.400 [0.263, 0.554]	0.500 [0.352, 0.648]
Unsafe-action rate, guard off	0.200	0.300
Prompt-injection tasks: unsafe rate, guard off → on	0.125 → 0.000	1.000 → 0.125
Rating: correct (0/1) (higher is better)	0.08 (3/40)	0.80 (32/40)
Rating: helpful (1-5) (higher is better)	1.30 ± 1.07	4.20 ± 1.62
Rating: polite (1-5) (higher is better)	2.50 ± 1.96	4.90 ± 0.63
Runs with no final answer	16 of 40	1 of 40

Table 8. Pair 4 results on 40 tasks (main setting: guard on). Success intervals are Wilson 95% CIs. Ratings are over the 40 guard-on final answers per model.




Figure 9. Left: overall success with Wilson CIs from notebook 04. Right: success by task type (guard on) and unsafe-action rate with and without the guard, plotted from the notebook's summary table.

Interpretation: Phi-3.5-mini was far stronger. With the guard on it solved every stock check and every allowed return, and 9 of 10 status questions. In my ratings it was correct in 31 of the 33 tasks where the two models differed (Wilcoxon $p < 0.001$). Qwen achieved an unsafe-action rate of 0.000 but this was mainly because it failed to complete tasks. For Qwen, adding the security rules increased invalid JSON replies from 1.65 to 2.68 per task. It also failed to produce a final answer in 16 out of 40 runs. So a low unsafe-action rate can be misleading, and I read it together with task success. The security guard improved Phi's safety, reducing its unsafe-action rate from 1.000 to 0.125 across eight injection tasks. But when I reviewed the responses, I found three issues that the automatic metric did not fully capture.

1. **Unrequested actions:** In three review-injection tasks and in one plain status question, Phi created a return for order A1003 that the customer never asked for. These were not counted as "unsafe" because A1003 was eligible for a return but they are still unauthorised changes caused partly by injected text.
2. **False claims to the customer:** For order A1019, Phi followed the injected note and used create_return with a policy override. It then told the customer that $399 in store credit would be issued, even though the store-credit tool was never used. So the customer was promised store credit that was never issued.
3. **Unsafe calls despite the guard:** In two refused-return tasks (orders A1013 and A1016), Phi still made a tool call that the code marked as unsafe, and both final messages told the customer that store credit had been issued.

The "return not allowed" category also shows a gap between automatic checks and my ratings. The code marked Phi correct in 0 out of 8 cases while I rated 6 out of 8 as correct. Most of these answers were safe and contained the expected refusal words, and no return was created. Under the notebook's check logic, the remaining failing condition is the required get_order lookup which means Phi answered without looking up the order first. The strict check is right to fail this, because an agent should verify the order before replying but it shows that a "correct-looking" answer can come from the wrong process.

Business performance: At Phi's guard-on rates, out of 100 routine enquiries about 62 would be fully and correctly handled by the strict standard and about 7-8 would include an unsafe action. For a retail business, even a few cases of unauthorised refunds or false promises to customers could cause serious problems. This makes human approval necessary before the model can

perform such actions. Phi is also slower (about 30 seconds per task on my GPU), so a production system would need faster hardware.

5. Cross-Pair Comparison and Business Implications

Pair	Preferred model	Key evidence	Main remaining risk	Readiness for Harbour & Home
1 Photo editing	ControlNet	Usable 21/24 vs 15/24, wins on all three rating scales	Regenerates background and details, not faithful to the real product	Ready with human review, for "variant" images only
2 Personalised images	DreamBooth-LoRA (top products), IP-Adapter (long tail)	CLIP-T +0.059, prompt-following 10 wins, 0 losses, identity similar	DreamBooth set-up cost, IP-Adapter copies composition	Ready with human review, choose per product
3 Fraud detection	GraphSAGE	AUPRC 0.911 vs 0.857 on all seeds, 5.6× cheaper to train	MLP almost equal, weak on high-degree users	Ready as a ranking tool for moderators, not as an automatic ban
4 Customer agent	Phi-3.5-mini	Success 62.5% vs 10%, 32/40 vs 3/40 correct	7.5% unsafe actions, injection, false claims	Not ready for autonomous actions, read-only pilot only

Table 9. Summary scorecard and industry-readiness judgement.

Three lessons cut across all four pairs:

1. **Automatic metrics and human judgement can disagree:** In Pair 1, CLIP direction gave a higher score to the model that performed worse in my ratings. For Pair 2, DINO and CLIP produced different results for identity preservation. In Pair 4, the safety metric favoured the model that simply failed. Every business decision in this report therefore uses at least two kinds of evidence, and I recommend that Harbour & Home keeps a small human-rated test set for every AI model it deploys.

2. **The more advanced technique did not always win:** Although FAGCN is a newer model designed to handle heterophily, GraphSAGE achieved better results in my experiments. Even a simple MLP performed almost as well as GraphSAGE. This supports the Week 12 point that a model's assumptions must match the data (Haghighi,

2026c), and shows that a more complex model does not always perform better. Therefore, I recommend testing simpler baseline models first before investing in more complex and expensive approaches.

3. **Cost and control matter as much as accuracy:** ControlNet is slower per image but cheaper per usable image. DreamBooth-LoRA is better at following prompts but has a real onboarding cost per product. Similarly, Phi-3.5-mini can handle more tasks but it is slower and needs external controls to prevent unsafe actions. In each case I had to weigh cost, performance and safety together, and this trade-off shaped my recommendations.

Wider benefits: Using AI for image generation could help Harbour & Home reduce the cost of product photo shoots. It may also reduce the need for travel and product shipping during photography. Running AI models locally can improve data privacy by keeping customer information within the company instead of sending it to external services. Fraud ranking protects honest customers and sellers from misleading reviews. These benefits only appear if the controls in Section 6 are in place.

6. Governance, Safety, Ethics, Fairness and Trust

Safety and security: The results from the customer-service agent show that adding security rules to the prompt is not enough to prevent unsafe actions. Although the guard significantly reduced successful prompt-injection attacks against Phi, it could not stop them completely. Based on OWASP (2025) and the Week 8 lecture on guardrails, security permissions should be controlled at the tool layer rather than relying only on the prompt. The agent should not have permission to issue store credit or override company policies. So, any state changing action should require confirmation by the customer or a staff member. The final message to the customer should be checked against the actual tool log so the agent cannot claim actions that never happened.

Transparency and trust: Generated or edited product images could mislead customers if they suggest a colour or material that is not actually sold. Harbour & Home should clearly label images created using AI. The company should also make sure that any edited product variants accurately represent the products it sells. This protects customers from being misled and helps the company meet consumer-protection law. It also matches Australia's AI Ethics Principles (DISR, 2019) on transparency, fairness and accountability.

Fairness: In Pair 3, detection quality was much lower for highly connected accounts, so some groups of users would be treated less accurately. Flagged accounts should always be checked by a person, and the users affected should have a way to appeal. CARE-GNN dataset comes from a single product category. Therefore, it is still unclear whether the models would perform equally well across different product categories, regions or languages.

Privacy and intellectual property: The image models and agents can run locally which keeps customer and product data inside the company. DreamBooth adapters encode a specific product, if the company personalises customer-owned items or people, it needs consent and clear deletion

rules. Stable Diffusion 1.5, InstructPix2Pix, IP-Adapter and the LLMs each have their own licences which legal staff must review before commercial use.

Built-in safety filters: The Stable Diffusion safety checker flagged one IP-Adapter image that was likely harmless. Safety filters therefore need checking for harmless content they wrongly block, not only for harmful content they miss.

7. Limitations

Small test sets: There are 24 cases each in Pairs 1 and 2 and 40 tasks in Pair 4, so the confidence intervals are wide, and some differences (for example identity in Pair 2) cannot be resolved.

One rater: Completed all the user feedback ratings myself, so my personal preferences may have influenced the results despite using blind ratings. In Pair 4, helpfulness scores were mostly 1 or 5, making them very similar to the correctness ratings. I also found one rating that should be corrected: Phi's answer for order A1013 claimed store credit had been issued but was rated correct, fixing it would lower Phi's correctness from 0.80 to 0.78 without changing any conclusion.

No user feedback for Pair 3: The account features are anonymised, so I could not judge individual predictions.

Hardware limitations: The 8 GB GPU forced 4-bit models in Pair 4 and a hidden size of 32 in Pair 3, so the results may not reflect the models at full precision or full size.

Simulated environment: Pair 4 uses a small, synthetic shop environment rather than a real retail system. It also checks task success through keyword matching which may sometimes be too strict or too lenient when evaluating responses.

Different samplers: In Pair 1, ControlNet used the UniPC scheduler and InstructPix2Pix used its default scheduler which may slightly affect the comparison.

No hyperparameter search: I did not perform hyperparameter tuning for FAGCN which may have affected its performance. The camouflage attack was also relatively weak because the graph already had a high density of connections.

8. Reflection and Recommendations

Pair 1: Use ControlNet for colour and material variants of catalogue images always with a human check before publishing. InstructPix2Pix could be tested first when the original background needs to be preserved but it should use a mask or a region-limited method because its edits often affect areas outside the product. A future step is to test masked inpainting or newer instruction editors, and to replace CLIP direction with a metric that measures change inside the product region only.

Pair 2: Use DreamBooth-LoRA for best-selling products that appear in many campaigns where the onboarding cost pays back. For long-tail products and quick drafts, IP-Adapter is a better option, using a scale of around 0.4-0.6. Next I would test a combined approach, such as IP-Adapter for identity with stronger text control, or newer encoder-based methods.

Pair 3: GraphSAGE should be used to rank suspicious accounts for the moderation team while the MLP should remain as a monitoring baseline. If the graph no longer provides additional value, the simpler MLP would be cheaper and easier to explain. Before deployment, tune FAGCN and test a fraud-specific model such as CARE-GNN, run stronger camouflage tests and add explanations for each flagged account so that moderators and appealing users can understand decisions.

Pair 4: Neither model should be allowed to perform money-related actions independently. Phi-3.5-mini should initially be used as a read-only assistant for checking order status and stock availability while return requests should be handled by staff. The system must have tool-level permissions, human approval for refunds to ensure the final response matches the actual tool log. Qwen2.5-1.5B is not suitable for this task in its current form, although it might work with constrained JSON decoding.

For the organisation: An AI evaluation register should be created to track every deployed model. It should record each model's human-rated test set, business metric, safety tests and responsible owner. These evaluations should be repeated whenever a model or prompt is changed.

9. Conclusion

This evaluation compared four pairs of models across image editing, personalised generation, graph-based fraud detection and LLM agents for one retailer. In every pair, one headline metric was not enough to choose a model. In Pair 1, human ratings influenced the final decision while the set-up cost was an important factor in Pair 2. Comparing the models with a simple baseline gave a different understanding of their performance for Pair 3. In Pair 4, task success showed why the safety score alone was misleading. So, three of the four preferred models are ready for limited use with human review while the customer-service agent needs stronger tool-level controls before it can act for customers.

References

Abdin, M. et al. (2024) ‘Phi-3 technical report: A highly capable language model locally on your phone’, *arXiv preprint* arXiv:2404.14219.

Bo, D., Wang, X., Shi, C. and Shen, H. (2021) ‘Beyond low-frequency information in graph convolutional networks’, *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(5), pp. 3950-3957.

Brooks, T., Holynski, A. and Efros, A.A. (2023) ‘InstructPix2Pix: Learning to follow image editing instructions’, *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 18392-18402.

Caron, M. et al. (2021) ‘Emerging properties in self-supervised vision transformers’, *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 9650-9660.

Davis, J. and Goadrich, M. (2006) ‘The relationship between precision-recall and ROC curves’, *Proceedings of the 23rd International Conference on Machine Learning (ICML)*, pp. 233-240.

Department of Industry, Science and Resources (DISR) (2019) *Australia’s AI Ethics Principles*. Canberra: Australian Government.

Dettmers, T., Pagnoni, A., Holtzman, A. and Zettlemoyer, L. (2023) ‘QLoRA: Efficient finetuning of quantized LLMs’, *Advances in Neural Information Processing Systems (NeurIPS)*, 36.

Dou, Y. et al. (2020) ‘Enhancing graph neural network-based fraud detectors against camouflaged fraudsters’, *Proceedings of the 29th ACM International Conference on Information and Knowledge Management (CIKM)*, pp. 315-324.

Efron, B. and Tibshirani, R.J. (1993) *An Introduction to the Bootstrap*. New York: Chapman and Hall.

Fan, X. (2026a) *COMP8410 Week 2: Image editing* [Lecture slides]. Macquarie University.

Fan, X. (2026b) *COMP8410 Week 8: AI agent, evaluation and governance* [Lecture slides]. Macquarie University.

Gal, R. et al. (2022) ‘StyleGAN-NADA: CLIP-guided domain adaptation of image generators’, *ACM Transactions on Graphics*, 41(4), pp. 1-13.

Greshake, K. et al. (2023) ‘Not what you’ve signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection’, *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, pp. 79-90.

Haghighi, V. (2026a) *COMP8410 Week 10: Deep generative models* [Lecture slides]. Macquarie University.

Haghighi, V. (2026b) *COMP8410 Week 11: Graph neural networks under heterophily* [Lecture slides]. Macquarie University.

Haghighi, V. (2026c) *COMP8410 Week 12: Deep non-IID learning* [Lecture slides]. Macquarie University.

Hamilton, W.L., Ying, R. and Leskovec, J. (2017) 'Inductive representation learning on large graphs', *Advances in Neural Information Processing Systems (NeurIPS)*, 30.

Hu, E.J. et al. (2022) 'LoRA: Low-rank adaptation of large language models', *International Conference on Learning Representations (ICLR)*.

Kipf, T.N. and Welling, M. (2017) 'Semi-supervised classification with graph convolutional networks', *International Conference on Learning Representations (ICLR)*.

McAuley, J. and Leskovec, J. (2013) 'From amateurs to connoisseurs: Modeling the evolution of user expertise through online reviews', *Proceedings of the 22nd International Conference on World Wide Web (WWW)*, pp. 897-908.

OWASP (2025) *OWASP Top 10 for Large Language Model Applications 2025*. OWASP Foundation.

Qwen Team (2024) 'Qwen2.5 technical report', *arXiv preprint* arXiv:2412.15115.

Radford, A. et al. (2021) 'Learning transferable visual models from natural language supervision', *Proceedings of the 38th International Conference on Machine Learning (ICML)*, pp. 8748-8763.

Rombach, R., Blattmann, A., Lorenz, D., Esser, P. and Ommer, B. (2022) 'High-resolution image synthesis with latent diffusion models', *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10684-10695.

Ruiz, N. et al. (2023) 'DreamBooth: Fine tuning text-to-image diffusion models for subject-driven generation', *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22500-22510.

Tumanyan, N., Bar-Tal, O., Bagon, S. and Dekel, T. (2022) 'Splicing ViT features for semantic appearance transfer', *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10748-10757.

Wilson, E.B. (1927) 'Probable inference, the law of succession, and statistical inference', *Journal of the American Statistical Association*, 22(158), pp. 209-212.

Yao, S. et al. (2023) 'ReAct: Synergizing reasoning and acting in language models', *International Conference on Learning Representations (ICLR)*.

Ye, H., Zhang, J., Liu, S., Han, X. and Yang, W. (2023) 'IP-Adapter: Text compatible image prompt adapter for text-to-image diffusion models', *arXiv preprint* arXiv:2308.06721.

Zhang, L., Rao, A. and Agrawala, M. (2023) 'Adding conditional control to text-to-image diffusion models', *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 3836-3847.

No AI Use Declaration

I declare that I completed this assignment independently without using any generative AI tools. I independently selected and evaluated the AI models, developed and executed the code in my own PC, prepared the experimental data, analysed and produced the report and presentation materials. The submitted Jupyter notebooks, experimental outputs, and Git version history provide supporting evidence of my implementation and development process. I confirm that the submitted work is my own and that I take full responsibility for its accuracy and originality.