

# Covid-19-false-positive

Maike Heinrich

24 5 2021

## Probability of getting a false positive Covid-19 PCR-test

This code calculates the probability of getting a false positive Covid-19 test using Bayes' rule. In this example the current incidence is set on 150 and the accuracy of the PCR-test is set on 99.9%

```
#Covid-19-Incidence of 150/100000 citizens
prev<-0.00150
#number of people tested
N<-100000

#testing people with probability of getting Covid-19 by Incidence
outcome<-sample(c("Corona","Healthy"),N,replace=TRUE, prob=c(prev,1-prev))
N_C<-sum(outcome=="Corona")
N_G<-sum(outcome=="Healthy")

#Accuracy of a Covid-19 Test (99,9%)
accuracy<-0.999

#Calculating the test-outcome with Bayes' Rule
test<-vector("character",N)
test[outcome=="Corona"]<-sample(c("+","-"),N_C,replace=TRUE,prob=c(accuracy,1-accuracy))
test[outcome=="Healthy"]<-sample(c("-","+"),N_G,replace=TRUE,prob=c(accuracy,1-accuracy))
```

Creating a tabel for the results where “-” means a negative test, “+” stands for a positive test and “Corona” and “Healthy” for the actual result.

```
#Creating a table for the outcome
result<-table(outcome,test)
result
```

```
##          test
## outcome   -    +
##  Corona     0  167
##  Healthy 99711  122
```

People who will get a false positive result (This is a random number based on probability and will vary every time this code will be run)

```
#Number of people per 100000, getting a false positive result
result[2,2]
```

```
## [1] 122
```