RAKA X (Twitter) Postiz Setup Guide

Step-by-Step X Developer Portal Configuration, OAuth 1.0a Native App Setup, and .env Formatting for RAKA (raka.pk)

1. Why X (Twitter) Connections Fail in Postiz (OAuth 1.0a vs. OAuth 2.0)

According to the Postiz X (Twitter) Setup Guide and Provider API Keys Overview, X is unique among Postiz integrations because X's newer OAuth 2.0 flow only supports the v2 text API, whereas uploading product photos and videos requires X's v1.1 media upload endpoint. Therefore, Postiz uses the **OAuth 1.0a Consumer Key flow** (which authenticates both v1.1 media uploads and v2 post creation). Authentication failures on X happen for four specific reasons:

- **Copying OAuth 2.0 Keys Instead of Consumer Keys (Causes Invalid App / Token Errors):** On the *Keys and tokens* tab of the X Developer Portal, X displays two different credential blocks. You must copy the **API Key** and **API Key Secret** located inside the top **Consumer Keys** section—*never* the OAuth 2.0 Client ID and Client Secret at the bottom.
- **Selecting "Web App" Instead of "Native App" (Causes Error Code 32):** Under *User authentication settings* → *Type of App*, you **must select Native App** (Public client). As warned in the Postiz X Documentation, selecting *"Web App, Automated App or Bot"* causes OAuth 1.0a authentication to fail immediately with **Error Code 32 ("Could not authenticate you")**.
- **Default "Read-Only" App Permissions:** Newly created X apps default to *Read* permissions. If you generate your Consumer Keys before switching App permissions to **Read and write** (or forget to click **Regenerate** after changing permissions), X rejects post and media publishing.
- **X Rejecting Plain `http://localhost` Callback URLs:** If the X Developer Portal form refuses to save a plain `http://localhost:4200` callback URI, Postiz supports wrapping your local callback with `https://redirectmeto.com/http://localhost:4200/integrations/social/x`.

RAKA Channel in Postiz UI	Postiz .env Variable Pair	Exact X Developer Portal Field	OAuth Callback / Redirect URI (Port 4200)
X (Twitter) (RAKA Brand Account)	`X_API_KEY` `X_API_SECRET`	**Keys and tokens → Consumer Keys:** *API Key* & *API Key Secret* (25-char key & 50-char secret)	`http://localhost:4200/integrations/social/x` *(or via HTTPS wrapper:* `https://redirectmeto.com/http://localhost:4200/integrations/social/x`*)*

2. Step-by-Step X Developer Portal Setup for RAKA

Step 2.1: Create a Project & App in the X Developer Portal

1. Sign in to the X Developer Portal using RAKA's official X account.
2. If you haven't enrolled yet, click **Sign up for Free Account** (the Free tier allows up to 1,500 posts per month and works with Postiz's OAuth 1.0a flow). Enter a brief use case description: *"Internal social media scheduling integration (Postiz) for RAKA (raka.pk) to publish brand updates and hair-care educational threads to our official X account."*

3. In the left sidebar, open **Projects & Apps**, select your Project (or create a Project named `RAKA Social`), and create or select your App (e.g., `RAKA Postiz Publishing`). Make sure your App is nested inside a **Project** (Standalone apps outside a Project cannot access the X v2 API).

Step 2.2: Open "User authentication settings"

1. Click on your RAKA App name under **Projects & Apps** in the left sidebar.
2. On the **Settings** tab, scroll down to the **User authentication settings** card and click **Set up** (or **Edit** if previously configured).

Step 2.3: Set Permissions to "Read and write" & App Type to "Native App"

Configure the three sections on the **User authentication settings** page exactly as required by the Postiz X Guide:

1. **App permissions:** Select **Read and write** (or *Read and write and Direct message*). Do **not** leave it on *Read*.
2. **Type of App (Critical):** Select **Native App** (Public client).
   - *Why this matters:* Selecting **Web App, Automated App or Bot** forces confidential client checks that break Postiz's OAuth 1.0a token exchange with **Error Code 32**.
3. **App info (Callback URI & RAKA URLs):** Fill in the fields below:
   - **Callback URI / Redirect URL:** Enter the Postiz X callback URL matching your `FRONTEND_URL="http://localhost:4200"`:

     ```
     http://localhost:4200/integrations/social/x
     ```

     Note: If X's form validation displays an error requiring an `https://` URL for localhost, enter the HTTPS redirect wrapper documented by Postiz instead:

     ```
     https://redirectmeto.com/http://localhost:4200/integrations/social/x
     ```

     (For Docker port 5000, use `http://localhost:5000/integrations/social/x`; for a live RAKA domain, use `https://social.raka.pk/integrations/social/x`).
   - **Website URL (Required):** `https://raka.pk`
   - **Organization name (Optional):** `RAKA` | **Organization URL (Optional):** `https://raka.pk`
   - **Terms of service & Privacy policy:** `https://raka.pk/policies/terms-of-service` and `https://raka.pk/policies/privacy-policy`
4. Click **Save** at the bottom of the page and click **Yes** on the confirmation prompt. (If X displays an OAuth 2.0 Client ID and Client Secret screen right after saving, you can ignore or close it—Postiz does not use those keys).

Step 2.4: Regenerate & Copy Your "Consumer Keys"

1. Scroll to the top of your App page and click the **Keys and tokens** tab (next to *Settings*).
2. Locate the very first section at the top labeled **Consumer Keys** (subtitled *"API Key and Secret"*).
3. Click **Regenerate** next to *API Key and Secret* and confirm by clicking **Yes, regenerate**. (Regenerating after saving your *Read and write* + *Native App* settings guarantees the keys carry the updated write permissions).
4. Copy both strings immediately:
   - **API Key** (~25 alphanumeric characters) → maps to `X_API_KEY`
   - **API Key Secret** (~50 alphanumeric characters) → maps to `X_API_SECRET`

---

3. Formatted Postiz .env Configuration for RAKA X (Twitter)

Add the X configuration block to your Postiz `.env` file (Postiz Configuration Reference). In addition to `X_API_KEY` and `X_API_SECRET`, we recommend setting `DISABLE_X_ANALYTICS="true"` if your RAKA X account is on the Free or Basic API tier so Postiz does not log noisy analytics errors:

```
# Configuration reference: https://docs.postiz.com/self-host/configuration/reference

# === Required Settings
DATABASE_URL="postgresql://postiz-user:postiz-password@localhost:5432/postiz-db-local"
REDIS_URL="redis://localhost:6379"
```

```
JWT_SECRET="random string for your JWT secret, make it long"

# === This needs to be exactly the URL you're accessing Postiz on
FRONTEND_URL="http://localhost:4200"
NEXT_PUBLIC_BACKEND_URL="http://localhost:3000"
BACKEND_INTERNAL_URL="http://localhost:3000"

STORAGE_PROVIDER="local"

# ==============================================================================
# 1. X (Twitter) — Use OAuth 1.0a Consumer API Key & Secret
#    Source: X Developer Portal -> Project App -> Keys and tokens -> Consumer Keys
#    Critical Portal Settings (User authentication settings):
#      - App permissions : Read and write
#      - Type of App     : Native App (DO NOT select Web App)
#      - Callback URI    : http://localhost:4200/integrations/social/x
#      - Website URL     : https://raka.pk
# ==============================================================================
X_API_KEY="your_x_consumer_api_key"
X_API_SECRET="your_x_consumer_api_secret"

# Optional X settings (see https://docs.postiz.com/self-host/providers/x-twitter):
# Skip analytics fetch if your X API tier does not include analytics access
DISABLE_X_ANALYTICS="true"
# Set to "true" only if you want Postiz to strip URLs from X posts automatically
#STRIP_LINKS_FROM_X_POSTS="false"
```

4. Connecting RAKA's X Account in Postiz & Troubleshooting

1. **Restart Postiz:** Because Postiz reads `.env` only on boot, restart your backend and orchestrator processes (or run `docker compose up -d --force-recreate`) after saving your keys.
2. **Authorize RAKA on X:** Open `http://localhost:4200` in your browser, click **Add Channel → X**, and click **Authorize app** on the X OAuth screen while logged into RAKA's X account.

Error / Symptom	Root Cause	Exact Fix
Error Code 32: "Could not authenticate you" during connect or post	*Type of App* was set to "Web App, Automated App or Bot", or you pasted the OAuth 2.0 Client ID/Secret instead of the **Consumer Keys**.	In X Developer Portal, change *Type of App* to **Native App**, click **Regenerate** under *Keys and tokens → Consumer Keys*, update `X_API_KEY` and `X_API_SECRET`, and restart Postiz.
"Callback URL not approved for this client application" (Error 415)	The Callback URI in X's *User authentication settings* does not match `{FRONTEND_URL}/integrations/social/x`.	Add `http://localhost:4200/integrations/social/x` (no trailing slash) under *User authentication settings → Callback URI / Redirect URL* and save.
"Read-only application cannot POST" (403 Forbidden when publishing)	Consumer Keys were generated while App permissions were still set to *Read*.	Switch *App permissions* to **Read and write**, then go to *Keys and tokens → Consumer Keys*, click **Regenerate**, update `.env`, and reconnect the X channel in Postiz.
`t/r is not a function` error on the Postiz X redirect screen	Known transient UI error in Postiz (Postiz Known Issues) if you refresh the callback page.	Do not refresh the broken callback URL; return to the main **Channels** page in Postiz and start the **Add Channel → X** flow fresh.