Raw data dictionary: Vonnegut conformance exports, July to September 2026

36 Excel exports, 3,763,516 rows, in 11 datasets: one per message type. A dataset is the Excel files of one message type, combined in the bronze layer into one table with every month's rows. Every value in the exports is text, as Vonnegut wrote it; an empty cell has no value. **Filled** is the share of the dataset's rows with a value in the field. **Months** are those whose files have the column.

Datasets

Dataset	Type	Sent by	Jul rows	Aug rows	Sep rows	Files	Fields	One row is
Logon `logon`	**A**	Client	44,399	13,205	16,976	3	5	A request to open a session on the JSE trading gateway.
Logon Response `logon_response`	**B**	JSE	4,312	9,860	9,674	3	5	The JSE reply to a Logon: accepted, accepted with a password warning, or refused.
Logout `logout`	**5**	Client or JSE	4,249	11,065	5,992	3	4	A message that ends a session.
New Order `new_order_single`	**D**	Client	62,040	205,986	57,318	3	20	A new order.
Order Cancel Request `order_cancel_request`	**F**	Client	274,697	124,881	140,008	3	9	A request to cancel one open order.
Order Cancel/Replace Request `order_cancel_replace_request`	**G**	Client	282,791	160,352	486,808	3	16	A request to amend one open order: a new quantity, price or time in force.
Order Mass Cancel Request `order_mass_cancel_request`	**q**	Client	42	134	178	3	9	A request to cancel many orders at once.
Execution Report `execution_report`	**8**	JSE	76,466	438,816	183,880	4	24	The JSE report of an event on an order: accepted, amended, cancelled, expired, rejected or traded.
Order Cancel Reject `order_cancel_reject`	**9**	JSE	8,737	11,476	1,696	3	14	The JSE reply that refuses a cancel or amend request.
Order Mass Cancel Report `order_mass_cancel_report`	**r**	JSE	8	188	268	3	9	The JSE reply to a mass cancel request, one per matching engine partition.
Reject `reject`	**3**	JSE	126	1,032,324	94,564	5	12	The JSE reply to a client message that failed the gateway's checks.

Fields in more than one dataset

Field	Format in the export	Meaning	In datasets
Timestamp	Text: date, 24-hour time with 4 decimal places of a second, then a redundant am or pm, e.g. 2026-08-03 09:41:49.8992 am	When Vonnegut captured the message, in South African time (SAST, UTC+2).	Logon, Logon Response, Logout, New Order, Order Cancel Request, Order Cancel/Replace Request, Order Mass Cancel Request, Execution Report, Order Cancel Reject, Order Mass Cancel Report, Reject
Comp ID	Text: 6 letters and digits, e.g. GJEN09. Every CompID in the exports is fictitious.	The CompID of the client connection the message was sent on or to. A CompID is the login name of one client connection; one firm can have several. Empty on some JSE replies.	Logon, Logon Response, Logout, New Order, Order Cancel Request, Order Cancel/Replace Request, Order Mass Cancel Request, Execution Report, Order Cancel Reject, Order Mass Cancel Report, Reject
Message Type	Text: one character	The message type: A Logon, B Logon Response, 5 Logout, D New Order, F Order Cancel Request, G Order Cancel/Replace Request, q Order Mass Cancel Request, 8 Execution Report, 9 Order Cancel Reject, r Order Mass Cancel Report, 3 Reject. Every row of a dataset has its dataset's type.	Logon, Logon Response, Logout, New Order, Order Cancel Request, Order Cancel/Replace Request, Order Mass Cancel Request, Execution Report, Order Cancel Reject, Order Mass Cancel Report, Reject
Client Order ID	Text: up to 20 letters, digits and hyphens, e.g. 00178573862373600000 or 125-R1	The ID the client gave its request. The JSE does not check that it is unique, and keeps it per CompID. On a JSE reply it is the ID of the client request the reply answers; on an execution report, the ID of the last request that changed the order.	New Order, Order Cancel Request, Order Cancel/Replace Request, Order Mass Cancel Request, Execution Report, Order Cancel Reject, Order Mass Cancel Report, Reject
Orig Client Order ID	Text, in the same form as Client Order ID. The header is "Original Client Order ID" in Order Cancel/Replace Request.	The Client Order ID of the order to cancel or amend.	Order Cancel Request, Order Cancel/Replace Request
Order ID	Text: 12 letters and digits starting with O, e.g. O0SGsBiEWvWV, or NONE	The JSE ID of the order, the same for the order's whole life. Empty on a cancel or amend request that names the order by its Orig Client Order ID instead. NONE on an Order Cancel Reject means the JSE could not find the order.	Order Cancel Request, Order Cancel/Replace Request, Execution Report, Order Cancel Reject

Field	Format in the export	Meaning	In datasets
Order Book	Text: a code number. The header is "OrderBook" in Order Mass Cancel Request.	The order book: 1 Regular, the only value in the exports.	New Order, Order Cancel Request, Order Mass Cancel Request, Execution Report, Order Cancel Reject, Order Mass Cancel Report
Order Sub Type	Text: a code number. The header is "OrderSubType" in Order Mass Cancel Request.	0 Order (normal), 50 Pegged to Mid, 51 Pegged to Bid, 52 Pegged to Offer.	New Order, Order Mass Cancel Request
Reject Code	Text: up to 6 digits, e.g. 1202; -1 means not set	The JSE reject code giving the reason for a rejection, as listed in JSE Volume 10 (Reject Codes and Reasons).	Logon Response, Execution Report, Order Cancel Reject, Order Mass Cancel Report, Reject
Transact Time	Text: date and time with up to 9 decimal places of a second, e.g. 2026-08-03 06:30:23.898764000	When the JSE processed the event, in UTC: 2 hours behind Timestamp.	Execution Report, Order Cancel Reject, Order Mass Cancel Report
Side	Text: a code number	1 Buy, 2 Sell.	New Order, Order Cancel Request, Order Cancel/Replace Request, Execution Report
Security ID	Text: up to 6 digits, e.g. 230	The JSE numeric instrument ID. The exports hold no instrument names or segments. 0 in every mass cancel request in the exports.	New Order, Order Cancel Request, Order Cancel/Replace Request, Order Mass Cancel Request, Execution Report
Display Quantity	Text: a whole number	The visible quantity of the order, in shares: less than the order quantity for an iceberg order, 0 for a pegged order.	New Order, Order Cancel/Replace Request, Execution Report
Order Quantity	Text: a whole number	The number of shares ordered.	New Order, Order Cancel/Replace Request
Minimum Quantity	Text: a whole number; -1 means not set	The smallest quantity the order may trade in one execution; required for pegged orders.	New Order, Order Cancel/Replace Request
Limit Price	Text: a number with a thousands comma and 4 decimal places, e.g. 14,340.0000; -1.0000 also occurs	The limit price in South African cents (ZAC) per share: divide by 100 for Rand.	New Order, Order Cancel/Replace Request
Stop Price	Text: a number with a thousands comma and 4 decimal places, e.g. 14,340.0000; -1.0000 means not set	The price in ZAC at which a stop or stop limit order becomes active.	New Order, Order Cancel/Replace Request
Order Type	Text: a code number	1 Market, 2 Limit, 3 Stop, 4 Stop Limit, 50 Pegged, 51 Pegged Limit.	New Order, Order Cancel/Replace Request

Field	Format in the export	Meaning	In datasets
Time In Force	Text: a code number	How long the order stays open: 0 DAY (until the end of the trading day), 1 GTC Good Till Cancel, 3 IOC Immediate or Cancel, 4 FOK Fill or Kill, 5 OPG opening auction only, 6 GTD Good Till Date, 8 GTT Good Till Time, 9 GFA next auction only, 10 ATC closing auction only, 12 CPX Closing Price Cross, 51 GFX intraday auction.	New Order, Order Cancel/Replace Request
Execution Instruction	Text: a code number	0 None, 2 Include in the end-of-day volume auction (the JSE removed this auction in May 2026).	New Order, Execution Report
Self Trade Prevention Key	Text: up to 12 characters; a few values hold unprintable characters	A key issued by the JSE that stops two orders with the same key trading with each other (self-match prevention). Used only with protocol version 3.	New Order, Execution Report
Partition ID	Text: a code number	The matching engine partition: 1 Equity, 2 Derivatives.	Order Cancel Reject, Order Mass Cancel Report
Source	Text: network address and port, e.g. 10.10.63.132:21501	The network address the message was sent from, as captured by Vonnegut.	Order Cancel Reject, Reject
Destination	Text: network address and port, e.g. 156.48.0.148:58428	The network address the message was sent to.	Order Cancel Reject, Reject
Bytes	Text: a whole number, with a thousands comma above 999	The length of the message, in bytes.	Order Cancel Reject, Reject
Sequence No	Text: a whole number	The message sequence number.	Order Cancel Reject, Reject
Packet ID	Text, e.g. range = 0-58 / initial packet = TS 2026-08-17T14:04:28.9927408+02:00 IDENT 0 SEQ 228637688 ACK 3341791649 PLEN 59	A description of the captured network packet: the byte range of the message, the packet's capture time, and its network sequence and acknowledgement numbers.	Order Cancel Reject, Reject

Fields of each dataset

Logon

type A · Client · 74,580 rows · 1logon

Files: August_2026/Logon.xlsx; July_2026/Logon.xlsx; September_2026/Logon [A].xlsx

Field	Format in the export	Meaning	Months	Filled
CompID	Text, in the same form as Comp ID	The CompID written inside the Logon message.	all	100%

Field	Format in the export	Meaning	Months	Filled
Protocol Version	Text: a code number	The version of the gateway protocol the client uses: 1, 2 (needed for iceberg orders) or 3 (needed for self-match prevention); 0 means the system default.	all	100%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	100%
Message Type			all	100%

Logon Response

type B · JSE · 23,846 rows · `logon_response`

Files: August_2026/Logon Response [B].xlsx; July_2026/Logout [B].xlsx; September_2026/Logon Response [B].xlsx

Field	Format in the export	Meaning	Months	Filled
Password Expiry	Text: a whole number; -1 means not set	Days until the CompID's password expires. -1 in every row of the exports.	all	100%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	78%
Message Type			all	100%
Reject Code			all	100%

Logout

type 5 · Client or JSE · 21,306 rows · `logout`

Files: August_2026/Logout.xlsx; July_2026/Logout[5].xlsx; September_2026/Logout.xlsx

Field	Format in the export	Meaning	Months	Filled
Reason	Text, at most 20 characters	Why the session ended, in free text, e.g. User logout received, Force Logout on End (JSE end of day), HB expired (heartbeats missed).	all	75%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	88%
Message Type			all	100%

New Order type D · Client · 325,344 rows · `new_order_single`

Files: August_2026/New Order [D].xlsx; July_2026/New Order [D].xlsx; September_2026/New Order.xlsx

Field	Format in the export	Meaning	Months	Filled
Account	Text: up to 10 characters, almost all digits	The client account the order is for.	Aug	63%
Cancel on Disconnect	Text: a code number	Whether the JSE cancels the order if the session disconnects: 0 Do not cancel, 1 Cancel.	all	100%
Capacity	Text: a code number	The capacity the firm trades in: 2 Principal (its own account), 3 Agency (for a client). 0 also occurs and is not in the JSE list.	Jul	19%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	100%
Message Type			all	100%
Client Order ID			all	100%
Order Book			Jul	19%
Order Sub Type			Jul, Aug	82%
Side			Jul, Aug	82%
Security ID			all	100%
Display Quantity			all	100%
Order Quantity			Jul, Aug	82%
Minimum Quantity			all	100%
Limit Price			Jul, Aug	82%
Stop Price			Jul, Aug	82%
Order Type			all	100%
Time In Force			Jul, Aug	82%
Execution Instruction			all	100%
Self Trade Prevention Key			all	0.2%

Order Cancel Request type F · Client · 539,586 rows · `order_cancel_request`

Files: August_2026/Order Cancel Request[F].xlsx; July_2026/Order Cancel Request[F].xlsx; September_2026/Order Cancel Request [F].xlsx

Field	Format in the export	Meaning	Months	Filled
No field of its own: every field is in another dataset too.				
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	100%
Message Type			all	100%
Client Order ID			all	100%
Orig Client Order ID			all	99%
Order ID			all	9%
Order Book			Jul, Aug	74%
Side			all	100%
Security ID			all	100%

Order Cancel/Replace Request

type G · Client · 929,951 rows · `order_cancel_replace_request`

Files: August_2026/Order Cancel Replace Request[G].xlsx; July_2026/Order Cancel Replace Request [G].xlsx; September_2026/Order Cancel Replace Request [G].xlsx

Field	Format in the export	Meaning	Months	Filled
Expire Time	Empty in every row	The time a GTT order expires.	Sep	0%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	100%
Message Type			all	100%
Client Order ID			all	100%
Orig Client Order ID			all	84%
Order ID			all	20%
Side			all	100%
Security ID			all	100%
Display Quantity			all	100%
Order Quantity			Jul	30%

Field	Format in the export	Meaning	Months	Filled
Minimum Quantity			all	100%
Limit Price			all	100%
Stop Price			Aug	17%
Order Type			all	100%
Time In Force			all	100%

Order Mass Cancel Request

type q · Client · 354 rows · `order_mass_cancel_request`

Files: August_2026/Order Mass Cancel Request.xlsx; July_2026/Order Mass Cancel Request.xlsx; September_2026/Order Mass Cancel Request [q].xlsx

Field	Format in the export	Meaning	Months	Filled
Mass Cancel Request Type	Text: a code number	Which orders to cancel: 3 all firm orders for an instrument, 4 all firm orders for a segment, 7 all orders of this CompID, 8 all orders of the firm, 9 this CompID's orders for an instrument, 15 this CompID's orders for a segment.	all	100%
Segment	Empty in every row	The market segment whose orders are cancelled.	all	0%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	100%
Message Type			all	100%
Client Order ID			all	100%
Order Book			Jul, Sep	62%
Order Sub Type			all	100%
Security ID			all	100%

Execution Report

type 8 · JSE · 699,162 rows · `execution_report`

Files: August_2026/Execution Report 1.xlsx; August_2026/Execution Report 2.xlsx; July_2026/Execution Report [8].xlsx; September_2026/Execution Report.xlsx

Field	Format in the export	Meaning	Months	Filled
Execution ID	Text: 12 letters and digits starting with E, e.g. E0SGs6sBxGkz	The JSE ID of this execution report, unique.	all	100%

Field	Format in the export	Meaning	Months	Filled
Working Indicator	Text: a code number	Set only when Order Status is 0: 0 Unset, 1 the order is being worked, 2 not currently working (a stop order not yet triggered).	all	100%
TypeofTrade	Text: a code number	Trades only: 0 visible passive, 1 hidden passive, 2 not specified (the executed part was aggressive), 3 pegged passive.	all	100%
Public Order ID	Text, in the same form as Order ID	The order ID shown to the market: equal to Order ID except for iceberg orders, where it changes each time the visible quantity is refilled.	all	100%
Leaves Quantity	Text: a whole number	The quantity of the order still open after the event.	Jul, Aug	74%
Liquidity Indicator	Text: a code number	Trades only: 0 Unset, 1 added liquidity (passive), 2 removed liquidity (aggressive), 4 auction.	Jul, Aug	74%
Execution Type	Text: a code number or letter	What happened: 0 New (accepted), 4 Cancelled, 5 Amended, 8 Rejected (reason in Reject Code), 9 Suspended, C Expired, F Trade, G Trade Correct, H Trade Cancel, D Restated, L Triggered.	Aug, Sep	89%
Executed Quantity	Text: a whole number	The number of shares traded in this report; 0 when the report is not a trade.	all	100%
Executed Price	Text: a number with a thousands comma and 4 decimal places, e.g. 14,340.0000	The trade price in ZAC; 0.0000 when the report is not a trade.	all	100%
Indicator Flags	Text: a code number	Trades only: 1 this order was the aggressor, 0 passive (both sides are 0 in an auction).	Jul, Sep	37%
Order Status	Text: a code number	The state of the order after the event: 0 New, 1 Partially Filled, 2 Filled, 4 Cancelled, 6 Expired, 8 Rejected, 9 Suspended.	Jul, Sep	37%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	74%
Message Type			all	100%
Client Order ID			all	100%
Order ID			all	100%
Order Book			Jul	11%
Reject Code			all	100%
Transact Time			Jul, Aug	74%

Field	Format in the export	Meaning	Months	Filled
Side			all	100%
Security ID			Jul	11%
Display Quantity			all	100%
Execution Instruction			Aug, Sep	89%
Self Trade Prevention Key			Jul, Sep	0.1%

Order Cancel Reject

type 9 · JSE · 21,909 rows · `order_cancel_reject`

Files: August_2026/Order Cancel Reject[9].xlsx; July_2026/Order Cancel Reject.xlsx; September_2026/Order Cancel Reject.xlsx

Field	Format in the export	Meaning	Months	Filled
No field of its own: every field is in another dataset too.				
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	97%
Message Type			all	100%
Client Order ID			all	100%
Order ID			Jul, Aug	92%
Order Book			all	100%
Reject Code			all	100%
Transact Time			all	100%
Partition ID			Jul	40%
Source			Sep	8%
Destination			Sep	8%
Bytes			Sep	8%
Sequence No			Sep	8%
Packet ID			Sep	8%

Order Mass Cancel Report

type r · JSE · 464 rows · `order_mass_cancel_report`

Files: August_2026/Order Mass Cancel Report.xlsx; July_2026/Order Mass Cancel Report.xlsx; September_2026/Order Mass Cancel Report [r].xlsx

Field	Format in the export	Meaning	Months	Filled
Status	Text: a code number	The result of the mass cancel request: 7 Accepted, 0 Rejected (reason in Reject Code).	all	100%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	89%
Message Type			all	100%
Client Order ID			all	100%
Order Book			all	100%
Reject Code			all	100%
Transact Time			all	100%
Partition ID			all	100%

Reject

type 3 · JSE · 1,127,014 rows · `reject`

Files: August_2026/Reject 1.xlsx; August_2026/Reject 2.xlsx; August_2026/Reject 3.xlsx; July_2026/Rejects.xlsx; September_2026/Reject.xlsx

Field	Format in the export	Meaning	Months	Filled
Message Type.1	Text: one character. The second column headed "Message Type"; stored as "Message Type.1" in the combined bronze table.	The type of the client message that was rejected, e.g. D New Order. M is a recovery request, which the exports do not otherwise contain.	all	100%
Reject Reason	Text	The field or reason named by the gateway, e.g. Unknown User, Account, Maximum message rate exceeded.	all	100%
Fields also in other datasets, described under Fields in more than one dataset				
Timestamp			all	100%
Comp ID			all	100%
Message Type			all	100%
Client Order ID			all	100%
Reject Code			all	100%
Source			Aug	87%
Destination			Aug	87%

Field	Format in the export	Meaning	Months	Filled
Bytes			Aug	87%
Sequence No			Aug	87%
Packet ID			Aug	87%