
Android BroadcastReceivers


Android - BroadcastReceiver

- Component that responds to system-wide broadcast announcements. •
- Example system broadcasts: screen has turned off, the battery is low, user is present using phone, or a picture was captured. •
- Applications can initiate broadcasts—e.g., to let other applications know that some data has been downloaded to the device and is available for them to use. •
- Don't display a UI, but can create a status bar notification to alert the user when a broadcast event occurs..

-
-
- Usually, a broadcast receiver is just a "gateway" to other components and is intended to do a very minimal amount of work. For instance, it might initiate a service to perform some work based on the event. —
 - Important: you must complete tasks in a Broadcast Receiver in <10s. If you have a task that will take longer, you must start a new thread to avoid app as sass in OS.

BroadcastReceivers Life Cycle

The system delivers a broadcast Intent to all interested broadcast receivers, which handle the Intent *sequentially*.



BroadcastReceivers Life Cycle

A broadcast receiver has a single callback method:

```
void onReceive(Context curContext, Intent broadcastMsg)
```

1. When a broadcast message arrives for the receiver, Android calls its `onReceive()` method and passes it the `Intent` object containing the message.
2. The broadcast receiver is considered to be active only while it is executing this method.
3. When `onReceive()` returns, it is inactive.

BroadcastReceivers Via xml

The manifest of applications using Android Services must include:

1. A **<service>** entry for each service used in the application.
2. If the application defines a **BroadcastReceiver** as an independent class, it must include a **<receiver>** clause identifying the component. In addition an **<intent-filter>** entry is needed to declare the actual filter the service and the receiver use.